

FAIRCHILD SEMICONDUCTOR

MADE IN
FAIRCHILD

THE LINEAR INTEGRATED CIRCUITS DATA CATALOG

LINEAR
LINEAR
LINEAR
LINEAR
LINEAR

NOVEMBER 1971

TABLE OF CONTENTS

INTRODUCTION	PAGE 1
PRODUCT INDEX	2
SELECTION GUIDES	3
Consumer Products	3
Line Drivers/Receivers	4
Operational Amplifiers	5
Voltage Comparators	7
COMPETITIVE CROSS-REFERENCE	8
DATA SHEETS	15
PLANNED NEW PRODUCTS	289
DICE	300
HI REL UNIQUE 38510	301
APPLICATION INFORMATION	303
ORDERING INFORMATION	304
PACKAGE OUTLINES	309
GLOSSARY	318

Introduction

This data catalog contains complete information on Fairchild's entire line of quality linear integrated circuits...the most comprehensive line in the industry. Some idea of just how comprehensive our product line is can be gained quickly by referring to the chart below, which summarizes by market and by major end-equipments within each market, the types of Fairchild devices that serve their needs. There are currently 84 device types in production.

You'll find that the catalog is organized to permit quick, convenient reference to such information as specification data, connection diagrams, block diagrams and ordering information.

Also included are the following special sections devoted to:

- Selection guides to consumer products, interface elements, operational amplifiers and voltage comparators.
- A comprehensive industry-wide cross reference listing direct replacement and equivalent Fairchild products.
- Fairchild's UNIQUE 38510 high reliability program, showing process summary product screening levels and device types currently available.
- A statement on dice, summarizing electrical performance specifications, visual inspection criteria and availability.
- A planned new products listing, illustrating Fairchild's continued technological advancement in proprietary and second source devices.

PRODUCT/MARKET RELATIONSHIP

Product Classifications	COMPUTER	CONSUMER					MILITARY	INDUSTRIAL					
	Mainframe	Peripheral	Transportation	Home Entertainment	Musical Instruments	Appliance	Vehicles/Ordnance	Communications Equipment	Office Machines	Control & Processing	Test & Measuring	Communications	Medical & Scientific
General Purpose Op Amps			▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
Precision Op Amps								▲		▲	▲	▲	▲
Multiple Op Amps			▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
Comparators				▲		▲			▲		▲	▲	▲
Drivers/Receivers		▲	▲					▲	▲		▲	▲	▲
TV Circuits					▲	▲			▲		▲		▲
Voltage Regulators		▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲
Sense Amps		▲	▲					▲	▲	▲	▲		
Low Level Amps									▲				▲
RF/IF Amps					▲				▲				▲
AC Power Control					▲		▲			▲	▲		
Ordnance								▲					

Product Index

DEVICE	PAGE	DEVICE	PAGE
μ A702	16	μ A9617	295
μ A703	23	μ A9620	211
μ A709	25	μ A9621	217
μ A710	32	μ A9622	223
μ A711	36	μ A9624	227
μ A715	40	μ A9625	227
μ A716	47	μ A9644	233
μ A722	50	μ A9650	298
μ A723	53	CA3018	237
μ A725	60	CA3018A	237
μ A726	68	CA3019	237
μ A727	71	CA3026	237
μ A729	75	CA3036	237
μ A730	78	CA3039	237
μ A732	84	CA3045	237
μ A733	87	CA3046	237
μ A734	93	CA3054	237
μ A739	100	CA3064	253
μ A740	104	CA3065	257
μ A741	107	CA3066	293
μ A742	114	CA3067	293
μ A746	118	CA3068	294
μ A747	122	CA3075	291
μ A748	128	CA3076	291
μ A749	136	CA3086	237
μ A750	299	LM101A	260
μ A754	142	LM108A	299
μ A757	146	LM109	267
μ A760	152	SN7524/5	271
μ A767	157	SN55/75107	296
μ A776	160	SN55/75108	296
μ A777	169	SN55/75109	296
μ A780	176	SN55/75110	296
μ A781	182	SN75325	297
μ A782	292	SN75450	275
μ A791	290	SN75451	297
μ A795	187	TAA630 (Formerly μ A786)	280
μ A796	191	TAA640 (Formerly μ A784)	283
μ A7800	196	TBA550 (Formerly μ A785)	285
μ A9614	203	TBA641B (Formerly μ A706)	290
μ A9615	207	ULN2131 (Formerly μ A753)	292
μ A9616	295		

Selection Guides

Consumer Products
Line Drivers/Receivers
Operational Amplifiers
Voltage Comparators

SELECTION GUIDE FOR CONSUMER TV CIRCUITS

CHROMA PROCESSING AND DEMODULATION

PARAMETER	$\mu A780/781/746$	$\mu A3066/3067$	$\mu A782$
ACC Figure of Merit	$\Delta V_{out} = -3 \text{ dB for } \Delta V_{in} = -20 \text{ dB}$	$\Delta V_{out} = 3 \text{ dB for } \Delta V_{in} = -20 \text{ dB}$	$\Delta V_{out} = 3 \text{ dB for } \Delta V_{in} = -20 \text{ dB}$
Chroma Input Resistance	2.4 k Ω	50 k Ω	1.8 k Ω
Demodulator Output Resistance	300 Ω	5 Ω	50 Ω
Max B-Y Output	10 volts	3.6 volts	7 volts
Chroma Input for Max Demodulator Output	200 mV	200 mV	20 mV
Number of External Components	77	62	42
Number of Alignment Adjustments	4	7	5

SOUND IF AND DETECTOR*

PARAMETER	$\mu A754$	TAA640**	CA3065**
Sensitivity (μV)	70	100	200
AMR (dB) at 30% AM	50	44	50
Audio Output (Volts) RMS	3.0	1.6	2.5
IF Voltage Gain (dB)	72	76	68
Detector—Recovered Audio Voltage at Detector Out (mV)	450	—	750

*Typical measurements made at 4.5 MHz for the $\mu A754/CA3065$ and 5.5 MHz for the TAA640 (formerly $\mu A784$)

**Includes DC Volume Control

SELECTION GUIDE FOR LINE DRIVERS/INTERFACE DRIVERS

Key Features	μA9614	μA9616 (1)	μA9621	μA9624 (2)	μA9644 (3, 4)	75450 (3,5)
Supply Voltages	+5.0	+12 -12	+5.0 +12	+5.0 0 to -30	+5.0	+5.0
V_{IH} (V)	51 59	1.7 1.8	2.0 2.0	1.9 1.9	2.1 2.1	
V_{IL} (V)	51 59	0.9 0.85	1.0 1.0	1.1 1.1	1.0 0.85	
V_{OH} (V)		+3.2	+4.3	-0.5	30 Max	30 Max
V_{OL} (V)		+0.2	+0.2	+0.2	0.8 1.25	0.4
I_O (on) (mA)					500	250
I_O (off) (μA)					100	100
I_{SC} (mA)	-90	+15 -15	300	-20		
P_D (mW)	175	250	120	40	120	30
t_{pd} (ns)	16	300	10	120	50	

NOTES FOR LINE DRIVERS/INTERFACE DRIVERS

1. The μA9616 is a triple EIA line driver. Each driver incorporates an internal response control circuit. The slew rate is a maximum of 30 V/ μs and a minimum of 4 V/ μs (3% of unit interval at 20 k band). The two values for I_{SC} are the typical V_{OH} and V_{OL} short circuit currents. The t_{pd} is measured from 1.5 V on the input to the output passing through the 0 V point. The delay is caused by the internally controlled slew rate of the output. The μA9616 meets the electrical interface requirements of EIA-RS-232-C and the CCITT recommendation V.24. By using an external capacitor from the output to ground for wave shaping, the μA9616 will also meet the low level digital interface for MIL STD 188C.
2. The μA9624 is designed to operate with a V_{DD} from 0 to -30 V.
3. The V_{OH} value is a maximum stand off voltage on the collector of the output device. I_O (on) is the maximum steady state current sinking capability of the output device. I_O (off) is the maximum leakage current into the output with the output device off.
4. V_{OL} is the typical V_{CE} (sat) of the output device at collector currents of 100 mA ($V_{OL} = 0.8$ V) and 500 mA ($V_{OL} = 1.25$ V).
5. V_{OL} is a typical V_{CE} (sat) of the output transistor at collector currents of 100 mA ($V_{OL} = 0.25$ V) and 300 mA ($V_{OL} = 0.5$ V).

SELECTION GUIDE FOR LINE RECEIVERS/INTERFACE RECEIVERS

Key Features	μA9615 (1)	μA9617 (1, 2)	μA9620 (1, 3)	μA9622 (1)	μA9625 (1, 4)
Supply Voltages	+5.0	+5.0	+5.0 +12	+5.0 -10	+5.0 -11 to -30
V_{OL} (V)	51 59	0.40 0.40	0.40 0.45	0.40 0.45	0.40 0.50
V_{OH} (V)	51 59	2.4 2.4	3.0 3.0	3.0 3.0	2.6 2.6
V_{TH} (V)		± 0.5	± 0.5	± 2.0	-3.0 -9.0
VCM (V)		± 15	± 15	± 10	
R_{IN} (k Ω)		7	2.4	5	22
P_{DISS} (mW)		175	110	140	60
t_{pd} (ns)		28	30	35	70
Diff. Inputs	X		X	X	
Output Enable	X			X	
Response Control	X	X	X		
Line Terminator	X	X		X	
Wired-OR Output	X	X	X	X	
Failsafe Control		X		X	

NOTES FOR LINE RECEIVERS/INTERFACE RECEIVERS

- V_{OL} is the worst-case, guaranteed maximum output low voltage at 25°C. V_{OH} is the worst-case, guaranteed minimum output high voltage at 25°C. Upper listed voltages are for 51 grade (temperature range -55°C to +125°C) devices, while lower voltages are for 59 grade (0°C to 70°C) devices.
- The $\mu A9617$ receiver has a V_{TH} of 1.0 when the hysteresis pin is left open. If the response control pin is shorted to the hysteresis pin, the $\mu A9617$ receiver will operate with a typical 1.3 volts of hysteresis (i.e. $V_{IH} = 20$ V, $V_{IL} = 0.7$ V). With or without hysteresis, the receiver in the $\mu A9617$ operates in a failsafe mode as described in section 2.5 of EIA RS-232-C. The inputs are protected to ± 25 volts (reference to ground). The $\mu A9617$ also meets the CCITT recommendation V.24.
- The $\mu A9620$ provides two sets of differential inputs to each receiver: a 5 to 1 attenuated input (normally used) and a direct input. The V_{TH} and V_{CM} shown refer to the attenuated inputs. Divide the values by a factor of five to find values for the direct inputs. The response control on the $\mu A9620$ may be achieved by using two capacitors for each receiver; one from each direct input to ground. The attenuator inputs are connected to the line.
- The $\mu A9625$ is not a line receiver; it is a dual MOS to TTL logic level converter. The negative 3.0 V V_{TH} is the guaranteed worst case V_{IH} necessary to produce a V_{OH} . The supply voltage range of -11 to -30 V is the min and max V_{DD} voltages allowable.

SELECTION GUIDE FOR COMMERCIAL GRADE OPERATIONAL AMPLIFIERS*

Key Features	$\mu A702^x$	$\mu A709$	$\mu A715$	$\mu A725$	$\mu A739$	$\mu A740$	$\mu A741$	$\mu A747$
	Wide Band General Purpose	General Purpose	High Slew Rate Wide Band	High Accuracy Low Drift Excellent Stability	Low Noise Dual	High Z_{in} $10^{12}\Omega$ High Slew Rate	Internally Compensated General Purpose	Dual
Input Offset Voltage Max. (mV)	5.0	7.5	7.5	2.5	6.0	100	6.0	6.0
Input Offset Current Max. (nA)	2000	500	250	35	1000		200	200
Input Bias Current Max. (nA)	7500	1500	1500	125	2000	2.0	500	500
Minimum Voltage Gain (V/mV)	3.4	15	10	250	6.5	25	20	20
Operating Supply Voltage Range Min. (V)	+6, -3	± 9.0	± 6.0	± 3.0	± 4.0	± 5.0	± 5.0	± 5.0
Max. (V)	+14, -7	± 18	± 18	± 22	± 18	± 22	± 18	± 18
Unity Gain Bandwidth (MHz)	30	5.0	65	2.0	10	3.0	1.0	1.0
Slew Rate $A_{CL} = 1$ (V/ μs)	3.5	0.3	18		1.0	6.0	0.5	0.5
$A_{CL} = -1$ (V/ μs)	3.5	0.3	100		2.5	6.0	0.5	0.5
$A_{CL} = 10$ (V/ μs)	5.0	3.0	38		8.0	6.0	0.5	0.5
Input Voltage Range (V)	+1.5, -6.0	± 10	± 15	± 22	± 15	± 15	± 15	± 15
Differential Input Voltage (V)	± 5.0	± 5.0	± 15	± 22	± 5.0	± 30	± 30	± 30
Temp. Coefficient of Input Offset Voltage [†] ($\mu V/^{\circ}C$)	10	10	6.0	0.5	4.0	20	7.0	7.0
Internal Compensation						x	x	x
Offset Adjust		x	x	x	x	x	x	x
Input Protection			x	x	x	x	x	x
Output Protection				x	x	x	x	x

SELECTION GUIDE FOR COMMERCIAL GRADE OPERATIONAL AMPLIFIERS*(Continued)

Key Features	$\mu A748$	$\mu A749$	$\mu A776$		$\mu A777$	LM201	LM301A
	Extended Bandwidth General Purpose	Dual Low Cost	Programmable		Precision	Extended Bandwidth General Purpose	Precision
			$I_{SET} = 1.5 \mu A$	$I_{SET} = 15 \mu A$			
Input Offset Voltage Max. (mV)	6.0	6.0	6.0	6.0	7.5	7.5	7.5
Input Offset Current Max. (nA)	200	500	6.0	25	50	200	50
Input Bias Current Max. (nA)	500	1000	10	50	250	500	250
Minimum Voltage Gain (V/mV)	20	15	50	50	25	20	25
Operating Supply Voltage Range Min. (V)	± 5.0	± 4.0	± 1.2	± 1.2	± 5.0	± 5.0	± 5.0
Max. (V)	± 18	± 18	± 18	± 18	± 20	± 20	± 20
Unity Gain Bandwidth (MHz)	1.0	10	0.2	1.0	1.0	1.0	1.0
Slew Rate $A_{CL} = 1$ (V/ μs)	0.5	1.5	0.1	0.7	0.5	0.5	0.5
$A_{CL} = -1$ (V/ μs)	6.0	2.5	0.1	0.7	6.0	6.0	6.0
$A_{CL} = 10$ (V/ μs)	2.0	8.0	0.1	0.7	2.0	2.0	2.0
Input Voltage Range (V)	± 15	± 15	± 15	± 15	± 15	± 15	± 15
Differential Input Voltage (V)	± 30	± 5.0	± 30	± 30	± 30	± 30	± 30
Temp. Coefficient of Input Offset Voltage [†] ($\mu V/^{\circ}C$)	7.0	3.0	3.0	3.0	3.0	7.0	6.0
Internal Compensation			x	x			
Offset Adjust	x	x	x	x	x	x	x
Input Protection	x	x	x	x	x	x	x
Output Protection	x	x	x	x	x	x	x

* $V_S = \pm 15$ V, $T_A = 25^{\circ}C$ unless otherwise specified

[†] Typical value, $0^{\circ}C \leq T_A \leq 70^{\circ}C$

x $V_S = +12, -6$ V

SELECTION GUIDE FOR MILITARY GRADE OPERATIONAL AMPLIFIERS*

Key Features	$\mu A702^x$ Wide Band General Purpose	$\mu A709$ (312) General Purpose	$\mu A709A$ (311) General Purpose	$\mu A715$ High Slew Rate Wide Band	$\mu A725$ High Accuracy Low Drift Excellent Stability	$\mu A740$ High Z_{in} $10^{12} \Omega$ High Slew Rate	$\mu A741$ Internally Compensated General Purpose	$\mu A747$ Dual
Input Offset Voltage Max. (mV)	2.0	5.0	2.0	5.0	1.0	20	5.0	5.0
Input Offset Current Max. (nA)	500	200	50	250	20		200	200
Input Bias Current Max. (nA)	5000	500	200	750	100	0.2	500	500
Minimum Voltage Gain (V/mV)	3.6	25	25	15	1000	50	50	50
Operating Supply Voltage Range Min. (V)	+6, -3	± 9.0	± 9.0	± 6.0	± 3.0	± 5.0	± 5.0	± 5.0
Max. (V)	+14, -7	± 18	± 18	± 18	± 22	± 22	± 22	± 22
Unity Gain Bandwidth (MHz)	30	5.0	5.0	65	2.0	3.0	1.0	1.0
Slew Rate $A_{CL} = 1$ (V/ μs)	3.5	0.3	0.3	18		6.0	0.5	0.5
$A_{CL} = -1$ (V/ μs)	3.5	0.3	0.3	100		6.0	0.5	0.5
$A_{CL} = 10$ (V/ μs)	5.0	3.0	3.0	38		6.0	0.5	0.5
Input Voltage Range (V)	+1.5, -6.0	± 10	± 10	± 15	± 22	± 15	± 15	± 15
Differential Input Voltage (V)	± 5.0	± 5.0	± 5.0	± 15	± 22	± 30	± 30	± 30
Temp. Coefficient of Input Offset Voltage [†] ($\mu V/^{\circ}C$)	10	10	1.8	6.0	0.5	20	7.0	7.0
Internal Compensation						x	x	x
Offset Adjust		x	x	x	x	x	x	x
Input Protection				x	x	x	x	x
Output Protection					x	x	x	x

SELECTION GUIDE FOR MILITARY GRADE OPERATIONAL AMPLIFIERS* (Continued)

Key Features	$\mu A748$ Extended Bandwidth General Purpose	$\mu A749$ Dual Low Cost	$\mu A776$ Programmable $I_{SET} = 1.5 \mu A$ $I_{SET} = 15 \mu A$		$\mu A777$ Precision	LM101 Extended Bandwidth General Purpose	LM101A Precision
Input Offset Voltage Max. (mV)	5.0	3.0	5.0	5.0	2.0	5.0	2.0
Input Offset Current Max. (nA)	200	400	3.0	15	10	200	10
Input Bias Current Max. (nA)	500	750	7.5	50	75	500	75
Minimum Voltage Gain (V/mV)	50	25	50	50	50	50	50
Operating Supply Voltage Range Min. (V)	± 5.0	± 4.0	± 1.2	± 1.2	± 5.0	± 5.0	± 5.0
Max. (V)	± 22	± 18	± 18	± 18	± 20	± 20	± 20
Unity Gain Bandwidth (MHz)	1.0	10	0.2	1.0	1.0	1.0	1.0
Slew Rate $A_{CL} = 1$ (V/ μs)	0.5	1.5	0.1	0.7	0.5	0.5	0.5
$A_{CL} = -1$ (V/ μs)	6.0	2.5	0.1	0.7	6.0	6.0	6.0
$A_{CL} = 10$ (V/ μs)	2.0	8.0	0.1	0.7	2.0	2.0	2.0
Input Voltage Range (V)	± 15	± 15	± 15	± 15	± 15	± 15	± 15
Differential Input Voltage (V)	± 30	± 5.0	± 30	± 30	± 30	± 30	± 30
Temp. Coefficient of Input Offset Voltage [†] ($\mu V/^{\circ}C$)	7.0	3.0	3.0	3.0	3.0	3.0	3.0
Internal Compensation			x	x			
Offset Adjust	x	x	x	x	x	x	x
Input Protection	x	x	x	x	x	x	x
Output Protection	x	x	x	x	x	x	x

* $V_S = \pm 15 V$, $T_A = 25^{\circ}C$ unless otherwise specified

[†] Typical value, $-55^{\circ}C \leq T_A \leq 125^{\circ}C$

x $V_S = +12, -6 V$

SELECTION GUIDE FOR COMMERCIAL GRADE VOLTAGE COMPARATORS ⁽¹⁾

PARAMETER	$\mu A710$	$\mu A711$	$\mu A734$	$\mu A760$
Input Offset Voltage, Max. (mV) (2)	5.0	5.0	7.5	6.0
Temperature Coefficient of Input Offset Voltage ($\mu V/^{\circ}C$)	5.0	5.0	3.5	3.0
Input Bias Current, Max. (μA)	40	150	0.15	60
Input Offset Current, Max. (μA)	7.5	25	0.045	7.5
Supply Voltage (V)	+12, -6.0	+12, -6.0	± 5.0 to ± 15	± 4.5 to ± 6.5
Response Time (ns)	40	40	200	16
Input Voltage Range (V)	± 5.0 (3)	± 5.0 (3)	± 5.0	± 4.0
Output Voltage Swing (V)	-0.5 to -3.2	-0.5 to +3.2	0 to +8.0	0 to ± 3.0
Voltage Gain, Min. (V/mV)	0.8	0.5	25	5.0 (4)
Power Consumption, Max. (mW)	150	230 (5)	145	325
TTL Fanout	1	1	2	2
Diff. Input Voltage Range (V)	± 5.0	± 5.0	± 10	± 5.0

- (1) Typical values at $25^{\circ}C$ unless otherwise specified.
- (2) Minimum and maximum values are for $0^{\circ}C \leq T_A \leq 70^{\circ}C$.
- (3) $V^- = -7.0 V$.
- (4) Typical.
- (5) $T_A = +25^{\circ}C$.

SELECTION GUIDE FOR MILITARY GRADE VOLTAGE COMPARATORS ⁽¹⁾

PARAMETER	$\mu A710$	$\mu A711$	$\mu A734$	$\mu A760$
Input Offset Voltage, Max. (mV) (2)	3.0	4.5	4.0	6.0
Temperature Coefficient of Input Offset Voltage ($\mu V/^{\circ}C$)	3.5	5.0	2.5	3.0
Input Bias Current, Max. (μA)	45	150	0.15	60
Input Offset Current, Max. (μA)	7.0	20	0.02	7.5
Supply Voltage (V)	+12, -6.0	+12, -6.0	± 5.0 to ± 15	± 4.5 to ± 6.5
Response Time (ns)	40	40	200	16
Input Voltage Range (V)	± 5.0 (3)	± 5.0 (3)	± 10	± 4.0
Output Voltage Swing (V)	-0.5 to +3.2	-0.5 to +3.2	0 to +8.0	0 to +3.0
Voltage Gain, Min. (V/mV)	1.0	0.5	25	5.0 (4)
Power Consumption, Max. (mW)	150	200 (5)	145	312
TTL Fanout	1	1	2	2
Diff. Input Voltage Range (V)	± 5.0	± 5.0	± 10	± 5.0

- (1) Typical values at $20^{\circ}C$ unless otherwise specified.
- (2) Maximum and minimum values are for $-55^{\circ}C \leq T_A \leq +125^{\circ}C$.
- (3) $V^- = -7.0 V$.
- (4) Typical.
- (5) $T_A = +25^{\circ}C$.

Competitive Cross-Reference

MOTOROLA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	MOTOROLA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
MC1303L		U6A7739393	MC1445F		U3F7733312
MC1304P	U6A7732394		MC1445G		U5F7733393
MC1304PQ	U7F7732394		MC1445L		U6A7733393
MC1305P	U6A7729394		MC1446L		U6A7733393
MC1305PQ	U7F7729394		MC1456G		U5T7725393
MC1307P	U6A7767394		MC1458G		U5F7747393
MC1307PQ	U7F7767394		MC1458P		U6A7747393
MC1326PQ		U7F7746394	MC1460G		U5R7723393
MC1326P		U6A7746394	MC1460R		U5R7723312
MC1328G	U5E7746394		MC1461G		U5R7723393
MC1328P	U6A7746394		MC1461R		U5R7723393
MC1328PQ	U7F7746394		MC1463R		U5R7723393
MC1345P		TBA550	MC1466L		U6A7723393
MC1350P		U6A7757394	MC1469R		U5R7723393
MC1351P		U6A7754394	MC1488L		U6A9616393
MC1352P		U6A7757394	MC1489L		U6A9617393
MC1353P		U6A7757394	MC1489AL		U6A9617393
MC1353PQ		U7F7757394	MC1495L	U6A7795393	
MC1355P		U6A7754394	MC1496G	U5E7796393	
MC1355PQ		U7F7754394	MC1510F		U3F7733312
MC1357P		U6A7754394	MC1510G		U5F7733312
MC1357PQ		U7F7754394	MC1514L		U6A7711312
MC1414L		U6A7711393	MC1519G		U5F7733312
MC1414P		U6A7711393	MC1520F		U3F7101311
MC1429G		U5B7730393	MC1520G		U5B7101311
MC1430F		U3F7702312	MC1525G		U5B7730312
MC1430G		U5B7702393	MC1526G		U5B7730312
MC1430L		U6A7702393	MC1529G		U5B7730312
MC1430P		U6A7702393	MC1530F		U3F7702312
MC1431F		U3F7702312	MC1530G		U5B7702312
MC1431G		U5B7702393	MC1531F		U3F7702312
MC1431L		U6A7702393	MC1531G		U5B7702312
MC1431P		U6A7702393	MC1533F		U3F7101311
MC1433F		U3F7101311	MC1533G		U5B7101311
MC1433G		U5B7101392	MC1533L		U6A7101311
MC1433L		U6A7101392	MC1535F		U6A7749312
MC1436G		U5B7101392	MC1535G		U6A7749312
MC1437L		U6A7749393	MC1536G		U5B7741312
MC1437P		U6A7749393	MC1537L		U6A7749312
MC1438P		U6A7749393	MC1539G		U5B7101311
MC1439G		U5B7101392	MC1539L		U6A7101311
MC1439L		U6A7101392	MC1540F		SN7525
MC1440F		SN7525	MC1540G		SN7525
MC1440G		SN7525	MC1540L		SN7525
MC1440L		SN7525	MC1541F		SN7524
MC1440P		SN7525	MC1541L		SN7524
MC1441F		SN7524	MC1543L		SN7524
MC1441L		SN7524	MC1545F		U3F7733312
MC1441P		SN7524	MC1545G		U5F7733312

MOTOROLA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	MOTOROLA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
MC1545L		U6A7733312	MC1710F	U3F7710312	
MC1546L		U6A7733312	MC1710G	U5B7710312	
MC1550F		U6A7757312	MC1710L	U6A7710312	
MC1550G		U6A7757312	MC1711CF	U3F7711312	
MC1552G		U5F7715312	MC1711CG	U5F7711393	
MC1553G		U5F7715312	MC1711CL	U6A7711393	
MC1556G		U5T7725312	MC1711F	U3F7711312	
MC1558G		U5F7747312	MC1711G	U5F7711312	
MC1558P		U6A7747312	MC1711L	U6A7711312	
MC1560G		U5R7723312	MC1712CF	U3F7702312	
MC1560R		U5R7723312	MC1712CG	U5B7702393	
MC1561G		U5R7723312	MC1712CL	U6A7702393	
MC1561R		U5R7723312	MC1712F	U3F7702312	
MC1563R		U5R7723312	MC1712L	U6A7702312	
MC1566L		U6A7723312	MC1723CG	U5R7723393	
MC1569R		U5R7723312	MC1723G	U5R7723312	
MC1580L		U6B961551X	MC1723CL	U6A7723393	
MC1582L		U6B961451X	MC1723L	U6A7723312	
MC1583L		U6B961551X	MC1741CF	U3F7741312	
MC1584L		U6B961551X	MC1741CG	U5B7741393	
MC1590G		U6A7757394	MC1741CL	U6A7741393	
MC1595L	U6A7795393		MC1741CP	U9T7741393	
MC1596G	U6A7796312		MC1741F	U3F7741312	
MC1709CF	U3F7709312		MC1741G	U5B7741312	
MC1709CG	U5B7709393		MC1741G	U5B7702312	
MC1709CL	U6A7709393		MC1741L	U6A7741312	
MC1709F	U3F7709312		MFC4060		U5R7723393
MC1709G	U5B7709312		MFC6010		U5Z7703394
MC1709L	U6A7709312		MFC8000		U6A7739393
MC1710CF	U3F7710312		MFC8001		U6A7739393
MC1710CG	U5B7710393		MFC8002		U6A7739393
MC1710CL	U6A7710393		MFC8040		UGH7791393

NATIONAL	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	NATIONAL	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
LH101		U5B7741312	LM112		U5B7776312
LH101D		U6A7741312	LM201	LM201	
LH101F		U3F7741312	LM201A	LM201A	
LH201		U5B7741393	LM201AF	LM201AF	
LH740A		U5B7740312	LM201AD	LM201AD	
LH740AC		U5B7740393	LM207		U5B7741312
LM100		U5R7723312	LM207D		U6A7741312
LM101	LM101		LM207F		U3F7741312
LM101A	LM101A		LM209K	LM209K	
LM101AD	LM101AD		LM210		U5B7741312
LM101D	LM101D		LM211		U5B7734312
LM101F	LM101F		LM212		U5B7776312
LM104		U5R7723312	LM300		U5R7723393
LM105		U5R7723312	LM301A	LM301A	
LM106		U5B7710312	LM301AD	LM301AD	
LM106F		U3F7710312	LM301AF	LM301AF	
LM107		U5B7741312	LM304		U5R7723393
LM107D		U6A7741312	LM305		U5R7723393
LM107F		U3F7741312	LM306		U5B7710393
LM109K	LM109K		LM307		U5B7741393
LM110		U5B7741312	LM307D		U6A7741393
LM111		U5B7734312			

NATIONAL	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	NATIONAL	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
LM307F		U3F7741393	LM711C	U5F7711393	
LM309K	LM309K		LM711CN	U6A7711393	
LM310		U5B7741393	LM723	U6R7723312	
LM311		U5B7734393	LM723C	U5R7723393	
LM312		U5B7776393	LM741	U5B7741312	
LM376		U6A7723393	LM741C	U5B7741393	
LM701C	U5B7710393		LM748	U5B7748312	
LM703L	U5B7703393		LM748C	U5B7748393	
LM709	U5B7709312		LM1303	U6A7739393	
LM709A	U5B7709311		LM1304	U6A7732394	
LM709C	U5B7709393		LM1305	U6A7732394	
LM709CN	U6A7709393		LM1458		U5F7747312
LM710	U5B7710312		LM1558		U5F7747393
LM710A	U5B7710312		LM3065	CA3065	
LM710CN	U6A7710393		LM7524	SN7524	
LM711	U5F7711312		LM7525	SN7525	

RCA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	RCA	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
CA3000		U5B7702312	CA3035		U6A7739393
CA3001		U5F7733312	CA3036	CA3036	
CA3002		U5Z7703394	CA3037		U6A7709312
CA3004		U5Z7703394	CA3038		U6A7709312
CA3005		U5Z7703394	CA3039	CA3039	
CA3006		U5Z7703394	CA3040		U5F7733312
CA3007		U5B7716393	CA3041		CA3065
CA3008		U3F7702312	CA3042		CA3065
CA3010		U5B7702312	CA3043		CA3065
CA3011		U5E7754394	CA3044		
CA3012		U5E7754394	CA3045	CA3045	
CA3013		U5E7754394	CA3046	CA3046	
CA3014		U5Z7754394	CA3047		U6A7709393
CA3015		U5B7702312	CA3048		U6A7749393
CA3016		U3F7702312	CA3052		U6A7739393
CA3018	CA3018		CA3053		U5Z7703394
CA3019	CA3019		CA3054	CA3054	
CA3021		U6A7757394	CA3055		U5R7723312
CA3022		U6A7757394	CA3056A		U5B7702312
CA3023		U6A7757394	CA3059		U6A7742393
CA3026	CA3026		CA3060		U6A7739393
CA3028		U5Z7703394	CA3064	CA3064	
CA3028A		U5Z7703394	CA3065	CA3065	
CA3029		U6A7702393	CA3066	CA3066	
CA3030		U6A7702393	CA3067	CA3067	
CA3031	U5B7702312		CA3068	CA3068	
CA3032	U5B7702393		CA3075	CA3075	
CA3033		U6A7709312	CA3076	CA3076	

SIGNETICS	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	SIGNETICS	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
SE501K		U5B7733312	S5595F	U6A7795393	
NE501K		U5B7733393	S5596K	U5E7796312	
NE501A		U6A7733393	N5596K	U5E7796393	
NE510A		U6A7754394	N5596A		U6A7796393
NE511A		CA3045	S5709T	U5B7709312	
SE515K		U5B7730312	N5709T	U5B7709393	
NE515K		U5B7730393	N5709A		U6A7709393
SE518K		U5F7711312	S5710T	U5B7710312	
NE518K		U5F7711393	N5710T	U5B7710393	
NE518A		U6A7711393	N5710A		U6A7710393
SE526K		U5B7710312	S5711K	U5F7711312	
NE526K		U5B7710393	S5711T		U5F7711312
NE526A		U6A7710393	N5711K	U5E7711393	
NE528B		U7B7525393	N5711A		U6A7711393
SE528E		U7B7525312	S5723L	U5R7723312	
SE528R		U7B7525312	N5723L	U5R7723393	
SE531T		U5F7715312	N5723A		U6A7723393
NE531T		U5F7715393	S5733K	U5F7733312	
SE533T		U5B7776312	N5733K	U5F7733393	
NE533T		U5B7776393	N5733A		U6A7733393
SE536T	U5B7740312		S5733F	U6A7733312	
NE536T	U5B7740393		S5740T	U5B7740312	
SE550L		U5R7723312	N5740T	U5B7740393	
NE550L		U5R7723393	S5741T	U5B7741312	
NE550A		U6A7723393	N5741T	U5B7741393	
S5101T	U5B7101312		N5741A		U6A7741393
S51A1T		U5B7101312	N5741V	U9T7741393	
S51A8T		U5B7108312	S5748T	U5B7748312	
N5201T	U5B7101333		N5748T	U5B7748393	
N5201A		U6A7101333	N5748A		U6A7748393
N53A1T		U5B7101392	N5748V	U9T7748393	
N53A1V		U9T7101393	N7524B	SN7524	
N53A8T		U5B7108392	N7525B	SN7525	
N5595A		U6A7795393			

SPRAGUE	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	SPRAGUE	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
ULN2111A		U6A7754394	ULN2124A	U6B7780394	
ULN2111N		U7F7754394	ULN2124N	U7F7780394	
ULN2113A		U6A7754394	ULN2126A		U6A7739393
ULN2113N		U7F7754394	ULN2126N		U7F7739393
ULN2114A	U6A7746394		ULN2127A	U6A7781394	
ULN2114K	U5E7746394		ULN2127N	U7F7781394	
ULN2114N	U7F7746394		ULN2128A	U6A7767394	
ULN2114W	U5E7746394		ULN2128N	U7F7767394	
ULN2120A	U6A7732394		ULN2129A	CA3075	
ULN2120N	U7F7732394		ULN2129N	CA3075	
ULN2121A		U6A7767394	ULN2131A		U6A7754394
ULN2121N		U7F7767394	ULN2131N		U7F7754394
ULN2122A	U6A7729394		ULN2165A	CA3065	
ULN2122N	U7F7729394		ULN2165N	CA3065	

TI	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	TI	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
SN5512L		U5F7733312	SN73710N	U6A7710393	
SN7512L		U5F7733393	SN72710L	U5B7710393	
SN5514L		U5F7733312	SN72710S	U3F7710393	
SN7514L		U5F7733393	SN52810J		U6A7710312
SN55107AJ	SN55107J		SN52810N		U6A7710312
SN75107AJ	SN75107J		SN52810L		U5B7710312
SN75107AN	SN75107N		SN52810Z		U3F7710312
SN55108AJ	SN55108J		SN72810J		U6A7710393
SN75108AJ	SN75108J		SN72810J		U6A7710393
SN75108AN	SN75108N		SN72810P		U6A7710393
SN55109J	SN55109J		SN72810L		U5B7710393
SN75109J	SN75109J		SN72810Z		U3F7710312
SN75109N	SN75109N		SN52510J		U6A7710312
SN55110J	SN55110J		SN52510N		U6A7710312
SN75110J	SN75110J		SN52510L		U5B7710312
SN75110N	SN75110N		SN52510Z		U3F7710312
SN75150J		U6A9616393	SN72510J		U6A7710393
SN75150N		U6A9616393	SN72510N		U6A7710393
SN75150P		U6A9616393	SN72510P		U6A7710393
SN75100L		U7B961559X	SN72510L		U5B7710393
SN75154J		U6A9617393	SN72510Z		U3F7710312
SN75154N		U6A9617393	SN52711J	U6A7711312	
SN52702AL		U5B7702312	SN52711N	U6A7711312	
SN52702AS		U3F7702312	SN52711L	U5F7711312	
SN52702L		U5B7702312	SN52711S	U3F7711312	
SN52702S		U3F7702312	SN72711J	U6A7711393	
SN72702N		U6A7702393	SN72711N	U6A7711393	
SN52702N		U6A7702312	SN72711L	U5F7711393	
SN72702L		U5B7702312	SN72711S	U3F7711312	
SN72702S		U3F7702312	SN52811J		U6A7711312
SN52101J	LM101D		SN52811N		U6A7711312
SN52101AL	LM101AH		SN52811L		U5F7711312
SN52101AZ	LM101AF		SN72811J		U6A7711393
SN72301AJ	LM301AD		SN72811P		U6A7711393
SN72301AN	LM301AD		SN72811L		U5F7711393
SN72301AL	LM301AH		SN2720N		U6A7711393
SN72301AZ	LM301AF		SN52820J		U6A7734312
SN52107J		U6A7777312	SN52820N		U6A7734312
SN52107L		U5B7777312	SN72820J		U6A7734393
SN52107S		U3F7777312	SN52733N	U6A7733312	
SN72107J		U6A7777393	SN52733L	U5F7733393	
SN72307N		U6A7777393	SN72733N	U6A7733393	
SN72307P		U9T7777393	SN72733L	U5F7733393	
SN72307L		U5B7777393	SN5510L		U5F7733312
SN72307Z		U3F7777312	SN5510F		U3F7733312
SN52709AL	U5B7709311		SN52741J	U6A7741312	
SN52709AS	U3F7709311		SN52741N	U6A7741312	
SN52709AN	U6A7709311		SN52741L	U5B7741312	
SN52709AJ	U6A7709311		SN52741Z	U3F7741312	
SN52709N	U6A7709312		SN72741N	U6A7741393	
SN52709J	U6A7709312		SN72741J	U6A7741393	
SN52709L	U5B7709393		SN72741P	U9T7741393	
SN52709S	U3F7709312		SN72741L	U5B7741393	
SN72709N	U6A7709393		SN72741Z	U3F7741312	
SN72709J	U6A7709393		SN52558L		U5F7747312
SN72709L	U5B7709393		SN72558P		U7A7747393
SN72709S	U3F7709312		SN72558L		U5F7747312
SN52701J	U6A7710312		SN52747J	U7A7747312	
SN52710N	U6A7710312		SN52747N	U7A7747314	
SN52710L	U5B7710312		SN52747L	U5F7747312	
SN52710S	U3F7710312		SN72747J	U7A7747393	
SN72710J	U6A7710393		SN72747N	U7A7747393	

TI	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT	TI	FAIRCHILD DIRECT REPLACEMENT	FAIRCHILD FUNCTIONAL EQUIVALENT
SN72747L	U5F7747393		SN75451AP	SN75451P	
SN52748J	U6A7748312		SN72400N		U6A7723393
SN52748N	U6A7748312		SN72400L		U5R7723393
SN52748L	U5B7748312		SN56514J		U6A7796393
SN52748Z	U3F7748312		SN56514N		U6A7706393
SN72748J	U6A7748393		SN56514L		U5F7796393
SN72748N	U6A7748393		SN76110N	U6A7767394	
SN72748P	U9T7748393		SN76104	U6A7732394	
SN72748L	U5B7748393		SN76105	U6A7729394	
SN72748Z	U3F7748312		SN76131	U6A7739393	
SN52770L		U5B7740312	SN76242	U6B7780394	
SN72770L		U5B7740393	SN76243	U6A7781394	
SN52771L		U5B7740312	SN76246	U6A7746394	
SN72771L		U5B7740393	SN76630	U6B7786354	
SN7524J	SN7524J		SN76533	U6B7785394	
SN7524N	SN7524N		SN76564	CA3064	
SN7525J	SN7525J		SN76619		U5Z7703394
SN7525N	SN7525N		SN76640		U6A7754394
SN75235J	SN75235J		SN76660		CA3065
SN75235N	SN75235N		SN76665	CA3065	
SN75450AN	SN75450AN		SN76110	U6A7767394	

For Complete Ordering Information See Page 304

LINEAR
LINEAR
LINEAR
LINEAR

μA702

WIDEBAND DC AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μA702 is a complete DC amplifier constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. It is intended for use as an operational amplifier in miniaturized analog computers, as a precision instrumentation amplifier, or in other applications requiring a feedback amplifier useful from DC to 30 MHz.

- **LOW OFFSET VOLTAGE**
- **LOW OFFSET VOLTAGE DRIFT**
- **WIDE BANDWIDTH — 20 MHz TYP.**
- **HIGH SLEW RATE — 5 V/μs TYP.**


ABSOLUTE MAXIMUM RATINGS

Voltage Between V ⁺ and V ⁻ Terminals	21 V
Peak Output Current	50 mA
Differential Input Voltage	±5.0 V
Input Voltage	+1.5 V to -6.0 V
Internal Power Dissipation (Note)	
Metal Can	500 mW
Ceramic DIP	670 mW
Flatpak	570 mW
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 60 seconds)	300°C

NOTE

Rating applies to ambient temperature up to 70°C. Above 70°C ambient derate linearly at 6.3 mW/°C for Metal Can, 8.3 mW/°C for Ceramic DIP and 7.1 mW/°C for the Flatpak package.


EQUIVALENT CIRCUIT



Pin numbers are shown for Metal Can only.

CONNECTION DIAGRAMS

8-LEAD METAL CAN (TOP VIEW)




NOTE: Pin 4 connected to case.

ORDER PART NOS:

U5B7702312

U5B7702393

14-LEAD DIP (TOP VIEW)




ORDER PART NOS.

U6A7702312

U6A7702393

FLATPAK (TOP VIEW)



ORDER PART NOS:

U3F7702312




*Planar is a patented Fairchild process.

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	$V^+ = 12.0\text{ V}, V^- = -6.0\text{ V}$			$V^+ = 6.0\text{ V}, V^- = -3.0\text{ V}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 2\text{ k}\Omega$		0.5	2.0		0.7	3.0	mV
Input Offset Current			180	500		120	500	nA
Input Bias Current			2.0	5.0		1.2	3.5	μA
Input Resistance		16	40		22	67		k Ω
Input Voltage Range		-4.0		+0.5	-1.5		+0.5	V
Common Mode Rejection Ratio	$R_S \leq 2\text{ k}\Omega, f \leq 1\text{ kHz}$	80	100		80	100		dB
Large-Signal Voltage Gain	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 5.0\text{ V}$	2500	3600	6000				
	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 2.5\text{ V}$				600	900	1500	
Output Resistance			200	500		300	700	Ω
Supply Current	$V_{OUT} = 0$		5.0	6.7		2.1	3.3	mA
Power Consumption	$V_{OUT} = 0$		90	120		19	30	mW
Transient Response (unity-gain)	$C_I = 0.01\text{ }\mu\text{F}, R_I = 20\text{ }\Omega,$ $R_L \geq 100\text{ k}\Omega, V_{IN} = 10\text{ mV}$							
			25	120				ns
Risetime			25	120				ns
Overshoot	$C_L \leq 100\text{ pF}$		10	50				%
Transient Response ($\times 100$ gain)	$C_3 = 50\text{ pF}, R_L \geq 100\text{ k}\Omega,$ $V_{IN} = 1\text{ mV}$							
			10	30				ns
Risetime			20	40				%
Overshoot								
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:								
Input Offset Voltage	$R_S \leq 2\text{ k}\Omega$			3.0			4.0	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\text{ }\Omega,$ $T_A = 25^\circ\text{C}$ to $T_A = +125^\circ\text{C}$		2.5	10		3.5	15	$\mu\text{V}/^\circ\text{C}$
	$R_S = 50\text{ }\Omega,$ $T_A = 25^\circ\text{C}$ to $T_A = -55^\circ\text{C}$		2.0	10		3.0	15	$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +125^\circ\text{C}$		80	500		50	500	nA
	$T_A = -55^\circ\text{C}$		400	1500		280	1500	nA
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ\text{C}$ to $T_A = +125^\circ\text{C}$		1.0	5.0		0.7	4.0	nA/ $^\circ\text{C}$
	$T_A = 25^\circ\text{C}$ to $T_A = -55^\circ\text{C}$		3.0	16		2.0	13	nA/ $^\circ\text{C}$
Input Bias Current	$T_A = -55^\circ\text{C}$		4.3	10		2.6	7.5	μA
Input Resistance		6.0			8.0			k Ω
Common Mode Rejection Ratio	$R_S \leq 2\text{ k}\Omega, f \leq 1\text{ kHz}$	70	95		70	95		dB
Supply Voltage Rejection Ratio	$V^+ = 12\text{ V}, V^- = -6\text{ V}$ to $V^+ = 6\text{ V}, V^- = -3\text{ V}$		75	200		75	200	$\mu\text{V}/\text{V}$
	$R_S \leq 2\text{ k}\Omega$							
Large-Signal Voltage Gain	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 5.0\text{ V}$	2000		7000				
	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 2.5\text{ V}$				500		1750	
Output Voltage Swing	$R_L \geq 100\text{ k}\Omega$	± 5.0	± 5.3		± 2.5	± 2.7		V
	$R_L \geq 10\text{ k}\Omega$	± 3.5	± 4.0		± 1.5	± 2.0		V
Supply Current	$T_A = +125^\circ\text{C}, V_{OUT} = 0$		4.4	6.7		1.7	3.3	mA
	$T_A = -55^\circ\text{C}, V_{OUT} = 0$		5.0	7.5		2.1	3.9	mA
Power Consumption	$T_A = +125^\circ\text{C}, V_{OUT} = 0$		80	120		15	30	mW
	$T_A = -55^\circ\text{C}, V_{OUT} = 0$		90	135		19	35	mW

TYPICAL PERFORMANCE CURVES (312 GRADE)




393 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER	CONDITIONS	$V^+ = 12.0\text{ V}, V^- = -6.0\text{ V}$			$V^+ = 6.0\text{ V}, V^- = -3.0\text{ V}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 2\text{ k}\Omega$		1.5	5.0		1.7	6.0	mV
Input Offset Current			0.5	2.0		0.3	2.0	μA
Input Bias Current			2.5	7.5		1.5	5.0	μA
Input Resistance		10	32		16	55		$\text{k}\Omega$
Input Voltage Range		-4.0		+0.5	-1.5		+0.5	V
Common Mode Rejection Ratio	$R_S \leq 2\text{ k}\Omega, f \leq 1\text{ kHz}$	70	92		70	92		dB
Large-Signal Voltage Gain	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 5.0\text{ V}$	2000	3400	6000				
	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 2.5\text{ V}$				500	800	1500	
Output Resistance			200	600		300	800	Ω
Supply Current	$V_{OUT} = 0$		5.0	6.7		2.1	3.3	mA
Power Consumption	$V_{OUT} = 0$		90	120		19	30	mW
Transient Response (unity gain)	$C_I = 0.01\text{ }\mu\text{F}, R_I = 20\text{ }\Omega$							
	$R_L \leq 100\text{ k}\Omega, V_{IN} = 10\text{ mV}$							
Risetime			25	120				ns
Overshoot	$C_L \leq 100\text{ pF}$		10	50				%
Transient Response (x100 gain)	$C_3 = 50\text{ pF}, R_L \geq 100\text{ k}\Omega,$							
	$V_{IN} = 1\text{ mV}$							
Risetime			10	30				ns
Overshoot			20	40				%
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:								
Input Offset Voltage	$R_S \leq 2\text{ k}\Omega$			6.5			7.5	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\text{ }\Omega, T_A = +70^\circ\text{C to } T_A = 0^\circ\text{C}$		5.0	20		7.5	25	$\mu\text{V}/^\circ\text{C}$
Input Offset Current				2.5			2.5	μA
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ\text{C to } T_A = +70^\circ\text{C}$		4.0	10		3.0	8.0	$\text{nA}/^\circ\text{C}$
	$T_A = 25^\circ\text{C to } T_A = 0^\circ\text{C}$		6.0	20		5.5	18	$\text{nA}/^\circ\text{C}$
Input Bias Current	$T_A = 0^\circ\text{C}$		4.0	12		2.7	8	μA
Input Resistance		6.0	18		9.0	27		$\text{k}\Omega$
Common Mode Rejection Ratio	$R_S \leq 2\text{ k}\Omega, f \leq 1\text{ kHz}$	65	86		65	86		dB
Supply Voltage Rejection Ratio	$V^+ = 12\text{ V}, V^- = 6\text{ V to } V^+ = 6\text{ V}, V^- = 3\text{ V}$		90	300		90	300	$\mu\text{V/V}$
	$R_S \leq 2\text{ k}\Omega$							
Large-Signal Voltage Gain	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 5.0\text{ V}$	1500		7000				
	$R_L \geq 100\text{ k}\Omega, V_{OUT} = \pm 2.5\text{ V}$				400		1750	
Output Voltage Swing	$R_L \geq 100\text{ k}\Omega$	± 5.0	± 5.3		± 2.5	± 2.7		V
	$R_L \geq 10\text{ k}\Omega$	± 3.5	± 4.0		± 1.5	± 2.0		V
Supply Current	$V_{OUT} = 0$		5.0	7.0		2.1	3.9	mA
Power Consumption	$V_{OUT} = 0$		90	125		19	35	mW

TYPICAL PERFORMANCE CURVES (393 GRADE)


VOLTAGE TRANSFER CHARACTERISTIC









VOLTAGE TRANSFER CHARACTERISTIC




VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES (312 GRADE)




**COMMON MODE REJECTION RATIO
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**POWER SUPPLY CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE**



**INPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**OUTPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE**




TYPICAL PERFORMANCE CURVES (393 GRADE)


VOLTAGE GAIN
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT BIAS CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGES




INPUT OFFSET CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGES




INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




SUPPLY VOLTAGE REJECTION RATIO
AS A FUNCTION OF
AMBIENT TEMPERATURE




COMMON MODE REJECTION RATIO
AS A FUNCTION OF
AMBIENT TEMPERATURE




POWER SUPPLY CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE



INPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE




OUTPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES (312 AND 393 GRADES)


OUTPUT VOLTAGE SWING
AS A FUNCTION OF
LOAD RESISTANCE




SUPPLY CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGES




COMMON MODE REJECTION RATIO
AS A FUNCTION OF
FREQUENCY




SLEW RATE
AS A FUNCTION OF
CLOSED-LOOP VOLTAGE GAIN
(LAG COMPENSATION)



SLEW RATE
AS A FUNCTION OF
CLOSED-LOOP VOLTAGE GAIN
(LEAD-LAG COMPENSATION)




TRANSIENT RESPONSE




TRANSIENT RESPONSE TEST CIRCUITS


UNITY-GAIN AMPLIFIER
(LAG COMPENSATION)




X100 AMPLIFIER
(LEAD COMPENSATION)




SERIES RESISTANCE LIMITING*



OUTPUT RISE-TIME LIMITING*



LOGIC COMPATIBILITY




*Peak Current Limiting with Capacitive Loads.


Pin numbers are shown for Metal Can only.

TYPICAL PERFORMANCE CURVES (312 AND 393 GRADES)


INPUT VOLTAGE RANGE
AS A FUNCTION OF
SUPPLY VOLTAGES




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGES




VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGES




FREQUENCY RESPONSE FOR
VARIOUS CLOSED-LOOP GAINS
(LAG COMPENSATION)




FREQUENCY RESPONSE
WITH CONSERVATIVE
COMPENSATION NETWORK




FREQUENCY RESPONSE FOR
VARIOUS CLOSED-LOOP GAINS
(LEAD-LAG COMPENSATION)



OUTPUT VOLTAGE SWING
AS A FUNCTION OF
FREQUENCY FOR VARIOUS
LAG COMPENSATION NETWORKS




OUTPUT VOLTAGE SWING
AS A FUNCTION OF FREQUENCY
WITH LEAD-LAG COMPENSATION




FREQUENCY COMPENSATION CIRCUITS

LAG COMPENSATION



LEAD-LAG COMPENSATION



Pin numbers are shown for Metal Can only.

μA703

RF-IF AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA703 is an RF-IF amplifier constructed on a single silicon chip and is intended for use as a limiting or non-limiting amplifier, harmonic mixer, or oscillator to 150 MHz. The low internal feedback of the device insures a higher stability-limited gain than that available from conventional circuitry. Including the biasing network in the same package reduces the number of external components required, thereby increasing the reliability and versatility of the device.

- 29 mmho MINIMUM FORWARD TRANSADMITTANCE
- 1.0 mmho/0.05 mmho MAXIMUM INPUT/OUTPUT CONDUCTANCE
- 12.5 pF/4.0 pF MAXIMUM INPUT/OUTPUT CAPACITANCE


ABSOLUTE MAXIMUM RATINGS

Supply Voltage
Output Collector Voltage
Voltage Between Input Terminals
Internal Power Dissipation
Operating Temperature Range
Storage Temperature Range
Lead Temperature (Soldering, 60 seconds)

20 V
24 V
±5.0 V
500 mW
0°C to + 70°C
-65°C to +150°C
300°C

PHYSICAL DIMENSIONS

in accordance with JEDEC (TO-78) outline




NOTES


All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.95 gram

ORDER PART NO. U5Z7703394

SCHEMATIC DIAGRAM



CONNECTION DIAGRAM



NOTE: Pin 4 connected to case.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = 12\text{ V}$ unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Power Consumption	$e_{in} = 0$		110	170	mW
Quiescent Output Current	$e_{in} = 0$	1.5	2.5	3.3	mA
Peak-to-Peak Output Current	$e_{in} = 400\text{ mV}_{rms}$, $f = 1\text{ kHz}$	3.0			mA
Output Saturation Voltage				1.7	V
Forward Transadmittance	$e_{in} = 10\text{ mV}_{rms}$, $f = 1\text{ kHz}$	29	33		mmho
Input Conductance	$e_{in} < 10\text{ mV}_{rms}$, $f = 10.7\text{ MHz}$		0.35	1.0	mmho
Input Capacitance	$e_{in} < 10\text{ mV}_{rms}$, $f = 10.7\text{ MHz}$		9.0	12.5	pF
Output Capacitance	$e_o = 100\text{ mV}_{rms}$, $f = 10.7\text{ MHz}$		2.0	4.0	pF
Output Conductance	$e_o = 100\text{ mV}_{rms}$, $f = 10.7\text{ MHz}$			0.05	mmho
Noise Figure	$f = 30\text{ MHz}$, $R_S = 500\ \Omega$		6.5		dB
	$f = 100\text{ MHz}$, $R_S = 500\ \Omega$		8.0		dB

The following specifications apply for $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$:


Quiescent Output Current	$e_{in} = 0$	1.7		3.5	mA
Peak-to-Peak Output Current	$e_{in} = 400\text{ mV}_{rms}$, $f = 1\text{ kHz}$	3.2			mA
Output Saturation Voltage				1.8	V
Forward Transadmittance	$e_{in} = 10\text{ mV}_{rms}$, $f = 1\text{ kHz}$	22			mmho
Input Conductance	$e_{in} < 10\text{ mV}_{rms}$, $f = 1\text{ kHz}$			0.71	mmho
Output Conductance	$e_o = 100\text{ mV}_{rms}$, $f \leq 5\text{ MHz}$			0.06	mmho

TYPICAL PERFORMANCE CURVES


INPUT RESISTANCE AND CAPACITANCE AS A FUNCTION OF INPUT VOLTAGE




INPUT ADMITTANCE AS A FUNCTION OF FREQUENCY




OUTPUT ADMITTANCE AS A FUNCTION OF FREQUENCY




FORWARD TRANSADMITTANCE AS A FUNCTION OF FREQUENCY



MAXIMUM REVERSE TRANSADMITTANCE AS A FUNCTION OF FREQUENCY



OUTPUT CURRENT AS A FUNCTION OF INPUT VOLTAGE



μA709

HIGH PERFORMANCE OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA709 is a high gain operational amplifier constructed on a single silicon chip using the Fairchild Planar* epitaxial process. It features low offset, high input impedance, large input common mode range, high output swing under load and low power consumption. The device displays exceptional temperature stability and will operate over a wide range of supply voltages with little degradation of performance. The amplifier is intended for use in DC servo systems, high impedance analog computers, low-level instrumentation applications and for the generation of special linear and nonlinear transfer functions.

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	±18 V
Internal Power Dissipation (Note)	
Metal Can	500 mW
Ceramic DIP	670 mW
Flatpak	570 mW
Differential Input Voltage	±5.0 V
Input Voltage	±10 V
Storage Temperature Range	
Metal Can, Ceramic DIP, and Flatpak	-65°C to +150°C
Operating Temperature Range	
Military (311 and 312 Grades)	-55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Lead Temperature	
Metal Can, Ceramic DIP and Flatpak (Soldering 60 seconds)	300°C
Output Short Circuit Duration	5 seconds


NOTE
Rating applies to ambient temperatures up to 70°C. Above 70°C ambient derate linearly at 6.3 mW/°C for Metal Can, 6.3 mW/°C for Silicone DIP, 8.3 mW/°C for Ceramic DIP and 7.1 mW/°C for the Flatpak package.

EQUIVALENT CIRCUIT



CONNECTION DIAGRAMS (TOP VIEWS)

8 LEAD METAL CAN




NOTE: Pin 4 connected to case

ORDER PART NOS.:

U5B7709311
U5B7709312
U5B7709393


14 LEAD DIP



ORDER PART NOS.:

U6A7709311
U6A7709312
U6A7709393

FLATPAK



ORDER PART NOS.:

U3F7709311
U3F7709312

*Planar is a patented Fairchild process.


(311 GRADE)

ELECTRICAL CHARACTERISTICS ($T_A = +25^\circ\text{C}$, $\pm 9\text{ V} \leq V_S \leq \pm 15\text{ V}$ unless otherwise specified)

PARAMETER (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		0.6	2.0	mV
Input Offset Current			10	50	nA
Input Bias Current			100	200	nA
Input Resistance		350	700		k Ω
Output Resistance			150		Ω
Supply Current	$V_S = \pm 15\text{ V}$		2.5	3.6	mA
Power Consumption	$V_S = \pm 15\text{ V}$		75	108	mW
Transient Response	$V_S = \pm 15\text{ V}$, $V_{IN} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_1 = 5\text{ nF}$, $R_1 = 1.5\text{ k}\Omega$, $C_2 = 200\text{ pF}$, $R_2 = 50\Omega$				
Risetime				1.5	μs
Overshoot	$C_L \leq 100\text{ pF}$			30	%
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$			3.0	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\Omega$, $T_A = +25^\circ\text{C}$ to $+125^\circ\text{C}$		1.8	10	$\mu\text{V}/^\circ\text{C}$
	$R_S = 50\Omega$, $T_A = +25^\circ\text{C}$ to -55°C		1.8	10	$\mu\text{V}/^\circ\text{C}$
	$R_S = 10\text{ k}\Omega$, $T_A = +25^\circ\text{C}$ to $+125^\circ\text{C}$		2.0	15	$\mu\text{V}/^\circ\text{C}$
	$R_S = 10\text{ k}\Omega$, $T_A = +25^\circ\text{C}$ to -55°C		4.8	25	$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +125^\circ\text{C}$		3.5	50	nA
	$T_A = -55^\circ\text{C}$		40	250	nA
Average Temperature Coefficient of Input Offset Current	$T_A = +25^\circ\text{C}$ to $T_A = +125^\circ\text{C}$		0.08	0.5	nA/ $^\circ\text{C}$
	$T_A = +25^\circ\text{C}$ to $T_A = -55^\circ\text{C}$		0.45	2.8	nA/ $^\circ\text{C}$
Input Bias Current	$T_A = -55^\circ\text{C}$		300	600	nA
Input Resistance	$T_A = -55^\circ\text{C}$	85	170		k Ω
Input Voltage Range	$V_S = \pm 15\text{ V}$	± 8.0			V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	80	110		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		40	100	$\mu\text{V}/\text{V}$
Large-Signal Voltage Gain	$V_S = \pm 15\text{ V}$, $R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 15\text{ V}$	25,000		70,000	
Output Voltage Swing	$V_S = \pm 15\text{ V}$, $R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$V_S = \pm 15\text{ V}$, $R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Supply Current	$T_A = +125^\circ\text{C}$, $V_S = \pm 15\text{ V}$		2.1	3.0	mA
	$T_A = -55^\circ\text{C}$, $V_S = \pm 15\text{ V}$		2.7	4.5	mA
Power Consumption	$T_A = +125^\circ\text{C}$, $V_S = \pm 15\text{ V}$		63	90	mW
	$T_A = -55^\circ\text{C}$, $V_S = \pm 15\text{ V}$		81	135	mW

GUARANTEED ELECTRICAL CHARACTERISTICS

(311 GRADE)







(312 GRADE)

ELECTRICAL CHARACTERISTICS ($T_A = +25^\circ\text{C}$, $\pm 9\text{ V} \leq V_S \leq \pm 15\text{ V}$ unless otherwise specified)

PARAMETER (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	5.0	mV
Input Offset Current			50	200	nA
Input Bias Current			200	500	nA
Input Resistance		150	400		k Ω
Output Resistance			150		Ω
Power Consumption	$V_S = \pm 15\text{ V}$		80	165	mW
Transient Response	$V_{IN} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$,				
Risetime	$C_1 = 5000\text{ pF}$, $R_1 = 1.5\text{ k}\Omega$, $C_2 = 200\text{ pF}$, $R_2 = 50\Omega$		0.3	1.0	μs
Overshoot	$C_L \leq 100\text{ pF}$		10	30	%
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$			6.0	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\Omega$ $R_S \leq 10\text{ k}\Omega$		3.0 6.0		$\mu\text{V}/^\circ\text{C}$ $\mu\text{V}/^\circ\text{C}$
Large-Signal Voltage Gain	$V_S = \pm 15\text{ V}$, $R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	25,000	45,000	70,000	
Output Voltage Swing	$V_S = \pm 15\text{ V}$, $R_L \geq 10\text{ k}\Omega$ $V_S = \pm 15\text{ V}$, $R_L \geq 2\text{ k}\Omega$	± 12 ± 10	± 14 ± 13		V V
Input Voltage Range	$V_S = \pm 15\text{ V}$	± 8.0	± 10		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		25	150	$\mu\text{V}/\text{V}$
Input Offset Current	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$		20 100	200 500	nA nA
Input Bias Current	$T_A = -55^\circ\text{C}$		0.5	1.5	μA
Input Resistance		40	100		k Ω

GUARANTEED ELECTRICAL CHARACTERISTICS

(312 GRADE)



(393 GRADE)

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)




PARAMETER (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$, $\pm 9\text{ V} \leq V_S \leq \pm 15\text{ V}$		2.0	7.5	mV
Input Offset Current			100	500	nA
Input Bias Current			0.3	1.5	μA
Input Resistance		50	250		$\text{k}\Omega$
Output Resistance			150		Ω
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	15,000	45,000		
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Input Voltage Range		± 8.0	± 10		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	65	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		25	200	$\mu\text{V/V}$
Power Consumption			80	200	mW
Transient Response					
Risetime	$V_{IN} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_1 = 5000\text{ pF}$, $R_1 = 1.5\text{ k}\Omega$, $C_2 = 200\text{ pF}$, $R_2 = 50\Omega$		0.3		μs
Overshoot	$C_L \leq 100\text{ pF}$		10		%

The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:




Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$, $\pm 9\text{ V} \leq V_S \leq \pm 15\text{ V}$		10	mV
Input Offset Current			750	nA
Input Bias Current			2.0	μA
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	12,000		
Input Resistance		35		$\text{k}\Omega$

GUARANTEED ELECTRICAL CHARACTERISTICS

(393 GRADE)




FREQUENCY COMPENSATION CURVES (FOR ALL GRADES)




TYPICAL PERFORMANCE CURVES (FOR 311 GRADE)


VOLTAGE TRANSFER CHARACTERISTIC




VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT VOLTAGE SWING AS A FUNCTION OF LOAD RESISTANCE




INPUT BIAS CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT BIAS CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




INPUT OFFSET CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT RESISTANCE AS A FUNCTION OF AMBIENT TEMPERATURE




POWER CONSUMPTION AS A FUNCTION OF AMBIENT TEMPERATURE



TRANSIENT RESPONSE




TRANSIENT RESPONSE TEST CIRCUIT




Pin numbers only apply to metal can package.

SLEW RATE AS A FUNCTION OF CLOSED-LOOP GAIN USING RECOMMENDED COMPENSATION NETWORKS




TYPICAL PERFORMANCE CURVES
(FOR 312 AND 393 GRADES)


VOLTAGE TRANSFER
CHARACTERISTIC




INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE




POWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT BIAS CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGE



OUTPUT VOLTAGE
SWING AS A FUNCTION OF
LOAD RESISTANCE




FREQUENCY COMPENSATION
CIRCUIT




* Use $R_2 = 50 \Omega$ when the amplifier is operated with capacitive loading.

TRANSIENT RESPONSE




TYPICAL PERFORMANCE CURVES
(FOR 312 AND 393 GRADES)

FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE




FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
SUPPLY VOLTAGE




PROTECTION CIRCUITS


OUTPUT SHORT-CIRCUIT
PROTECTION




INPUT BREAKDOWN
PROTECTION



LATCH-UP PROTECTION



SUPPLY OVERVOLTAGE
PROTECTION



Pin numbers only apply to metal can package.

μA710

HIGH-SPEED DIFFERENTIAL COMPARATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA710 is a differential voltage comparator intended for applications requiring high accuracy and fast response times. It is constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The device is useful as a variable threshold Schmitt trigger, a pulse height discriminator, a voltage comparator in high-speed A/D converters, a memory sense amplifier or a high-noise immunity line receiver. The output of the comparator is compatible with all integrated logic forms.

- 5 mV MAXIMUM OFFSET VOLTAGE
- 5 μA MAXIMUM OFFSET CURRENT
- 1000 MINIMUM VOLTAGE GAIN
- 20 μV/°C MAXIMUM OFFSET VOLTAGE DRIFT

ABSOLUTE MAXIMUM RATINGS


Positive Supply Voltage	+14.0 V
Negative Supply Voltage	-7.0 V
Peak Output Current	10 mA
Differential Input Voltage	±5.0 V
Input Voltage	±7.0 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Flatpak	570 mW
Storage Temperature Range	
Metal Can, Ceramic DIP, and Flatpak	-65°C to +150°C
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to + 70°C
Lead Temperature	
Metal Can, Ceramic DIP and Flatpak (Soldering, 60 seconds)	300°C

EQUIVALENT CIRCUIT



CONNECTION DIAGRAMS

8 LEAD METAL CAN (TOP VIEW)




NOTE: Pin 4 connected to case.

ORDER PART NOS:

U5B7710312
U5B7710393


14 LEAD DIP (TOP VIEW)



ORDER PART NOS: FOR CERAMIC DIP

U6A7710312
U6A7710393

FLATPAK (TOP VIEW)



ORDER PART NO: U3F7710312

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = +25^\circ\text{C}$, $V_+ = 12.0\text{ V}$, $V_- = -6.0\text{ V}$ unless otherwise specified)

PARAMETER (see definitions)	CONDITIONS (Note 3)	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200\ \Omega$		0.6	2.0	mV
Input Offset Current			0.75	3.0	μA
Input Bias Current			13	20	μA
Voltage Gain		1250	1700		
Output Resistance			200		Ω
Output Sink Current	$\Delta V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 0$	2.0	2.5		mA
Response Time (Note 3)			40		ns
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 200\ \Omega$			3.0	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\ \Omega$, $T_A = 25^\circ\text{C}$ to $T_A = +125^\circ\text{C}$ $R_S = 50\ \Omega$, $T_A = 25^\circ\text{C}$ to $T_A = -55^\circ\text{C}$		3.5 2.7	10 10	$\mu\text{V}/^\circ\text{C}$ $\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$		0.25 1.8	3.0 7.0	μA μA
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ\text{C}$ to $T_A = +125^\circ\text{C}$ $T_A = 25^\circ\text{C}$ to $T_A = -55^\circ\text{C}$		5.0 15	25 75	nA/ $^\circ\text{C}$ nA/ $^\circ\text{C}$
Input Bias Current	$T_A = -55^\circ\text{C}$		27	45	μA
Input Voltage Range	$V_- = -7.0\text{ V}$	± 5.0			V
Common Mode Rejection Ratio	$R_S \leq 200\ \Omega$	80	100		dB
Differential Input Voltage Range		± 5.0			V
Voltage Gain		1000			
Positive Output Level	$\Delta V_{IN} \geq 5\text{ mV}$, $0 \leq I_{OUT} \leq 5.0\text{ mA}$	2.5	3.2	4.0	V
Negative Output Level	$\Delta V_{IN} \geq 5\text{ mV}$	-1.0	-0.5	0	V
Output Sink Current	$T_A = +125^\circ\text{C}$, $\Delta V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 0$ $T_A = -55^\circ\text{C}$, $\Delta V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 0$	0.5 1.0	1.7 2.3		mA mA
Positive Supply Current	$V_{OUT} \leq 0$		5.2	9.0	mA
Negative Supply Current			4.6	7.0	mA
Power Consumption			90	150	mW

393 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V_+ = 12.0\text{ V}$, $V_- = -6.0\text{ V}$ unless otherwise specified)


PARAMETERS (see definitions)	CONDITIONS (Note 3)	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200\ \Omega$		1.6	5.0	mV
Input Offset Current			1.8	5.0	μA
Input Bias Current			16	25	μA
Voltage Gain		1000	1500		
Output Resistance			200		Ω
Output Sink Current	$\Delta V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 0$	1.6	2.5		mA
Response Time (Note 2)			40		ns
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 200\ \Omega$			6.5	mV
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\ \Omega$, $T_A = 0^\circ\text{C}$ to $T_A = +70^\circ\text{C}$		5.0	20	$\mu\text{V}/^\circ\text{C}$
Input Offset Current				7.5	μA
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ\text{C}$ to $T_A = +70^\circ\text{C}$ $T_A = 25^\circ\text{C}$ to $T_A = 0^\circ\text{C}$		15 24	50 100	nA/ $^\circ\text{C}$ nA/ $^\circ\text{C}$
Input Bias Current	$T_A = 0^\circ\text{C}$		25	40	μA
Input Voltage Range	$V_- = -7.0\text{ V}$	± 5.0			V
Common Mode Rejection Ratio	$R_S \leq 200\ \Omega$	70	98		dB
Differential Input Voltage Range		± 5.0			V
Voltage Gain		800			
Positive Output Level	$\Delta V_{IN} \geq 5\text{ mV}$, $0 \leq I_{OUT} \leq 5.0\text{ mA}$	2.5	3.2	4.0	V
Negative Output Level	$\Delta V_{IN} \geq 5\text{ mV}$	-1.0	-0.5	0	V
Output Sink Current	$\Delta V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 0$	0.5			mA
Positive Supply Current	$V_{OUT} \leq 0$		5.2	9.0	mA
Negative Supply Current			4.6	7.0	mA
Power Consumption			90	150	mW

NOTES


- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for Ceramic DIP, $6.3\text{ mW}/^\circ\text{C}$ for Silicone DIP and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak package.
- Derate linearly at $4.4\text{ mW}/^\circ\text{C}$ for case temperatures above $+115^\circ\text{C}$; Derate linearly at $3.3\text{ mW}/^\circ\text{C}$ for ambient temperatures above $+100^\circ\text{C}$.
- The response time specified (see definitions) is for a 100 mV input step with 5 mV overdrive.
- The input offset voltage and input offset current (see definitions) are specified for a logic threshold voltage as follows: For 312 grade, 1.8 V at -55°C , 1.4 V at $+25^\circ\text{C}$ and 1.0 V at $+125^\circ\text{C}$. For 393 grade, 1.5 V at $+25^\circ\text{C}$ and 1.2 V at $+70^\circ\text{C}$.

312 GRADE TYPICAL PERFORMANCE CURVES


VOLTAGE TRANSFER CHARACTERISTIC




VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGES




INPUT BIAS CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT OFFSET CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE




POWER CONSUMPTION AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT SINK CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT VOLTAGE LEVELS AS A FUNCTION OF AMBIENT TEMPERATURE




RESPONSE TIME FOR VARIOUS INPUT OVERDRIVES



RESPONSE TIME FOR VARIOUS INPUT OVERDRIVES




COMMON MODE PULSE RESPONSE




393 GRADE TYPICAL PERFORMANCE CURVES


VOLTAGE TRANSFER CHARACTERISTIC




INPUT BIAS CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




POWER CONSUMPTION AS A FUNCTION OF AMBIENT TEMPERATURE




RESPONSE TIME FOR VARIOUS INPUT OVERDRIVES




VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT OFFSET CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT SINK CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGES




COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



OUTPUT VOLTAGE LEVELS AS A FUNCTION OF AMBIENT TEMPERATURE



COMMON MODE PULSE RESPONSE



μA711

DUAL COMPARATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA711 is a dual, differential voltage comparator intended primarily for core-memory sense amplifier applications. The device features high accuracy, fast response times, large input voltage range, low power consumption and compatibility with practically all integrated logic forms. When used as a sense amplifier, the threshold voltage can be adjusted over a wide range, almost independent of the integrated circuit characteristics. Independent strobing of each comparator channel is provided, and pulse stretching on the output is easily accomplished. Other applications of the dual comparator include a window discriminator in pulse height detectors and a double-ended limit detector for automatic Go/No-go test equipment. The μA711, which is similar to the μA710 differential comparator, is constructed using the Fairchild Planar* epitaxial process.

- **FAST RESPONSE TIME - 40 ns TYPICAL**
- **5 mV MAXIMUM OFFSET VOLTAGE**
- **10 μA MAXIMUM OFFSET CURRENT**
- **INDEPENDENT STROBING OF EACH COMPARATOR**

ABSOLUTE MAXIMUM RATINGS


Positive Supply Voltage	+14 V
Negative Supply Voltage	-7.0 V
Peak Output Current	50 mA
Differential Input Voltage	±5.0 V
Input Voltage	±7.0 V
Strobe Voltage	0 to +6.0 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Flatpak	570 mW
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature	
Metal Can, Ceramic DIP and Flatpak (Soldering, 60 seconds)	300°C

EQUIVALENT CIRCUIT



Notes on following page.


CONNECTION DIAGRAMS (TOP VIEWS) 10 LEAD METAL CAN



Note: Pin 5 connected to case.


ORDER PART NOS. U5F7711312
U5F7711393

14 LEAD DIP



ORDER PART NOS.
FOR CERAMIC DIP: U6A7711312
U6A7711393

10 LEAD FLATPAK



ORDER PART NOS. U3F7711312

*Planar is a patented Fairchild process.

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = 12\text{ V}$, $V^- = -6.0\text{ V}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$V_{out} = +1.4\text{ V}$, $R_S \leq 200\ \Omega$, $V_{CM} = 0$		1.0	3.5	mV
	$V_{out} = +1.4\text{ V}$, $R_S \leq 200\ \Omega$		1.0	5.0	mV
Input Offset Current	$V_{out} = +1.4\text{ V}$		0.5	10.0	μA
Input Bias Current			25	75	μA
Voltage Gain		750	1500		
Response Time (Note 2)			40		ns
Strobe Release Time			12		ns
Input Voltage Range	$V^- = -7.0\text{ V}$	± 5.0			V
Differential Input Voltage Range		± 5.0			V
Output Resistance			200		Ω
Positive Output Level	$V_{in} \geq 10\text{ mV}$		4.5	5.0	V
Loaded Positive Output Level	$V_{in} \geq 10\text{ mV}$, $I_O = 5\text{ mA}$	2.5	3.5		V
Negative Output Level	$V_{in} \geq 10\text{ mV}$	-1.0	-0.5	0	V
Strobed Output Level	$V_{strobe} \leq 0.3\text{ V}$	-1.0		0	V
Output Sink Current	$V_{in} \geq 10\text{ mV}$, $V_{out} \geq 0$	0.5	0.8		mA
Strobe Current	$V_{strobe} = 100\text{ mV}$		1.2	2.5	mA
Positive Supply Current	$V_{out} \leq 0$		8.6		mA
Negative Supply Current			3.9		mA
Power Consumption			130	200	mW

The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:

Input Offset Voltage (Note 3)	$R_S \leq 200\ \Omega$, $V_{CM} = 0$			4.5	mV
	$R_S \leq 200\ \Omega$			6.0	mV
Input Offset Current (Note 3)				20	μA
Input Bias Current				150	μA
Temperature Coefficient of					
Input Offset Voltage			5.0		$\mu\text{V}/^\circ\text{C}$
Voltage Gain		500			

NOTES

- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for the Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP, and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak package.
- The response time specified (see definitions) is for a 100 mV step input with 5 mV overdrive.
- The input offset voltage is specified for a logic threshold as follows:
312 Grade: 1.8 V at -55°C , 1.4 V at $+25^\circ\text{C}$, 1.0 V at $+125^\circ\text{C}$
393 Grade: 1.5 V at 0°C , 1.4 V at $+25^\circ\text{C}$, 1.2 V at $+70^\circ\text{C}$

393 GRADE











ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = 12\text{ V}$, $V^- = -6.0\text{ V}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$V_{\text{out}} = +1.4\text{ V}$, $R_S \leq 200\ \Omega$, $V_{\text{CM}} = 0$		1.0	5.0	mV
	$V_{\text{out}} = +1.4\text{ V}$, $R_S \leq 200\ \Omega$		1.0	7.5	mV
Input Offset Current	$V_{\text{out}} = +1.4\text{ V}$		0.5	15	μA
Input Bias Current			25	100	μA
Voltage Gain		700	1500		
Response Time (Note 2)			40		ns
Strobe Release Time			12		ns
Input Voltage Range	$V^- = -7.0\text{ V}$	± 5.0			V
Differential Input Voltage Range		± 5.0			V
Output Resistance			200		Ω
Positive Output Level	$V_{\text{in}} \geq 10\text{ mV}$		4.5	5.0	V
Loaded Positive Output Level	$V_{\text{in}} \geq 10\text{ mV}$, $I_O = 5\text{ mA}$	2.5	3.5		V
Negative Output Level	$V_{\text{in}} \geq 10\text{ mV}$	-1.0	-0.5	0	V
Strobed Output Level	$V_{\text{strobe}} \leq 0.3\text{ V}$	-1.0		0	V
Output Sink Current	$V_{\text{in}} \geq 10\text{ mV}$, $V_{\text{out}} \geq 0$	0.5	0.8		mA
Strobe Current	$V_{\text{strobe}} = 100\text{ mV}$		1.2	2.5	mA
Positive Supply Current	$V_{\text{out}} \leq 0$		8.6		mA
Negative Supply Current			3.9		mA
Power Consumption			130	230	mW

The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:

Input Offset Voltage (Note 3)	$R_S \leq 200\ \Omega$, $V_{\text{CM}} = 0$			6.0	mV
	$R_S \leq 200\ \Omega$			10	mV
Input Offset Current (Note 3)				25	μA
Input Bias Current				150	μA
Temperature Coefficient of					
Input Offset Voltage			5.0		$\mu\text{V}/^\circ\text{C}$
Voltage Gain		500			

TYPICAL PERFORMANCE CURVES

VOLTAGE TRANSFER
CHARACTERISTIC
312 GRADEVOLTAGE TRANSFER
CHARACTERISTIC
393 GRADEVOLTAGE GAIN
AS A FUNCTION OF
AMBIENT TEMPERATUREVOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGESCOMMON MODE
PULSE RESPONSEINPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURERESPONSE TIME
FOR VARIOUS INPUT
OVERDRIVESSTROBE RELEASE TIME
FOR VARIOUS INPUT
OVERDRIVESOUTPUT PULSE
STRETCHING WITH
CAPACITIVE LOADINGPOWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATURE

μA715

HIGH SPEED OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA715 is a high speed, high gain, monolithic operational amplifier constructed on a single silicon chip using the Fairchild Planar* epitaxial process. It is intended for use in a wide range of applications where fast signal acquisition or wide bandwidth is required. The μA715 features fast settling time, high slew rate, low offsets, and high output swing for large signal applications. In addition, the device displays excellent temperature stability and will operate over a wide range of supply voltages. The μA715 is ideally suited for use in A to D and D to A converters, active filters, deflection amplifiers, video amplifiers, phase locked loops, multiplexed analog gates, precision comparators, sample and holds, and general feedback applications requiring DC wide bandwidth operation.

- HIGH SLEW RATE 100 V/μs
- FAST SETTLING TIME 300 ns
- WIDE BANDWIDTH 65 MHz
- WIDE OPERATING SUPPLY RANGE
- WIDE INPUT VOLTAGE RANGES

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	±18 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Differential Input Voltage	±15 V
Input Voltage (Note 2)	±15 V
Storage Temperature Range	
Metal Can, Ceramic DIP	−65°C to +150°C
Operating Temperature Range	
Military (312 grade)	−55°C to +125°C
Commercial (393 grade)	0°C to +70°C
Lead Temperature (Soldering, 60 Seconds)	
Metal Can, Ceramic DIP	300°C

EQUIVALENT CIRCUIT



CONNECTION DIAGRAMS


10 LEAD METAL CAN (TOP VIEW)



ORDER PART NOS:

U5F7715312
U5F7715393

14 LEAD DIP (TOP VIEW)



ORDER PART NOS:

For Ceramic DIP
U6A7715312
U6A7715393


312 Grade

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		2.0	5.0	mV
Input Offset Current			70	250	nA
Input Bias Current			400	750	nA
Input Resistance			1.0		M Ω
Input Voltage Range		± 10	± 12		Volts
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	15,000	30,000		
Output Resistance			75		Ω
Supply Current			5.5	7.0	mA
Power Consumption			165	210	mW
Acquisition Time (Unity Gain)	$V_{OUT} = +5\text{ V}$		800		ns
Settling Time (Unity Gain)			300		ns
Transient Response (Unity Gain)	$V_{IN} = 400\text{ mV}$				
Risetime			30	60	ns
Overshoot			25	40	%
Slew Rate	$A_v = 100$		70		V/ μs
	$A_v = 10$		38		V/ μs
	$A_v = 1$ (non-inverting)	15	18		V/ μs
	$A_v = 1$ (inverting)		100		V/ μs
The following apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$			7.5	mV
Input Offset Current	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$			250 800	nA
Input Bias Current	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$			750 4.0	nA μA
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	74	92		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		45	300	$\mu\text{V/V}$
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	10,000			
Output Voltage Swing	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V

TYPICAL PERFORMANCE CURVES


OPEN LOOP GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




SUPPLY VOLTAGE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



SLEW RATE AS A FUNCTION OF TEMPERATURE



COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



393 Grade

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		2.0	7.5	mV
Input Offset Current			70	250	nA
Input Bias Current			0.4	1.5	nA
Input Resistance			1.0		M Ω
Input Voltage Range		± 10	± 12		Volts
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	74	92		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		45	400	$\mu\text{V/V}$
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	10,000	30,000		
Output Resistance			75		Ω
Supply Current			5.5	10	mA
Power Consumption			165	300	mW
Acquisition Time (Unity Gain)	$V_{OUT} = +5\text{ V}$		800		ns
Settling Time (Unity Gain)			300		ns
Transient Response (Unity Gain)	$V_{IN} = 400\text{ mV}$				
Risetime			30	75	ns
Overshoot			25	50	%
Slew Rate	$A_v = 100$		70		V/ μs
	$A_v = 10$		38		V/ μs
	$A_v = 1$ (non-inverting)	10	18		V/ μs
	$A_v = 1$ (inverting)		100		V/ μs

The following apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:


Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$			10	mV
Input Offset Current	$T_A = +70^\circ\text{C}$			250	nA
	$T_A = 0^\circ\text{C}$			750	nA
Input Bias Current	$T_A = +70^\circ\text{C}$			1.5	μA
	$T_A = 0^\circ\text{C}$			7.5	μA
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	8,000			
Output Voltage Swing	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		Volts

TYPICAL PERFORMANCE CURVES


OPEN LOOP GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




SUPPLY VOLTAGE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



SLEW RATE AS A FUNCTION OF TEMPERATURE




COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



**TYPICAL PERFORMANCE CURVES
FOR 312 AND 393 GRADES**
(unless otherwise specified)

**FREQUENCY COMPENSATION
CIRCUIT**




**NON-INVERTING
COMPENSATION COMPONENTS VALUES**


CLOSED LOOP GAIN	C_1	C_2	C_3
1000	10 pF	—	—
100	50 pF	—	250 pF
10	100 pF	500 pF	1000 pF
1	500 pF	2000 pF	1000 pF

*For Gain 10, compensation may be simplified by removing C_2 , C_3 and adding a 200 pF capacitor (C_4) between Pin 7 and 10.


**SUGGESTED VALUES OF
COMPENSATION CAPACITORS
AS A FUNCTION OF
THE CLOSED LOOP GAIN**




**LARGE SIGNAL PULSE
RESPONSE UNITY GAIN**




**INVERTING UNITY GAIN
HIGH SLEW RATE CIRCUIT**




**SMALL SIGNAL PULSE RESPONSE
INVERTING UNITY GAIN**




**UNITY GAIN LARGE SIGNAL
PULSE RESPONSE**




**LARGE SIGNAL PULSE RESPONSE
FOR GAIN 10**




**LARGE SIGNAL PULSE RESPONSE
FOR GAIN 100**




**SLEW RATE AS A FUNCTION
OF THE CLOSED LOOP GAIN**



**SLEW RATE AS A FUNCTION
OF SUPPLY VOLTAGE**




**VOLTAGE OFFSET
NULL CIRCUIT**




**TYPICAL PERFORMANCE CURVES
FOR 312 AND 393 GRADES**
(unless otherwise specified)


**OPEN LOOP RESPONSE WITH
COMPENSATION NECESSARY FOR
VARIOUS CLOSED LOOP
GAIN CONFIGURATIONS**




**CLOSED LOOP FREQUENCY
RESPONSE FOR VARIOUS
GAIN CONFIGURATIONS**




**OPEN LOOP GAIN AS A
FUNCTION OF FREQUENCY**




**SUPPLY VOLTAGE REJECTION RATIO
AS A FUNCTION OF FREQUENCY**




**OUTPUT SWING AS A FUNCTION
OF FREQUENCY FOR VARIOUS
CLOSED LOOP GAIN CONFIGURATIONS**




**OPEN LOOP PHASE AS A
FUNCTION OF FREQUENCY**




**VOLTAGE FOLLOWER
TRANSIENT RESPONSE**



VOLTAGE FOLLOWER



**COMMON MODE REJECTION RATIO
AS A FUNCTION OF FREQUENCY**





NOTES

1. Rating applies to ambient temperature up to $70^\circ C$. Above $70^\circ C$ ambient derate linearly at $6.3 mW/^\circ C$ for Metal Can and $8.3 mW/^\circ C$ for the Ceramic DIP package.
2. For supply voltages less than $\pm 15V$, the absolute maximum input voltage is equal to the supply voltage.


TYPICAL APPLICATIONS

WIDE BAND VIDEO AMPLIFIER WITH 75 Ω COAX CABLE DRIVE CAPABILITY




HIGH SPEED 10 BIT DIGITAL TO ANALOG CONVERTER

ANALOG OUTPUT 0 TO +5.0 V



$\mu A722/\mu A715$ op amp switching ON, as it should with typical logic voltage on least significant bits. Note complete absence of ringing.




Conversion Rate
6 bits - 300 ns
8 bits - 600 ns
10 bits - 1000 ns



NOTE:


Contact Fairchild for additional information including how to increase conversion speed by clamping LSB's and how to obtain bipolar outputs.

HIGH SPEED SAMPLE AND HOLD



HIGH SPEED INTEGRATOR





HELPFUL HINTS

LAYOUT — The layout should be such that stray capacitance is minimal.

SUPPLIES — The supplies should be adequately bypassed. Use of $0.1 \mu F$ high quality ceramic capacitors is recommended.

RINGING — Excessive ringing (long acquisition time) may occur with large capacitive loads. This may be reduced by isolating the capacitive load with a resistance of 100Ω . Large source resistances may also give rise to the same problem and this may be decreased by the addition of a capacitance across the feedback resistance. A value of around $50 pF$ for unity gain configuration and around $3.0 pF$ for gain 10 should be adequate.

LATCH UP — This may occur when the amplifier is used as a voltage follower. The inclusion of a diode between pins 6 and 2 with the cathode towards pin 2 is the recommended preventive.

μA716

FIXED-GAIN, LOW DISTORTION AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA716 is a fixed-gain, medium power amplifier intended for use as a telephone system channel amplifier, headset amplifier or general purpose audio amplifier. It provides medium output current capability, low distortion, excellent gain stability, and wide bandwidth. Fixed voltage gains of 10, 20, 100 and 200 are available by selecting external taps.



ABSOLUTE MAXIMUM RATINGS:

Supply Voltage
Internal Power Dissipation
Input Voltage
Peak Output Current ($T_A = 25^\circ\text{C}$)
Storage Temperature Range
Operating Temperature Range
Lead Temperature (Soldering, 60 seconds)

27 V
500 mW
 $\pm 5\text{ V}$
100 mA
 -65°C to $+150^\circ\text{C}$
 0°C to $+70^\circ\text{C}$
300°C

PHYSICAL DIMENSIONS


in accordance with
JEDEC(TO-99) outline




NOTES: All dimensions in inches.
Leads are gold-plated Kovar.
Package weight is 1.22 grams.

ORDER PART NO. U5B7716393

SCHEMATIC DIAGRAM





CONNECTION DIAGRAM



NOTE: Pin 4 internally connected to case.


ELECTRICAL CHARACTERISTICS ($0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$, $V^+ = 21\text{V}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Quiescent Power Consumption	$T_A = 25^\circ\text{C}$		280	350	mW
Total Harmonic Distortion	$A_V = 10$, $f = 1\text{ kHz}$, $P_O = 50\text{ mW}$, $R_L = 150\ \Omega$		0.01	0.05	%
	$A_V = 100$, $f = 1\text{ kHz}$, $P_O = 50\text{ mW}$, $R_L = 150\ \Omega$		0.10	0.50	%
Input Noise Voltage	$R_S = 600\ \Omega$, $T_A = 25^\circ\text{C}$, $B_n = 16\text{ Hz to } 150\text{ kHz}$		8.0		μV_{rms}
Output Voltage Swing	$R_L = 150\ \Omega$	10	14		$\text{V}_{\text{p-p}}$
	$R_L \geq 5\text{ k}\Omega$	15	17		$\text{V}_{\text{p-p}}$
Input Resistance		9.0	11		$\text{k}\Omega$
Output Resistance			1.0		Ω
Voltage Gain	See Table I				
10x		9.0	10	11	
20x		18	20	22	
100x		95	105	115	
200x		185	205	225	
Bandwidth	$T_A = 25^\circ\text{C}$		2.0		MHz
Temperature Stability of Voltage Gain	$T_{\text{ref}} = 25^\circ\text{C}$				
10x			± 0.02	± 0.25	dB
20x			± 0.02	± 0.25	dB
100x			± 0.02	± 0.25	dB
200x			± 0.05	± 0.50	dB


TYPICAL PERFORMANCE CURVES**VOLTAGE GAIN
AS A FUNCTION OF FREQUENCY****TRANSIENT RESPONSE**

TYPICAL PERFORMANCE CURVES


TOTAL POWER CONSUMPTION AND INTERNAL DEVICE DISSIPATION AS A FUNCTION OF OUTPUT POWER




TOTAL HARMONIC DISTORTION AS A FUNCTION OF OUTPUT POWER




POWER OUTPUT AS A FUNCTION OF FREQUENCY 5% AND 1% THD




RELATIVE VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGE




VOLTAGE SWING AS A FUNCTION OF SUPPLY VOLTAGE




QUIESCENT POWER CONSUMPTION AS A FUNCTION OF SUPPLY VOLTAGE



RELATIVE VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE



CONNECTION DIAGRAM AND COMPONENT TABLE FOR AVAILABLE GAIN OPTIONS



Voltage Gain	C_1	C_2	R_1	Decouple Pins:
10	68 pF	39 pF	75 Ω	1
20	50 pF	27 pF	75 Ω	8
100	None	3 pF	None	1, 7
200	None	3 pF	None	7, 8

TABLE I

μA722

10-BIT CURRENT SOURCE


FAIRCHILD LINEAR INTEGRATED CIRCUITS

- $8 \pm \frac{1}{2}$ BIT ACCURACY FROM 0°C TO $+55^{\circ}\text{C}$
- $7 \pm \frac{1}{2}$ BIT ACCURACY FROM -20°C TO $+85^{\circ}\text{C}$
- 600 ns SWITCHING SPEED
- INTERNAL PRECISION REFERENCE
- TTL COMPATIBLE

Voltage from V^+ to V^-
Voltage from Output to V^+
Voltage from Output to V^-
Voltage from Logic Inputs to Output
Voltage from Logic Inputs to V^+
Voltage from Logic Inputs to V^-
Internal Power Dissipation (Note 1)
Operating Temperature Range
Storage Temperature Range
Lead Temperature (Soldering, 60 seconds)

-0.5 V to +18 V
 -12 V to +6 V
 0 V to +12 V
 -9 V to +7 V
 -18 V to 0 V
 0 V to +12 V
 450 mW
 -20°C to +85°C
 -65°C to +150°C
 300°C


(TYPICAL FLAT PACKAGE)
(TOP VIEW)



U3M7722333
U3M7722334

The diagram illustrates a 10-bit digital-to-analog converter (DAC) circuit. It consists of a precision voltage source (13) connected to a series of 10 current sources (Q1-Q10). Each current source is controlled by a bit control gate (G1-G10) and a current source resistor (RE1-RE10). The output is taken from the summing junction of the current sources. The diagram is labeled "BIT CONTROL LOGIC INPUTS" at the top and "EXTERNAL RESISTOR ARRAY" at the bottom right.

(TOP VIEW)



Notes on following pages.

*Planar is a patented Fairchild process

(333 GRADE)

ELECTRICAL CHARACTERISTICS

PARAMETER	CONDITIONS (Note 2)	MIN.	TYP.	MAX.	UNITS
Resolution				10	Bits
Absolute Error	$T_A = 25^\circ\text{C}$		$\pm .07$	$\pm .20$	%
	$0^\circ\text{C} \leq T_A \leq +55^\circ\text{C}$		$\pm .10$	$\pm .20$	%
	$-20^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$		$\pm .13$	$\pm .39$	%
Output Current					
Full-Scale	Logic Inputs = 0.4 V	2160	2560	3000	μA
Zero-Scale	Logic Inputs = 2.5 V		$\pm .002$	$\pm .25$	μA
Power Supply Rejection	$\Delta V^+ = \Delta V^- = \pm 5\%$		$\pm .06$	± 0.1	%/%
Output Resistance		0.2	1.2		$\text{M}\Omega$
Switching Speed			600		ns
Logic Input High Voltage		2.1	2.5		V
Logic Input Low Voltage			0.4	0.7	V
Power Consumption			165	250	mW

(334 GRADE)

ELECTRICAL CHARACTERISTICS

PARAMETER	CONDITIONS (Note 2)	MIN.	TYP.	MAX.	UNITS
Resolution				10	Bits
Absolute Error	$T_A = 25^\circ\text{C}$		$\pm .08$	$\pm .39$	%
	$0^\circ\text{C} \leq T_A \leq +55^\circ\text{C}$		$\pm .17$	$\pm .39$	%
	$-20^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$		$\pm .22$	$\pm .78$	%
Output Current					
Full-Scale	Logic Inputs = 0.4 V	2160	2560	3000	μA
Zero-Scale	Logic Inputs = 2.5 V		$\pm .002$	$\pm .25$	μA
Power Supply Rejection	$\Delta V^+ = \Delta V^- = \pm 5\%$		$\pm .06$	± 0.1	%/%
Output Resistance		0.2	1.2		$\text{M}\Omega$
Switching Speed			600		ns
Logic Input High Voltage		2.1	2.5		V
Logic Input Low Voltage			0.4	0.7	V
Power Consumption			165	250	mW


NOTES:

- (1) Rating applies for ambient temperatures to $+85^\circ\text{C}$.
 (2) Unless otherwise specified, $T_A = 25^\circ\text{C}$, $V^+ = 6.00 \text{ V} \pm .01 \text{ V}$, $V^- = -6.00 \text{ V} \pm .01 \text{ V}$, $V_{\text{out}} = 0 \text{ V}$, $C_1 = 200 \text{ pF}$, and external resistor array as per Table 1.
 (3) In Table 1, the maximum absolute value tolerance for $R_{E1} = \pm 10\%$.


TABLE 1
BINARY CODE RESISTOR ARRAY
FOR $8 \pm \frac{1}{2}$ BIT ACCURACY

Resistor Number (R_{Ej})	Nominal Value ($\text{k}\Omega$)	Nominal Ratio (R_{Ej}/R_{E1})	333 GRADE		334 GRADE	
			Max. Ratio Tolerance ($T_A = 25^\circ\text{C}$) (%)	Max. Ratio Temp. Coeff. ($\text{ppm}/^\circ\text{C}$)	Max. Ratio Tolerance ($T_A = 25^\circ\text{C}$) (%)	Max. Ratio Temp. Coeff. ($\text{ppm}/^\circ\text{C}$)
R_{E1}	2.547	1.000	Note 3	± 5	Note 3	± 20
R_{E2}	5.094	2.000	± 0.02	± 5	± 0.10	± 20
R_{E3}	10.245	4.022	± 0.05	± 10	± 0.20	± 50
R_{E4}	20.60	8.088	± 0.10	± 20	± 0.20	± 50
R_{E5}	41.43	16.265	± 0.20	± 20	± 0.50	± 100
R_{E6}	81.93	32.17	± 0.20	± 50	± 0.50	± 100
R_{E7}	163.4	64.16	± 0.50	± 100	± 1.0	± 500
R_{E8}	325.7	127.9	± 1.0	± 200	± 1.0	± 500
R_{E9}	644.9	253.2	± 2.0	± 500	± 5.0	± 1000
R_{E10}	1275	500.8	± 2.0	± 500	± 5.0	± 1000


TYPICAL FULL-SCALE
OUTPUT CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL DIGITAL-TO-ANALOG CONVERTER



TYPICAL ANALOG-TO-DIGITAL CONVERTER



SCHEMATIC DIAGRAM



μA723

PRECISION VOLTAGE REGULATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION – The μA723 is a monolithic voltage regulator constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The device consists of a temperature compensated reference amplifier, error amplifier, power series pass transistor and current limit circuitry. Additional NPN or PNP pass elements may be used when output currents exceeding 150 mA are required. Provisions are made for adjustable current limiting and remote shutdown. In addition to the above, the device features low standby current drain, low temperature drift and high ripple rejection. The μA723 is intended for use with positive or negative supplies as a series, shunt, switching or floating regulator. Applications include laboratory power supplies, isolation regulators for low level data amplifiers, logic card regulators, small instrument power supplies, airborne systems and other power supplies for digital and linear circuits.

- POSITIVE OR NEGATIVE SUPPLY OPERATION
- SERIES, SHUNT, SWITCHING OR FLOATING OPERATION
- .01% LINE AND LOAD REGULATION
- OUTPUT VOLTAGE ADJUSTABLE FROM 2 TO 37 VOLTS
- OUTPUT CURRENT TO 150 mA WITHOUT EXTERNAL PASS TRANSISTOR


ABSOLUTE MAXIMUM RATINGS

Pulse Voltage from V^+ to V^- , (50 ms) (312 Grade)	50 V
Continuous Voltage from V^+ to V^-	40 V
Input-Output Voltage Differential	40 V
Differential Input Voltage	±5 V
Voltage Between Non-Inverting Input and V^-	+8 V
Current from V_Z	25 mA
Current from V_{REF}	15 mA
Internal Power Dissipation (Note 1)	
Metal Can	800 mW
Ceramic DIP	1000 mW
Silicone DIP	620 mW
Storage Temperature Range	
Metal Can, Ceramic DIP	–65°C to +150°C
Silicone DIP	–55°C to +125°C
Operating Temperature Range	
Military (312 Grade)	–55°C to +125°C
Commercial (393 Grade)	0°C to + 70°C
Lead Temperature	
Metal Can, Ceramic DIP (Soldering, 60 seconds)	300°C
Silicone DIP (Soldering, 10 seconds)	260°C

EQUIVALENT CIRCUIT




CONNECTION DIAGRAMS (TOP VIEW) 10 LEAD METAL CAN



Note: Pin 5 connected to case.

ORDER PART NOS: U5R7723312
U5R7723393

14 LEAD DIP (TOP VIEW)



FOR CERAMIC DIP
ORDER PART NOS.: U6A7723312
U6A7723393

FOR SILICONE DIP
ORDER PART NO.: U9A772393

ELECTRICAL CHARACTERISTICS (Note 2)

(312 GRADE)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Line Regulation	$V_{IN} = 12 \text{ V to } V_{IN} = 15 \text{ V}$		.01	0.1	% V_{OUT}
	$V_{IN} = 12 \text{ V to } V_{IN} = 40 \text{ V}$		.02	0.2	% V_{OUT}
	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_{IN} = 12 \text{ V to } V_{IN} = 15 \text{ V}$			0.3	% V_{OUT}
Load Regulation	$I_L = 1 \text{ mA to } I_L = 50 \text{ mA}$		.03	0.15	% V_{OUT}
	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $I_L = 1 \text{ mA to } I_L = 50 \text{ mA}$			0.6	% V_{OUT}
Ripple Rejection	$f = 50 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 0$		74		dB
	$f = 50 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 5 \mu\text{F}$		86		dB
Average Temperature Coefficient of Output Voltage	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		.002	.015	%/ $^{\circ}\text{C}$
Short Circuit Current Limit	$R_{SC} = 10 \Omega$, $V_{OUT} = 0$		65		mA
Reference Voltage		6.95	7.15	7.35	V
Output Noise Voltage	$BW = 100 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 0$		20		μV_{rms}
	$BW = 100 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 5 \mu\text{F}$		2.5		μV_{rms}
Long Term Stability			0.1		%/1000 hrs
Standby Current Drain	$I_L = 0$, $V_{IN} = 30 \text{ V}$		2.3	3.5	mA
Input Voltage Range		9.5		40	V
Output Voltage Range		2.0		37	V
Input-Output Voltage Differential		3.0		38	V


ELECTRICAL CHARACTERISTICS (Note 2)

(393 GRADE)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Line Regulation	$V_{IN} = 12 \text{ V to } V_{IN} = 15 \text{ V}$		.01	0.1	% V_{OUT}
	$V_{IN} = 12 \text{ V to } V_{IN} = 40 \text{ V}$		0.1	0.5	% V_{OUT}
	$0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$, $V_{IN} = 12 \text{ V to } V_{IN} = 15 \text{ V}$			0.3	% V_{OUT}
Load Regulation	$I_L = 1 \text{ mA to } I_L = 50 \text{ mA}$		.03	0.2	% V_{OUT}
	$0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$, $I_L = 1 \text{ mA to } I_L = 50 \text{ mA}$			0.6	% V_{OUT}
Ripple Rejection	$f = 50 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 0$		74		dB
	$f = 50 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 5 \mu\text{F}$		86		dB
Average Temperature Coefficient of Output Voltage	$0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$		.003	.015	%/ $^{\circ}\text{C}$
Short Circuit Current Limit	$R_{SC} = 10 \Omega$, $V_{OUT} = 0$		65		mA
Reference Voltage		6.80	7.15	7.50	V
Output Noise Voltage	$BW = 100 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 0$		20		μV_{rms}
	$BW = 100 \text{ Hz to } 10 \text{ kHz}$, $C_{REF} = 5 \mu\text{F}$		2.5		μV_{rms}
Long Term Stability			0.1		%/1000 hrs
Standby Current Drain	$I_L = 0$, $V_{IN} = 30 \text{ V}$		2.3	4.0	mA
Input Voltage Range		9.5		40	V
Output Voltage Range		2.0		37	V
Input-Output Voltage Differential		3.0		38	V

TYPICAL PERFORMANCE CURVES (312 GRADE)


MAXIMUM LOAD CURRENT
AS A FUNCTION OF
INPUT-OUTPUT VOLTAGE
DIFFERENTIAL




LOAD REGULATION
CHARACTERISTICS WITHOUT
CURRENT LIMITING




LOAD REGULATION
CHARACTERISTICS WITH
CURRENT LIMITING




LOAD REGULATION
CHARACTERISTICS
WITH CURRENT LIMITING



CURRENT LIMITING
CHARACTERISTICS




STANDBY CURRENT DRAIN
AS A FUNCTION OF
INPUT VOLTAGE




TYPICAL PERFORMANCE CURVES (393 GRADE)


MAXIMUM LOAD CURRENT
AS A FUNCTION OF
INPUT-OUTPUT VOLTAGE
DIFFERENTIAL




MAXIMUM LOAD CURRENT
AS A FUNCTION OF
INPUT-OUTPUT VOLTAGE
DIFFERENTIAL




LOAD REGULATION
CHARACTERISTICS WITHOUT
CURRENT LIMITING




LOAD REGULATION
CHARACTERISTICS
WITH CURRENT LIMITING



CURRENT LIMITING
CHARACTERISTICS




STANDBY CURRENT DRAIN
AS A FUNCTION OF
INPUT VOLTAGE




TYPICAL PERFORMANCE CURVES (FOR 312 AND 393 GRADES)


LINE REGULATION AS A FUNCTION OF INPUT-OUTPUT VOLTAGE DIFFERENTIAL




LOAD REGULATION AS A FUNCTION OF INPUT-OUTPUT VOLTAGE DIFFERENTIAL




CURRENT LIMITING CHARACTERISTICS AS A FUNCTION OF JUNCTION TEMPERATURE




LINE TRANSIENT RESPONSE



LOAD TRANSIENT RESPONSE



OUTPUT IMPEDANCE AS A FUNCTION OF FREQUENCY



NOTES

- Rating applies to ambient temperatures up to $25^\circ C$. Above $25^\circ C$ ambient derate linearly at $6.3 \text{ mW}/^\circ C$ for the Metal Can, $8.3 \text{ mW}/^\circ C$ for the Ceramic DIP and $6.3 \text{ mW}/^\circ C$ for the Silicone DIP.
- Unless otherwise specified, $T_A = 25^\circ C$, $V_{IN} = V^+ = V_C = 12V$, $V^- = 0$, $V_{OUT} = 5V$, $I_L = 1mA$, $R_{SC} = 0$, $C_1 = 100 \text{ pF}$, $C_{REF} = 0$ and divider impedance as seen by error amplifier $\leq 10 \text{ k}\Omega$ connected as shown in Fig. 1. Line and load regulation specifications are given for the condition of constant chip temperature. Temperature drifts must be taken into account separately for high dissipation conditions.
- L_1 is 40 turns of No. 20 enameled copper wire wound on Ferroxcube P36/22-3B7 pot core or equivalent with 0.009" air gap.
- Figures in parentheses may be used if R_1/R_2 divider is placed on opposite side of error amp.
- Replace R_1/R_2 in figures with divider shown in figure 13.
- V^+ must be connected to a +3 V or greater supply.
- For metal can applications where V_Z is required, an external 6.2 volt zener diode should be connected in series with V_{OUT} .

TABLE I
RESISTOR VALUES (k Ω) FOR STANDARD OUTPUT VOLTAGES


POSITIVE OUTPUT VOLTAGE	APPLICABLE FIGURES	FIXED OUTPUT $\pm 5\%$		OUTPUT ADJUSTABLE $\pm 10\%$ (Note 5)			NEGATIVE OUTPUT VOLTAGE	APPLICABLE FIGURES	FIXED OUTPUT $\pm 5\%$		5% OUTPUT ADJUSTABLE $\pm 10\%$		
		R_1	R_2	R_1	P_1	R_2			R_1	R_2	R_1	P_1	R_2
+3.0	1, 5, 6, 9, 12 (4)	4.12	3.01	1.8	0.5	1.2	+100	7	3.57	102	2.2	10	91
+3.6	1, 5, 6, 9, 12 (4)	3.57	3.65	1.5	0.5	1.5	+250	7	3.57	255	2.2	10	240
+5.0	1, 5, 6, 9, 12 (4)	2.15	4.99	.75	0.5	2.2	-6 (note 6)	3, (10)	3.57	2.43	1.2	0.5	.75
+6.0	1, 5, 6, 9, 12 (4)	1.15	6.04	0.5	0.5	2.7	-9	3, 10	3.48	5.36	1.2	0.5	2.0
+9.0	2, 4, (5, 6, 12, 9)	1.87	7.15	.75	1.0	2.7	-12	3, 10	3.57	8.45	1.2	0.5	3.3
+12	2, 4, (5, 6, 9, 12)	4.87	7.15	2.0	1.0	3.0	-15	3, 10	3.65	11.5	1.2	0.5	4.3
+15	2, 4, (5, 6, 9, 12)	7.87	7.15	3.3	1.0	3.0	-28	3, 10	3.57	24.3	1.2	0.5	10
+28	2, 4, (5, 6, 9, 12)	21.0	7.15	5.6	1.0	2.0	-45	8	3.57	41.2	2.2	10	33
+45	7	3.57	48.7	2.2	10	39	-100	8	3.57	97.6	2.2	10	91
+75	7	3.57	78.7	2.2	10	68	-250	8	3.57	249	2.2	10	240

TABLE II
FORMULAE FOR INTERMEDIATE OUTPUT VOLTAGES

Outputs from +2 to +7 volts [Figures 1, 5, 6, 9, 12, (4)] $V_{OUT} = [V_{REF} \times \frac{R_2}{R_1 + R_2}]$	Outputs from +4 to +250 volts [Figure 7] $V_{OUT} = [\frac{V_{REF}}{2} \times \frac{R_2 - R_1}{R_1}]; R_3 = R_4$	Current Limiting $I_{LIMIT} = \frac{V_{SENSE}}{R_{SC}}$
Outputs from +7 to +37 volts [Figures 2, 4, (5, 6, 9, 12)] $V_{OUT} = [V_{REF} \times \frac{R_1 + R_2}{R_2}]$	Outputs from -6 to -250 volts [Figures 3, 8, 10] $V_{OUT} = [\frac{V_{REF}}{2} \times \frac{R_1 + R_2}{R_1}]; R_3 = R_4$	Foldback Current Limiting $I_{KNEE} = [\frac{V_{OUT}}{R_{SC}} \times \frac{R_3}{R_4} + \frac{V_{SENSE}(R_3 + R_4)}{R_{SC} R_4}]$ $I_{SHORT\ CT} = [\frac{V_{SENSE}}{R_{SC}} \times \frac{R_3 + R_4}{R_4}]$

Figure 1


BASIC LOW VOLTAGE REGULATOR
($V_{out} = 2$ to 7 Volts)



Note: $R_3 = \frac{R_1 R_2}{R_1 + R_2}$ for minimum temperature drift.


Figure 2

BASIC HIGH VOLTAGE REGULATOR
($V_{out} = 7$ to 37 Volts)



Note: $R_3 = \frac{R_1 R_2}{R_1 + R_2}$ for minimum temperature drift.
 R_3 may be eliminated for minimum component count.

Figure 3
NEGATIVE VOLTAGE REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage -15 V
Line Regulation ($\Delta V_{IN} = 3\text{ V}$) 1 mV
Load Regulation ($\Delta I_L = 100\text{ mA}$) 2 mV

Note 7


Figure 4
POSITIVE VOLTAGE REGULATOR
(External NPN Pass Transistor)



TYPICAL PERFORMANCE

Regulated Output Voltage $+15\text{ V}$
Line Regulation ($\Delta V_{IN} = 3\text{ V}$) 1.5 mV
Load Regulation ($\Delta I_L = 1\text{ A}$) 15 mV


Figure 5
POSITIVE VOLTAGE REGULATOR
(External PNP Pass Transistor)



TYPICAL PERFORMANCE

Regulated Output Voltage $+5\text{ V}$
Line Regulation ($\Delta V_{IN} = 3\text{ V}$) 0.5 mV
Load Regulation ($\Delta I_L = 1\text{ A}$) 5 mV


Figure 6
FOLDBACK CURRENT LIMITING



TYPICAL PERFORMANCE

Regulated Output Voltage $+5\text{ V}$
Line Regulation ($\Delta V_{IN} = 3\text{ V}$) 0.5 mV
Load Regulation ($\Delta I_L = 10\text{ mA}$) 1 mV
Short Circuit Current 20 mA

Figure 7
POSITIVE FLOATING REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage $+50\text{ V}$
Line Regulation ($\Delta V_{IN} = 20\text{ V}$) 15 mV
Load Regulation ($\Delta I_L = 50\text{ mA}$) 20 mV

Note 7

Figure 8
NEGATIVE FLOATING REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage -100 V
Line Regulation ($\Delta V_{IN} = 20\text{ V}$) 30 mV
Load Regulation ($\Delta I_L = 100\text{ mA}$) 20 mV

Note 7

Figure 9
POSITIVE SWITCHING REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage	+5 V
Line Regulation ($\Delta V_{IN} = 30$ V)	10 mV
Load Regulation ($\Delta I_L = 2$ A)	80 mV

Note 3

Figure 10
NEGATIVE SWITCHING REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage	-15 V
Line Regulation ($\Delta V_{IN} = 20$ V)	8 mV
Load Regulation ($\Delta I_L = 2$ A)	6 mV

Notes 3, 7

Figure 11
REMOTE SHUTDOWN REGULATOR WITH CURRENT LIMITING




Note 1: Current limit transistor may be used for shutdown if current limiting is not required.
2: Add if $V_{out} > 10$ V

TYPICAL PERFORMANCE

Regulated Output Voltage	+5 V
Line Regulation ($\Delta V_{IN} = 3$ V)	0.5 mV
Load Regulation ($\Delta I_L = 50$ mA)	1.5 mV

Note 7


Figure 12
SHUNT REGULATOR




TYPICAL PERFORMANCE

Regulated Output Voltage	+5 V
Line Regulation ($\Delta V_{IN} = 10$ V)	0.5 mV
Load Regulation ($\Delta I_L = 100$ mA)	1.5 mV

Figure 13
OUTPUT VOLTAGE ADJUST



EQUIVALENT CIRCUIT



μA725

INSTRUMENTATION OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA725 is an instrumentation operational amplifier constructed on a single silicon chip using the Fairchild Planar* epitaxial process. It is intended for precise, low level signal amplification applications where low noise, low drift and accurate closed loop gain are required. The offset null capability, low power consumption, very high voltage gain as well as wide power supply voltage range provide superior performance for a wide range of instrumentation applications. The μA725 is pin compatible with the popular μA741 operational amplifier.

- **LOW INPUT NOISE CURRENT** **0.15 pA $\sqrt{\text{Hz}}$**
- **HIGH OPEN LOOP GAIN** **3,000,000**
- **LOW INPUT OFFSET CURRENT** **2 nA**
- **LOW INPUT VOLTAGE DRIFT** **0.6 $\mu\text{V}/^\circ\text{C}$**
- **HIGH COMMON MODE REJECTION** . . . **120 dB**
- **HIGH INPUT VOLTAGE RANGE** **$\pm 14 \text{ V}$**
- **WIDE POWER SUPPLY RANGE** **$\pm 3 \text{ V TO } \pm 22 \text{ V}$**
- **OFFSET NULL CAPABILITY**

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	$\pm 22 \text{ V}$
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Differential Input Voltage (Note 2)	$\pm 22 \text{ V}$
Input Voltage (Note 3)	$\pm 22 \text{ V}$
Voltage Between Offset Null and V^+	$\pm 0.5 \text{ V}$
Storage Temperature Range	
Metal Can, Ceramic DIP	$-65^\circ\text{C to } +150^\circ\text{C}$
Operating Temperature Range	
Military (312 grade)	$-55^\circ\text{C to } +125^\circ\text{C}$
Instrument (333 grade)	$-20^\circ\text{C to } +85^\circ\text{C}$
Commercial (393 grade)	$0^\circ\text{C to } +70^\circ\text{C}$
Lead Temperature	
Metal Can, Ceramic DIP (Soldering, 60 Seconds)	300°C


EQUIVALENT CIRCUIT



Pin numbers are shown for Metal Can only.

CONNECTION DIAGRAM


8 LEAD METAL CAN (TOP VIEW)



ORDER PART NOS.:

U5T7725312
U5T7725333
U5T7725393

14 LEAD DIP (TOP VIEW)



FOR CERAMIC DIP ORDER PART NOS.:

U6A7725312
U6A7725333
U6A7725393

312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$		0.5	1.0	mV
Input Offset Current			2.0	20	nA
Input Bias Current			42	100	nA
Input Noise Voltage	$f_o = 10\text{ Hz}$		15		$\text{nV}/\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		9.0		$\text{nV}/\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		8.0		$\text{nV}/\sqrt{\text{Hz}}$
Input Noise Current	$f_o = 10\text{ Hz}$		1.0		$\text{pA}/\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		0.3		$\text{pA}/\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		0.15		$\text{pA}/\sqrt{\text{Hz}}$
Input Resistance			1.5		$\text{M}\Omega$
Input Voltage Range		± 13.5	± 14		V
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$ $V_O = \pm 10\text{ V}$	1,000,000	3,000,000		V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	110	120		dB
Power Supply Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		2.0	10	$\mu\text{V}/\text{V}$
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 13.5		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13.5		V
Output Resistance			150		Ω
Power Consumption			80	105	mW


The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$ unless otherwise specified:

Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$			1.5	mV
Average Input Offset Voltage Drift (Without external trim)	$R_S = 50\Omega$		2.0	5.0	$\mu\text{V}/^\circ\text{C}$
Average Input Offset Voltage Drift (With external trim)	$R_S = 50\Omega$		0.6		$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +125^\circ\text{C}$		1.2	20	nA
	$T_A = -55^\circ\text{C}$		7.5	40	nA
Average Input Offset Current Drift			35	150	$\text{pA}/^\circ\text{C}$
Input Bias Current	$T_A = +125^\circ\text{C}$		20	100	nA
	$T_A = -55^\circ\text{C}$		80	200	nA
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $T_A = +125^\circ\text{C}$	1,000,000			V/V
	$R_L \geq 2\text{ k}\Omega$, $T_A = -55^\circ\text{C}$	250,000			V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	100			dB
	$R_S \leq 10\text{ k}\Omega$			20	$\mu\text{V}/\text{V}$
	$R_L \geq 2\text{ k}\Omega$	± 10			V


TYPICAL PERFORMANCE CURVES

312 GRADE


OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF TEMPERATURE FOR VARIOUS SUPPLY VOLTAGES



NULLED INPUT OFFSET VOLTAGE AS A FUNCTION OF TEMPERATURE



UNNULLED INPUT OFFSET VOLTAGE AS A FUNCTION OF TEMPERATURE



333 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)




PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$		0.5	1.5	mV
Input Offset Current			2.0	20	nA
Input Bias Current			50	100	nA
Input Noise Voltage	$f_o = 10\text{ Hz}$		15		nV/ $\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		12		nV/ $\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		8.0		nV/ $\sqrt{\text{Hz}}$
Input Noise Current	$f_o = 10\text{ Hz}$		1.0		pA/ $\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		0.8		pA/ $\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		0.6		pA/ $\sqrt{\text{Hz}}$
Input Resistance			1.5		M Ω
Input Voltage Range		± 13.5	± 14		V
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	500,000	3,000,000		V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	100	120		dB
Power Supply Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		2.0	10	$\mu\text{V/V}$
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 13.5		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13.5		V
Output Resistance			150		Ω
Power Consumption			80	120	mW

The following specifications apply for $-20^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$ unless otherwise specified:

Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$			2.5	mV
Average Input Offset Voltage Drift (Without external trim)	$R_S = 50\Omega$		2.0	10	$\mu\text{V}/^\circ\text{C}$
Average Input Offset Voltage Drift (With external trim)	$R_S = 50\Omega$		0.6		$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +85^\circ\text{C}$		2.0	20	nA
	$T_A = -20^\circ\text{C}$		5.0	40	nA
Average Input Offset Current Drift				300	pA/ $^\circ\text{C}$
Input Bias Current	$T_A = +85^\circ\text{C}$			100	nA
	$T_A = -20^\circ\text{C}$			200	nA
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $T_A = +85^\circ\text{C}$	500,000			V/V
	$R_L \geq 2\text{ k}\Omega$, $T_A = -20^\circ\text{C}$	250,000			V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	100			dB
Power Supply Rejection Ratio	$R_S \leq 10\text{ k}\Omega$			20	$\mu\text{V/V}$
Output Voltage Swing	$R_L \geq 2\text{ k}\Omega$	± 10			V

NOTES

- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for Metal Can and $8.3\text{ mW}/^\circ\text{C}$ for Ceramic DIP package.
- Rating applies for 5 ms pulses with 10% duty cycle, derate to $\pm 5\text{ V}$ for continuous operation.
- For supply voltages less than $\pm 22\text{ V}$, the absolute maximum input voltage is equal to the supply voltage.

TYPICAL PERFORMANCE CURVES
333 GRADE

393 GRADE


ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$		0.5	2.5	mV
Input Offset Current			2.0	35	nA
Input Bias Current			42	125	nA
Input Noise Voltage	$f_o = 10\text{ Hz}$		15		$\text{nV}/\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		9.0		$\text{nV}/\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		8.0		$\text{nV}/\sqrt{\text{Hz}}$
Input Noise Current	$f_o = 10\text{ Hz}$		1.0		$\text{pA}/\sqrt{\text{Hz}}$
	$f_o = 100\text{ Hz}$		0.3		$\text{pA}/\sqrt{\text{Hz}}$
	$f_o = 1\text{ kHz}$		0.15		$\text{pA}/\sqrt{\text{Hz}}$
Input Resistance			1.5		$\text{M}\Omega$
Input Voltage Range		± 13.5	± 14		V
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{OUT} = \pm 10\text{ V}$	250,000	3,000,000		V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	94	120		dB
Power Supply Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		2.0	35	$\mu\text{V}/\text{V}$
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 13.5		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13.5		V
Output Resistance			150		Ω
Power Consumption			80	150	mW

The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$ unless otherwise specified:


Input Offset Voltage (Without external trim)	$R_S \leq 10\text{ k}\Omega$			3.5	mV
Average Input Offset Voltage Drift (Without external trim)	$R_S = 50\Omega$		2.0		$\mu\text{V}/^\circ\text{C}$
Average Input Offset Voltage Drift (With external trim)	$R_S = 50\Omega$		0.6		$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$T_A = +70^\circ\text{C}$		1.2	35	nA
	$T_A = 0^\circ\text{C}$		4.0	50	nA
Average Input Offset Current Drift			10		$\text{pA}/^\circ\text{C}$
Input Bias Current	$T_A = +70^\circ\text{C}$			125	nA
	$T_A = 0^\circ\text{C}$			250	nA
Large Signal Voltage	$R_L \geq 2\text{ k}\Omega$, $T_A = +70^\circ$	125,000			V/V
	$R_L \geq 2\text{ k}\Omega$, $T_A = 0^\circ\text{C}$	125,000			V/V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		115		dB
Power Supply Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		20		$\mu\text{V}/\text{V}$
Output Voltage Swing	$R_L \geq 2\text{ k}\Omega$	± 10			V

OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF TEMPERATURE FOR VARIOUS SUPPLY VOLTAGES




TYPICAL PERFORMANCE CURVES 393 GRADE

NULLED INPUT OFFSET VOLTAGE AS A FUNCTION OF TEMPERATURE




UNNULLED INPUT OFFSET VOLTAGE AS A FUNCTION OF TEMPERATURE




TYPICAL PERFORMANCE CURVES FOR ALL GRADES (Unless Otherwise Specified)


INPUT OFFSET CURRENT
AS A FUNCTION
OF TEMPERATURE
312 GRADE




INPUT OFFSET CURRENT
AS A FUNCTION
OF TEMPERATURE
333 GRADE




INPUT OFFSET CURRENT
AS A FUNCTION
OF TEMPERATURE
393 GRADE




INPUT BIAS CURRENT
AS A FUNCTION
OF TEMPERATURE
312 GRADE




INPUT BIAS CURRENT
AS A FUNCTION
OF TEMPERATURE
333 GRADE




INPUT BIAS CURRENT
AS A FUNCTION
OF TEMPERATURE
393 GRADE




COMMON MODE REJECTION
RATIO AS A FUNCTION OF
TEMPERATURE




SUPPLY VOLTAGE
REJECTION RATIO
AS A FUNCTION
OF TEMPERATURE




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
TEMPERATURE




COMMON MODE REJECTION
RATIO AS A FUNCTION
OF SUPPLY VOLTAGE



D.C. CLOSED LOOP
VOLTAGE GAIN ERROR
AS A FUNCTION OF
SOURCE RESISTANCE




COMMON MODE INPUT
VOLTAGE RANGE AS A
FUNCTION OF
SUPPLY VOLTAGE




TYPICAL PERFORMANCE CURVES FOR ALL GRADES (Unless Otherwise Specified)


INPUT OFFSET VOLTAGE
DRIFT AS A
FUNCTION OF TIME




STABILIZATION TIME OF
INPUT OFFSET VOLTAGE
FROM POWER TURN-ON




CHANGE IN INPUT OFFSET
VOLTAGE DUE TO
THERMAL SHOCK AS A
FUNCTION OF TIME




INPUT NOISE VOLTAGE
AS A FUNCTION
OF FREQUENCY




INPUT NOISE CURRENT
AS A FUNCTION
OF FREQUENCY




BROADBAND NOISE FOR
VARIOUS BANDWIDTHS




NARROW BAND SPOT
NOISE FIGURE CONTOURS




NOISE FIGURE AS A
FUNCTION OF SOURCE
RESISTANCE




EQUIVALENT INPUT NOISE
VOLTAGE DUE TO
EXTERNAL COMMON MODE
NOISE AS A FUNCTION
OF FREQUENCY




EQUIVALENT INPUT RIPPLE
VOLTAGE DUE TO POWER
SUPPLY RIPPLE AS A
FUNCTION OF FREQUENCY



ABSOLUTE MAXIMUM
POWER DISSIPATION AS
A FUNCTION OF
AMBIENT TEMPERATURE




POWER CONSUMPTION
AS A FUNCTION OF
TEMPERATURE




Typical Performance Curves for All Grades


OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF FREQUENCY USING RECOMMENDED COMPENSATION NETWORKS




VALUES FOR SUGGESTED COMPENSATION NETWORKS FOR VARIOUS CLOSED LOOP VOLTAGE GAINS




FREQUENCY RESPONSE FOR VARIOUS CLOSED-LOOP GAINS USING RECOMMENDED COMPENSATION NETWORKS




OUTPUT VOLTAGE SWING AS A FUNCTION OF FREQUENCY FOR RECOMMENDED COMPENSATION NETWORKS



SLEW RATE AS A FUNCTION OF CLOSED-LOOP GAIN USING RECOMMENDED COMPENSATION NETWORKS




VOLTAGE OFFSET NULL CIRCUIT




COMPENSATION COMPONENT VALUES

A_{VCL}	R_1 (Ω)	C_1 (μF)	R_2 (Ω)	C_2 (μF)
10,000	10 k	50 pF	—	—
1,000	470	.001	—	—
100	47	.01	—	—
10	27	.05	270	.0015
1	10	.05	39	.02

FREQUENCY COMPENSATION CIRCUIT




TRANSIENT RESPONSE TEST CIRCUIT




Pin numbers are shown for Metal Can only.

TRANSIENT RESPONSE




TYPICAL APPLICATIONS

PRECISION AMPLIFIER — $AV_{CL} = 1000$




CHARACTERISTICS:
 $AV_{CL} = 1000 = 60 \text{ dB}$
 DC Gain Error = 0.05%
 Bandwidth = 1 kHz for -0.05% error
 Diff. Input Res. = 1 MΩ
 Typical amplifying capability
 $e_{IN} = 10 \mu V$ on $V_{CMI} = 1.0 \text{ V}$
 Caution: Minimize Stray Capacitance


ACTIVE FILTER — BANDPASS WITH 60 dB GAIN



ACTIVE FILTER FREQUENCY RESPONSE




OPEN LOOP VOLTAGE GAIN TEST CIRCUIT




$$A_{VO} \approx \frac{e_0}{e_1} \left(\frac{R_2 R_i + R_1 R_i + R_1 R_2}{R_1 R_i} \right) = \frac{e_0}{e_1} 101$$

PIN PHOTODIODE AMPLIFIER



NOTE: * Indicates $\pm 1\%$ Metal film resistors recommended for temperature stability.

THERMOCOUPLE AMPLIFIER



NOTE: * Indicates $\pm 1\%$ metal film resistors recommended for temperature stability.


$\pm 100 \text{ V}$ COMMON MODE RANGE INSTRUMENTATION AMPLIFIER

$$\frac{R_1}{R_7} = \frac{R_3}{R_4} \text{ for best CMRR}$$

$$R_3 = R_4$$

$$R_1 = R_6 = 10 R_3$$

$$\text{Gain} = \frac{R_7}{R_6}$$




INSTRUMENTATION AMPLIFIER WITH HIGH COMMON MODE REJECTION

$$\frac{R_2}{R_5} = \frac{R_6}{R_7} \text{ for best CMR}$$

$$R_1 = R_4$$

$$R_2 = R_5$$

$$\text{Gain} = \frac{R_6}{R_2} \left(1 + \frac{2R_1}{R_3} \right)$$



μA726

TEMPERATURE-CONTROLLED DIFFERENTIAL PAIR

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA726 is a monolithic transistor pair in high thermal-resistance package, held at a constant temperature by active temperature regulator circuitry. The transistor pair displays the excellent matching, close thermal coupling, and fast thermal response inherent in monolithic construction. The high gain and low standby dissipation of the regulator circuit permits tight temperature control over a wide range of ambient temperatures. It is intended for use as an input stage in very-low-drift DC amplifiers, replacing complex chopper-stabilized amplifiers; it is also useful as the nonlinear element in logarithmic amplifiers and multipliers where the highly predictable exponential relation between emitter-base voltage and collector current is employed. The device is constructed on a single silicon chip using the Fairchild Planar* process.

ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range

Military (312 Grade)

Commercial (323 Grade)

Storage Temperature Range

Lead Temperature (Soldering, 60 seconds)

Supply Voltage

Internal Power Dissipation

−55°C to +125°C

0°C to +85°C

−65°C to +150°C

300°C

±18 V

500 mW

MAXIMUM RATINGS FOR EACH TRANSISTOR

Maximum collector-to-substrate voltage

BVCBO

LVCEO (Note 1)

BVEBO

Collector Current

40 V

40 V


30 V

5 V

5 mA

Note 1: Measured at 1 mA collector current.

PHYSICAL DIMENSIONS



NOTES

All dimensions in inches


Leads are gold-plated kovar

Package weight is 1.32 grams


ORDER PART NOS. U5U7726312
U5U7726323

CONNECTION DIAGRAM

(TOP VIEW)



SCHEMATIC DIAGRAM



312 GRADE

ELECTRICAL CHARACTERISTICS ($-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_S = \pm 15\text{ V}$, $R_{adj} = 62\text{ k}\Omega$ unless otherwise specified)



PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$ $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$		1.0	2.5	mV
Input Offset Current	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		10	50	nA
Input Offset Current	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		50	200	nA
Average Input Bias Current	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		50	150	nA
Average Input Bias Current	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		250	500	nA
Offset Voltage Change	$I_C = 10\text{ }\mu\text{A}$, $5\text{ V} \leq V_{CE} \leq 25\text{ V}$, $R_S \leq 100\text{ k}\Omega$		0.3	6.0	mV
Offset Voltage Change	$I_C = 100\text{ }\mu\text{A}$, $5\text{ V} \leq V_{CE} \leq 25\text{ V}$, $R_S \leq 10\text{ k}\Omega$		0.3	6.0	mV
Input Offset Voltage Drift	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $+25^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		0.2	1.0	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Voltage Drift	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $-55^{\circ}\text{C} \leq T_A \leq +25^{\circ}\text{C}$		0.2	1.0	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current Drift	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		10		$\text{pA}/^{\circ}\text{C}$
Input Offset Current Drift	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		30		$\text{pA}/^{\circ}\text{C}$
Supply Voltage Rejection Ratio	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$, $R_S \leq 50\Omega$		25		$\mu\text{V}/\text{V}$
Low-Frequency Noise	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$ $\text{BW} = .001\text{ Hz to }0.1\text{ Hz}$		4.0		$\mu\text{V pp}$
Broadband Noise	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$ $\text{BW} = 0.1\text{ Hz to }10\text{ kHz}$		10		$\mu\text{V pp}$
Long-term Drift	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $T_A = 25^{\circ}\text{C}$		5.0		$\mu\text{V}/\text{week}$
High Frequency Current Gain	$f = 20\text{ MHz}$, $I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$	1.5	3.5		
Output Capacitance	$I_E = 0$, $V_{CB} = 5\text{ V}$		1.0		pF
Emitter Transition Capacitance	$I_E = 100\text{ }\mu\text{A}$		1.0		pF
Collector Saturation Voltage	$I_B = 100\text{ }\mu\text{A}$, $I_C = 1\text{ mA}$		0.5	1.0	V

323 GRADE



ELECTRICAL CHARACTERISTICS ($0^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$, $V_S = \pm 15\text{ V}$, $R_{adj} = 75\text{ k}\Omega$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$10\text{ }\mu\text{A} \leq I_C \leq 100\text{ }\mu\text{A}$ $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$		1.0	3.0	mV
Input Offset Current	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		10	100	nA
Input Offset Current	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		50	400	nA
Average Input Bias Current	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		50	300	nA
Average Input Bias Current	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		250	1000	nA
Offset Voltage Change	$I_C = 10\text{ }\mu\text{A}$, $5\text{ V} \leq V_{CE} \leq 25\text{ V}$, $R_S \leq 100\text{ k}\Omega$		0.3	6.0	mV
Offset Voltage Change	$I_C = 100\text{ }\mu\text{A}$, $5\text{ V} \leq V_{CE} \leq 25\text{ V}$, $R_S \leq 10\text{ k}\Omega$		0.3	6.0	mV
Input Offset Voltage Drift	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$		0.2	2.0	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current Drift	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		10		$\text{pA}/^{\circ}\text{C}$
Input Offset Current Drift	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$		30		$\text{pA}/^{\circ}\text{C}$
Supply Voltage Rejection Ratio	$I_C = 100\text{ }\mu\text{A}$, $R_S = 50\Omega$		25		$\mu\text{V}/\text{V}$
Low-Frequency Noise	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $\text{BW} = 0.001\text{ Hz to }0.1\text{ Hz}$		4.0		$\mu\text{V pp}$
Broadband Noise	$I_C = 10\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $\text{BW} = 0.1\text{ Hz to }10\text{ kHz}$		10		$\mu\text{V pp}$
Long-Term Drift	$I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$, $R_S \leq 50\Omega$, $T_A = 25^{\circ}\text{C}$		5.0		$\mu\text{V}/\text{week}$
High-Frequency Current Gain	$f = 20\text{ MHz}$, $I_C = 100\text{ }\mu\text{A}$, $V_{CE} = 5\text{ V}$	1.5	3.5		
Output Capacitance	$I_E = 0$, $V_{CB} = 5\text{ V}$		1.0		pF
Emitter Transition Capacitance	$I_E = 100\text{ }\mu\text{A}$		1.0		pF
Collector Saturation Voltage	$I_B = 100\text{ }\mu\text{A}$, $I_C = 1\text{ mA}$		0.5	1.0	V


TYPICAL PERFORMANCE CURVES 312 GRADE



323 GRADE



TYPICAL X1000 CIRCUIT



μA727

PREAMPLIFIER TEMPERATURE-CONTROLLED DIFFERENTIAL

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA727 is a monolithic, fixed gain, differential-input differential-output amplifier, constructed with the Fairchild Planar* epitaxial process, mounted in a high thermal-resistance package, and held at constant temperature by active regulator circuitry. The high gain and low standby dissipation of the regulator circuit give tight temperature control over a wide ambient temperature range. The device is intended for use as a self-contained input stage in very low-drift DC amplifiers, replacing complex chopper-stabilized amplifiers in such applications as thermo-couple bridges, strain gage transducers, and A to D converters.


- **VERY LOW OFFSET DRIFTS**
- **HIGH INPUT IMPEDANCE**
- **WIDE COMMON MODE RANGE**

ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	—55°C to +125°C
Military (312 Grade)	—20°C to +85°C
Commercial (333 Grade)	—65°C to +150°C
Storage Temperature Range	300°C
Lead Temperature (Soldering, 60 second time limit)	500 mW
Internal Power Dissipation	±18 V
Supply Voltage (Amplifier and Heater)	±10 V
Differential Input Voltage	±15 V
Common Mode Input Voltage	

PHYSICAL DIMENSIONS


(In accordance with JEDEC TO-100)



NOTES:


All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 grams

ORDER PART NOS. U5U7727312
U5U7727333



CONNECTION DIAGRAM

(Top View)



312 GRADE

ELECTRICAL CHARACTERISTICS ($-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_H^+ = V_A^+ = +15\text{ V}$, $V^- = -15\text{ V}$, $R_{ADJ} = 330\text{ k}\Omega$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\ \Omega$		2.0	10	mV
Input Offset Current			2.5	15	nA
Input Bias Current			12	40	nA
Input Offset Voltage Drift	$R_S \leq 50\ \Omega$, $+25^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		0.6	1.5	$\mu\text{V}/^{\circ}\text{C}$
	$R_S \leq 50\ \Omega$, $-55^{\circ}\text{C} \leq T_A \leq +25^{\circ}\text{C}$		0.6	1.5	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current Drift	$+25^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		2.0		$\text{pA}/^{\circ}\text{C}$
	$-55^{\circ}\text{C} \leq T_A \leq +25^{\circ}\text{C}$		2.0		$\text{pA}/^{\circ}\text{C}$
Input Bias Current Drift	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		15		$\text{pA}/^{\circ}\text{C}$
Differential Input Resistance			300		$\text{M}\Omega$
Common Mode Input Resistance			1000		$\text{M}\Omega$
Input Voltage Range		± 12	± 13		V
Supply Voltage Rejection Ratio	$R_S \leq 100\text{ k}\Omega$		80		$\mu\text{V}/\text{V}$
Common Mode Rejection Ratio	$R_S \leq 100\text{ k}\Omega$	80	100		dB
Output Resistance			1.0	4.0	$\text{k}\Omega$
Output Common Mode Voltage		-6.0	-5.0	-4.0	V
Differential Output Voltage Swing		± 5.0	± 7.0	± 10	V
Output Sink Current		10	30	80	μA
Differential Load Rejection			5.0	10	$\mu\text{V}/\mu\text{A}$
Differential Voltage Gain		60	100	250	
Low Frequency Noise	$\text{BW} = 10\text{ Hz to } 500\text{ Hz}$, $R_S \leq 50\ \Omega$		3.0		μV_{rms}
Long Term Drift	$R_S \leq 50\ \Omega$		5.0		$\mu\text{V}/\text{week}$
Amplifier Supply Current	$T_A = +25^{\circ}\text{C}$		1.0	2.0	mA
Heater Supply Current	$T_A = +25^{\circ}\text{C}$		10	15	mA


333 GRADE

ELECTRICAL CHARACTERISTICS ($-20^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$, $V_H^+ = V_A^+ = +15\text{ V}$, $V^- = -15\text{ V}$, $R_{ADJ} = 1\text{M}\Omega$, unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\ \Omega$		2.0	10	mV
Input Offset Current			2.5	25	nA
Input Bias Current			12	75	nA
Input Offset Voltage Drift	$R_S \leq 50\ \Omega$		0.6	3.0	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current Drift			2.0		$\text{pA}/^{\circ}\text{C}$
Input Bias Current Drift			15		$\text{pA}/^{\circ}\text{C}$
Differential Input Resistance			300		$\text{M}\Omega$
Common Mode Input Resistance			1000		$\text{M}\Omega$
Input Voltage Range		± 12	± 13		V
Supply Voltage Rejection Ratio	$R_S \leq 100\text{ k}\Omega$		80		$\mu\text{V}/\text{V}$
Common Mode Rejection Ratio	$R_S \leq 100\text{ k}\Omega$	70	100		dB
Output Resistance			1.0	4.0	$\text{k}\Omega$
Output Common Mode Voltage		-7.0	-5.0	-4.0	V
Differential Output Voltage Swing		± 3.0	± 7.0	± 10	V
Output Sink Current		10	30	80	μA
Differential Load Rejection			5.0	15	$\mu\text{V}/\mu\text{A}$
Differential Voltage Gain		50	100	250	
Low Frequency Noise	$\text{BW} = 10\text{ Hz to } 500\text{ Hz}$, $R_S \leq 50\ \Omega$		3.0		μV_{rms}
Long Term Drift	$R_S \leq 50\ \Omega$		5.0		$\mu\text{V}/\text{week}$
Amplifier Supply Current	$T_A = +25^{\circ}\text{C}$		1.0	2.0	mA
Heater Supply Current	$T_A = +25^{\circ}\text{C}$		10	15	mA

TYPICAL PERFORMANCE CURVES


**NOISE VOLTAGE
AS A FUNCTION OF
FREQUENCY**




**NOISE CURRENT
AS A FUNCTION OF
FREQUENCY**




SPOT NOISE FIGURE CONTOURS




**RECOMMENDED R_{ADJ} AS
A FUNCTION OF MAXIMUM
AMBIENT TEMPERATURE**




**RELATIVE CHIP TEMPERATURE
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**POWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**INPUT COMMON MODE VOLTAGE
RANGE AS A FUNCTION OF
SUPPLY VOLTAGE**




**OUTPUT COMMON MODE
VOLTAGE AS A FUNCTION OF
SUPPLY VOLTAGE**




**AMPLIFIER CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGE**




**DIFFERENTIAL VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGE**




**REQUIRED R_{ADJ} FOR CONSTANT
 I_{ADJ} AS A FUNCTION OF
SUPPLY VOLTAGE**




**OPEN-LOOP FREQUENCY
RESPONSE FOR VARIOUS
VALUES OF COMPENSATION**



FREQUENCY COMPENSATION CIRCUIT



TYPICAL X1000 CIRCUIT



μA729

FM STEREO MULTIPLEX DECODER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA729 is a monolithic FM Stereo Multiplex Decoder System constructed on a single silicon chip using the Fairchild Planar® Epitaxial Process. This integrated circuit accomplishes the demodulation of a Stereo Multiplex Signal into the Right and Left audio channels while inherently suppressing SCA frequency components. Internal provision is made for interstation audio muting, stereo/mono mode switching and driving an external stereo mode indicator lamp. The excellent performance, wide supply range and low external parts requirement makes the μA729 suitable for all line-operated and automotive FM Stereo Multiplex applications. For Stereo Decoding with internal separation adjustment, see the μA732 Data Sheet. For stereo decoding without automatic muting and stereo switching, see the μA767 Data Sheet. See Note 1.

- 55 dB CHANNEL SEPARATION, EXTERNALLY ADJUSTABLE
- 55 dB STORECAST REJECTION WITHOUT SCA FILTERS
- HIGH-CURRENT STEREO INDICATOR LAMP DRIVER
- OPERATION WITH 8 V TO 14 V SUPPLIES
- INTERNAL STEREO SWITCHING AND AUDIO MUTING FUNCTIONS

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (Note 2)	+15 V
Voltage at Stereo Lamp Driver Terminal	+22 V
Current into Stereo Lamp Driver Terminal (Note 3)	100 mA
Internal Power Dissipation	670 mW
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +125°C
Lead Temperature (Soldering, 10 Sec.)	+260°C


BLOCK DIAGRAM



Notes on following page.

PHYSICAL DIMENSIONS CERAMIC DIP

In accordance with
JEDEC (TO-116) outline




NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020 inch diameter lead
Leads are tin-plated kovar
Package weight is 2.0 grams

ORDER PART NO. U6A7729394

CONNECTION DIAGRAM (TOP VIEW)




*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = +12\text{V}$, 200 mV RMS Standard Stereo Multiplex signal applied to Input, unless otherwise specified (Note 4). Refer to Test Circuit of Figure 1.)

PARAMETER	MIN.	TYP.	MAX.	UNITS
Supply Current		10	18	mA
Input Resistance	12	20		k Ω
Stereo Separation (Adjusted)				
$f = 100\text{ Hz}$		45		dB
$f = 1\text{ kHz}$	30	55		dB
$f = 10\text{ kHz}$	20	50		dB
Channel Balance (Monaural Input)		0.2		dB
Total Harmonic Distortion		0.5	1.0	%
Voltage Gain		1.0		V/V
67 kHz Storecast Rejection (Note 5)		55		dB
19 kHz Pilot Level Required at Input for:				
Stereo Indicator Lamp on		12	22	mV RMS
Stereo Indicator Lamp off	4.0	8.0		mV RMS
DC Voltage Required at Pin 4 for				
Stereo-Monaural Switching				
Stereo on	1.0	1.25	1.5	V DC
Stereo off	0.6	0.85	1.0	V DC
DC Voltage Required at Pin 5 for Audio				
Mute Switching				
Audio on	1.0	1.20	1.5	V DC
Audio off	0.6	0.85	1.0	V DC
Mute Attenuation of Audio	45	55		dB
High Frequency Audio Components in Left and Right Outputs (dB below 1 kHz output)				
19 kHz		30		dB
38 kHz		25		dB

NOTES:

- (1) The $\mu A729$ is a plug-in replacement for the MC1305. For $\mu A729$ applications information, and other Fairchild Communications Integrated circuits see listing on last page.
- (2) Power supply transients up to 22V are permissible for periods of 15 seconds. However, extended operation at voltages greater than 15V should be avoided as the maximum allowable internal power dissipation for this device may be exceeded.
- (3) Rating applies to steady state current. Maximum permissible surge current during turn-on of the Stereo Indicator Lamp is 500 mA.
- (4) "Standard Stereo Multiplex Signal" here refers to a 200mV RMS (0.56V p-p) composite stereo signal including 10% pilot with $L = 1$ and $R = 1$ as described in the FCC Rules on FM Broadcasting.
- (5) Measured with a stereo composite signal consisting of 80% stereo, 10% pilot and 10% SCA as defined in the FCC Rules on FM Broadcasting.

TYPICAL PERFORMANCE CURVES



- (1) Capacitors C_1 , C_2 and C_3 should be polystyrene or mylar.
- (2) Coils L_1 and L_2 are 7.0 mH nominal with $Q_{u1} = 60$ (Miller #1361 or equivalent).
- (3) Coil L_3 is 8.0 mH nominal with $Q_{u1} = 80$, tapped at 10:1 turns ratio. (Miller #1362 or equivalent).
- (4) Resistor R_1 can be increased (or decreased) in value to increase (or decrease) the 19kHz sensitivity.



μA730

DIFFERENTIAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA730 is a differential amplifier constructed on a single silicon-chip using the Fairchild Planar* epitaxial process. This device has a wide range of applications since it has both a differential input and output; any combination of single-ended or differential configurations can be employed at its input and output. The emitter follower output stage gives this device a low output impedance making it useful as a preamplifier.


ABSOLUTE MAXIMUM RATINGS

Supply Voltage	15 V
Differential Input Voltage	±5 V
Common Mode Input Voltage	2.5 to 5.5 V
Internal Power Dissipation (Note 1)	500 mW
Operating Temperature Range	
Military (312 Grade)	−55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Storage Temperature Range	−65°C to +150°C
Lead Temperature (Soldering, 60 seconds)	+300°C

NOTES:


(1) Rating applies for ambient temperature to +70°C; derate linearly at 6.3 mW/°C for ambient temperatures above +70°C.

SCHEMATIC DIAGRAM



PHYSICAL DIMENSIONS


in accordance with
JEDEC(TO-99) outline



NOTES: Dimensions as per latest J-10 committee
All dimensions in inches
Leads are gold plated Kovar
Package weight is 1.22 grams

**ORDER PART NOS. U5B7730312
U5B7730393**

CONNECTION DIAGRAM (Top View)



Note: Pin 4 connected to case




*Planar is a patented Fairchild process.

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = 12.0\text{ V}$, and $V_{CM} = 3.5\text{ V}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\Omega$		1.0	2.5	mV
Input Offset Current			0.5	1.5	μA
Input Bias Current			3.5	7.5	μA
Input Resistance		5.0	20		$k\Omega$
Differential Voltage Gain	$R_L \geq 100\text{ k}\Omega$	100	145	160	
Differential Distortion	$R_L \geq 100\text{ k}\Omega$		80	300	mVpp
Bandwidth		1.0	1.5		MHz
Single-Ended Output Resistance			70	500	Ω
Output Voltage Swing	$R_L \geq 100\text{ k}\Omega$	5.0	8.0		Vpp
Supply Current	$R_L \geq 100\text{ k}\Omega$		9.5	13	mA
Power Consumption	$R_L \geq 100\text{ k}\Omega$		114	156	mW
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 50\Omega$			3.5	mV
Input Offset Current	$T_A = +125^\circ\text{C}$		0.2	1.5	μA
	$T_A = -55^\circ\text{C}$		1.0	3.0	μA
Input Bias Current	$T_A = -55^\circ\text{C}$		6.5	15	μA
Input Resistance		0.9			$k\Omega$
Input Voltage Range		3.5		5.2	V
Common Mode Rejection Ratio	$R_S \leq 50\Omega$ $f \leq 1.0\text{ kHz}$	70	85		dB
	$+3.5\text{ V} \leq V_{CM} \leq +5.2\text{ V}$				
Differential Voltage Gain	$R_L \geq 100\text{ k}\Omega$	90		175	
Common Mode Output Voltage		5.5	7.0	7.75	V
Output Resistance				600	Ω
Output Voltage Swing		4.5	6.8		Vpp
Supply Current	$T_A = -55^\circ\text{C}$		10	15	mA
	$T_A = 125^\circ\text{C}$		8.0	11	mA
Power Consumption	$T_A = -55^\circ\text{C}$		120	180	mW
	$T_A = 125^\circ\text{C}$		96	121	mW

TYPICAL PERFORMANCE CURVES






393 GRADE













ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V_+ = 12.0\text{ V}$, and $V_{CM} = 3.5\text{ V}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\Omega$		2.0	5.0	mV
Input Offset Current			0.7	3.0	μA
Input Bias Current			4.5	16.0	μA
Input Resistance		2.5	15		$k\Omega$
Differential Voltage Gain	$R_L \geq 100\text{ k}\Omega$	100	135	160	
Differential Distortion	$R_L \geq 100\text{ k}\Omega$		85	300	mVpp
Bandwidth		1.0	1.5		MHz
Single-Ended Output Resistance			70	500	Ω
Output Voltage Swing	$R_L \geq 100\text{ k}\Omega$	5.0	8.0		Vpp
Supply Current	$R_L \geq 100\text{ k}\Omega$		9.5	13	mA
Power Consumption	$R_L \geq 100\text{ k}\Omega$		114	156	mW
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$					
Input Offset Voltage	$R_S \leq 50\Omega$			7.5	mV
Input Offset Current	$T_A = +70^\circ\text{C}$		0.5	3.0	μA
	$T_A = 0^\circ\text{C}$		0.8	5.0	μA
Input Bias Current	$T_A = 0^\circ\text{C}$		5.0	20	μA
Input Resistance		1.8			$k\Omega$
Input Voltage Range		+3.5		+5.2	
Common Mode Rejection Ratio	$R_S \leq 50\Omega$ $f \leq 1.0\text{ kHz}$	60	80		dB
	$+3.5\text{ V} \leq V_{CM} \leq +5.2\text{ V}$				
Differential Voltage Gain	$R_L \geq 100\text{ k}\Omega$	80		190	
Common Mode Output Voltage		5.0	7.0	8.0	V
Output Resistance				600	Ω
Output Voltage Swing		4.5	7.5		Vpp
Supply Current	$T_A = 0^\circ\text{C}$		10	15	mA
	$T_A = +70^\circ\text{C}$		8.8	13	mA
Power Consumption	$T_A = 0^\circ\text{C}$		120	180	mW
	$T_A = +70^\circ\text{C}$		106	156	mW

TYPICAL PERFORMANCE CURVES




TYPICAL PERFORMANCE CURVES (FOR 312 GRADE)




TYPICAL PERFORMANCE CURVES (FOR 393 GRADE)


INPUT BIAS CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




INPUT RESISTANCE AS A FUNCTION OF AMBIENT TEMPERATURE




VOLTAGE TRANSFER CHARACTERISTICS




DIFFERENTIAL VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




DIFFERENTIAL VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGE




DIFFERENTIAL DISTORTION AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT RESISTANCE AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT VOLTAGE SWING AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT VOLTAGE SWING AS A FUNCTION OF SUPPLY VOLTAGE




OUTPUT VOLTAGE SWING AS A FUNCTION OF LOAD RESISTANCE



SUPPLY CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




SUPPLY CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




TYPICAL PERFORMANCE CURVES


COMMON MODE REJECTION RATIO AS A FUNCTION OF AMBIENT TEMPERATURE



COMMON MODE OUTPUT VOLTAGE AS A FUNCTION OF AMBIENT TEMPERATURE



COMMON MODE OUTPUT VOLTAGE AS A FUNCTION OF SUPPLY VOLTAGE



μA732

FM STEREO MULTIPLEX DECODER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA732 is a monolithic FM Stereo Multiplex Decoder System constructed on a single silicon chip using the Fairchild Planar* Epitaxial Process. This integrated circuit accomplishes the demodulation of a Stereo Multiplex Signal into the Right and Left audio channels while inherently suppressing SCA frequency components. Internal provision is made for interstation audio muting, stereo/mono mode switching and driving an external stereo mode indicator lamp. The excellent performance, wide supply range and low external parts requirement makes the μA732 suitable for all line-operated and automotive FM Stereo Multiplex applications. For Stereo Decoding with external separation adjustment, see the μA729 Data Sheet. See Note 1.

- 45 dB CHANNEL SEPARATION
- 55 dB STORECAST REJECTION WITHOUT SCA FILTERS
- HIGH-CURRENT STEREO INDICATOR LAMP DRIVER
- OPERATION WITH 8 V TO 14 V SUPPLIES
- INTERNAL STEREO SWITCHING AND AUDIO MUTING FUNCTIONS

ABSOLUTE MAXIMUM RATINGS


Supply Voltage (Note 2)	+15 V
Voltage at Stereo Lamp Driver Terminal	+22 V
Current into Stereo Lamp Driver Terminal (Note 3)	100 mA
Internal Power Dissipation	670 mW
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +125°C
Lead Temperature (Soldering, 10 Sec.)	+260°C

BLOCK DIAGRAM



PHYSICAL DIMENSIONS CERAMIC DIP

In accordance with
JEDEC (TO-116) outline




NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers.
- They are purposely shipped with "positive" misalignment to facilitate insertion.
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams

ORDER PART NO. U6A7732394

CONNECTION DIAGRAM (TOP VIEW)




ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = +12\text{ V}$, 200 mV RMS Standard Stereo Multiplex signal applied to Input, unless otherwise specified (Note 4). Refer to Test Circuit of Figure 1.)

PARAMETER	MIN.	TYP.	MAX.	UNITS
Supply Current		11	18	mA
Input Resistance	12	20		k Ω
Stereo Separation				
$f = 100\text{ Hz}$		40		dB
$f = 1\text{ kHz}$	30	45		dB
$f = 10\text{ kHz}$	20	40		dB
Channel Balance (Monaural Input)		0.2		dB
Total Harmonic Distortion		0.5	1.0	%
Voltage Gain		1.0		V/V
67 kHz Storecast Rejection (Note 5)		55		dB
19 kHz Pilot Level Required at Input for:				
Stereo Indicator Lamp on		12	22	mV RMS
Stereo Indicator Lamp off	4.0	8.0		mV RMS
DC Voltage Required at Pin 4 for				
Stereo-Monaural Switching				
Stereo on	1.0	1.25	1.5	V DC
Stereo off	0.6	0.85	1.0	V DC
DC Voltage Required at Pin 5 for Audio				
Mute Switching				
Audio on	1.0	1.20	1.5	V DC
Audio off	0.6	0.85	1.0	V DC
Mute Attenuation of Audio	45	55		dB
High Frequency Audio Components in Left and Right Outputs (dB below 1 kHz output)				
19 kHz		30		dB
38 kHz		25		dB

NOTES:

- (1) The $\mu A732$ is a plug-in replacement for the MC1304.
- (2) Power supply transients up to 22V are permissible for periods of 15 seconds. However, extended operation at voltages greater than 15V should be avoided as the maximum allowable internal power dissipation for this device may be exceeded.
- (3) Rating applies to steady state current. Maximum permissible surge current during turn-on of the Stereo Indicator Lamp is 500 mA.
- (4) "Standard Stereo Multiplex Signal" here refers to a 200mV RMS (0.56V p-p) composite stereo signal including 10% pilot with L = 1 and R = 1 as described in the FCC Rules on FM Broadcasting.
- (5) Measured with a stereo composite signal consisting of 80% stereo, 10% pilot and 10% SCA as defined in the FCC Rules on FM Broadcasting.

TYPICAL PERFORMANCE CURVES

$\mu A732$ FM STEREO MULTIPLEX DECODER TEST CIRCUIT AND TYPICAL APPLICATION





Fig. 1

NOTES:

- (1) Capacitors C_1 , C_2 and C_3 should be polystyrene or mylar.
- (2) Coils L_1 and L_2 are 7.0 mH nominal with $Q_{UL} = 60$ (Miller #1361 or equivalent).
- (3) Coil L_3 is 8.0mH nominal with $Q_{UL} = 80$, tapped at 10:1 turns ratio. (Miller #1362 or equivalent).
- (4) Resistor R_1 can be increased (or decreased) in value to increase (or decrease) the 19kHz sensitivity.

$\mu A732$ FM STEREO MULTIPLEX DECODER EQUIVALENT CIRCUIT



μA733

DIFFERENTIAL VIDEO AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA733 is a monolithic two-stage differential input, differential output video amplifier constructed on a single silicon chip using the Fairchild Planar* epitaxial process. Internal series-shunt feedback is used to obtain wide bandwidth, low phase distortion, and excellent gain stability. Emitter follower outputs enable the device to drive capacitive loads and all stages are current-source biased to obtain high power supply and common mode rejection ratios. It offers fixed gains of 10, 100, or 400 without external components, and adjustable gains from 10 to 400 by the use of a single external resistor. No external frequency compensation components are required for any gain option. The device is particularly useful in magnetic tape or disc file systems using phase or NRZ encoding and in high-speed thin film or plated wire memories. Other applications include general-purpose video and pulse amplifiers where wide bandwidth, low phase shift, and excellent gain stability are required.

- 120 MHz BANDWIDTH
- 250 kΩ INPUT RESISTANCE
- SELECTABLE GAINS OF 10, 100, AND 400
- NO FREQUENCY COMPENSATION REQUIRED

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	±8 V
Differential Input Voltage	±5 V
Common Mode Input Voltage	±6 V
Output Current	10 mA
Internal Power Dissipation (Note 1)	
Flatpak	570 mW
Metal Can	500 mW
Ceramic DIP	670 mW
Operating Temperature Range	-55°C to +125°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 60 second time limit)	300°C

CONNECTION DIAGRAM (Top Views)



PHYSICAL DIMENSIONS

In accordance with JEDEC (TO-100) outline
METAL CAN




NOTES:

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 grams
Lead 5 is connected to case

ORDER PART NO.

U5F773312
U5F773393

In accordance with JEDEC (TO-116) outline
14 LEAD DUAL IN-LINE




NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers
They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for a .020 inch diameter lead
Leads are tin plated kovar
Package weight is 2.0 grams

ORDER PART NO. U6A7733312
U6A7733393

In accordance with JEDEC (TO-91) outline
10 LEAD CERPAK



NOTES:

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.26 gram

ORDER PART NO. U3F7733312

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V_S = \pm 6.0\text{ V}$ unless otherwise specified)

PARAMETER (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Differential Voltage Gain					
Gain 1 (Note 2)		300	400	500	
Gain 2 (Note 3)		90	100	110	
Gain 3 (Note 4)		9.0	10	11	
Bandwidth	$R_S = 50\ \Omega$				
Gain 1			40		MHz
Gain 2			90		MHz
Gain 3			120		MHz
Risetime	$R_S = 50\ \Omega$, $V_{out} = 1\text{ Vpp}$				
Gain 1			10.5		ns
Gain 2			4.5	10	ns
Gain 3			2.5		ns
Propagation Delay	$R_S = 50\ \Omega$, $V_{out} = 1\text{ Vpp}$				
Gain 1			7.5		ns
Gain 2			6.0	10	ns
Gain 3			3.6		ns
Input Resistance					
Gain 1			4.0		k Ω
Gain 2		20	30		k Ω
Gain 3			250		k Ω
Input Capacitance	Gain 2		2.0		pF
Input Offset Current			0.4	3.0	μA
Input Bias Current			9.0	20	μA
Input Noise Voltage	$R_S = 50\ \Omega$, BW = 1 kHz to 10 MHz		12		μVrms
Input Voltage Range		± 1.0			V
Common Mode Rejection Ratio					
Gain 2	$V_{cm} = \pm 1\text{ V}$, $f \leq 100\text{ kHz}$	60	86		dB
Gain 2	$V_{cm} = \pm 1\text{ V}$, $f = 5\text{ MHz}$		60		dB
Supply Voltage Rejection Ratio					
Gain 2	$\Delta V_S = \pm 0.5\text{ V}$	50	70		dB
Output Offset Voltage					
Gain 1			0.6	1.5	V
Gain 2 and Gain 3			0.35	1.0	V
Output Common Mode Voltage		2.4	2.9	3.4	V
Output Voltage Swing		3.0	4.0		Vpp
Output Sink Current		2.5	3.6		mA
Output Resistance			20		Ω
Power Supply Current			18	24	mA

The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$

Differential Voltage Gain					
Gain 1 (Note 2)		200		600	
Gain 2 (Note 3)		80		120	
Gain 3 (Note 4)		8.0		12	
Input Resistance—Gain 2		8.0			k Ω
Input Offset Current				5.0	μA
Input Bias Current				40	μA
Input Voltage Range		± 1.0			V
Common Mode Rejection Ratio		50			dB
Supply Voltage Rejection Ratio		50			dB
Output Offset Voltage—Gain 1				1.5	V
Output Offset Voltage—Gain 2 & 3				1.2	V
Output Swing		2.5			Vpp
Output Sink Current		2.2			mA
Positive Supply Current				27	mA

393 GRADE













ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V_S = \pm 6.0\text{ V}$ unless otherwise specified)

PARAMETER (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Differential Voltage Gain					
Gain 1 (Note 2)		250	400	600	
Gain 2 (Note 3)		80	100	120	
Gain 3 (Note 4)		8.0	10	12	
Bandwidth	$R_S = 50\ \Omega$				
Gain 1			40		MHz
Gain 2			90		MHz
Gain 3			120		MHz
Risetime	$R_S = 50\ \Omega$, $V_{out} = 1\text{ Vpp}$				
Gain 1			10.5		ns
Gain 2			4.5	12	ns
Gain 3			2.5		ns
Propagation Delay	$R_S = 50\ \Omega$, $V_{out} = 1\text{ Vpp}$				
Gain 1			7.5		ns
Gain 2			6.0	10	ns
Gain 3			3.6		ns
Input Resistance					
Gain 1			4.0		k Ω
Gain 2		10	30		k Ω
Gain 3			250		k Ω
Input Capacitance	Gain 2		2.0		pF
Input Offset Current			0.4	5.0	μA
Input Bias Current			9.0	30	μA
Input Noise Voltage	$R_S = 50\ \Omega$, BW = 1 kHz to 10 MHz		12		μVrms
Input Voltage Range		± 1.0			V
Common Mode Rejection Ratio					
Gain 2	$V_{cm} = \pm 1\text{ V}$, $f \leq 100\text{ kHz}$	60	86		dB
Gain 2	$V_{cm} = \pm 1\text{ V}$, $f = 5\text{ MHz}$		60		dB
Supply Voltage Rejection Ratio					
Gain 2	$\Delta V_S = \pm 0.5\text{ V}$	50	70		dB
Output Offset Voltage					
Gain 1			0.6	1.5	V
Gain 2 and Gain 3			0.35	1.5	V
Output Common Mode Voltage		2.4	2.9	3.4	V
Output Voltage Swing		3.0	4.0		Vpp
Output Sink Current		2.5	3.6		mA
Output Resistance			20		Ω
Power Supply Current			18	24	mA

The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$


Differential Voltage Gain					
Gain 1 (Note 2)		250		600	
Gain 2 (Note 3)		80		120	
Gain 3 (Note 4)		8.0		12	
Input Resistance—Gain 2		8.0			k Ω
Input Offset Current				6.0	μA
Input Bias Current				40	μA
Input Voltage Range		± 1.0			V
Common Mode Rejection Ratio					
Gain 2	$V_{cm} = \pm 1\text{ V}$, $f \leq 100\text{ kHz}$	50			dB
Supply Voltage Rejection Ratio					
Gain 2	$\Delta V_S = \pm 0.5\text{ V}$	50			dB
Output Offset Voltage (All Gain)				1.5	V
Output Voltage Swing		2.8			Vpp
Output Sink Current		2.5			mA
Power Supply Current				27	mA

TYPICAL PERFORMANCE CURVES




TYPICAL PERFORMANCE CURVES


OUTPUT VOLTAGE AND CURRENT SWING AS A FUNCTION OF SUPPLY VOLTAGE




OUTPUT VOLTAGE SWING AS A FUNCTION OF LOAD RESISTANCE





GAIN VERSUS FREQUENCY AS A FUNCTION OF SUPPLY VOLTAGE




INPUT NOISE VOLTAGE AS A FUNCTION OF SOURCE RESISTANCE




VOLTAGE GAIN ADJUST CIRCUIT

VOLTAGE GAIN AS A FUNCTION OF R_{ADJ} 


INPUT RESISTANCE AS A FUNCTION OF TEMPERATURE



SUPPLY CURRENT AS A FUNCTION OF TEMPERATURE



SUPPLY CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




NOTES


1. Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for the Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak package.
2. Gain Select pins G_{1A} and G_{1B} connected together.
3. Gain Select pins G_{2A} and G_{2B} connected together.
4. All Gain Select pins open.

TYPICAL APPLICATIONS


VOLTAGE CONTROLLED OSCILLATOR




OSCILLATOR FREQUENCY FOR VARIOUS CAPACITOR VALUES



PHASE ENCODING PLAYBACK SYSTEM



EQUIVALENT CIRCUIT



μA734

PRECISION VOLTAGE COMPARATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA734 is a precision voltage comparator constructed on a single silicon chip using the Fairchild Planar* epitaxial process. It is specifically designed for high accuracy level sensing and measuring applications. The μA734 is extremely useful for analog-to-digital converters with twelve bit accuracies and one mega-bit conversion rates. Maximum resolution is obtained by high gain, low input offset current, and low input offset voltage. Its superior temperature stability can be improved by offset nulling which further reduces offset voltage drift. Balanced or unbalanced supply operation and standard TTL logic compatibility enhance the μA734's versatility.

- **CONSTANT INPUT IMPEDANCE OVER DIFFERENTIAL INPUT RANGE**
- **HIGH INPUT IMPEDANCE**
- **LOW DRIFT**
- **HIGH GAIN**
- **BALANCED OFFSET NULL CAPABILITY**
- **WIDE SUPPLY VOLTAGE RANGE**
- **TTL COMPATIBLE**

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	±18 V
Peak Output Current	10 mA
Differential Input Voltage	±10 V
Input Voltage Range	±V _S -2.0 V
Voltage Between Offset Null and V ⁻	±0.5 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Silicone DIP	340 mW
Mini DIP	310 mW
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Storage Temperature Range	
Metal Can, Ceramic DIP	-65°C to +150°C
Silicone DIP and Mini DIP	-55°C to +125°C
Lead Temperature	
Metal Can, Ceramic DIP (Soldering, 60 Seconds Max.)	300°C
Silicone DIP and Mini DIP (Soldering, 10 Seconds Max.)	260°C

EQUIVALENT CIRCUIT




CONNECTION DIAGRAMS

10-LEAD METAL CAN (TOP VIEW)



ORDER PART NOS: U5F7734312
U5F7734393


14-LEAD DIP (TOP VIEW)



FOR CERAMIC DIP
ORDER PART NOS: U6A7734312
U6A7734393

FOR SILICONE DIP
ORDER PART NO: U9A7734393

MINI DIP (TOP VIEW)



ORDER PART NO: U9T7734393

± 15 VOLT OPERATION FOR 312 GRADEELECTRICAL CHARACTERISTICS [$T_A = 25^\circ\text{C}$, Pin 8 (Note 2) tied to +15 V, unless otherwise specified]

PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\text{ k}\Omega$		0.9	3.0	mV
Input Offset Current			1.5	10	nA
Input Bias Current			28	50	nA
Input Resistance		20	60		M Ω
Input Capacitance			3.0		pF
Offset Voltage Adjustment Range			8.5		mV
Large Signal Voltage Gains	$R_L = 1.5\text{ k}\Omega$ to +5.0V	35k	70k		V/V
Positive Supply Current — Output Low			4.0	5.0	mA
Negative Supply Current — Output Low			1.5	2.0	mA
Power Consumption — Output Low			82	105	mW
Transient Response	$R_L = 1.5\text{ k}\Omega$ to +5.0V 5mV overdrive, 100mV pulse		0.2		μs
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$					
Input Offset Voltage	$R_S \leq 50\text{ k}\Omega$		1.1	4.0	mV
Input Offset Current			3.0	20	nA
Average Input Offset Voltage Drift	$R_S \leq 50\text{ k}\Omega$				
Without External Trim			2.5	15	$\mu\text{V}/^\circ\text{C}$
Average Input Offset Current Drift					
	$+25^\circ\text{C}$ to $+125^\circ\text{C}$		0.01	0.1	nA/ $^\circ\text{C}$
	$+25^\circ\text{C}$ to -55°C		0.05	0.4	nA/ $^\circ\text{C}$
Input Bias Current				150	nA
Large Signal Voltage Gain	$R_L = 1.5\text{ k}\Omega$ to +5.0V	25k			V/V
Input Common Mode Voltage Range		± 10			V
Differential Input Voltage Range		± 10			V
Common Mode Rejection Ratio	$R_S \leq 50\text{ k}\Omega$	70	100		dB
Supply Voltage Rejection Ratio	$R_S \leq 50\text{ k}\Omega$		5.0	100	$\mu\text{V}/\text{V}$
$(V_S = \pm 5\text{V}$ to $\pm 18\text{V})$					
Positive Output Voltage Level	$I_O = .080\text{ mA}$	7.0			V
	$I_O = .080\text{ mA}$, $V_8 = +5\text{V}$	2.4		5.0	V
Negative Output Voltage Level	$I_{\text{SINK}} = 3.2\text{ mA}$			0.4	V
Positive Supply Current — Output Low				7.0	mA
Negative Supply Current — Output Low				2.5	mA
Power Dissipation — Output Low				145	mW

± 15 VOLT OPERATION FOR 393 GRADEELECTRICAL CHARACTERISTICS [$T_A = 25^\circ\text{C}$, Pin 8 (Note 2) tied to +15 V, unless otherwise specified]


PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50\text{ k}\Omega$		1.1	5.0	mV
Input Offset Current			3.5	25	nA
Input Bias Current			30	100	nA
Input Resistance		7.0	55		M Ω
Input Capacitance			3.0		pF
Offset Voltage Adjustment Range			8.5		mV
Large Signal Voltage Gains	$R_L = 1.5\text{ k}\Omega$ to +5.0V	35k	60k		V/V
Positive Supply Current — Output Low			4.0	5.0	mA
Negative Supply Current — Output Low			1.5	2.0	mA
Power Consumption — Output Low			82	105	mW
Transient Response	$R_L = 1.5\text{ k}\Omega$ to +5.0V 5 mV overdrive, 100 mV Pulse		0.2		μ s
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$					
Input Offset Voltage	$R_S \leq 50\text{ k}\Omega$		1.2	7.5	mV
Input Offset Current			4.0	45	nA
Average Input Offset Voltage Drift	$R_S \leq 50\Omega$				
Without External Trim			3.5	20	$\mu\text{V}/^\circ\text{C}$
Average Input Offset Current Drift	$+25^\circ\text{C}$ to $+70^\circ\text{C}$		0.02	0.3	nA/ $^\circ\text{C}$
	$+25^\circ\text{C}$ to 0°C		0.05	0.75	nA/ $^\circ\text{C}$
Input Bias Current				150	nA
Large Signal Voltage Gain	$R_L = 1.5\text{ k}\Omega$ to +5.0V	25k			V/V
Input Common Mode Voltage Range		± 10			V
Differential Input Voltage Range		± 10			V
Common Mode Rejection Ratio	$R_S \leq 50\text{ k}\Omega$	70	100		dB
Supply Voltage Rejection Ratio	$R_S \leq 50\text{ k}\Omega$		6.0	100	$\mu\text{V}/\text{V}$
($V_S = \pm 15\text{V}$ to $\pm 18\text{V}$)					
Positive Output Voltage Level	$I_O = .080\text{ mA}$	7.0			V
	$I_O = .080\text{ mA}$, $V_G = +5\text{V}$	2.4		5.0	V
Negative Output Voltage Level	$I_{\text{SINK}} = 3.2\text{ mA}$			0.4	V
Positive Supply Current — Output Low				7.0	mA
Negative Supply Current — Output Low				2.5	mA
Power Dissipation — Output Low				145	mW

NOTES



- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for Ceramic DIP, $6.3\text{ mW}/^\circ\text{C}$ for Silicone DIP and $5.6\text{ mW}/^\circ\text{C}$ for the Mini DIP package.
- Pin numbers refer to metal can package.

TYPICAL PERFORMANCE CURVES (Note 2)


TRANSFER CHARACTERISTICS




UN-NULLED INPUT OFFSET VOLTAGE AS A FUNCTION OF AMBIENT TEMPERATURE

INPUT OFFSET VOLTAGE CHANGE AS A FUNCTION OF AMBIENT TEMPERATURE - NULLED TO ZERO AT $25^{\circ}C$ 


INPUT BIAS CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT BIAS CURRENT AS A FUNCTION OF DIFFERENTIAL INPUT VOLTAGE




INPUT OFFSET CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT HIGH VOLTAGE AS A FUNCTION OF SUPPLY VOLTAGE AND AMBIENT TEMPERATURE




OUTPUT LOW VOLTAGE AS A FUNCTION OF SUPPLY VOLTAGE AND AMBIENT TEMPERATURE




OUTPUT VOLTAGE LOW VS SINK CURRENT




VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE



VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGE




POSITIVE AND NEGATIVE SUPPLY CURRENTS AS A FUNCTION OF AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES


RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




INPUT OFFSET VOLTAGE
DRIFT AS A FUNCTION
OF TIME




RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




STABILIZATION TIME OF
INPUT OFFSET VOLTAGE
FROM POWER TURN-ON




RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




RESPONSE TIME FOR
VARIOUS INPUT
OVERDRIVES




THERMAL RESPONSE OF
INPUT OFFSET VOLTAGE
TO STEP CHANGE OF CASE
TEMPERATURE




COMMON MODE REJECTION
RATIO AS A FUNCTION OF
AMBIENT TEMPERATURE



OFFSET NULL CIRCUIT
TO-100 PIN NUMBERS




A. C. TEST CIRCUIT




$V_{IN} = -100 \text{ mV}, 100 \text{ kHz}$

TYPICAL APPLICATIONS (Note 2)

STROBE CIRCUITRY




ALTERNATE STROBE CIRCUITRY




* 1/2 9944


LEVEL DETECTOR WITH HYSTERESIS




HIGH POWER OUTPUT CIRCUITS



PRECISION DUAL LIMIT GO-NO GO TESTER




VOLTAGE CONTROLLED OSCILLATOR




$$f = \frac{V_{IN}}{|V_{REF}| R_1 C_1} \quad R_2 C_2 > \frac{|V_{REF}| C_1}{I_{DSS}}$$

FREE RUNNING OSCILLATOR




FREQUENCY DIVIDER & STAIRCASE GENERATOR



$$|V_{REF}| = 2V_D + N \left[3.5T + 2V_D - \frac{C_1 V_{IN}}{C_2} \right]$$

T In Seconds
 V_D for FJT 1000 $\approx 0.31V$


PULSE WIDTH DISCRIMINATOR




V_OUT Pulse Appears
 Whenever $T > \frac{R C V_2}{|V_1|}$

TYPICAL APPLICATIONS (Note 2)


PHASE METER



12 BIT A/D CONVERTER



12 BIT A/D CONVERTER



μA739

DUAL LOW-NOISE OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION—The μA739 consists of two identical operational amplifiers constructed on a single silicon chip using the Fairchild Planar* epitaxial process. These low-noise, high-gain amplifiers exhibit extremely stable operating characteristics over a wide range of supply voltage and temperatures. The device is intended for a variety of applications requiring two high performance operational amplifiers.

- SINGLE OR DUAL SUPPLY OPERATION
- LOW NOISE FIGURE, 2.0 dB
- HIGH GAIN, 20,000 V/V
- LARGE COMMON MODE RANGE, ± 11 V
- EXCELLENT GAIN STABILITY VS. SUPPLY VOLTAGE
- NO LATCH-UP
- OUTPUT SHORT CIRCUIT PROTECTED

TYPICAL APPLICATIONS


- DUAL OPERATIONAL AMPLIFIER
- PHONO AND TAPE STEREO PREAMPLIFIER
- TV REMOTE CONTROL RECEIVER
- DUAL COMPARATOR
- SENSE AMPLIFIER
- OSCILLATOR
- ACTIVE FILTER

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	± 18 V
Internal Power Dissipation (Note 1)	670 mW
Differential Input Voltage	± 5 V
Input Voltage (Note 2)	± 15 V
Storage Temperature Range	-55°C to $+125^{\circ}\text{C}$
Operating Temperature Range	0°C to $+70^{\circ}\text{C}$
Lead Temperature (Soldering, 10 seconds)	260°C
Output Short-Circuit Duration, $T_A = 25^{\circ}\text{C}$ (Note 3)	30 seconds

PHYSICAL DIMENSIONS

In accordance with JEDEC (TO-116) outline
14 Lead Dual In-Line




NOTES:


All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion.
Board-drilling dimensions should equal your practice for .020 inch diameter lead.
Leads are gold-plated kovar
Package weight is 0.9 gram

ORDER PART NO. U6A7739393

EQUIVALENT CIRCUIT



CONNECTION DIAGRAM (TOP VIEW)



ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $R_L = 50$ k Ω to Pin 7, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200 \Omega$		1.0	6.0	mV
Input Offset Current			50	1000	nA
Input Bias Current			300	2000	nA
Input Resistance		37	150		k Ω
Large-Signal Voltage Gain	$V_{OUT} = \pm 5.0$ V	6500	20,000		V/V
Positive Output Voltage Swing		+12	+13		V
Negative Output Voltage Swing		-14	-15		V
Output Resistance	$f = 1.0$ kHz		5.0		k Ω
Input Voltage Range		± 10	± 11		V
Common Mode Rejection Ratio	$R_S \leq 10$ k Ω	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10$ k Ω		50		$\mu\text{V/V}$
Power Consumption	$V_{OUT} = 0$		270	420	mW
Supply Current	$V_{OUT} = 0$		9.0	14	mA
Broadband Noise Figure	$R_S = 5.0$ k Ω , BW = 10 Hz to 10 kHz		2.0		dB
Turn On Delay (See Figure 1)	Open Loop, $V_{IN} = \pm 20$ mV		0.2		μs
Turn Off Delay (See Figure 1)	Open Loop, $V_{IN} = \pm 20$ mV		0.3		μs
Slew Rate (unity gain) (See Figure 2)	$C_1 = 0.1 \mu\text{F}$, $R_1 = 4.7 \Omega$		1.0		V/ μs
Channel Separation (See Figure 3)	$R_S \leq 10$ k Ω , $f = 10$ kHz		140		dB

The following specifications apply for $V_S = \pm 4.0$ V, $T_A = 25^\circ\text{C}$

Input Offset Voltage	$R_S \leq 200 \Omega$		1.0	6.0	mV
Input Offset Current			50	1000	nA
Input Bias Current			300		nA
Supply Current	$V_{OUT} = 0$		2.5		mA
Power Consumption	$V_{OUT} = 0$		20		mW
Large-Signal Voltage Gain	$V_{OUT} = \pm 1.0$ V	2500	15,000		V/V
Positive Output Voltage Swing		+2.5	+2.8		V
Negative Output Voltage Swing		-3.6	-4.0		V

NOTES:

- (1) Rating applies at ambient temperature below 70°C .
- (2) For supply voltages less than ± 15 V, the absolute maximum input voltage is equal to the supply voltage.
- (3) Short circuit may be to ground or either supply.

**PULSE RESPONSE
WAVEFORMS**




Figure 1

**FREQUENCY RESPONSE
TEST CIRCUIT**




Figure 2

**CHANNEL SEPARATION
TEST CIRCUIT**























Figure 3

TYPICAL PERFORMANCE CURVES


INPUT NOISE VOLTAGE
AS A FUNCTION
OF FREQUENCYINPUT NOISE CURRENT
AS A FUNCTION
OF FREQUENCYWIDE BAND INPUT NOISE
VOLTAGE AS A FUNCTION
OF TEMPERATUREWIDE BAND INPUT NOISE
CURRENT AS A FUNCTION
OF TEMPERATURECOMMON MODE RANGE
AS A FUNCTION OF
SUPPLY VOLTAGETYPICAL OUTPUT VOLTAGE
AS A FUNCTION OF
SUPPLY VOLTAGEOUTPUT CAPABILITY
AS A FUNCTION OF
SUPPLY VOLTAGETOTAL SUPPLY CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGETOTAL POWER DISSIPATION
AS A FUNCTION OF
SUPPLY VOLTAGE AND LOADOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGEOPEN LOOP GAIN
AS A FUNCTION OF
TEMPERATUREINPUT OFFSET CURRENT
AND BIAS CURRENT AS
FUNCTIONS OF TEMPERATURE

TYPICAL PERFORMANCE CURVES

CLOSED LOOP GAIN
AS A FUNCTION OF
FREQUENCYOPEN LOOP FREQUENCY
RESPONSE USING RECOMMENDED
COMPENSATION NETWORKSOUTPUT VOLTAGE
SWING AS A FUNCTION OF
FREQUENCY FOR VARIOUS
COMPENSATION NETWORKSFREQUENCY COMPENSATION
NETWORKOPEN LOOP PHASE SHIFT
WITHOUT COMPENSATIONCHANNEL SEPARATION
AS A FUNCTION OF
FREQUENCYCHANGE OF A.C.
CHARACTERISTICS
WITH TEMPERATURE

TYPICAL APPLICATION

STEREO PHONO PREAMPLIFIER—RIAA EQUALIZED



TYPICAL PERFORMANCE

Gain 40 dB at 1 kHz, RIAA equalized
Input overload point, 80 mV rms
Noise level, 2 μ V referred to input
Signal to noise ratio, 74 dB below 10 mV
Channel separation @ 1 kHz, 80 dB

μA740

FET INPUT OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA740 is a high performance FET input operational amplifier constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. It is intended for a wide range of analog applications where very high input impedance is required and features very low input offset current and very low input bias current. High slew rate, high common mode voltage range and absence of "latch up" make the μA740 ideal for use as a voltage follower. The high gain and wide range of operating voltages provide superior performance in active filters, integrators, summing amplifiers, sample and holds, transducer amplifiers, and other general feedback applications. The μA740 is short circuit protected and has the same pin configuration as the popular μA741 operational amplifier. No external components for frequency compensation are required as the internal 6 dB/octave roll-off insures stability in closed loop applications.



- **HIGH INPUT IMPEDANCE . . . 1,000,000 MΩ**
- **NO FREQUENCY COMPENSATION REQUIRED**
- **SHORT-CIRCUIT PROTECTION**
- **OFFSET VOLTAGE NULL CAPABILITY**
- **LARGE COMMON-MODE AND DIFFERENTIAL VOLTAGE RANGES**
- **NO LATCH UP**

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	±22 V
Internal Power Dissipation (Note 1)	500 mW
Differential Input Voltage	±30 V
Input Voltage (Note 2)	±15 V
Voltage between Offset Null and V ⁺	±0.5 V
Storage Temperature Range	−65°C to +150°C
Operating Temperature Range	
Military (312 Grade)	−55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Lead Temperature (Soldering, 60 seconds)	300°C
Output Short-Circuit Duration (Note 3)	Indefinite

PHYSICAL DIMENSIONS

in accordance with JEDEC (TO-99) outline




NOTES:


All dimensions in inches
Leads are gold-plated Kovar
Package weight is 1.22 grams

**ORDER PART NOS. U5B7740312
U5B7740393**

EQUIVALENT CIRCUIT



CONNECTION DIAGRAM (TOP VIEW)





NOTE: PIN 4 CONNECTED TO CASE

312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_C = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 100\text{ k}\Omega$		10	20	mV
Input Offset Current			40		pA
Input Current (either input)			100	200	pA
Input Resistance			1,000,000		M Ω
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	50,000	1,000,000		
Output Resistance			75		Ω
Output Short-Circuit Current			20		mA
Common Mode Rejection Ratio		64	80		dB
Supply Voltage Rejection Ratio			70	300	$\mu\text{V/V}$
Supply Current			4.2	5.2	mA
Power Consumption			126	156	mW
Slew Rate			6.0		V/ μs
Unity Gain Bandwidth			3.0		MHz
Transient Response (Unity Gain)	$C_L \leq 100\text{ pF}$, $R_L = 2\text{ k}\Omega$, $V_{in} = 100\text{ mV}$				
Risetime			110		ns
Overshoot			10	20	%
The following specifications apply for $T_C = -55^\circ\text{C}$ to $+85^\circ\text{C}$:					
Input Voltage Range		± 10		± 12	V
Large Signal Voltage Gain		25,000			
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Input Offset Voltage	$R_S \leq 100\text{ k}\Omega$		15	30	mV
Input Offset Current	$T_A = -55^\circ\text{C}$		185		pA
	$T_A = +85^\circ\text{C}$		30		pA
Input Current (either input)	$T_A = -55^\circ\text{C}$			200	pA
	$T_A = +85^\circ\text{C}$		2.5	4.0	nA

**VOLTAGE OFFSET
NULL CIRCUIT****TRANSIENT RESPONSE
TEST CIRCUIT**

393 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_C = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 100\text{ k}\Omega$		30		mV
Input Offset Current			60		pA
Input Current (either input)			0.1	2.0	nA
Input Resistance			1,000,000		M Ω
Large Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$		1,000,000		
Output Resistance			75		Ω
Output Short-Circuit Current			20		mA
Supply Current			4.2	8.0	mA
Power Consumption			126	240	mW
Slew Rate			6.0		V/ μs
Unity Gain Bandwidth			1.0		MHz
Transient Response (Unity Gain)	$C_L \leq 100\text{ pF}$, $R_L = 2\text{ k}\Omega$, $V_{in} = 100\text{ mV}$				
Risetime			300		ns
Overshoot			10		%
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:					
Input Voltage Range			± 12		V
Common Mode Rejection Ratio			80		dB
Supply Voltage Rejection Ratio			70		$\mu\text{V/V}$
Large Signal Voltage Gain			500,000		
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Input Offset Voltage			30		mV
Input Offset Current			60		pA
Input Current (either input)			1.1	10	nA

NOTES:

- (1) Rating applies for ambient temperature to $+70^\circ\text{C}$; derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for ambient temperatures above $+70^\circ\text{C}$.
- (2) For supply voltages less than $\pm 15\text{ V}$, the absolute maximum input voltage is equal to the supply voltage.
- (3) Short circuit may be to ground or either supply. Rating applies to $+125^\circ\text{C}$ case temperature or $+75^\circ\text{C}$ ambient temperature.

μA741

FREQUENCY-COMPENSATED OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA741 is a high performance monolithic operational amplifier constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. It is intended for a wide range of analog applications. High common mode voltage range and absence of "latch-up" tendencies make the μA741 ideal for use as a voltage follower. The high gain and wide range of operating voltage provides superior performance in integrator, summing amplifier, and general feedback applications.

- NO FREQUENCY COMPENSATION REQUIRED
- SHORT-CIRCUIT PROTECTION
- OFFSET VOLTAGE NULL CAPABILITY
- LARGE COMMON-MODE AND DIFFERENTIAL VOLTAGE RANGES
- LOW POWER CONSUMPTION
- NO LATCH UP

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	
Military (312 Grade)	±22 V
Commercial (393 Grade)	±18 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Silicone DIP	340 mW
Mini DIP	310 mW
Flatpak	570 mW
Differential Input Voltage	±30 V
Input Voltage (Note 2)	±15 V
Storage Temperature Range	
Metal Can, Ceramic DIP, and Flatpak	−65°C to +150°C
Mini DIP and Silicon DIP	−55°C to +125°C
Operating Temperature Range	
Military (312 Grade)	−55°C to +125°C
Commercial (393 Grade)	0°C to + 70°C
Lead Temperature (Soldering)	
Metal Can, Ceramic DIP and Flatpak (60 seconds)	300°C
Mini DIP and Silicone DIP (10 seconds)	260°C
Output Short Circuit Duration (Note 3)	Indefinite


EQUIVALENT CIRCUIT



Notes on following pages.

CONNECTION DIAGRAMS (TOP VIEW)


8 LEAD METAL CAN



ORDER PART NOS.

U5B7741312
U5B7741393

14 LEAD DIP




FOR CERAMIC DIP ORDER PART NOS.

U6A7741312
U6A7741393

FOR SILICONE DIP ORDER PART NO.:

U9A7741393


FLATPACK



ORDER PART NO.

U3F7741312

MINIDIP



ORDER PART NO.

U9T7741393

*Planar is a patented Fairchild process.


312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	5.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			1.4		pF
Offset Voltage Adjustment Range			± 15		mV
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	50,000	200,000		
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.7	2.8	mA
Power Consumption			50	85	mW
Transient Response (unity gain)	$V_{in} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L \leq 100\text{ pF}$				
Risettime			0.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2\text{ k}\Omega$		0.5		V/ μs
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	6.0	mV
Input Offset Current	$T_A = +125^\circ\text{C}$		7.0	200	nA
	$T_A = -55^\circ\text{C}$		85	500	nA
Input Bias Current	$T_A = +125^\circ\text{C}$		0.03	0.5	μA
	$T_A = -55^\circ\text{C}$		0.3	1.5	μA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		30	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	25,000			
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Supply Current	$T_A = +125^\circ\text{C}$		1.5	2.5	mA
	$T_A = -55^\circ\text{C}$		2.0	3.3	mA
Power Consumption	$T_A = +125^\circ\text{C}$		45	75	mW
	$T_A = -55^\circ\text{C}$		60	100	mW

TYPICAL PERFORMANCE CURVES
312 GRADE


**OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGE**



**OUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGE**



**INPUT COMMON MODE
VOLTAGE RANGE AS A
FUNCTION OF SUPPLY VOLTAGE**






393 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		2.0	6.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			1.4		pF
Offset Voltage Adjustment Range			± 15		mV
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		30	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	20,000	200,000		
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.7	2.8	mA
Power Consumption			50	85	mW
Transient Response (unity gain)	$V_{in} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L \leq 100\text{ pF}$				
Risetime			0.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2\text{ k}\Omega$		0.5		V/ μs

The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:







Input Offset Voltage				7.5	mV
Input Offset Current				300	nA
Input Bias Current				800	nA
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	15,000			
Output Voltage Swing	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V

TYPICAL PERFORMANCE CURVES
393 GRADEOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGEOUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGEINPUT COMMON MODE
VOLTAGE RANGE AS A
FUNCTION OF SUPPLY VOLTAGE







NOTES

- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for the Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP, $6.3\text{ mW}/^\circ\text{C}$ for the Silicone DIP, $5.6\text{ mW}/^\circ\text{C}$ for the Mini DIP and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak.
- For supply voltages less than $\pm 15\text{ V}$, the absolute maximum input voltage is equal to the supply voltage.
- Short circuit may be to ground or either supply. Rating applies to $+125^\circ\text{C}$ case temperature or 75°C ambient temperature.













TYPICAL PERFORMANCE CURVES (312 GRADE)

INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREINPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATUREOUTPUT SHORT-CIRCUIT CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREINPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREPOWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATUREFREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE


(393 GRADE)

INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREINPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATUREINPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREPOWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATUREOUTPUT SHORT-CIRCUIT CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATUREFREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE


TYPICAL PERFORMANCE CURVES (312 AND 393 GRADES)

POWER CONSUMPTION
AS A FUNCTION OF
SUPPLY VOLTAGEOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCYOPEN LOOP PHASE RESPONSE
AS A FUNCTION OF
FREQUENCYINPUT OFFSET CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGEINPUT RESISTANCE AND
INPUT CAPACITANCE AS A
FUNCTION OF FREQUENCYOUTPUT RESISTANCE
AS A FUNCTION OF
FREQUENCYOUTPUT VOLTAGE SWING
AS A FUNCTION OF
LOAD RESISTANCEOUTPUT VOLTAGE SWING
AS A FUNCTION OF
FREQUENCYABSOLUTE MAXIMUM POWER
DISSIPATION AS A FUNCTION
OF AMBIENT TEMPERATUREINPUT NOISE VOLTAGE
AS A FUNCTION OF
FREQUENCYINPUT NOISE CURRENT
AS A FUNCTION OF
FREQUENCYBROADBAND NOISE FOR
VARIOUS BANDWIDTHS


TRANSIENT RESPONSE




FREQUENCY CHARACTERISTICS AS A FUNCTION OF SUPPLY VOLTAGE




TRANSIENT RESPONSE TEST CIRCUIT




COMMON MODE REJECTION RATIO AS A FUNCTION OF FREQUENCY



VOLTAGE OFFSET NULL CIRCUIT




VOLTAGE FOLLOWER LARGE-SIGNAL PULSE RESPONSE




TYPICAL APPLICATIONS

UNITY-GAIN VOLTAGE FOLLOWER




$R_{IN} = 400 M\Omega$
 $C_{IN} = 1 pF$
 $R_{out} < 1 \Omega$
 B.W. = 1 MHz

NON-INVERTING AMPLIFIER




GAIN	R_1	R_2	B.W.	R_{IN}
10	1 k Ω	9 k Ω	100 kHz	400 M Ω
100	100 Ω	9.9 k Ω	10 kHz	280 M Ω
1000	100 Ω	99.9 k Ω	1 kHz	80 M Ω

INVERTING AMPLIFIER



GAIN	R_1	R_2	B.W.	R_{IN}
1	10 k Ω	10 k Ω	1 MHz	10 k Ω
10	1 k Ω	10 k Ω	100 kHz	1 k Ω
100	1 k Ω	100 k Ω	10 kHz	1 k Ω
1000	100 Ω	100 k Ω	1 kHz	100 Ω

CLIPPING AMPLIFIER



$$\frac{E_{out}}{E_{in}} = \frac{R_2}{R_1} \text{ if } |E_{out}| \leq V_Z + 0.7 V$$

where V_Z = Zener breakdown voltage

$$E_{out} = -\frac{1}{R_1 C_1} \int E_{IN} dt$$

$$E_{out} = -R_2 C_1 \frac{dE_{IN}}{dt}$$

Voltage Gain = 10^3
Input Offset Voltage Drift = $0.6 \mu\text{V}/^\circ\text{C}$
Input Offset Current Drift = $2.0 \text{ pA}/^\circ\text{C}$

A log-log plot showing the relationship between the center frequency (Hz) and the capacitor value (C_1 in μF) for the μA741 op-amp. The y-axis, labeled 'CENTER FREQUENCY - Hz', ranges from 10 to 10k. The x-axis, labeled 'CAPACITOR $C_1 = \mu\text{F}$ ', ranges from 0.0001 to 1.0. A single curve is plotted, showing that the center frequency decreases as the capacitor value increases.

Capacitor C_1 (μF)	Center Frequency (Hz)
0.0001	~15,000
0.001	~1,500
0.01	~150
0.1	~15
1.0	~3

μA742

ZERO CROSSING AC TRIGGER-TRIGAC

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION—The μA742 is a Zero Crossing AC Trigger - TRIGAC which is constructed on a single chip utilizing the Fairchild Planar® Epitaxial Process. It is intended for use in AC power control circuits for operation directly off the AC line or with a separate AC or DC power supply. The TRIGAC functions as a threshold detector and a driver for triacs and SCR's; as a threshold detector, it senses level changes at the inputs and as a driver it supplies high energy pulses for thyristor triggering. The trigger pulses occur at the zero crossing of the load current and therefore minimize RFI generation for either resistive or inductive loads.

- DESIGNED FOR APPLICATIONS IN 60 Hz AND 400 Hz AC POWER CONTROL SYSTEMS HAVING RESISTIVE OR INDUCTIVE LOADS
- OPERATES DIRECTLY FROM AN AC LINE OR FROM A DC SUPPLY
- INPUT COMPATIBLE WITH A WIDE RANGE OF SENSOR IMPEDANCES
- BRIDGE SENSING WITH ADJUSTABLE HYSTERESIS SET POINTS
- PROVISIONS FOR TIME PROPORTIONING OPERATION
- PROVIDES ZERO CROSSING THYRISTOR TRIGGERING FOR MINIMUM RFI
- EVEN NUMBER OF CONSECUTIVE HALF-CYCLE TRIGGERING FOR TRIACS AND INVERSE PARALLEL SCR's IN MOST APPLICATIONS

ABSOLUTE MAXIMUM RATINGS

Peak Current into Supply Terminal (AC Operation)	±30 mA
Continuous Current into Supply Terminal (DC Operation)	20 mA
RMS Current into Sync Input Terminal	15 mA
Current into Switch Terminal	10 mA
Power Dissipation	670 mW
Voltage at (+) or (−) Input Terminal	(Note 1) ±7 V
Differential Voltage between (+) and (−) Input Terminals	±7 V
Current into Clamp Terminal (Clamp ON)	20 mA
Voltage at Clamp Terminal (Clamp OFF)	20 V
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	−55°C to +125°C
Lead Temperature (Soldering, 10 second time limit)	260°C
Trigger Output Short-Circuit Duration (Note 2)	Continuous

PHYSICAL DIMENSIONS (Typical Dual In-Line Package)




NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020" diameter lead
Leads are tin plated kovar
Package weight is 2.0 grams


ORDER PART NO. U6A7742393

EQUIVALENT CIRCUIT



Notes on following page.

CONNECTION DIAGRAM (TOP VIEW)



*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS

($T_A = 25^\circ\text{C}$, Voltage Range at the (+) and (−) Input Terminals:
 0.15 to $0.75 \cdot (V_{\text{Supply}})$; $V_{(+)\text{Input}} - V_{(-)\text{Input}} \geq 100 \text{ mV}$, Test Circuit 1, unless otherwise specified.

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Peak Supply Voltage	S_1 in DC position		20		Volts
	S_1 in AC position, positive half cycles of AC line		20		Volts
	S_1 in AC position, negative half cycle of AC line		−0.7		Volts
Peak Trigger Output Pulse	S_1 in AC position, beginning of positive half cycles		0.9		Amp
	S_1 in AC or DC position, beginning of negative half cycles		1.3		Amp
	S_1 in DC position beginning of positive half cycles		2.2		Amp
Bias Current at (+) and (−) Input Terminals			10		μA
ON Voltage at Clamp Terminal	$I_C = 1 \text{ mA}$		0.1		Volts
ON Voltage at Switch Terminal	$I_F = 5 \text{ mA}$		1.0		Volts
ON Voltage at Sync Input Terminal	$I_F = 10 \text{ mA}$		1.0		Volts
Switching Voltage at Sync Input Terminal			6.0		Volts
Switching Voltage at Switch Terminal			7.0		Volts
Holding Current at Switch Terminal			25		μA
Sync Input Threshold Current for Trigger Output	Beginning of positive half cycles		0.3		mA
	Beginning of negative half cycles		−0.7		mA
Sync Input Threshold Voltage for Trigger Output	Beginning of positive half cycles		2.0		Volts
	Beginning of negative half cycles		−0.7		Volts

DEFINITIONS

VOLTAGE RANGE: The range of voltage on the (+) or (−) input terminals, which, if exceeded, could cause the TRIGAC to cease functioning.


BIAS CURRENT: The average of the two currents into the (+) and (−) input terminals.

NOTES:


- (1) The maximum voltage should not exceed the instantaneous supply voltage of the $\mu A742$.
- (2) Rating applies for an external storage capacitor having a value of not more than $2\mu\text{F}$.

TYPICAL ELECTRICAL CHARACTERISTICS (TEST CIRCUIT 1 UNLESS OTHERWISE SPECIFIED)


TRIGGER OUTPUT PULSE WAVE FORMS




TRIGGER OUTPUT PULSE WIDTH VERSUS STORAGE CAPACITOR




SUPPLY VOLTAGE VERSUS SUPPLY CURRENT




NORMALIZED TRIGGER OUTPUT PULSE HEIGHT VERSUS TEMPERATURE



OPERATING STATE AS A FUNCTION OF DIFFERENTIAL INPUT VOLTAGE AND TEMPERATURE



$\mu A742$ TEST CIRCUIT 1



TYPICAL APPLICATIONS

FIG. 1 — ZERO CROSSING CONTROL CIRCUIT WITHOUT HYSTERESIS




FIG. 2 — ZERO CROSSING CIRCUIT WITH DC SUPPLY




FIG. 3 — ZERO CROSSING CIRCUIT




FIG. 4 — SCR FIRING — HALF WAVE




FIG. 5 — INVERSE PARALLEL SCR PAIR FIRING WITH A PULSE TRANSFORMER




FIG. 6 — INVERSE PARALLEL SCR PAIR FIRING WITH A THIRD SCR





FIG. 7 — ZERO CROSSING WITH PROPORTIONAL CONTROL



*Recommended Values

AC Supply Voltage 60 Hz Volts - RMS	R_{DR}	R_{SYN}	C_{ST}
24	1.0 kΩ	2.2 kΩ	0.47 μF/25 V
110	10 kΩ	10 kΩ	0.47 μF/25 V
220	22 kΩ	22 kΩ	0.47 μF/25 V

 FOR SUPPLY VOLTAGE FREQUENCY OF 400 Hz REDUCE C_{ST} TO .047 μF/25 V

**Necessary with inductive loads.

 ***The sensor resistance will determine the values of the bridge resistors. For the values of R_{DR} shown, the total current into the bridge should not exceed 5 mA at 20 V.

μA746

COLOR TV CHROMA DEMODULATOR


FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA746 is a color TV chroma demodulator constructed on a single silicon chip using the Fairchild Planar* epitaxial process. This device demodulates the chroma subcarrier information contained in a color television video signal and provides color-difference signals at the outputs. The low voltage drift of the D.C. output insures excellent performance in direct-coupled chrominance output circuitry.


- **LOW OUTPUT VOLTAGE DRIFT WITH TEMPERATURE**
- **DOUBLY BALANCED DEMODULATION**
- **INTERNAL COLOR-DIFFERENCE MATRIX FOR NTSC COLOR TV**
- **10 VOLT PEAK-TO-PEAK $E_B - E_Y$ OUTPUT**

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	+28 V
Minimum Load Resistance	3 kΩ
Peak-to-Peak Reference Input Voltage	5.0 V
Peak-to-Peak Chroma Input Voltage	5.0 V
Internal Power Dissipation	500 mW
Metal Can	670 mW
Ceramic DIP	0°C to +70°C
Operating Temperature Range	-65°C to +150°C
Storage Temperature Range	
(5E and 6A Packages)	+300°C
Lead Temperature (Soldering, 10 seconds)	
(5E and 6A Packages)	




CONNECTION DIAGRAMS (TOP VIEWS) METAL CAN



DIP




PHYSICAL DIMENSIONS



NOTES:

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 grams

ORDER PART NO. U5E7746394



ORDER PART NO. U6A7746394

NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020 inch diameter lead
Package weight is 2.0 grams.

*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = 24\text{ V}$, Test Circuit 1 unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current	$e_C = 0, R_L = 1\text{ M}\Omega$	5.5	9.0	12.5	mA
	$e_C = 0, R_L = 1\text{ M}\Omega, T_A = 70^\circ\text{C}$		9.0	13.0	mA
	$e_C = 0$	16.5	22	25.5	mA
	$e_C = 0, T_A = 70^\circ\text{C}$		22		mA
Internal Power Dissipation	$e_C = 0$		340	430	mW
	$e_C = 0, T_A = 70^\circ\text{C}$		340	445	mW
DC Voltage at any Output Terminal	$e_C = 0$	13.2	14.5	15.8	Volts
	$e_C = 0, T_A = 70^\circ\text{C}$	13.0	14.5	16.0	Volts
Temperature Coefficient of DC Voltage at any Output Terminal	$e_C = 0$	-5.0	-0.3	+5.0	mV/ $^\circ\text{C}$
Absolute Value of DC Difference Voltage between any Two Outputs	$e_C = 0$		0.15	0.6	Volts
DC Voltage at either Reference Terminal	$e_A = e_B = e_C = 0$		5.8		Volts
DC Voltage at either Chroma Terminal	$e_C = 0$		3.2		Volts
Reference Input Resistance	$e_C = 0$		1.7		k Ω
Reference Input Capacitance	$e_C = 0$		6.0		pF
Chroma Input Resistance			0.8		k Ω
Chroma Input Capacitance			5.0		pF
Peak-to-Peak Chroma Input Voltage	$E_B - E_Y = 5\text{ Vp-p}$		0.4	0.7	Volts
Peak-to-Peak $E_R - E_Y$ Output Voltage	$E_B - E_Y = 5\text{ Vp-p}$	3.5	3.8	4.2	Volts
Peak-to-Peak $E_G - E_Y$ Output Voltage	$E_B - E_Y = 5\text{ Vp-p}$	0.75	1.0	1.25	Volts
Maximum Peak-to-Peak $E_B - E_Y$ Output Voltage	$e_C = 1.5\text{ Vp-p}$	8.0	10		Volts
$E_B - E_Y$ Demodulation Angle	$E_B - E_Y = 5\text{ Vp-p}$		3		Degrees
$E_R - E_Y$ Demodulation Angle	$E_B - E_Y = 5\text{ Vp-p}$		109		Degrees
$E_G - E_Y$ Demodulation Angle	$E_B - E_Y = 5\text{ Vp-p}$		259		Degrees
$E_R - E_Y$ Demodulation Angle relative to $E_B - E_Y$ Demodulation Angle	$E_B - E_Y = 5\text{ Vp-p}$	101	106	111	Degrees
$E_B - E_Y$ Demodulation Angle relative to $E_G - E_Y$ Demodulation Angle	$E_B - E_Y = 5\text{ Vp-p}$	96	104	112	Degrees
Highest Peak-to-Peak Demodulator AC Unbalance Voltage at any Output Terminal	$e_C = 0$		0.3	0.8	Volts











DEFINITIONS

Color-Difference Demodulation Angle — A color-difference demodulation angle is defined as the instantaneous phase of the (+) Chroma input signal which produces the most positive voltage at the respective color-difference output with the phase of Reference "A" taken at 3 degrees and the phase of Reference "B" taken at 106 degrees.

(+) Chroma Input — A composite chroma signal containing the burst at a phase of 180 degrees is demodulated to produce specified color-difference demodulation angles when applied to the (+) Chroma input.

(-) Chroma Input — A composite chroma signal containing the burst at a phase of 0 degrees is demodulated to produce specified color-difference demodulation angles when applied to the (-) Chroma input.


TYPICAL ELECTRICAL CHARACTERISTICS (TEST CIRCUIT 1 UNLESS OTHERWISE SPECIFIED)



INPUTS


CHROMA:
 $E_C \leq 1.5\text{V p-p}$
 $f_C = 3.59\text{MHz}$

REFERENCE
 $E_A = E_B = 1\text{V p-p}$
 $f_A = f_B = 3.58\text{MHz}$
 $\theta_B = \theta_A + 103^\circ$



TYPICAL APPLICATION


COMPLETE R-G-B VIDEO OUTPUT STAGE



PIN NUMBER SHOWN FOR DUAL IN-LINE PACKAGE

Fully D.C. coupled circuit exhibits negligible drift with temperature, eliminates interaction between contrast and brightness controls, and minimizes gray-scale set-up time. For further applications information, see Application Brief 104.

COMPLETE R-G-B VIDEO OUTPUT STAGE



Pin numbers shown for Dual In-Line Package.

From:

"A Semiconductor Video Output Amplifier for a Red Blue Green Large Screen Color Television Receiver", by D. Poppy. IEEE Transactions on Broadcast and Television Receivers, BTR-15, #2, pp. 167-70, July 1969.

Reprinted with permission.

μA747

DUAL FREQUENCY COMPENSATED OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA747 is a pair of high performance monolithic operational amplifiers constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. They are intended for a wide range of analog applications where board space or weight are important. High common mode voltage range and absence of "latch-up" make the μA747 ideal for use as a voltage follower. The high gain and wide range of operating voltage provides superior performance in integrator, summing amplifier, and general feedback applications. The μA747 is short-circuit protected and requires no external components for frequency compensation. The internal 6 dB/octave roll-off insures stability in closed loop applications. For single amplifier performance, see μA741 data sheet.

- NO FREQUENCY COMPENSATION REQUIRED
- SHORT-CIRCUIT PROTECTION
- OFFSET VOLTAGE NULL CAPABILITY
- LARGE COMMON-MODE AND DIFFERENTIAL VOLTAGE RANGES
- LOW POWER CONSUMPTION
- NO LATCH UP

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	
Military (312 Grade)	±22 V
Commercial (393 Grade)	±18 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Differential Input Voltage	±30 V
Input Voltage (Note 2)	±15 V
Voltage between Offset Null and V—	±0.5 V
Storage Temperature Range	–65°C to +150°C
Operating Temperature Range	–55°C to +125°C
Lead Temperature (Soldering, 60 seconds)	300°C
Output Short-Circuit Duration (Note 3)	Indefinite

EQUIVALENT CIRCUIT (Each Side)



Notes on following pages.


CONNECTION DIAGRAMS (TOP VIEWS) 14 LEAD DIP



ORDER PART NOS.

U7A7747312
U7A7747393

10 LEAD METAL CAN



ORDER PART NOS.

U5F7747312
U5F7747393

*Planar is a patented Fairchild process.




312 GRADE

ELECTRICAL CHARACTERISTICS — Each Amplifier ($V_S = \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	5.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			1.4		pF
Offset Voltage Adjustment Range			± 15		mV
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	50,000	200,000		
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.7	2.8	mA
Power Consumption			50	85	mW
Transient Response (unity gain)	$V_{in} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L \leq 100\text{ pF}$				
Risetime			0.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2\text{ k}\Omega$		0.5		V/ μs
Channel Separation			120		dB
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$.					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	6.0	mV
Input Offset Current	$T_A = +125^\circ\text{C}$		7.0	200	nA
	$T_A = -55^\circ\text{C}$		85	500	nA
Input Bias Current	$T_A = +125^\circ\text{C}$		0.03	0.5	μA
	$T_A = -55^\circ\text{C}$		0.3	1.5	μA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		30	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10\text{ V}$	25,000			
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Supply Current	$T_A = +125^\circ\text{C}$		1.5	2.5	mA
	$T_A = -55^\circ\text{C}$		2.0	3.3	mA
Power Consumption	$T_A = +125^\circ\text{C}$		45	75	mW
	$T_A = -55^\circ\text{C}$		60	100	mW

TYPICAL PERFORMANCE CURVES (Each Amplifier)

TYPICAL PERFORMANCE CURVES

OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGEOUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGEINPUT COMMON MODE
VOLTAGE RANGE AS A
FUNCTION OF SUPPLY VOLTAGE

393 GRADE













ELECTRICAL CHARACTERISTICS — Each Amplifier ($V_S = \pm 15$ V, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	6.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			1.4		pF
Offset Voltage Adjustment Range			± 15		mV
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10$ V	25,000	200,000		
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.7	2.8	mA
Power Consumption			50	85	mW
Transient Response (unity gain)	$V_{in} = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L \leq 100\text{ pF}$				
Risetime			0.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2\text{ k}\Omega$		0.5		V/ μs
Channel Separation			120		dB
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$.					
Input Offset Voltage	$R_S \leq 10\text{ k}\Omega$		1.0	7.5	mV
Input Offset Current			7.0	300	nA
Input Bias Current			0.03	0.8	μA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		30	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 2\text{ k}\Omega$, $V_{out} = \pm 10$ V	15,000			
Output Voltage Swing	$R_L \geq 10\text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2\text{ k}\Omega$	± 10	± 13		V
Supply Current			2.0	3.3	mA
Power Consumption			60	100	mW

NOTES


1. Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for the Metal Can and $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP package.
2. For supply voltages less than ± 15 V, the absolute maximum input voltage is equal to the supply voltage.
3. Short circuit may be to ground or either supply. Military rating applies to $+125^\circ\text{C}$ case temperature or $+60^\circ\text{C}$ ambient temperature for each side.

TYPICAL PERFORMANCE CURVES (Each Amplifier)




TYPICAL PERFORMANCE CURVES (Each Amplifier)


OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCY




OPEN LOOP PHASE RESPONSE
AS A FUNCTION OF
FREQUENCY




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
FREQUENCY




INPUT RESISTANCE AND
INPUT CAPACITANCE AS A
FUNCTION OF FREQUENCY




OUTPUT RESISTANCE
AS A FUNCTION OF
FREQUENCY




COMMON MODE REJECTION
RATIO AS A FUNCTION OF
FREQUENCY




TRANSIENT RESPONSE




TRANSIENT RESPONSE
TEST CIRCUIT




VOLTAGE FOLLOWER
LARGE-SIGNAL PULSE RESPONSE




FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
SUPPLY VOLTAGE



VOLTAGE OFFSET
NULL CIRCUIT




FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL APPLICATIONS

UNITY-GAIN VOLTAGE FOLLOWER




$R_{IN} = 400 \text{ M}\Omega$
 $C_{IN} = 1 \text{ pF}$
 $R_{out} < 1 \Omega$
 $B.W. = 1 \text{ MHz}$

NON-INVERTING AMPLIFIER




GAIN	R_1	R_2	B.W.	R_{IN}
10	1 k Ω	9 k Ω	100 kHz	400 M Ω
100	100 Ω	9.9 k Ω	10 kHz	280 M Ω
1000	100 Ω	99.9 k Ω	1 kHz	80 M Ω

INVERTING AMPLIFIER



GAIN	R_1	R_2	B.W.	R_{IN}
1	10 k Ω	10 k Ω	1 MHz	10 k Ω
10	1 k Ω	10 k Ω	100 kHz	1 k Ω
100	1 k Ω	100 k Ω	10 kHz	1 k Ω
1000	100 Ω	100 k Ω	1 kHz	100 Ω


WEIGHTED AVERAGING AMPLIFIER




$$\begin{aligned}
 -E_{out} = & E_{IN1} \left(\frac{R_f}{R_1} \right) + E_{IN2} \left(\frac{R_f}{R_2} \right) + \\
 & E_{IN3} \left(\frac{R_f}{R_3} \right) - E_{IN4} \left(\frac{R_f}{R_4} \right) - E_{IN5} \left(\frac{R_f}{R_5} \right)
 \end{aligned}$$

TYPICAL APPLICATIONS


QUADRATURE OSCILLATOR




ANALOG MULTIPLIER




COMPRESSOR/EXPANDER AMPLIFIERS




TRACKING POSITIVE AND NEGATIVE VOLTAGE REFERENCES



NOTCH FILTER USING THE $\mu A747$ AS A GYRATOR



NOTCH FREQUENCY AS A FUNCTION OF C_1



μA748

HIGH PERFORMANCE OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA748 is a high performance monolithic operational amplifier constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. It is intended for a wide range of analog applications where tailoring of frequency characteristics is desirable. High common mode voltage range and absence of "latch-up" make the μA748 ideal for use as a voltage follower. The high gain and wide range of operating voltages provide superior performance in integrator, summing amplifier, and general feedback applications. The μA748 is short-circuit protected and has the same pin configuration as the popular μA741 operational amplifier. Unity gain frequency compensation is achieved by means of a single 30 pF capacitor.

- **SHORT-CIRCUIT PROTECTION**
- **OFFSET VOLTAGE NULL CAPABILITY**
- **LARGE COMMON-MODE AND DIFFERENTIAL VOLTAGE RANGES**
- **LOW POWER CONSUMPTION**
- **NO LATCH UP**


ABSOLUTE MAXIMUM RATINGS

Supply Voltage	±22 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic Dip	670 mW
Mini DIP	310 mW
Flatpak	570 mW
Differential Input Voltage	±30 V
Input Voltage (Note 2)	±15 V
Storage Temperature Range	
Metal Can, Ceramic DIP, and Flatpak	-65°C to +150°C
Mini DIP	-55°C to +125°C
Operating Temperature Range	
Military (312 grade)	-55°C to +125°C
Commercial (393 grade)	0°C to +70°C
Lead Temperature (Soldering, 60 Seconds)	
Metal Can, Ceramic DIP and Flatpak	300°C
Mini DIP and Silicone DIP	260°C
Output Short Circuit Duration (Note 3)	Indefinite

EQUIVALENT CIRCUIT




8 LEAD METAL CAN (TOP VIEW)



NOTE: Pin 4 connected to case


ORDER PART NOS: U5B7748312
U5B7748393

14 LEAD DIP (TOP VIEW)




ORDER PART NOS: U6A7748312
U6A7748393

MINI DIP (TOP VIEW)



ORDER PART NO: U9T7748393

10 LEAD FLATPAK† (TOP VIEW)



†Available on special request

ORDER PART NO: U3F7748312



312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $T_A = 25^\circ$ C, $C_C = 30$ pF unless otherwise specified)

PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10$ k Ω		1.0	5.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			2.0		pF
Offset Voltage Adjustment Range			± 15		mV
Large-Signal Voltage Gain	$R_L \geq 2$ k Ω , $V_{OUT} = \pm 10$ V	50,000	150,000		V/V
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.9	2.8	mA
Power Consumption			60	85	mW
Transient Response (Voltage Follower, Gain of 1)	$V_{IN} = 20$ mV, $C_C = 30$ pF, $R_L = 2$ k Ω , $C_L \leq 100$ pF				
Risetime			0.3		μ s
Overshoot			5.0		%
Slew Rate (Voltage Follower, Gain of 1)	$R_L \geq 2$ k Ω		0.5		V/ μ s
Transient Response (Voltage Follower, Gain of 10)	$V_{IN} = 20$ mV, $C_C = 3.5$ pF, $R_L = 2$ k Ω , $C_L \leq 100$ pF				
Risetime			0.2		μ s
Overshoot			5.0		%
Slew Rate (Voltage Follower, Gain of 10)	$R_L \geq 2$ k Ω , $C_C = 3.5$ pF		5.5		V/ μ s

The following specifications apply for -55° C $\leq T_A \leq +125^\circ$ C:


Input Offset Voltage	$R_S \leq 10$ k Ω		1.0	6.0	mV
Input Offset Current	$T_A = +125^\circ$ C $T_A = -55^\circ$ C		10 50	200 500	nA
Input Bias Current	$T_A = +125^\circ$ C $T_A = -55^\circ$ C		0.03 0.3	0.5 1.5	μ A
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10$ k Ω	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10$ k Ω		30	150	μ V/V
Large-Signal Voltage Gain	$R_L \geq 2$ k Ω , $V_{OUT} = \pm 10$ V	25,000			V/V
Output Voltage Swing	$R_L \geq 10$ k Ω $R_L \geq 2$ k Ω	± 12 ± 10	± 14 ± 13		V V
Supply Current	$T_A = +125^\circ$ C $T_A = -55^\circ$ C		1.5 2.0	2.5 3.3	mA
Power Consumption	$T_A = +125^\circ$ C $T_A = -55^\circ$ C		45 60	75 100	mW

**VOLTAGE OFFSET
NULL CIRCUIT****SUGGESTED****ALTERNATE**

393 GRADE


ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $T_A = 25^\circ$ C, $C_C = 30$ pF unless otherwise specified)

PARAMETERS (see definitions)	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 10$ k Ω		2.0	6.0	mV
Input Offset Current			20	200	nA
Input Bias Current			80	500	nA
Input Resistance		0.3	2.0		M Ω
Input Capacitance			2.0		pF
Offset Voltage Adjustment Range			± 15		mV
Large-Signal Voltage Gain	$R_L \geq 2$ k Ω , $V_{OUT} = \pm 10$ V	20,000	150,000		V/V
Output Resistance			75		Ω
Output Short-Circuit Current			25		mA
Supply Current			1.9	2.8	mA
Power Consumption			60	85	mW
Transient Response (Voltage Follower, Gain of 1)	$V_{IN} = 20$ mV, $C_C = 30$ pF, $R_L = 2$ k Ω , $C_L \leq 100$ pF				
Risetime			0.3		μ s
Overshoot			5.0		%
Slew Rate (Voltage Follower, Gain of 1)	$R_L \geq 2$ k Ω		0.5		V/ μ s
Transient Response (Voltage Follower, Gain of 10)	$V_{IN} = 20$ mV, $C_C = 3.5$ pF, $R_L = 2$ k Ω , $C_L \leq 100$ pF				
Risetime			0.2		μ s
Overshoot			5.0		%
Slew Rate (Voltage Follower, Gain of 10)	$R_L \geq 2$ k Ω		5.5		V/ μ s
The following specifications apply for 0° C $\leq T_A \leq +70^\circ$ C:					
Input Offset Voltage	$R_S \leq 10$ k Ω			7.5	mV
Input Offset Current				300	nA
Input Bias Current				800	nA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 10$ k Ω	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10$ k Ω		30	150	μ V/V
Large-Signal Voltage Gain	$R_L \geq 2$ k Ω , $V_{OUT} = \pm 10$ V	15,000			V/V
Output Voltage Swing	$R_L \geq 10$ k Ω	± 12	± 14		V
	$R_L \geq 2$ k Ω	± 10	± 13		V
Power Consumption			60	100	mW


GAIN TEST CIRCUIT

TYPICAL PERFORMANCE CURVES (FOR 312 GRADE)


INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE




OUTPUT SHORT-CIRCUIT CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT OFFSET CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGE



INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




POWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES (FOR 393 GRADE)


INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT RESISTANCE
AS A FUNCTION OF
AMBIENT TEMPERATURE




OUTPUT SHORT-CIRCUIT CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT OFFSET CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGE



INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE




POWER CONSUMPTION
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES (FOR 312 AND 393 GRADES)

(unless otherwise specified)


OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGE




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGE




INPUT COMMON MODE
VOLTAGE RANGE AS A
FUNCTION OF SUPPLY VOLTAGE




POWER CONSUMPTION
AS A FUNCTION OF
SUPPLY VOLTAGE




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
LOAD RESISTANCE




ABSOLUTE MAXIMUM POWER
DISSIPATION AS A FUNCTION
OF AMBIENT TEMPERATURE




FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
SUPPLY VOLTAGE




312 GRADE
FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE




393 GRADE
FREQUENCY CHARACTERISTICS
AS A FUNCTION OF
AMBIENT TEMPERATURE




INPUT NOISE VOLTAGE
AS A FUNCTION OF
FREQUENCY



INPUT NOISE CURRENT
AS A FUNCTION OF
FREQUENCY




BROADBAND NOISE FOR
VARIOUS BANDWIDTHS




TYPICAL PERFORMANCE CURVES (FOR 312 AND 393 GRADES)


OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCY




OPEN LOOP PHASE RESPONSE
AS A FUNCTION OF
FREQUENCY




OUTPUT VOLTAGE SWING
AS A FUNCTION OF
FREQUENCY




OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCY FOR VARIOUS
GAIN/COMPENSATION OPTIONS




FREQUENCY RESPONSE
FOR VARIOUS
CLOSED-LOOP GAINS




COMPENSATION CAPACITANCE
AS A FUNCTION OF
CLOSED LOOP VOLTAGE GAIN




INPUT RESISTANCE AND
INPUT CAPACITANCE AS A
FUNCTION OF FREQUENCY




OUTPUT RESISTANCE
AS A FUNCTION OF
FREQUENCY




COMMON MODE REJECTION
RATIO AS A FUNCTION OF
FREQUENCY




VOLTAGE FOLLOWER
TRANSIENT RESPONSE
(GAIN OF 1)



TRANSIENT RESPONSE
TEST CIRCUIT




VOLTAGE FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE




TYPICAL PERFORMANCE CURVES
(FOR 312 AND 393 GRADES)

FEED-FORWARD COMPENSATION




LARGE SIGNAL FEED-FORWARD
TRANSIENT RESPONSE




TYPICAL APPLICATIONS


PULSE WIDTH MODULATOR



PRACTICAL DIFFERENTIATOR



CIRCUIT FOR OPERATING THE $\mu A748$
WITHOUT A NEGATIVE SUPPLY



NOTES

1. Rating applies to ambient temperature up to 70°C. Above 70°C ambient derate linearly at 6.3 mW/°C for the Metal Can, 8.3 mW/°C for the Ceramic DIP, 5.6 mW/°C for the Mini DIP and 7.1 mW/°C for the Flatpak package.
2. For supply voltages less than ±15 V, the absolute maximum input voltage is equal to the supply voltage.
3. Short circuit may be to ground or either supply. Rating applies to +125°C case temperature or +75°C case temperature or +75°C ambient temperature.

μA749

DUAL OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA749 consists of two identical high gain operational amplifiers constructed on a single silicon chip using the Fairchild Planar* epitaxial process. These three-stage amplifiers use class A PNP transistor output stages with uncommitted collectors. This enables a variety of loads to be employed for general purpose applications from DC to 10 MHz where two high performance operational amplifiers are required. In addition, the outputs may be 'OR'ed for use as a dual comparator or they may function as diodes in low threshold rectifying circuits such as absolute value amplifiers, peak detectors, etc.

- SINGLE OR DUAL SUPPLY OPERATION
- LOW POWER CONSUMPTION
- HIGH GAIN, 25,000 V/V
- LARGE COMMON MODE RANGE, +11 V, -13 V
- EXCELLENT GAIN STABILITY VS. SUPPLY VOLTAGE
- NO LATCH-UP
- OUTPUT SHORT CIRCUIT PROTECTED

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	±18 V
(312 and 393 Grades)	±12 V
(393 Grade)	
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	650 mW
Differential Input Voltage	±5 V
Input Voltage (Note 2)	
(312 and 393 Grades)	±15 V
(393 Grade)	±12 V
Storage Temperature Range	-65°C to +150°C
Operating Temperature Range	
(312 Grade)	-55°C to +125°C
(393 and 394 Grades)	0°C to +70°C
Lead Temperature (Soldering, 60 seconds)	300°C
Output Short-Circuit Duration, T _A = 25°C (Note 3)	30 seconds

EQUIVALENT CIRCUIT



CONNECTION DIAGRAMS (TOP VIEWS)


8 LEAD METAL CAN



Note: Pin 4 connected to case

ORDER PART NO. U5B7749394

14 LEAD DIP



ORDER PART NOS:
U6A7749312
U6A7749393

312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $R_L = 5$ k Ω to Pin 7, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S = 200\ \Omega$		1.0	3.0	mV
Input Offset Current			50	400	nA
Input Bias Current			0.30	0.75	μA
Input Resistance		100	150		k Ω
Large-Signal Voltage Gain	$V_{OUT} = \pm 10$ V	20,000	50,000		V/V
Positive Output Voltage Swing		+12	+13		V
Negative Output Voltage Swing		-14	-15		V
Output Resistance	$f = 1.0$ kHz		5.0		k Ω
Common Mode Rejection Ratio	$R_S = 200\ \Omega$, $V_{IN} = +11.5$ V to -13.5 V	70	90		dB
Positive Supply Voltage Rejection Ratio	$R_S = 200\ \Omega$		50	200	$\mu\text{V/V}$
Negative Supply Voltage Rejection Ratio	$R_S = 200\ \Omega$		50	200	$\mu\text{V/V}$
Input Voltage Range		-13		+11	V
Internal Power Dissipation	$V_{OUT} = 0$		180	220	mW
Supply Current	$V_{OUT} = 0$		9.0	10.4	mA
Broadband Noise Figure	$R_S = 10$ k Ω BW = 10 Hz to 10 kHz		2.5		dB
Turn On Delay (See Fig. 3)	Open Loop, $V_{IN} = \pm 20$ mV		0.2		μs
Turn Off Delay (See Fig. 3)	Open Loop, $V_{IN} = \pm 20$ mV		0.3		μs
Slew Rate (unity gain) (See Figure 2)	$C_L = .02\ \mu\text{F}$, $R_I = 33\ \Omega$, $C_2 = 10$ pF		2.0	/	V/ μs
Channel Separation (See Fig. 4)	$R_S = 1$ k Ω , $f = 10$ kHz		140		dB
The following specifications apply for $V_S = \pm 4.0$ V, $R_L = 10$ k Ω to Pin 7 $T_A = 25^\circ\text{C}$:					
Input Offset Voltage	$R_S = 200\ \Omega$		1.0	3.0	mV
Input Offset Current			50	300	nA
Input Bias Current			0.15	0.75	μA
Supply Current	$V_{OUT} = 0$		2.5	4.8	mA
Internal Power Dissipation	$V_{OUT} = 0$		20	36	mW
Large-Signal Voltage Gain	$V_{OUT} = \pm 2.0$ V	20,000	60,000		V/V
Positive Output Voltage Swing		+2.5	+2.8		V
Negative Output Voltage Swing		-3.6	-4.0		V
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$: $V_S = \pm 15$ V, $R_L = 5$ k Ω to Pin 7:					
Large Signal Voltage Gain	$V_{OUT} = \pm 10$ V, $T_A = +125^\circ\text{C}$	6,500	20,000		V/V
	$V_{OUT} = \pm 10$ V, $T_A = -55^\circ\text{C}$	20,000	30,000		V/V
Positive Output Voltage Swing		+12	+13		V
Negative Output Voltage Swing		-14	-15		V
Input Offset Voltage	$R_S = 200\ \Omega$		1.0	6.0	mV
Input Offset Current	$T_A = +125^\circ\text{C}$		0.05	1.0	μA
	$T_A = -55^\circ\text{C}$		0.05	1.5	μA
Input Bias Current	$T_A = +125^\circ\text{C}$		0.15	0.75	μA
	$T_A = -55^\circ\text{C}$		0.3	3.0	μA
Input Offset Voltage Drift	$R_S = 200\ \Omega$, $+25^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		3.0		$\mu\text{V}/^\circ\text{C}$
	$R_S = 200\ \Omega$, $-55^\circ\text{C} \leq T_A \leq +25^\circ\text{C}$		3.0		$\mu\text{V}/^\circ\text{C}$
Input Offset Current Drift	$+25^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		0.5		nA/ $^\circ\text{C}$
	$-55^\circ\text{C} \leq T_A \leq +25^\circ\text{C}$		2.0		nA/ $^\circ\text{C}$
Input Bias Current Drift	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		5.0		nA/ $^\circ\text{C}$
Supply Current	$V_{OUT} = 0$, $T_A = +125^\circ\text{C}$			9.7	mA
	$V_{OUT} = 0$, $T_A = -55^\circ\text{C}$			13	mA
Internal Power Dissipation	$V_{OUT} = 0$, $T_A = +125^\circ\text{C}$			200	mW
	$V_{OUT} = 0$, $T_A = -55^\circ\text{C}$			300	mW
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$: $V_S = \pm 4$ V, $R_L = 10$ k Ω to Pin 7:					
Input Offset Voltage	$R_S = 200\ \Omega$		1.5	6.0	mV
Input Offset Current			50	750	nA
Large-Signal Voltage Gain	$V_{OUT} = \pm 2.0$ V, $T_A = +125^\circ\text{C}$	5,000			V/V
	$V_{OUT} = \pm 2.0$ V, $T_A = -55^\circ\text{C}$	20,000			V/V
Positive Output Voltage Swing		+2.5	+2.8		V
Negative Output Voltage Swing		-3.6	-4.0		V

NOTES

1. Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP package.
2. For supply voltages less than ± 15 V, the absolute maximum input voltage is equal to the supply voltage.
3. Short circuit may be to ground or either supply.

393 GRADE





ELECTRICAL CHARACTERISTICS ($V_S = \pm 15$ V, $R_L = 5$ k Ω to Pin 7, $T_A = 25^\circ$ C unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S = 200 \Omega$		1.0	6.0	mV
Input Offset Current			50	750	nA
Input Bias Current			0.30	1.5	μA
Input Resistance		50	150		k Ω
Large-Signal Voltage Gain	$V_{OUT} = \pm 10$ V	15,000	50,000		V/V
Positive Output Voltage Swing		+12	+13		V
Negative Output Voltage Swing		-14	-15		V
Output Resistance	$f = 1.0$ kHz		5.0		k Ω
Common Mode Rejection Ratio	$R_S = 200 \Omega$, $V_{IN} = +11.5$ V to -13.5 V	70	90		dB
Positive Supply Voltage Rejection Ratio	$R_S = 200 \Omega$		50	350	$\mu V/V$
Negative Supply Voltage Rejection Ratio	$R_S = 200 \Omega$		50	200	$\mu V/V$
Input Voltage Range		-13		+11	V
Internal Power Dissipation	$V_{OUT} = 0$		180	330	mW
Supply Current	$V_{OUT} = 0$		9.0	14	mA
Broadband Noise Figure	$R_S = 10$ k Ω , BW = 10 Hz to 10 kHz		2.5		dB
Turn On Delay (See Fig. 3)	Open Loop, $V_{IN} = \pm 20$ mV		0.2		μs
Turn Off Delay (See Fig. 3)	Open Loop, $V_{IN} = \pm 20$ mV		0.3		μs
Slew Rate (unity gain) (See Figure 2)	$C_1 = .02 \mu F$, $R_1 = 33 \Omega$, $C_2 = 10$ pF		2.0		V/ μs
Channel Separation (See Fig. 4)	$R_S = 1$ k Ω , $f = 10$ kHz		140		dB
The following specifications apply for $V_S = \pm 4.0$ V, $R_L = 10$ k Ω to Pin 7, $T_A = 25^\circ$ C:					
Input Offset Voltage	$R_S = 200 \Omega$		1.0	6.0	mV
Input Offset Current			50	600	nA
Input Bias Current			0.3	1.5	μA
Supply Current	$V_{OUT} = 0$		2.5		mA
Internal Power Dissipation	$V_{OUT} = 0$		20		mW
Large-Signal Voltage Gain	$V_{OUT} = \pm 2.0$ V	15,000	60,000		V/V
Positive Output Voltage Swing		+2.5	+2.8		V
Negative Output Voltage Swing		-3.6	-4.0		V
The following specifications apply for $0^\circ C \leq T_A \leq +70^\circ C$: $V_S = \pm 15$ V, $R_L = 5$ k Ω to Pin 7:					
Large Signal Voltage Gain	$V_{OUT} = \pm 10$ V, $T_A = +70^\circ C$	8,000	40,000		V/V
	$V_{OUT} = \pm 10$ V, $T_A = 0^\circ C$	15,000	50,000		V/V
Positive Output Voltage Swing		+12	+13		V
Negative Output Voltage Swing		-14	-15		V
Input Offset Voltage	$R_S = 200 \Omega$		1.0	9.0	mV
Input Offset Current			0.05	1.5	μA
Input Bias Current			0.3	3.0	μA
Input Offset Voltage Drift	$R_S = 200 \Omega$, $+25^\circ C \leq T_A \leq +70^\circ C$		3.0		$\mu V/^\circ C$
	$R_S = 200 \Omega$, $0^\circ C \leq T_A \leq +25^\circ C$		3.0		$\mu V/^\circ C$
Input Offset Current Drift	$+25^\circ C \leq T_A \leq +70^\circ C$		0.5		nA/ $^\circ C$
	$0^\circ C \leq T_A \leq +25^\circ C$		2.0		nA/ $^\circ C$
Input Bias Current Drift	$0^\circ C \leq T_A \leq +70^\circ C$		4.0		nA/ $^\circ C$
The following specifications apply for $0^\circ C \leq T_A \leq +70^\circ C$: $V_S = \pm 4$ V, $R_L = 10$ k Ω to Pin 7:					
Input Offset Voltage	$R_S = 200 \Omega$		1.5	9.0	mV
Input Offset Current			0.05	1.0	μA
Large-Signal Voltage Gain	$V_{OUT} = \pm 2.0$ V, $T_A = 70^\circ C$	8,000			V/V
Large-Signal Voltage Gain	$V_{OUT} = \pm 2.0$ V, $T_A = 0^\circ C$	15,000			V/V
Positive Output Voltage Swing		+2.5	+2.8		V
Negative Output Voltage Swing		-3.6	-4.0		V













394 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 6\text{ V}$, $R_L = 10\text{ k}\Omega$ to Pin 4, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200\ \Omega$		1.0	10	mV
Input Offset Current			50	600	nA
Input Bias Current			300	1500	nA
Input Resistance		50	150		$\text{k}\Omega$
Large-Signal Voltage Gain	$V_{OUT} = \pm 4.0\text{ V}$	10,000	20,000		V/V
Positive Output Voltage Swing		+4.5	+5		Volts
Negative Output Voltage Swing		-5.5	-6		Volts
Output Resistance	$f = 1.0\text{ kHz}$		10		$\text{k}\Omega$
Input Voltage Range		-4		+2.5	Volts
Common Mode Rejection Ratio	$R_S \leq 10\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{ k}\Omega$		50	100	$\mu\text{V/V}$
Power Consumption (including load)	$V_{OUT} = 0$	24	36	54	mW
Supply Current (including load)	$V_{OUT} = 0$	2.0	3.0	4.5	mA
Turn On Delay (See Figure 1)	Open Loop, $V_{IN} = \pm 20\text{ mV}$, $R_L = 5\text{ k}\Omega$		0.2		μs
Turn Off Delay (See Figure 1)	Open Loop, $V_{IN} = \pm 20\text{ mV}$, $R_L = 5\text{ k}\Omega$		0.3		μs
Channel Separation (See Figure 3)	$R_S \leq 10\text{ k}\Omega$, $f = 10\text{ kHz}$		140		dB


OFFSET NULL NETWORK**Fig. 1****FREQUENCY RESPONSE TEST CIRCUIT****Fig. 2****CHANNEL SEPARATION TEST CIRCUIT****Fig. 4****PULSE RESPONSE WAVEFORMS****Fig. 3**

TYPICAL PERFORMANCE CURVES


INPUT NOISE VOLTAGE
AS A FUNCTION
OF FREQUENCYINPUT NOISE CURRENT
AS A FUNCTION
OF FREQUENCYABSOLUTE MAXIMUM POWER
DISSIPATION AS A FUNCTION
OF TEMPERATUREOPEN LOOP 180° PHASE SHIFT
FREQUENCY AS A FUNCTION OF
SUPPLY VOLTAGECOMMON MODE RANGE
AS A FUNCTION OF
SUPPLY VOLTAGETYPICAL OUTPUT VOLTAGE
AS A FUNCTION OF
SUPPLY VOLTAGEOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
LOAD RESISTANCETOTAL SUPPLY CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGETOTAL POWER DISSIPATION
AS A FUNCTION OF
SUPPLY VOLTAGE AND LOADOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
SUPPLY VOLTAGEOPEN LOOP GAIN
AS A FUNCTION OF
TEMPERATUREINPUT OFFSET CURRENT
AND BIAS CURRENT AS
FUNCTIONS OF TEMPERATURE

TYPICAL PERFORMANCE CURVES


CLOSED LOOP GAIN AS A FUNCTION OF FREQUENCY




OPEN LOOP FREQUENCY RESPONSE USING RECOMMENDED COMPENSATION NETWORKS




OUTPUT CAPABILITY AS A FUNCTION OF FREQUENCY AND COMPENSATION




OPEN LOOP PHASE SHIFT WITHOUT COMPENSATION



CHANNEL SEPARATION AS A FUNCTION OF FREQUENCY





CHANGE OF A.C. CHARACTERISTICS WITH TEMPERATURE



APPLICATION

VOLTAGE TO FREQUENCY CONVERTER



$$t = t_1 + t_2 = 4 \frac{R_1 C_1}{V_{IN}} + \frac{4 R^* C_1}{15}$$

$$R^* = R_{pin 1} + R_9 + R_{CE Q1} + R_6 \text{ output stage.}$$

μA754

TV/FM SOUND SYSTEM

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA754 monolithic TV/FM Sound System consists of a four-stage limiting IF amplifier, doubly-balanced Quadrature FM Detector and a high output audio driver stage constructed on a single silicon chip using the Fairchild Planar* Epitaxial Process. Excellent sensitivity, high AM rejection and an internally regulated power supply coupled with low external component requirement make the μA754 suitable for a wide variety of applications including TV sound channels, line operated and automobile FM radios and mobile communications equipment. Other applications include analog multipliers, phase-locked loops, and synchronous detectors.


- 70 μV SENSITIVITY
- 50 dB AM REJECTION
- INTERNALLY REGULATED SUPPLY
- SINGLE COIL QUADRATURE DETECTOR
- 3 VRMS AUDIO OUTPUT
- LOW EXTERNAL COMPONENT COUNT

ABSOLUTE MAXIMUM RATINGS



Voltage at any terminal must not exceed V_{SUPPLY}

Supply Current	40 mA
Input Voltage (Note 1)	±5 Volts
Internal Power Dissipation (Note 2)	
Metal Can	500 mW
Ceramic DIP	670 mW
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	−65°C to +150°C
TO-100 and Ceramic DIP	
Lead Temperature	+300°C
TO-100 and Ceramic DIP (Soldering, 60 seconds)	
Audio Output Short Circuit Duration	60 Seconds


BLOCK DIAGRAM



CONNECTION DIAGRAMS (TOP VIEW)



PHYSICAL DIMENSIONS In accordance with JEDEC (TO-100) Outline




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 grams

ORDER PART NO. U5E7754394

14 LEAD CERAMIC DIP



NOTES

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers
They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020 inch diameter lead
Leads are tin-plated kovar
Package weight is 2.0 grams

ORDER PART NO. U6A7754394

Notes on following page.

*Planar is a patented Fairchild process.



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $I^+ = 35\text{ mA}$, unless otherwise specified)

PARAMETERS	CONDITIONS	TEST CIRCUIT	MIN.	TYP.	MAX.	UNITS
Static Characteristics						
Voltage at SUPPLY terminal		1	11.8	13	13.5	Volts
Supply Current	$V_{\text{supply}} = 9.0\text{ V}$	1	11.8	23	28	mA
Voltage at LOW INPUT terminal		1	1.2	1.4	1.8	Volts
Voltage at QUAD BIAS terminal		1	2.5	2.8	3.5	Volts
Voltage at I.F. OUTPUT terminal		1		0.7		Volts
Voltage at AUDIO INPUT terminal		1	1.2	1.5	1.7	Volts
Voltage at AUDIO OUTPUT terminal		1	4.8	5.7	7.5	Volts
Internal Power Dissipation		1	400	450	480	mW
Voltage at DETECTOR OUTPUT terminal		1	5.8	8.0	9.5	Volts
Short-circuit Current at AUDIO OUTPUT terminal		1		35	45	mA
Dynamic Characteristics of IF Amplifier & Detector at 4.5 MHz (FM = $\pm 25\text{ kHz}$ at 400 Hz, $V_{\text{in}} = 10\text{ mV}$)						
Input Voltage for -3 dB Limiting		2		70	200	μV
IF Amplifier Voltage Gain		2	65	72		dB
A.M. Rejection	AM = 30% at 1 kHz	2	40	50		dB
Recovered Audio Voltage at Detector Output		2	250	450		mV
Total Harmonic Distortion		2		1.0	2.0	%
Detector Output Resistance				8.0		$\text{k}\Omega$
Quad. Input Resistance				90		$\text{k}\Omega$
Quad. Input Capacitance				7.0		pF
IF Amplifier Input Resistance				10		$\text{k}\Omega$
IF Amplifier Input Capacitance				4.0		pF
IF Output Voltage		2	0.4	0.6		$V_{\text{p-p}}$
IF Output Resistance				125		Ω
IF Output Capacitance				7.0		pF
Dynamic Characteristics of IF Amplifier & Detector at 10.7 MHz (FM = $\pm 75\text{ kHz}$ at 400 Hz, $V_{\text{in}} = 10\text{ mV}$)						
Input Voltage for -3 dB Limiting		2		200	300	μV
IF Amplifier Voltage Gain		2	55	62		dB
A.M. Rejection	AM = 30% at 1 kHz	2	35	45		dB
Recovered Audio Voltage at Detector Output		2	200	300		mV
Total Harmonic Distortion		2		0.5	2.0	%
Detector Output Resistance				8.0		$\text{k}\Omega$
Quad. Input Resistance				100		$\text{k}\Omega$
Quad. Input Capacitance				7.0		pF
IF Amplifier Input Resistance				10		$\text{k}\Omega$
IF Amplifier Input Capacitance				4.0		pF
IF Output Voltage		2	0.4	0.6		$V_{\text{p-p}}$
IF Output Resistance				150		Ω
IF Output Capacitance				7.0		pF
Dynamic Characteristics of Audio Section ($f = 1\text{ kHz}$, $R_S = 50\ \Omega$)						
Open Loop Voltage Gain		3	12.5	16		V/V
Input Resistance			0.1	1.0		$\text{k}\Omega$
Output Resistance				30		Ω
Maximum Output Voltage	THD = 5%, $R_L = 2.4\text{ k}\Omega$	3	2.5	3.0		V_{rms}
Total Harmonic Distortion	$V_{\text{out}} = 2 V_{\text{rms}}$, $R_L = 2.4\text{ k}\Omega$	3		0.8	3.0	%

NOTES


1. Voltage applied from High Input to Low Input.
2. Rating applies to ambient temperatures up to 70°C .

TYPICAL PERFORMANCE CURVES




TEST CIRCUITS


TEST CIRCUIT 1
STATIC CHARACTERISTICS



TEST CIRCUIT 2
DYNAMIC CHARACTERISTICS
OF IF AMPLIFIER &
QUADRATURE DETECTOR




TEST CIRCUIT 3
AUDIO AMPLIFIER
DYNAMIC CHARACTERISTICS



NOTE: For values of Quadrature Components — see Table 1 below

EQUIVALENT CIRCUIT



NOTES:

- (1) C_1 is a reverse-biased E-B Junction Capacitor.
- (2) Pin numbers shown for Dual In-Line Package.


TABLE 1
VALUE OF QUADRATURE
COMPONENTS

TABLE I

f_0	4.5 MHz	10.7 MHz
FM	± 25 kHz	75 kHz
L	10.4 μH	3.1 μH
C	120 pF	68 pF
Q_U	40	40
Q_L	30	15
Separation	300 kHz	1.1 MHz

TYPICAL APPLICATION

I.F. AMPLIFIER-DETECTOR 2W CLASS A OUTPUT STAGE



f_o	4.5	10.7	MHz
L	10.4	3.1	μH
C	120	68	pF
R	20 k	3.3 k	Ω


TYPICAL PERFORMANCE OF 2W CIRCUIT

f_o	4.5 MHz	10.7 MHz
Deviation for 100% FM	± 25 kHz	± 75 kHz
AM Rejection at 1 mV	45 dB	35 dB
Limiting sensitivity	80 μV	150 μV
Recovered Audio at Detector Output	380 mV	160 mV
T.H.D. at Detector Output	1.0%	0.5%
Deviation for 2W output	± 15 kHz	—


NOTES:

- (1) Circuitry on printed circuit board shown inside dotted lines.
 *(2) Unused pins should be grounded for shielding.

SUGGESTED CIRCUIT LAYOUT



COPPER SIDE



COMPONENT SIDE

μA757

GAIN CONTROLLED IF AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA757 is a high performance, gain-controlled IF amplifier constructed on a silicon chip using the Fairchild Planar* epitaxial process. The amplifier contains two sections which may be operated independently, or in cascade, from audio frequencies to 25 MHz. The μA757 is intended primarily as a gain-controlled, intermediate-frequency amplifier in AM and FM communications receivers. It also has excellent performance when operated in FM receivers as a limiting-amplifier.


- 70 dB GAIN AT 10.7 MHz
- 70 dB AGC RANGE AT 10.7 MHz
- 300 mV SIGNAL HANDLING CAPABILITY AT INPUT
- CONSTANT INPUT AND OUTPUT IMPEDANCE WITH AGC
- STABLE GAIN WITH SUPPLY VOLTAGE AND TEMPERATURE AT ALL LEVELS OF GAIN REDUCTION.

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	+15 V
Voltage at any Output Terminal	+24 V
Voltage at either AGC Terminal (Note 1)	+12 V
Differential Voltage at either Input (Pins 1 and 14, Pins 2 and 10)	±5 V
Internal Power Dissipation (Note 2)	670 mW
Storage Temperature Range	
Ceramic DIP	-65°C to +150°C
Operating Temperature Range	
Military (312 grade)	-55°C to +125°C
Commercial (393 grade)	0°C to +70°C
Lead Temperature	
Ceramic DIP (Soldering 60 seconds)	300°C

PHYSICAL DIMENSIONS

in accordance with JEDEC (TO-116) outline




NOTES


All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers
They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020 inch diameter lead
Leads are tin-plated kovar
Package weight is 2.0 grams

**ORDER PART NOS: U6A7757312
U6A7757393**

EQUIVALENT CIRCUIT



CONNECTION DIAGRAM (TOP VIEW)



Notes on following pages.

*Planar is a patented Fairchild process.

$T_A = +25^\circ\text{C}$, 312 GRADEELECTRICAL CHARACTERISTICS ($V^+ = +12\text{ V}$, unless otherwise specified)

PARAMETERS	CONDITIONS	TEST CIRCUIT	MIN.	TYP.	MAX.	UNITS
Supply Current	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		13	17	mA
	$V_{AGC\ 1,2} = +3.0\text{ V}$			17	20	mA
Internal Power Dissipation	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		170	210	mW
	$V_{AGC\ 1,2} = +3.0\text{ V}$			200	240	mW
Voltage Gain at no Gain Reduction	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 500\text{ kHz}$	2	65	74		dB
	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$	2	60	70		dB
Voltage Gain at Partial Gain Reduction	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2	20	39	46	dB
	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 10.7\text{ MHz}$	2		37		dB
Voltage Gain at Full Gain Reduction	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 500\text{ kHz}$	2		2.0	10	dB
	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$	2		1.0	8	dB
Current into either AGC Terminal	$V_{AGC\ 1,2} = +3.0\text{ V}$	1		15	50	μA
Gain Reduction Sensitivity	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2		50		dB/V
Input Voltage for -3 dB Limiting at Output	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 500\text{ kHz}$	2		0.5		mV
Intermodulation Products	Two-tone signal $f_1 = 500\text{ kHz}$, $e_1 = 100\text{ mV}$ $f_2 = 510\text{ kHz}$, $e_2 = 100\text{ mV}$ $I_{OUT} = 1\text{ mA p-p}$	2		-50		dB
SECTION 1						
Input Resistance at either Input Terminal	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$		3.0	5.0		k Ω
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			4.5		k Ω
Input Capacitance at either Input Terminal	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Output Resistance	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			100		k Ω
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			100		k Ω
Output Capacitance	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			2.6		pF
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Forward Transadmittance	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 500\text{ kHz}$			14		mmho
	$V_{AGC\ 1} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			13		mmho
Peak-to-Peak Output Current	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 500\text{ kHz}$		0.25	0.4		mA
	Output in full limiting					
Output Saturation Voltage	$I_{OUT} = 0.1\text{ mA}$, $V_{AGC\ 1} = +3.0\text{ V}$			8.0	9.0	Volts
Noise Figure	$R_S = 1.0\text{ k}\Omega$, $f = 10.7\text{ MHz}$			8.0		dB
Noise Figure	$R_S = 1.0\text{ k}\Omega$, $f = 500\text{ kHz}$			8.0		dB
Interfering Signal Voltage at Input for 1.0% Cross Modulation	Carrier signal, $f_c = 500\text{ kHz}$			15		mV
	Interfering signal, $f_i = 510\text{ kHz}$					
	$I_{OUT} = 0.5\text{ mA p-p}$, $V_{AGC\ 1} = +0.8\text{ V}$					
SECTION 2						
Input Resistance	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$		3.0	5.0		k Ω
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			4.5		k Ω
Input Capacitance	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Output Resistance at either Output Terminal	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			26		k Ω
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			20		k Ω
Output Capacitance at either Output Terminal	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
Forward Transadmittance	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 500\text{ kHz}$			440		mmho
	$V_{AGC\ 2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$			280		mmho
Quiescent Output Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$		1.7	2.4	3.5	mA
Peak-to-Peak Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 500\text{ kHz}$		3.8	4.8	7.0	mA
	Output in full limiting					
Output Saturation Voltage at either Output Terminal	$I_{OUT} = 1.0\text{ mA}$, $V_{AGC\ 2} = +3.0\text{ V}$			5.0	6.0	Volts
Power Supply Sensitivity	$V_S = 12\text{ V}$ to 15 V					
	0 dB Gain Reduction			0.5		dB/V
	30 dB Gain Reduction			0.8		dB/V
	60 dB Gain Reduction			1.0		dB/V

$T_A = +125^\circ\text{C}$, 312 GRADE**ELECTRICAL CHARACTERISTICS** ($V^+ = +12\text{ V}$, unless otherwise specified)

PARAMETERS	CONDITIONS	TEST CIRCUIT	MIN.	TYP.	MAX.	UNITS
Supply Current	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		14	17	mA
	$V_{AGC\ 1,2} = +3.0\text{ V}$			17	20	mA
Internal Power Dissipation	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		170	210	mW
	$V_{AGC\ 1,2} = +3.0\text{ V}$			200	240	mW
Voltage Gain at no Gain Reduction	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 500\text{ kHz}$	2	55	71		dB
	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$	2		62		dB
Voltage Gain at Partial Gain Reduction	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2		35		dB
Voltage Gain at Full Gain Reduction	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 500\text{ kHz}$	2		2.0	15	dB
	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$	2		-1.0		dB
Current into either AGC Terminal	$V_{AGC\ 1,2} = +3.0\text{ V}$	1		15	50	μA

SECTION 1

Peak-to-Peak Output Current	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		0.2	0.4		mA
Output Saturation Voltage	$I_{OUT} = 0.1\text{ mA}$, $V_{AGC\ 1} = +3.0\text{ V}$			8.0	9.4	Volts

SECTION 2

Quiescent Output Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$		1.7	2.8	3.5	mA
Peak-to-Peak Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		3.8	5.6	7.0	mA
Output Saturation Voltage at either Output Terminal	$I_{OUT} = 1.0\text{ mA}$, $V_{AGC\ 2} = +3.0\text{ V}$			6.0	7.0	Volts

 $T_A = -55^\circ\text{C}$, 312 GRADE**ELECTRICAL CHARACTERISTICS** ($V^+ = +12\text{ V}$, unless otherwise specified)

PARAMETERS	CONDITIONS	TEST CIRCUIT	MIN.	TYP.	MAX.	UNITS
Supply Current	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		10	17	mA
	$V_{AGC\ 1,2} = +3.0\text{ V}$			14	20	mA
Internal Power Dissipation	$V_{AGC\ 1,2} = +0.8\text{ V}$	1		120	210	mW
	$V_{AGC\ 1,2} = +3.0\text{ V}$			170	240	mW
Voltage Gain at no Gain Reduction	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 500\text{ kHz}$	2	55	68		dB
	$V_{AGC\ 1,2} = +0.8\text{ V}$, $f = 10.7\text{ MHz}$	2		64		dB
Voltage Gain at Partial Gain Reduction	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2		28		dB
Voltage Gain at Full Gain Reduction	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 500\text{ kHz}$	2		2.0	15	dB
	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$	2		-3.0		dB
Current into either AGC Terminal	$V_{AGC\ 1,2} = +3.0\text{ V}$	1		30	70	μA

SECTION 1

Peak-to-Peak Output Current	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		0.2	0.4		mA
Output Saturation Voltage	$I_{OUT} = 0.1\text{ mA}$, $V_{AGC\ 1} = +3.0\text{ V}$			8.0	9.0	Volts

SECTION 2

Quiescent Output Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$		1.0	1.7	3.5	mA
Peak-to-Peak Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		2.3	3.4	7.0	mA
Output Saturation Voltage at either Output Terminal	$I_{OUT} = 1.0\text{ mA}$, $V_{AGC\ 2} = +3.0\text{ V}$			4.0	6.0	Volts


393 GRADE

ELECTRICAL CHARACTERISTICS ($V^+ = +12\text{ V}$, $T_A = +25^\circ\text{C}$, unless otherwise specified)


PARAMETERS	CONDITIONS	TEST CIRCUIT	MIN.	TYP.	MAX.	UNITS
Supply Current	$V_{AGC\ 1,2} = +1.0\text{ V}$	1		14	17	mA
	$V_{AGC\ 1,2} = +3.0\text{ V}$			18	22	mA
Internal Power Dissipation	$V_{AGC\ 1,2} = +1.0\text{ V}$	1		170	210	mW
	$V_{AGC\ 1,2} = +3.0\text{ V}$			220	270	mW
Voltage Gain at no Gain Reduction	$V_{AGC\ 1,2} = +1.0\text{ V}$, $f = 500\text{ kHz}$	2	65	74		dB
	$V_{AGC\ 1,2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$	2	60	70		dB
Voltage Gain at Partial Gain Reduction	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2	20	39	46	dB
	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 10.7\text{ MHz}$	2		37		dB
Voltage Gain at Full Gain Reduction	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 500\text{ kHz}$	2		2.0	10	dB
	$V_{AGC\ 1,2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$	2		1.0	8	dB
Current into either AGC Terminal	$V_{AGC\ 1,2} = +3.0\text{ V}$	1		15	50	μA
Gain Reduction Sensitivity	$V_{AGC\ 1,2} = +1.7\text{ V}$, $f = 500\text{ kHz}$	2		50		dB/V
Input Voltage for -3 dB Limiting at Output	$V_{AGC\ 1,2} = +1.0\text{ V}$, $f = 500\text{ kHz}$	2		0.5		mV
Intermodulation Products	Two-tone signal $f_1 = 500\text{ kHz}$, $e_1 = 100\text{ mV}$ $f_2 = 510\text{ kHz}$, $e_2 = 100\text{ mV}$ $I_{OUT} = 1\text{ mA p-p}$	2		-50		dB
SECTION 1						
Input Resistance at either Input Terminal	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$		3.0	5.0		k Ω
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			4.5		k Ω
Input Capacitance at either Input Terminal	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Output Resistance	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			100		k Ω
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			100		k Ω
Output Capacitance	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			2.6		pF
	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Forward Transadmittance	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 500\text{ kHz}$			14		mmho
	$V_{AGC\ 1} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			13		mmho
Peak-to-Peak Output Current	$V_{AGC\ 1} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		.25	0.4		mA
Output Saturation Voltage	$I_{OUT} = 0.1\text{ mA}$, $V_{AGC\ 1} = +3.0\text{ V}$			8.0	9.0	Volts
Noise Figure	$R_S = 1.0\text{ k}\Omega$, $f = 10.7\text{ MHz}$			8.0		dB
Noise Figure	$R_S = 1.0\text{ k}\Omega$, $f = 500\text{ kHz}$			8.0		dB
Interfering Signal Voltage at Input for 1.0% Cross Modulation	Carrier signal, $f_c = 500\text{ kHz}$ Interfering signal, $f_i = 510\text{ kHz}$ $I_{OUT} = 0.5\text{ mA p-p}$, $V_{AGC\ 1} = +1.0\text{ V}$			15		mV
SECTION 2						
Input Resistance	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$		3.0	5.0		k Ω
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			4.5		k Ω
Input Capacitance	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
Output Resistance at either Output Terminal	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			26		k Ω
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			20		k Ω
Output Capacitance at either Output Terminal	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			2.2		pF
	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 10.7\text{ MHz}$			2.5		pF
Forward Transadmittance	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 500\text{ kHz}$			440		mmho
	$V_{AGC\ 2} = +1.0\text{ V}$, $f = 10.7\text{ MHz}$			280		mmho
Quiescent Output Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$		1.7	2.4	3.5	mA
Peak-to-Peak Current at either Output Terminal	$V_{AGC\ 2} = +3.0\text{ V}$, $f = 500\text{ kHz}$ Output in full limiting		3.8	4.8	7.0	mA
Output Saturation Voltage at either Output Terminal	$I_{OUT} = 1.0\text{ mA}$, $V_{AGC\ 2} = +3.0\text{ V}$			5.0	6.0	Volts
Power Supply Sensitivity	$V_S = 12\text{ V}$ to 15 V 0 dB Gain Reduction 30 dB Gain Reduction 60 dB Gain Reduction			0.5 0.8 1.0		dB/V dB/V dB/V

TYPICAL PERFORMANCE CURVES


PRODUCT OF SECTIONS 1 AND 2
FORWARD TRANSMITTANCE
AS A FUNCTION OF FREQUENCY




SECTION 1
FORWARD TRANSMITTANCE
AS A FUNCTION OF FREQUENCY




SECTION 2
FORWARD TRANSMITTANCE
AS A FUNCTION OF FREQUENCY




SECTION 1 AND 2
INPUT RESISTANCE AND
CAPACITANCE AS A FUNCTION
OF GAIN REDUCTION




SECTION 2
OUTPUT RESISTANCE AND
CAPACITANCE AS A FUNCTION
OF GAIN REDUCTION




VOLTAGE GAIN AS A FUNCTION
OF TEMPERATURE




GAIN REDUCTION AS A
FUNCTION OF
GAIN CONTROL VOLTAGE




SIGNAL TO NOISE RATIO
IMPROVEMENT AND NOISE
FIGURE AS A FUNCTION OF
GAIN REDUCTION




POWER SUPPLY CURRENT
AS A FUNCTION OF
SUPPLY VOLTAGE




TWO TONE IM DISTORTION
PRODUCTS AS A FUNCTION OF
INPUT SIGNAL LEVEL



TEST CIRCUIT 1



TEST CIRCUIT 2

**NOTE**

For 10.7 MHz measurements, interstage capacitance and Section 2 output capacitance are tuned out. Pin 9 should be connected to GND

NOTES

1. For supply voltages less than +12 V, the absolute maximum voltage at either AGC terminal is equal to the supply voltage.
2. Rating applies to ambient temperatures up to 70°C. Above 70°C ambient derate linearly at 8.3 mW/°C.

μA760

HIGH SPEED DIFFERENTIAL COMPARATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA760 is a differential voltage comparator offering considerable speed improvement over the μA710 family and operation from symmetric supplies of from ± 4.5 volts to ± 6.5 volts. Complementary outputs are TTL compatible with a minimum sink capability of two gate loads.

- GUARANTEED HIGH SPEED
- GUARANTEED DELAY MATCHING ON BOTH OUTPUTS
- COMPLEMENTARY TTL COMPATIBLE OUTPUTS
- HIGH SENSITIVITY
- USES STANDARD SUPPLY VOLTAGES

ABSOLUTE MAXIMUM RATINGS

Positive Supply Voltage	+8 V
Negative Supply Voltage	-8 V
Peak Output Current	10 mA
Differential Input Voltage	± 5 V
Input Voltage	$\pm V_S$
Internal Power Dissipation (Note 1) Metal Can	500 mW
Ceramic DIP	670 mW
Mini DIP	310 mW

Operating Temperature Range

Military (312 Grade)

-55°C to 125°C

Commercial (393 Grade)

0°C to 70°C

Storage Temperature Range


Metal Can and DIP

-65°C to 150°C


Mini DIP

-55°C to 125°C

EQUIVALENT CIRCUIT




CONNECTION DIAGRAM 8 LEAD METAL CAN (TOP VIEW)




ORDER PART NOS.: PRODUCT CODE
U5B7760312
U5B7760393

14 LEAD DIP (TOP VIEW)



ORDER PART NOS.: PRODUCT CODE
U6A7760312
U6A7760393

MINI DIP (TOP VIEW)



ORDER PART NO.: PRODUCT CODE
U9T7760393

312 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 4.5V$ to $\pm 6.5V$, $T_A = -55^\circ C$ to $+125^\circ C$, $T_A = 25^\circ C$ for typical figures unless otherwise specified.)

PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200\Omega$		1.0	6.0	mV
Input Offset Current			0.5	7.5	μA
Input Bias Current			8.0	60	μA
Output Resistance	$V_{OUT} = V_{OH}$		100		Ω
Response Time	Note 2, $T_A = 25^\circ C$		18	30	ns
	Note 3, $T_A = 25^\circ C$			25	ns
	Note 4		16		ns
Response Time Difference between outputs					
$t_{pd+1} - t_{pd-2}$	Note 2, $T_A = 25^\circ C$			5.0	ns
$t_{pd+2} - t_{pd-1}$	Note 2, $T_A = 25^\circ C$			5.0	ns
$t_{pd+1} - t_{pd+2}$	Note 2, $T_A = 25^\circ C$			7.5	ns
$t_{pd-1} - t_{pd-2}$	Note 2, $T_A = 25^\circ C$			7.5	ns
Input Resistance	$f = 1 \text{ MHz}$		12		k Ω
Input Capacitance	$f = 1 \text{ MHz}$		8.0		pF
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\Omega$, $T_A = -55^\circ C$ to $T_A = +125^\circ C$		3.0		$\mu V/^\circ C$
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ C$ to $T_A = +125^\circ C$		2.0		nA/ $^\circ C$
	$T_A = 25^\circ C$ to $T_A = -55^\circ C$		7.0		nA/ $^\circ C$
Input Voltage Range	$V_S = \pm 6.5V$	± 4.0	± 4.5		V
Differential Input Voltage Range			± 5.0		V
Positive Output Level	$0 \leq I_{OUT} \leq 5.0 \text{ mA}$				
	$V_S = \pm 5.0V$	2.4	3.2		V
	$I_{OUT} = 80 \mu A$, $V_S = \pm 4.5V$	2.4	3.0		V
Negative Output Level	$I_{SINK} = 3.2 \text{ mA}$		0.25	0.4	V
Positive Supply Current	$V_S = \pm 6.5V$		18	32	mA
Negative Supply Current	$V_S = \pm 6.5V$		9.0	16	mA

393 GRADE

ELECTRICAL CHARACTERISTICS ($V_S = \pm 4.5V$ to $\pm 6.5V$, $T_A = 0^\circ C$ to $+70^\circ C$, $T_A = 25^\circ C$ for typical figures unless otherwise specified.)


PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 200\Omega$		1.0	6.0	mV
Input Offset Current			0.5	7.5	μA
Input Bias Current			8.0	60	μA
Output Resistance	$V_{OUT} = V_{OH}$		100		Ω
Response Time	Note 2, $T_A = 25^\circ C$		18	30	ns
	Note 3, $T_A = 25^\circ C$			25	ns
	Note 4		16		ns
Response Time Difference between outputs					
$t_{pd+1} - t_{pd-2}$	Note 2, $T_A = 25^\circ C$			5.0	ns
$t_{pd+2} - t_{pd-1}$	Note 2, $T_A = 25^\circ C$			5.0	ns
$t_{pd+1} - t_{pd+2}$	Note 2, $T_A = 25^\circ C$			10	ns
$t_{pd-1} - t_{pd-2}$	Note 2, $T_A = 25^\circ C$			10	ns
Input Resistance	$f = 1\text{ MHz}$		12		$k\Omega$
Input Capacitance	$f = 1\text{ MHz}$		8.0		pF
Average Temperature Coefficient of Input Offset Voltage	$R_S = 50\Omega$, $T_A = 0^\circ C$ to $T_A = +70^\circ C$		3.0		$\mu V/^\circ C$
Average Temperature Coefficient of Input Offset Current	$T_A = 25^\circ C$ to $T_A = +70^\circ C$		5.0		$nA/^\circ C$
	$T_A = 25^\circ C$ to $T_A = 0^\circ C$		10		$nA/^\circ C$
Input Voltage Range	$V_S = \pm 6.5V$	± 4.0	± 4.5		V
Differential Input Voltage Range			± 5.0		V
Positive Output Level	$0 \leq I_{OUT} \leq 5.0\text{ mA}$				
	$V_S = \pm 5.0V$	2.4	3.2		V
	$I_{OUT} = 80\mu A$, $V_S = \pm 4.5V$	2.5	3.0		V
Negative Output Level	$I_{SINK} = 3.2\text{ mA}$		0.25	0.4	V
Positive Supply Current	$V_S = \pm 6.5V$		18	34	mA
Negative Supply Current	$V_S = \pm 6.5V$		9.0	16	mA

NOTES


- Rating applies to ambient temperatures up to $70^\circ C$. Above $70^\circ C$ ambient derate linearly at $6.3\text{ mW}/^\circ C$ for Metal Can and $8.3\text{ mW}/^\circ C$ for the Ceramic DIP.
- Response time measured from the 50% point of a 30 mVp-p 10 MHz sinusoidal input to the 50% point of the output.
- Response time measured from the 50% point of a 2 Vp-p 10 MHz sinusoidal input to the 50% point of the output.
- Response time measured from the start of a 100 mV input step with 5 mV overdrive to the time when the output crosses the logic threshold.

TYPICAL PERFORMANCE CURVES


RESPONSE TIME FOR
VARIOUS INPUT OVERDRIVES




RESPONSE TIME FOR
VARIOUS INPUT OVERDRIVES




RESPONSE TIME AS A
FUNCTION OF INPUT VOLTAGE




RESPONSE TIME AS A
FUNCTION OF INPUT VOLTAGE




VOLTAGE TRANSFER
CHARACTERISTIC




VOLTAGE TRANSFER
CHARACTERISTIC




VOLTAGE GAIN AS A
FUNCTION OF
SUPPLY VOLTAGE




VOLTAGE GAIN AS A
FUNCTION OF AMBIENT
TEMPERATURE




INPUT BIAS CURRENT AS A
FUNCTION OF AMBIENT
TEMPERATURE




INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE



RESPONSE TIME AS A
FUNCTION OF
AMBIENT TEMPERATURE




OUTPUT VOLTAGE LEVELS
AS A FUNCTION OF
AMBIENT TEMPERATURE




TYPICAL PERFORMANCE CURVES (Cont.)


RISE TIME AS A FUNCTION OF CAPACITIVE LOAD




FALL TIME AS A FUNCTION OF CAPACITIVE LOAD



INPUT BIAS CURRENT AS A FUNCTION OF DIFFERENTIAL INPUT VOLTAGE




COMMON MODE RANGE AS A FUNCTION OF SUPPLY VOLTAGE




APPLICATIONS

Pin numbers shown are only for Metal Can and Mini DIP.


FAST POSITIVE PEAK DETECTOR



LEVEL DETECTOR WITH HYSTERESIS




ZERO CROSSING DETECTOR



Total delay = 30 ns
Input frequency = 300 Hz to 3 MHz
Minimum input voltage = 20 mVp-p

LINE RECEIVER WITH HIGH COMMON MODE RANGE




$$\text{Common mode range} = \pm 4 \times \frac{R_S}{50} V$$

$$\text{Differential Input sensitivity} = 5 \times \frac{R_S}{50} mV$$

P_1 must be adjusted for optimum common mode rejection.

For $R_S = 200 \Omega$
Common mode range = $\pm 16V$
Sensitivity = 20 mV

HIGH SPEED 3-BIT A/D CONVERTER



Input voltage range: 3.5V
Typical conversion speed: 30 ns

μA767

FM STEREO MULTIPLEX DECODER

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION—The μA767 is a monolithic FM Stereo Multiplex Decoder System constructed on a single silicon chip using the Fairchild Planar* Epitaxial Process. This integrated circuit accomplishes the demodulation of a Stereo Multiplex Signal into the Right and Left audio channels while inherently suppressing SCA frequency components. Internal provision is made for driving an external stereo mode indicator lamp. The excellent performance, wide supply range and low external parts requirement makes the μA767 suitable for all line-operated and automotive FM Stereo Multiplex applications. For Stereo Decoding including interstation audio muting and stereo/mode switching, see the μA729 and μA732 data sheets. See Note 1.

- 45 dB CHANNEL SEPARATION
- 55 dB STORECAST REJECTION WITHOUT SCA FILTERS
- HIGH-CURRENT STEREO INDICATOR LAMP DRIVER
- OPERATION WITH 8 V TO 14 V SUPPLIES

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (Note 2)	+15 V
Voltage at Stereo Lamp Driver Terminal	+22 V
Current into Stereo Lamp Driver Terminal (Note 3)	100 mA
Internal Power Dissipation	
Ceramic DIP	670 mW
Silicone DIP	340 mW
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +125°C
9A Package	-65°C to +150°C
6A Package	+260°C
Lead Temperature (Soldering, 10 seconds) 9A Package	+300°C
(Soldering, 60 seconds) 6A Package	


BLOCK DIAGRAM



Notes on following page.


PHYSICAL DIMENSIONS

In accordance with JEDEC (TO-116) outline
14 LEAD SILICONE DUAL IN-LINE



ORDER PART NO. U9A7767394

In accordance with JEDEC (TO-116) outline
14 LEAD CERAMIC DUAL IN-LINE




ORDER PART NO. U6A7767394

NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 0.9 gram for 9A
- 2.0 gram for 6A package

CONNECTION DIAGRAM (TOP VIEW)



* Planar is a patented Fairchild process.


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V^+ = +12\text{ V}$, 200 mV RMS Standard Stereo Multiplex signal applied to Input, unless otherwise specified (Note 4). Refer to Test Circuit of Figure 1.)

PARAMETER	MIN.	TYP.	MAX.	UNITS
Supply Current		12	18	mA
Input Resistance	12	20		$k\Omega$
Stereo Separation				
$f = 100\text{ Hz}$		40		dB
$f = 1\text{ kHz}$	30	45		dB
$f = 10\text{ kHz}$	20	40		dB
Channel Balance (Monaural Input)		0.2		dB
Total Harmonic Distortion		0.5	1.0	%
Voltage Gain		1.0		V/V
67 kHz Storecast Rejection (Note 5)		55		dB
19 kHz Pilot Level Required at Input for:				
Stereo Indicator Lamp on		12	22	mV RMS
Stereo Indicator Lamp off	4.0	8.0		mV RMS
High Frequency Audio Components in Left and Right Outputs (dB below 1 kHz output)				
19 kHz		30		dB
38 kHz		25		dB

NOTES:

- (1) The $\mu A767$ is a plug-in replacement for the MC1307.
- (2) Power supply transients up to 22V are permissible for periods of 15 seconds. However, extended operation at voltages greater than 15V should be avoided as the maximum allowable internal power dissipation for this device may be exceeded.
- (3) Rating applies to steady state current. Maximum permissible surge current during turn-on of the Stereo Indicator Lamp is 500 mA.
- (4) "Standard Stereo Multiplex Signal" here refers to a 200mV RMS (0.56V p-p) composite stereo signal including 10% pilot with $L=1$ and $R=1$ as described in the FCC Rules on FM Broadcasting.
- (5) Measured with a stereo composite signal consisting of 80% stereo, 10% pilot and 10% SCA as defined in the FCC Rules on FM Broadcasting.

TYPICAL PERFORMANCE CURVES



$\mu A767$ FM STEREO MULTIPLEX DECODER TEST CIRCUIT AND TYPICAL APPLICATION





Fig. 1

NOTES:

- (1) Capacitors C_1 , C_2 , and C_3 should be polystyrene or mylar.
- (2) Coils L_1 and L_2 are 7.0 mH nominal with $Q_{UL} = 60$ (Miller #1361 or equivalent).
- (3) Coil L_3 is 8.0 mH nominal with $Q_{UL} = 80$, tapped at 10:1 turns ratio. (Miller #1362 or equivalent).
- (4) Resistor R_1 can be increased (or decreased) in value to increase (or decrease) the 19 kHz sensitivity.

$\mu A767$ FM STEREO MULTIPLEX DECODER EQUIVALENT CIRCUIT



μA776

MULTI-PURPOSE PROGRAMMABLE OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

DESCRIPTION — The μA776 Programmable Operational Amplifier is constructed on a single silicon chip using the Fairchild Planar* epitaxial process. High input impedance, low supply currents, and low input noise over a wide range of operating supply voltages coupled with programmable electrical characteristics result in an extremely versatile amplifier for use in high accuracy, low power consumption analog applications. Input voltage and current noise, power consumption, and input current can be optimized by a single resistor or current source that sets the chip quiescent current for nano-watt power consumption or for characteristics similar to the μA741. Internal frequency compensation, absence of latch up high slew rate and short circuit current protection assure ease of use in long time integrators, active filters, and sample and hold circuits.


- MICROPOWER CONSUMPTION
- $\pm 1.2\text{V}$ to $\pm 18\text{V}$ OPERATION
- NO FREQUENCY COMPENSATION REQUIRED
- LOW INPUT BIAS CURRENTS
- WIDE PROGRAMMING RANGE

- HIGH SLEW RATE
- LOW NOISE
- SHORT CIRCUIT PROTECTION
- OFFSET NULL CAPABILITY
- NO LATCH UP

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	$\pm 18\text{ V}$
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Silicone DIP	340 mW
Mini DIP	310 mW
Differential Input Voltage	$\pm 30\text{ V}$
Input Voltage (Note 2)	$\pm 15\text{ V}$
Voltage Between Offset Null and V-	$\pm 0.5\text{ V}$
I _{SET} (Maximum Current at I _{SET})	200 μA
V _{SET} (Maximum Voltage to Ground at I _{SET})	$(V^+ - 1.0\text{ V}) \leq V_{SET} \leq V^+$
Storage Temperature Range	
Metal Can, Ceramic DIP	-65°C to +150°C
Mini DIP and Silicone DIP	-55°C to +125°C
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to +70°C
Lead Temperature (Soldering, 60 seconds)	300°C
Metal Can, Ceramic DIP	260°C
Mini DIP and Silicone DIP	Indefinite
Output Short-Circuit Duration (Note 3)	

EQUIVALENT CIRCUIT



Notes on following page.


CONNECTION DIAGRAMS 8 LEAD METAL CAN



PRODUCT CODE

ORDER PART NOS: U5B7776312
U5B7776393


14 LEAD DIP



ORDER PART NOS:
FOR CERAMIC DIP : PRODUCT CODE
U6A7776312
U6A7776393

FOR SILICONE DIP: PRODUCT CODE
U9A7776393

MINI DIP



PRODUCT CODE:

ORDER PART NO.: U9T7776393

*Planar is a patented Fairchild process.

± 3 VOLT OPERATION FOR 312 GRADEELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Unless Otherwise Specified)

PARAMETERS	CONDITIONS	$I_{SET} = 1.5\mu\text{A}$			$I_{SET} = 15\mu\text{A}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$		2.0	5.0		2.0	5.0	mV
Input Offset Current			0.7	3.0		2.0	15	nA
Input Bias Current			2.0	7.5		15	50	nA
Input Resistance			50			5.0		$\text{M}\Omega$
Input Capacitance			2.0			2.0		pF
Offset Voltage Adjustment Range			9.0			18		mV
Large Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 1\text{V}$	50k	200k					V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 1\text{V}$				50k	200k		V/V
Output Resistance			5k			1k		Ω
Output Short-Circuit Current			2.0			5.0		mA
Supply Current			13	20		100	130	μA
Power Consumption			78	120		600	720	μW
Transient Response (unity gain)	$V_{IN} = 20\text{mV}, R_L \geq 5\text{k}\Omega, C_L = 100\text{pF}$							
Risettime			3.0			0.6		μs
Overshoot			0			5		%
Slew Rate	$R_L \geq 5\text{k}\Omega$		0.03			0.35		V/ μs
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$								
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$			6.0			6.0	mV
Input Offset Current	$T_A = +125^\circ\text{C}$			5.0			15	nA
	$T_A = -55^\circ\text{C}$			10			40	nA
Input Bias Current	$T_A = +125^\circ\text{C}$			7.5			50	nA
	$T_A = -55^\circ\text{C}$			20			120	nA
Input Voltage Range		± 1.0			± 1.0			V
Common Mode Rejection Ratio	$R_S \leq 10\text{k}\Omega$	70	86		70	86		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{k}\Omega$		25	150		25	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 1\text{V}$	25k						V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 1\text{V}$				25k			V/V
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 2.0	± 2.4					V
	$R_L \geq 5\text{k}\Omega$				± 1.9	± 2.1		V
Supply Current				25			135	μA
Power Consumption				150			750	μW

NOTES

- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP, $6.3\text{ mW}/^\circ\text{C}$ for the Silicone DIP and $5.6\text{ mW}/^\circ\text{C}$ for the Mini DIP package.
- For supply voltages less than $\pm 15\text{ V}$, the absolute maximum input voltage is equal to the supply voltage.
- Short circuit may be to ground or either supply. Rating applies to $+125^\circ\text{C}$ case temperature or $+75^\circ\text{C}$ ambient temperature for $I_{SET} \leq 30\mu\text{A}$.

± 15 VOLT OPERATION FOR 312 GRADEELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Unless Otherwise Specified)

PARAMETERS	CONDITIONS	$I_{SET} = 1.5\mu\text{A}$			$I_{SET} = 15\mu\text{A}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$		2.0	5.0		2.0	5.0	mV
Input Offset Current	$R_S \leq 10\text{k}\Omega$		0.7	3.0		2.0	15	nA
Input Bias Current			2.0	7.5		15	50	nA
Input Resistance			50			5.0		$\text{M}\Omega$
Input Capacitance			2.0			2.0		pF
Offset Voltage Adjustment Range			9.0			18		mV
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 10\text{V}$	200k	400k					V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 10\text{V}$				100k	400k		V/V
Output Resistance			5.0k			1.0k		Ω
Output Short-Circuit Current			2.0			10		mA
Supply Current			20	25		125	150	μA
Power Consumption				0.75			4.5	mW
Transient Response (unity gain)	$V_{IN} = 20\text{mV}, R_L \geq 5\text{k}\Omega, C_L \leq 100\text{pF}$							
Risetime			1.6			0.35		μs
Overshoot			0			10		%
Slew Rate	$R_L \geq 5\text{k}\Omega$		0.1			0.8		V/ μs
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 12	± 14					V
	$R_L \geq 5\text{k}\Omega$				± 10	± 13		V
The following specifications apply $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$								
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$			6.0			6.0	mV
Input Offset Current	$T_A = +125^\circ\text{C}$			5.0			15	nA
	$T_A = -55^\circ\text{C}$			10			40	nA
Input Bias Current	$T_A = +125^\circ\text{C}$			7.5			50	nA
	$T_A = -55^\circ\text{C}$			20			120	nA
Input Voltage Range		± 10			± 10			V
Common Mode Rejection Ratio	$R_S \leq 10\text{k}\Omega$	70	90		70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{k}\Omega$		25	150		25	150	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 10\text{V}$	100k			75k			V/V
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 10			± 10			V
Supply Current				30			170	μA
Power Consumption				0.9			5.1	mW


± 3 VOLT OPERATION FOR 393 GRADEELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Unless Otherwise Specified)

PARAMETERS	CONDITIONS	$I_{SET} = 1.5\mu\text{A}$			$I_{SET} = 15\mu\text{A}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$		2.0	6.0		2.0	6.0	mV
Input Offset Current			0.7	6.0		2.0	25	nA
Input Bias Current			2.0	10		15	50	nA
Input Resistance			50			5.0		M Ω
Input Capacitance			2.0			2.0		pF
Offset Voltage Adjustment Range			9.0			18		mV
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 1\text{V}$	25k	200k					V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 1\text{V}$				25 k	200k		V/V
Output Resistance			5.0			1.0		k Ω
Output Short-Circuit Current			2.0			5.0		mA
Supply Current			13	20		100	130	μA
Power Consumption			78	120		600	720	μW
Transient Response (unity gain)	$V_{IN} = 20\text{mV}, R_L \geq 5\text{k}\Omega, C_L = 100\text{pF}$							
Risetime			3.0			0.6		μs
Overshoot			0			5		%
Slew Rate	$R_L \geq 5\text{k}\Omega$		0.03			0.35		V/ μs
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$								
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$			7.5			7.5	mV
Input Offset Current	$T_A = +70^\circ\text{C}$			6.0			25	nA
	$T_A = 0^\circ\text{C}$			10			40	nA
Input Bias Current	$T_A = +70^\circ\text{C}$			10			50	nA
	$T_A = 0^\circ\text{C}$			20			100	nA
Input Voltage Range		± 1.0			± 1.0			V
Common Mode Rejection Ratio	$R_S \leq 10\text{k}\Omega$	70	86		70	86		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{k}\Omega$		25	200		25	200	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 1\text{V}$	25k						V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 1\text{V}$				25k			V/V
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 2.0	± 2.4					V
	$R_L \geq 5\text{k}\Omega$				± 2.0	± 2.1		V
Supply Current				25			135	μA
Power Consumption				150			750	μW


± 15 VOLT OPERATION FOR 393 GRADEELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Unless Otherwise Specified)

PARAMETERS	CONDITIONS	$I_{SET} = 1.5\mu\text{A}$			$I_{SET} = 15\mu\text{A}$			UNITS
		MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$		2.0	6.0		2.0	6.0	mV
Input Offset Current			0.7	6.0		2.0	25	nA
Input Bias Current			2.0	10		15	50	nA
Input Resistance			50			5.0		M Ω
Input Capacitance			2.0			2.0		pF
Offset Voltage Adjustment Range			9.0			18		mV
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 10\text{V}$	50k	400k					V/V
	$R_L \geq 5\text{k}\Omega, V_{OUT} = \pm 10\text{V}$				50k	400k		V/V
Output Resistance			5.0			1.0		k Ω
Output Short-Circuit Current			2.0			10		mA
Supply Current			20	30		125	160	μA
Power Consumption				0.9			4.8	mW
Transient Response (unity gain)	$V_{IN} = 20\text{mV}, R_L \geq 5\text{k}\Omega, C_L \leq 100\text{pF}$							
Risetime			1.6			0.35		μs
Overshoot			0			10		%
Slew Rate	$R_L \geq 5\text{k}\Omega$		0.1			0.8		V/ μs
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 12	± 14					V
	$R_L \geq 5\text{k}\Omega$				± 10	± 13		V
The following specifications apply to $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$								
Input Offset Voltage	$R_S \leq 10\text{k}\Omega$			7.5			7.5	mV
Input Offset Current	$T_A = +70^\circ\text{C}$			6.0			25	nA
	$T_A = 0^\circ\text{C}$			10			40	nA
Input Bias Current	$T_A = +70^\circ\text{C}$			10			50	nA
	$T_A = 0^\circ\text{C}$			20			100	nA
Input Voltage Range		± 10			± 10			V
Common Mode Rejection Ratio	$R_S \leq 10\text{k}\Omega$	70	90		70	90		dB
Supply Voltage Rejection Ratio	$R_S \leq 10\text{k}\Omega$		25	200		25	200	$\mu\text{V/V}$
Large-Signal Voltage Gain	$R_L \geq 75\text{k}\Omega, V_{OUT} = \pm 10\text{V}$	50k			50k			V/V
Output Voltage Swing	$R_L \geq 75\text{k}\Omega$	± 10			± 10			V
Supply Current				35			170	μA
Power Consumption				1.05			5.10	mW


**INPUT BIAS CURRENT
AS A FUNCTION OF
SET CURRENT**




**INPUT BIAS CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**INPUT OFFSET CURRENT
AS A FUNCTION OF
AMBIENT TEMPERATURE**




**CHANGE IN INPUT OFFSET
VOLTAGE AS A FUNCTION
OF SET CURRENT**




**CHANGE IN INPUT OFFSET
VOLTAGE AS A FUNCTION
OF AMBIENT TEMPERATURE
(UNNULLED)**




**INPUT NOISE VOLTAGE
AS A FUNCTION OF
SET CURRENT**




**INPUT NOISE VOLTAGE AND
CURRENT AS A FUNCTION
OF FREQUENCY**




**INPUT NOISE CURRENT
AS A FUNCTION OF
SET CURRENT**




**OPTIMUM SOURCE RESISTOR
FOR MINIMUM NOISE AS A
FUNCTION OF SET CURRENT**




**OUTPUT VOLTAGE SWING
AS A FUNCTION OF
LOAD RESISTANCE**




**OUTPUT VOLTAGE SWING
AS A FUNCTION OF
SUPPLY VOLTAGE**




**GAIN-BANDWIDTH
PRODUCT AS A FUNCTION
OF SET CURRENT**




OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF AMBIENT TEMPERATURE




OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF SET CURRENT




COMMON MODE REJECTION RATIO AS A FUNCTION OF SET CURRENT




POWER SUPPLY REJECTION RATIO AS A FUNCTION OF SET CURRENT




SUPPLY CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




STANDBY SUPPLY CURRENT AS A FUNCTION OF SET CURRENT




THERMAL RESPONSE OF INPUT OFFSET VOLTAGE TO STEP CHANGE OF CASE TEMPERATURE




STABILIZATION TIME OF INPUT OFFSET VOLTAGE FROM POWER ON




INPUT OFFSET VOLTAGE DRIFT AS A FUNCTION OF TIME



SLEW RATE AS A FUNCTION OF SET CURRENT




VOLTAGE FOLLOWER TRANSIENT RESPONSE (UNITY GAIN)




BIASING CIRCUITS

RESISTOR BIASING




R_{SET} CONNECTED TO GROUND


TRANSISTOR CURRENT SOURCE BIASING




VOLTAGE OFFSET NULL CIRCUIT



FET CURRENT SOURCE BIASING




TRANSIENT RESPONSE TEST CIRCUIT



R_{SET} CONNECTED TO V^- *

* Recommended for supply voltages less than $\pm 6V$.

SET CURRENT AS A FUNCTION OF SET RESISTOR



QUIESCENT CURRENT SETTING RESISTOR (I_{SET} TO V^-)

V_S	I_{SET}	
	1.5 μA	15 μA
$\pm 1.5 V$	1.7M Ω	170k Ω
$\pm 3.0 V$	3.6M Ω	360k Ω
$\pm 6.0 V$	7.5M Ω	750k Ω
$\pm 15 V$	20M Ω	2.0M Ω

Note: The $\mu A776$ may be operated with R_{set} connected to ground or V^- .


I_{SET} EQUATIONS:

$$I_{SET} = \frac{V^+ - 0.7 - V^-}{R_{SET}}$$


where R_{SET} is connected to V^-

$$I_{SET} = \frac{V^+ - 0.7}{R_{SET}}$$


where R_{SET} is connected to ground.




MULTIPLEXING AND SIGNAL CONDITIONING WITHOUT FET'S



NANO-WATT AMPLIFIER



HIGH INPUT IMPEDANCE AMPLIFIER



μA777

PRECISION OPERATIONAL AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUIT


GENERAL DESCRIPTION — The μA777 is a precision operational amplifier constructed on a single silicon chip, using a low noise Fairchild Planar* epitaxial process. It is an excellent choice when performance versus cost trade-offs are possible between super beta or FET input operational amplifiers and low cost general purpose operational amplifiers. Low offset and bias currents improve system accuracy when used in applications such as long term integrators, sample and hold circuits and high source impedance summing amplifiers. Even though the input bias current is extremely low, the μA777 maintains full ± 30 V differential voltage range. The internal construction utilizes isothermal layout and special electrical design to maintain system performance despite variations in temperature or output load. High common mode input voltage range, latch-up protection, short circuit protection and simple frequency compensation make the device versatile and essentially foolproof.

- **LOW OFFSET VOLTAGE AND OFFSET CURRENT**
- **LOW OFFSET VOLTAGE AND CURRENT DRIFT**
- **LOW INPUT BIAS CURRENT**
- **LOW INPUT NOISE VOLTAGE**
- **LARGE COMMON-MODE AND DIFFERENTIAL VOLTAGE RANGES**

ABSOLUTE MAXIMUM RATINGS


Supply Voltage	±22 V
Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Silicone DIP	340 mW
Mini DIP	310 mW
Flatpak	570 mW
Differential Input Voltage	±30 V
Input Voltage (Note 2)	±15 V
Storage Temperature Range	
Metal Can, Ceramic DIP, and Flatpak	-65°C to +150°C
Mini DIP and Silicone DIP	-55°C to +125°C
Operating Temperature Range	
Military (312 Grade)	-55°C to +125°C
Commercial (393 Grade)	0°C to 70°C
Lead Temperature (Soldering, 60 Seconds)	300°C
Metal Can, Ceramic DIP and Flatpak	260°C
Mini DIP and Silicone DIP	Indefinite
Output Short Circuit Duration (Note 3)	

EQUIVALENT CIRCUIT



CONNECTION DIAGRAMS


8 LEAD METAL CAN (TOP VIEW)



NOTE: Pin 4 connected to case


ORDER PART NOS: U5B7777312
U5B7777393

14 LEAD DIP (TOP VIEW)




ORDER PART NOS: U6A7777312
U6A7777393
U9A7777393

MINI DIP (TOP VIEW)



ORDER PART NO: U9T7777393

10 LEAD FLAT PACK ‡ (TOP VIEW)



‡Available on special request

ORDER PART NO: U3F7777312

ELECTRICAL CHARACTERISTICS FOR μ A777 (312 GRADE) ($V_S = \pm 15$ V, $T_A = 25^\circ\text{C}$, $C_C = 30$ pF unless otherwise specified)

PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50 \text{ k}\Omega$		.5	2.0	mV
Input Offset Current			.25	3.0	nA
Input Bias Current			8.0	25	nA
Input Resistance		2.0	10.0		M Ω
Input Capacitance			3.0		pF
Offset Voltage Adjustment Range			± 25		mV
Large-Signal Voltage Gain	$R_L \geq 2 \text{ k}\Omega$, $V_{OUT} = \pm 10$ V	50,000	250,000		
Output Resistance			100		Ω
Output Short-Circuit Current			± 25		mA
Supply Current			1.9	2.8	mA
Power Consumption			60	85	mW
Transient Response	$V_{IN} = 20 \text{ mV}$, $C_C = 30 \text{ pF}$, (Voltage Follower, Gain of 1) $R_L = 2 \text{ k}\Omega$, $C_L \leq 100 \text{ pF}$				
Risetime			.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2 \text{ k}\Omega$		.5		V/ μs
(Voltage Follower, Gain of 1)					
Transient Response	$V_{IN} = 20 \text{ mV}$, $C_C = 3.5 \text{ pF}$, (Voltage Follower, Gain of 10) $R_L = 2 \text{ k}\Omega$, $C_L \leq 100 \text{ pF}$				
Risetime			.2		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2 \text{ k}\Omega$, $C_C = 3.5 \text{ pF}$		5.5		V/ μs
(Voltage Follower, Gain of 10)					
The following specifications apply for $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$:					
Input Offset Voltage	$R_S \leq 50 \text{ k}\Omega$		0.5	3.0	mV
Average Input Offset Voltage Drift	$R_S \leq 50 \text{ k}\Omega$		2.5	15	$\mu\text{V}/^\circ\text{C}$
Input Offset Current				10	nA
Average Input Offset Current Drift	$25^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ $-55^\circ\text{C} \leq T_A \leq 25^\circ\text{C}$		2.5 6.5	30 150	pA/ $^\circ\text{C}$ pA/ $^\circ\text{C}$
Input Bias Current				75	nA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 50 \text{ k}\Omega$	80	95		dB
Supply Voltage Rejection Ratio	$R_S \leq 50 \text{ k}\Omega$		13	100	$\mu\text{V}/\text{V}$
Large-Signal Voltage Gain	$R_L \geq 2 \text{ k}\Omega$, $V_{OUT} = \pm 10$ V	25,000			
Output Voltage Swing	$R_L \geq 10 \text{ k}\Omega$ $R_L \geq 2 \text{ k}\Omega$	± 12 ± 10	± 14 ± 13		V V
Supply Current	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$		1.5 2.0	2.5 3.3	mA mA
Power Consumption	$T_A = +125^\circ\text{C}$ $T_A = -55^\circ\text{C}$		40 60	75 100	mW mW

ELECTRICAL CHARACTERISTICS FOR μ A777 (393 GRADE) ($V_S = \pm 15$ V, $T_A = 25^\circ\text{C}$, $C_C = 30$ pF unless otherwise specified)


PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Offset Voltage	$R_S \leq 50 \text{ k}\Omega$		0.7	5.0	mV
Input Offset Current			0.7	20.0	nA
Input Bias Current			25	100	nA
Input Resistance		1.0	2.0		M Ω
Input Capacitance			3.0		pF
Offset Voltage Adjustment Range			± 25		mV
Large-Signal Voltage Gain	$R_L \geq 2 \text{ k}\Omega$, $V_{OUT} = \pm 10$ V	25,000	250,000		
Output Resistance			100		Ω
Output Short-Circuit Current			± 25		mA
Supply Current			1.9	2.8	mA
Power Consumption			60	85	mW
Transient Response	$V_{IN} = 20 \text{ mV}$, $C_C = 30 \text{ pF}$,				
(Voltage Follower, Gain of 1)	$R_L = 2 \text{ k}\Omega$, $C_L \leq 100 \text{ pF}$				
Risetime			.3		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2 \text{ k}\Omega$		.5		V/ μ
(Voltage Follower, Gain of 1)					
Transient Response	$V_{IN} = 20 \text{ mV}$, $C_C = 3.5 \text{ pF}$,				
(Voltage Follower, Gain of 10)	$R_L = 2 \text{ k}\Omega$, $C_L \leq 100 \text{ pF}$				
Risetime			.2		μs
Overshoot			5.0		%
Slew Rate	$R_L \geq 2 \text{ k}\Omega$		5.5		V/ μs
(Voltage Follower, Gain of 10)					
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$					
Input Offset Voltage	$R_S \leq 50 \text{ k}\Omega$		0.8	5.0	mV
Average Input Offset Voltage Drift	$R_S \leq 50 \text{ k}\Omega$		4	30	$\mu\text{V}/^\circ\text{C}$
Input Offset Current				40	nA
Average Input Offset Current Drift	$25^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$		.01	0.3	nA/ $^\circ\text{C}$
	$0^\circ\text{C} \leq T_A \leq 25^\circ\text{C}$		.02	0.6	nA/ $^\circ\text{C}$
Input Bias Current				200	nA
Input Voltage Range		± 12	± 13		V
Common Mode Rejection Ratio	$R_S \leq 50 \text{ k}\Omega$	70	95		dB
Supply Voltage Rejection Ratio	$R_S \leq 50 \text{ k}\Omega$		15	150	$\mu\text{V}/\text{V}$
Large-Signal Voltage Gain	$R_L \geq 2 \text{ k}\Omega$, $V_{OUT} = \pm 10$ V	15,000			
Output Voltage Swing	$R_L \geq 10 \text{ k}\Omega$	± 12	± 14		V
	$R_L \geq 2 \text{ k}\Omega$	± 10	± 13		V
Power Consumption			60	100	mW

NOTES


- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3 \text{ mW}/^\circ\text{C}$ for Metal Can, $8.3 \text{ mW}/^\circ\text{C}$ for the Ceramic DIP, $6.3 \text{ mW}/^\circ\text{C}$ for Silicone DIP, $5.6 \text{ mW}/^\circ\text{C}$ for the Mini DIP and $7.1 \text{ mW}/^\circ\text{C}$ for the Flatpak package.
- For supply voltages less than ± 15 V, the absolute maximum input voltage is equal to the supply voltage.
- Short circuit may be to ground or either supply. Rating applies to $+125^\circ\text{C}$ case temperature or $+75^\circ\text{C}$ ambient temperature.

TYPICAL PERFORMANCE CURVES


OPEN LOOP VOLTAGE GAIN AS A FUNCTION OF SUPPLY VOLTAGE




OUTPUT VOLTAGE SWING AS A FUNCTION OF SUPPLY VOLTAGE




INPUT COMMON MODE VOLTAGE RANGE AS A FUNCTION OF SUPPLY VOLTAGE




POWER CONSUMPTION AS A FUNCTION OF SUPPLY VOLTAGE




INPUT CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT RESISTANCE AS A FUNCTION OF AMBIENT TEMPERATURE




INPUT OFFSET CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




POWER CONSUMPTION AS A FUNCTION OF AMBIENT TEMPERATURE




OUTPUT VOLTAGE SWING AS A FUNCTION OF LOAD RESISTANCE




OUTPUT SHORT-CIRCUIT CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE















ABSOLUTE MAXIMUM POWER DISSIPATION AS A FUNCTION OF AMBIENT TEMPERATURE



INPUT NOISE VOLTAGE AND CURRENT AS A FUNCTION OF FREQUENCY




TYPICAL PERFORMANCE CURVES


OPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCYOPEN LOOP VOLTAGE GAIN
AS A FUNCTION OF
FREQUENCY FOR VARIOUS
GAIN/COMPENSATION OPTIONSINPUT RESISTANCE,
OUTPUT RESISTANCE,
AND INPUT CAPACITANCE
AS A FUNCTION OF FREQUENCYVOLTAGE FOLLOWER
TRANSIENT RESPONSE
(GAIN OF 1)OPEN LOOP PHASE
RESPONSE AS A
FUNCTION OF FREQUENCYFREQUENCY RESPONSE
FOR VARIOUS
CLOSED-LOOP GAINSCOMMON MODE REJECTION
RATIO AS A FUNCTION OF
FREQUENCYOUTPUT VOLTAGE SWING
AS A FUNCTION OF
FREQUENCYCOMPENSATION
CAPACITANCE AS A
FUNCTION OF CLOSED
LOOP VOLTAGE GAININPUT OFFSET VOLTAGE
DRIFT AS A FUNCTION
OF TIMETRANSIENT RESPONSE
TEST CIRCUITVOLTAGE FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE

TYPICAL PERFORMANCE CURVES

THERMAL RESPONSE OF INPUT OFFSET VOLTAGE TO STEP CHANGE OF CASE TEMPERATURE





STABILIZATION TIME OF INPUT OFFSET VOLTAGE FROM POWER TURN-ON




FEED-FORWARD COMPENSATION


LARGE SIGNAL FEEDFORWARD TRANSIENT RESPONSE



VOLTAGE OFFSET NULL CIRCUIT




SUGGESTED




ALTERNATE

GAIN TEST CIRCUIT




TYPICAL APPLICATIONS

BIAS COMPENSATED LONG TIME INTEGRATOR




* Adjust R_3 for minimum integrator drift


SAMPLE AND HOLD



CAPACITANCE MULTIPLIER




AMPLIFIER FOR CAPACITANCE TRANSDUCERS




Low Frequency Cutoff $R_1 \times C_1$

BILATERAL CURRENT SOURCE



$$I_{OUT} = \frac{R_3 V_{IN}}{R_1 R_5}; R_1 = R_2; R_3 = R_4 + R_5$$

HIGH SLEW RATE POWER AMPLIFIER




± 100 V COMMON MODE RANGE INSTRUMENTATION AMPLIFIER

$$\frac{R_1}{R_7} \equiv \frac{R_3}{R_4} \text{ for best CMRR}$$


$$R_3 = R_4$$

$$R_1 = R_6 = 10R_3$$

$$\text{Gain} = \frac{R_7}{R_6}$$



INSTRUMENTATION AMPLIFIER WITH HIGH COMMON MODE REJECTION



μ A780

PHASE LOCKED LOOP

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μ A780 is a Phase Locked Loop designed for use as a Color TV Subcarrier Regenerator and is constructed on a single silicon chip using the Fairchild Planar* epitaxial process. This integrated circuit, which uses an Automatic Phase Control (APC) loop, accepts the composite NTSC color video signal, extracts the color subcarrier reference and generates a CW signal suitable for use as a chroma demodulation reference. Other features include control of the CW phase (tint) by a DC voltage, blanking of the CW output during burst time and synchronous generation of an Automatic Color Control (ACC) voltage.

The μ A780 in combination with the μ A781 Chroma IF Amplifier and the μ A746 Chroma Demodulator form a complete low cost, high quality chroma processing system for color TV receivers.

The μ A780 is also useful as a communications phase locked loop system to select, amplify and demodulate AM, FM, FSK and SSB signals.

- COMPLETE COLOR TV SUBCARRIER REGENERATOR
- AUTOMATIC PHASE CONTROL LOOP
- DC TINT CONTROL
- SYNCHRONOUS ACC/KILLER DETECTOR
- COLOR BURST GATING AND BLANKING
- INTERNALLY REGULATED SUPPLY

ABSOLUTE MAXIMUM RATINGS

Supply Current 40 mA

Current into Gate Input Terminal

Peak-to-Peak Voltage at either APC or ACC Detector

Input Terminals 5 V

Internal Power Dissipation

Ceramic DIP 720 mA



Storage Temperature Range

Ceramic DIP 65°C to +150°C


Operating Temperature Range

Lead Temperature 0 C to + 70 C


Ceramic DIP (Soldering, 60 seconds) 300°C



**CONNECTION DIAGRAM
(TOP VIEW)**



**PHYSICAL DIMENSIONS
6B—PACKAGE CERAMIC DIP**



ORDER PART NO. U6B7780394

NOTES:

All dimensions in inches

Leads are intended for insertion in

hole rows on .300" centers

They are purposely shipped with "positive" results.

positive misalignment to facilitate insertion

Board-drilling dimensions should

equal your practice for .020 inch diameter lead

Leads are tin-plated kovar

Package weight is 2.0 grams

STATIC ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Gate "ON," Test Circuit 1 unless otherwise specified)










PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current			26		mA
Voltage at Supply Terminal		11.3	12.0	12.6	V
Supply Regulation	$V^+ = 21\text{ V to } V^+ = 27\text{ V}$		40		mV
Total Current into Oscillator Output Terminals	Gate "OFF," 50 k Ω resistor connected between Pin 10 and Pin 6, Pin 2 shorted to Pin 3	4.2	5.8	7.6	mA
Current into either APC Detector Output Terminal	12 k Ω resistor connected between Pin 6 and Ground		12	40	μA
Offset Voltage between ACC Detector Output Terminals ($V_{15} - V_{16}$)	50 k Ω resistor connected between Pin 10 and Pin 6	-330	-70	+300	mV
Offset Voltage between APC Detector Output Terminals ($V_{11} - V_{12}$)	50 k Ω resistor connected between Pin 10 and Pin 6	-315	-50	+315	mV
Offset Voltage between Oscillator Control Terminals ($V_7 - V_8$)	12 k Ω resistor connected between Pin 6 and Ground, $V_{11} = V_{12} = 9.5\text{ V}$	-330	-20	+330	mV
Offset Voltage between Oscillator Output Terminals ($V_2 - V_3$)	Gate "OFF"	-200	+300	+800	mV
Voltage at Oscillator Feedback Terminal			2.8		V
Voltage at ACC Detector Input Terminal		6.0	6.5	7.0	V
Voltage at APC Detector Input Terminal		6.0	6.5	7.0	V
Voltage at Tint Control Terminal			200	300	mV
Voltage at Tint Control Terminal	Gate "OFF"	7.3	7.6	8.2	V
Internal Power Dissipation			310	400	mV

DYNAMIC ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, peak-to-peak burst level at APC Detector Input Terminal = 200 mV. Standard NTSC Signal, $f_0 = 3.579545\text{ MHz}$, Test Circuit 2 unless otherwise specified.)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Oscillator Pull-in Range	$f_{\text{free run}} > f_0$		+510		Hz
	$f_{\text{free run}} < f_0$		-750		Hz
Oscillator Static Phase Error	$f_{\text{free run}} = f_0 + 120\text{ Hz}$		+2.2		Degree
	$f_{\text{free run}} = f_0 - 120\text{ Hz}$		-2.2		Degree
Oscillator Control Sensitivity			12		Hz/mV
Input Resistance at Oscillator Feedback Terminal			2.2		k Ω
Input Capacitance at Oscillator Feedback Terminal			4.5		pF
Peak-to-Peak Current at Oscillator Output Terminal (Pin 3)	Tint Control Wiper at Ground		6.8		mA
ACC Detector Input Resistance			2.2		k Ω
ACC Detector Input Capacitance			4.5		pF
ACC Detector Sensitivity	100 mV p-p burst level at ACC Detector Input Terminal, Oscillator Locked		+2.2		mVDC/mV p-p
APC Detector Input Resistance			2.2		k Ω
APC Detector Input Capacitance			4.5		pF
APC Detector Sensitivity			5		mV/Degree

TYPICAL PERFORMANCE CURVES


(Test Circuit 2 unless otherwise specified)

SUPPLY VOLTAGE AS A
FUNCTION OF SUPPLY
CURRENTSTATIC PHASE ERROR
AS A FUNCTION OF
FREQUENCY OFFSETSTATIC PHASE ERROR
AS A FUNCTION OF
BURST INPUT LEVELSTATIC PHASE ERROR
AS A FUNCTION OF
TEMPERATUREFREQUENCY PULL-IN
RANGE AS A FUNCTION OF
BURST INPUT LEVELDIFFERENTIAL DC
VOLTAGE AT ACC
DETECTOR OUTPUT AS A
FUNCTION OF BURST
INPUT LEVELDIFFERENTIAL DC
VOLTAGE AT APC
DETECTOR OUTPUT
TERMINALS AS A
FUNCTION OF OSCILLATOR
FREQUENCY OFFSETAPC DETECTOR OUTPUT
AS A FUNCTION OF
RELATIVE PHASE
DIFFERENCEOSCILLATOR OUTPUT AS A
FUNCTION OF TINT
CONTROL CURRENT


TEST CIRCUIT 1



TEST CIRCUIT 2




EQUIVALENT CIRCUIT





INTEGRATED CIRCUIT COLOR TV CHROMA PROCESSING SYSTEM

(BLOCK DIAGRAM)



μA781

GAIN CONTROLLED IF AMPLIFIER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μA781 is a dual gain controlled IF amplifier designed for use as a Color TV Chroma IF Amplifier and constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The first section is a gain controlled chroma signal amplifier whose output is used to drive a subcarrier regenerator circuit. The gain of the second section is controlled by means of an external DC voltage to set chroma level. In addition, the second stage may be gated off to provide "color killing" action in the absence of a color signal with the trip point of the gate adjusted externally.

The μA781 in combination with the μA780 Phase Locked Loop Subcarrier Regenerator and the μA746 Chroma Demodulator forms a complete low cost, high quality chroma processing system for color TV receivers.


The μA781 is also useful as a gain-controlled, intermediate-frequency amplifier in AM and FM communication circuits.

- COMPLETE COLOR TV CHROMA IF AMP
- 10 MHz BANDWIDTH
- AUTOMATIC COLOR CONTROL (ACC) AMPLIFIER
- DC CHROMA LEVEL CONTROL
- ADJUSTABLE COLOR KILLER
- OUTPUT SHORT CIRCUIT PROTECTION


ABSOLUTE MAXIMUM RATINGS

Supply Voltage	30 V
Internal Power Dissipation	
Ceramic DIP	670 mW
Storage Temperature Range	
Ceramic DIP	-65°C to +150°C
Operating Temperature Range	0°C to + 70°C
Lead Temperature	
Ceramic DIP (Soldering, 60 seconds)	300°C
Output Short Circuit Duration	30 seconds


BLOCK DIAGRAM



CONNECTION DIAGRAM



PHYSICAL DIMENSIONS 6A PACKAGE - CERAMIC DIP



ORDER PART NO. U6A7781394

NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead

Leads are tin-plated kovar

Package weight is 2.0 grams

*Planar is a patented Fairchild process.


ELECTRICAL CHARACTERISTICS (NOTE 1)

PARAMETER	CONDITION	MIN.	TYP.	MAX.	UNITS
Supply Current	$R_{L6} = R_{L9} = 1 \text{ M}\Omega$	8	13	18	mA
Supply Current		17	24	31	mA
Internal Power Dissipation			400	550	mW
Short Circuit Load Current, Chroma Output 1	$R_{L6} = 0 \Omega$	20	42		mA
Short Circuit Load Current, Chroma Output 2	$R_{L9} = 0 \Omega$	20	36		mA
DC Voltage at Chroma Output 1 Terminal		15.5	17.5	20.0	V
DC Voltage at Chroma Output 2 Terminal		17.5	18.0	18.5	V
Gain, ACC Amplifier Stage		14	17	19	dB
Gain Reduction ACC Amplifier Stage	$V_{ACC} = V_1 - V_{14} = 0 \text{ mV to } V_1 - V_{14} = -75 \text{ mV}$	12	14	16	dB
Maximum Gain, Chroma Level Amplifier Stage		12	15.8	17	dB
DC Voltage at Chroma Level Control Terminal for 90% Maximum Output Level, Chroma Level Amplifier Stage	Chroma Level Control set for 90% Maximum Output	2.3	3.5	4.8	V
DC Voltage at Chroma Level Control Terminal for 10% Maximum Output Level, Chroma Level Amplifier Stage	Chroma Level Control Wiper set for 10% of Maximum Output	17	19.5	21.7	V
Killer "ON" Threshold			16.6	17.0	V
Killer "OFF" Threshold		16.0	16.3		V
DC Voltage at Decouple Terminal, Pin 11		15	15.5	16	V
DC Voltage at Decouple Terminal, Pin 12		14.5	15.3	16	V
DC Voltage at Gain Preselect Terminal		0.7	1.0	1.2	V
DC Voltage at Chroma Input 1 Terminal			1.7		V
DC Voltage at Chroma Input 2 Terminal			1.4		V
Gain Change with V^+ , Chroma Level Amplifier Stage	$V^+ = 24 \text{ V to } V^+ = 21 \text{ V}$	-1.9	-0.4	1.6	dB
	$V^+ = 24 \text{ V to } V^+ = 27 \text{ V}$	-1.9	0.8	1.6	dB
	Adjust Input Level at Chroma Input 2 for Output Level = 1.0 V RMS at Maximum Gain. Set Chroma Level Control Wiper for Output Level = 100 mV RMS				
Gain Change with Temperature, Chroma Level Amplifier Stage	$T_A = 25^\circ\text{C to } T_A = 70^\circ\text{C}$		0.7		dB
	Adjust Input Level at Chroma Input 2 for Output Level = 1.0 V RMS at Maximum Gain. Set Chroma Level Control Wiper for Output Level = 100 mV RMS				
Chroma Input 1 Resistance			2.4		k Ω
Chroma Input 1 Capacitance			6.2		pF
Chroma Input 2 Resistance			2.4		k Ω
Chroma Input 2 Capacitance			4.2		pF


NOTE (1)

$T_A = 25^\circ\text{C}$, $V^+ = 24 \text{ V}$, $R_{L6} = 3.3 \text{ k}\Omega$, $R_{L9} = 2.7 \text{ k}\Omega$, Chroma Level Control Wiper at Ground, Voltage at ACC Input Terminals = 10 V, zero Differential Voltage between ACC Input Terminals, $f = 3.58 \text{ MHz}$, Peak-to-peak Input at Chroma Input 1 = 200 mV, Peak-to-peak Input at Chroma Input 2 = 400 mV, unless otherwise specified. Refer to Test Circuit 1.


SUPPLY CURRENT AS A FUNCTION OF SUPPLY VOLTAGE




ACC AMPLIFIER GAIN AS A FUNCTION OF DIFFERENTIAL DC VOLTAGE AT ACC INPUT TERMINALS




CHROMA LEVEL AMPLIFIER GAIN AS A FUNCTION OF DC VOLTAGE AT CHROMA LEVEL CONTROL TERMINAL




TEST CIRCUIT



EQUIVALENT CIRCUIT




INTEGRATED CIRCUIT COLOR TV CHROMA PROCESSING SYSTEM



INTEGRATED CIRCUIT COLOR TV CHROMA PROCESSING SYSTEM

(BLOCK DIAGRAM)



μA795

FOUR QUADRANT MULTIPLIER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA795 is a four Quadrant Analog Multiplier constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The μA795 provides excellent linearity and operates over a wide supply range and input voltage range. The differential output current is the product of two input analog voltages multiplied by a pre-determined scale factor. The μA795 is ideally suited for applications as a multiplier, squarer, divider, phase detector, frequency doubler or balanced modulator.

- EXCELLENT LINEARITY
- HIGH INPUT VOLTAGE RANGE
- WIDE SUPPLY VOLTAGE OPERATION
- WIDE BANDWIDTH
- EXCELLENT PHASE MATCHING
- ADJUSTABLE GAIN FACTOR
- EXCELLENT TEMPERATURE STABILITY


ABSOLUTE MAXIMUM RATINGS

Applied Voltage (Note 1)
Differential Input Signal

Maximum Bias Current
Power Dissipation (Note 2)
Storage Temperature Range
Operating Temperature Range
Lead Temperature (soldering, 60 seconds)

30 V
 $V_9 - V_{12} = \pm(6 + I_{13} R_x)$
 $V_4 - V_8 = \pm(6 + I_3 R_y)$
 10 mA
 670 mW
 -65°C to $+150^\circ\text{C}$
 0°C to $+70^\circ\text{C}$
 300°C


EQUIVALENT CIRCUIT



Notes on following page.

PHYSICAL DIMENSIONS

In accordance with JEDEC (TO-116) outline




NOTES

All dimensions in inches
 Leads are intended for insertion in hole rows on .300" centers
 They are purposely shipped with "positive" misalignment to facilitate insertion
 Board-drilling dimensions should equal your practice for .020 inch diameter lead
 Leads are tin-plated kovar
 Package weight is 2.0 grams

ORDER PART NO. U6A7795393

CONNECTION DIAGRAM







*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS (Note 3; $T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Linearity Error in % Of Full Scale	$-10 < V_X < +10$ $V_Y = +10\text{ V}$		1.0	2.0	%
	$-10 < V_X < +10$ $V_Y = -10\text{ V}$		2.0		%
	$-10 < V_Y < +10$ $V_X = +10\text{ V}$		2.0	4.0	%
	$-10 < V_Y < +10$ $V_X = -10\text{ V}$		2.0	4.0	%
Squaring Mode Error			0.75		%
Scale Factor Adjustable $K = \frac{2 R_L}{I_3 R_X R_Y}$			0.1		—
Input Resistance	$f = 20\text{ Hz}$		20		$\text{M}\Omega$
Differential Output Resistance	$f = 20\text{ Hz}$		300		$\text{k}\Omega$
Input Bias Current			2.0	12	μA
Input Offset Current			0.4	2.0	μA
Frequency Response	—3 dB Bandwidth		3.0		MHz
	3° Relative Phase Shift		750		kHz
	1% Absolute Error Due to Input-Output Phase Shift		30		kHz
Input Voltage Range		± 10.5	± 12		V
Common Mode Gain		—40	—50		dB
Output Common Mode Voltage			21		V
Differential Output Voltage Swing			± 14		V
Positive Supply Voltage Rejection Ratio			5.0		mV/V
Negative Supply Voltage Rejection Ratio			10		mV/V
Negative Supply Current			6.0	7.0	mA
Power Consumption			135	170	mW
The following specifications apply for $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$:					
Linearity Error in % Of Full Scale	$-10 < V_X < +10$ $V_Y = +10\text{ V}$		1.5		%
	$-10 < V_X < +10$ $V_Y = -10\text{ V}$		3.0		%
	$-10 < V_Y < +10$ $V_X = +10\text{ V}$		3.0		%
	$-10 < V_Y < +10$ $V_X = -10\text{ V}$		3.0		%
Squaring Mode Error			1.0		%
Average Temperature Coefficient Of Input Offset Current			2.0		$\text{nA}/^\circ\text{C}$

NOTES:


- (1) Voltage applied between pins 2-1, 14-1, 1-9, 1-12, 1-4, 1-8, 12-7, 9-7, 8-7, 4-7.
 (2) Applies for ambient temperature to 70°C .
 (3) Connected as shown in Figure 1, set up 1, with resistor values as shown.

TYPICAL ELECTRICAL CHARACTERISTICS

TYPICAL ELECTRICAL CHARACTERISTICS

MAXIMUM ALLOWABLE INPUT
VOLTAGE VERSUS OUTPUT
VOLTAGE (PIN 1 OR PIN 7)

OFFSET ADJUSTMENT




for $V^+ = 15\text{ V}$, $R = 10\text{ k}\Omega$
 $V^+ = 32\text{ V}$, $R = 22\text{ k}\Omega$

For best output accuracy, use above network; see RECOMMENDED ZERO ADJUST AND SCALE SETTING PROCEDURE on back page.

TYPICAL APPLICATIONS

MULTIPLY WITH OP-AMP LEVEL SHIFT



SET UP	RESISTOR*	R_1	R_5	R_6	R_7	R_8	R_9	R_{13}	R_A	R_B	R_L	R_X	R_Y
	TOLERANCE	5%	1%	1%	1%	1%	1%	1%	5%	20%	0.5%	5%	5%
1	$V^+ = +32\text{ V}$, $V^- = -15\text{ V}$ $-10\text{ V} \leq V_X \leq +10\text{ V}$ $-10\text{ V} \leq V_Y \leq +10\text{ V}$	9.1	121	100	11	121	15	13.7	12	5.0	11	15	15
2	$V^+ = +15\text{ V}$, $V^- = -15\text{ V}$ $-5\text{ V} \leq V_X \leq +5\text{ V}$ $-5\text{ V} \leq V_Y \leq +5\text{ V}$	3.0	300	100	100	300	∞	13.7	12	5.0	3.4	8.2	8.2
3	$V^+ = +15\text{ V}$, $V^- = -15\text{ V}$ $-10\text{ V} \leq V_X \leq +10\text{ V}$ $-10\text{ V} \leq V_Y \leq +10\text{ V}$	1.2	121	100	11	910	13.7	13.7	12	5.0	1.5	15	15

*All resistors are k ohms

Figure 1

TYPICAL APPLICATIONS

DIVIDE AND SQUARE ROOT




Figure 2

FREQUENCY DOUBLER




Figure 3

RECOMMENDED ZERO ADJUST AND SCALE SETTING PROCEDURE

With $V_X = V_Y = 0$ volts adjust the output offset adjustment until the output of the external amplifier reads zero volts. Set $V_X = 5.000$ volts, $V_Y = 0.000$ volt and adjust the Y-input offset control until the output amplifier reads zero volts. Repeat this procedure for $V_X = 0.000$ volt, $V_Y = 5.000$ volts and adjust the X-input offset control until the output amplifier reads zero volts. This procedure should be repeated until complete null is achieved.

Next, set $V_X = V_Y = 5.000$ volts and adjust the K factor potentiometer until the output reads the desired output.

$V_{out} = 2.500V = K V_X V_Y$ for a K factor of .100.

When a high degree of accuracy is unnecessary for small output signals, the above procedure may be simplified by eliminating the output offset adjustment.

SUGGESTIONS AND GENERAL PRECAUTIONS

The high frequency performance of the $\mu A795$ is primarily determined by two conditions. One, by the load resistors and the associated stray output capacitance of the multiplier and two, the operational amplifier used at the output. For maximum frequency of operation, low value load resistors and a $\mu A715$ wideband high slew rate operational amplifier should be used.

Phase shift at higher frequencies due to load resistors and output stray capacitances and relative phase shift between X and Y channels should be considered for maximum accuracy. As an example if the input to output phase shift is only 0.6° , the output product of two sine waves will exhibit a vector error of 1%. A 3° relative phase shift between the input signals will result in a vector error of 5%.

The normal circuit precautions should be taken to avoid parasitic oscillation. Leads should be as short as possible and the power supplies should be decoupled with a $0.1 \mu F$ high frequency capacitor. An RC parasitic suppression network of 510Ω in series with a $10 pF$ from each input to ground can be used to reduce the Q_2 of a source-tuned circuit, which may cause the oscillation. As an alternate solution, a 510Ω resistor network can be placed in series with each input of the $\mu A795$.

μA796

DOUBLE-BALANCED MODULATOR/DEMODULATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA796 is a monolithic Double-Balanced Modulator/Demodulator constructed on a single silicon chip using the Fairchild Planar* epitaxial process. This circuit produces an output voltage which is the product of an input voltage (signal) and a switching function (carrier). Communications applications include modulation and demodulation of AM, SSB, DSB, FSK, FM and phase encoded signals. Signal conditioning techniques possible include frequency doubling and halving, linear mixing and chopping, with additional uses as phase detectors in phase locked loops and as differentiators in NRZ and phase encoded digital tape and disk memories.

- EXCELLENT CARRIER SUPPRESSION
- LOW OFFSETS AND DRIFT
- FULLY BALANCED INPUTS AND OUTPUT
- USEFUL TO 100 MHz
- WIDE RANGE OF APPLICATION

ABSOLUTE MAXIMUM RATINGS

Internal Power Dissipation (Note 1)	
Metal Can	500 mW
Ceramic DIP	670 mW
Applied Voltage (Note 2)	
	30 V
Differential Input Signal ($V_7 - V_8$)	± 5.0 V
Differential Input Signal ($V_4 - V_1$)	$\pm (5 + I_5 R_E)$ V
Input Signal ($V_2 - V_1, V_3 - V_4$)	5.0 V
Bias Current (I_5)	12 mA
Storage Temperature Range	
Metal Can, Ceramic DIP	-65°C to $+150^\circ\text{C}$
Operating Temperature Range	
Military (312 Grade)	-55°C to $+125^\circ\text{C}$
Commercial (393 Grade)	0°C to $+70^\circ\text{C}$
Lead Temperature	
Metal Can, Ceramic DIP (Soldering, 60 seconds)	300°C


EQUIVALENT CIRCUIT



Pin numbers, see Note 3.

CONNECTION DIAGRAMS


10 LEAD METAL CAN (TOP VIEW)



Pin 10 electrically connected to case through substrate.

ORDER PART NOS: U5E7796312
U5E7796393

14 LEAD DIP (TOP VIEW)



ORDER PART NOS:
For Ceramic DIP
U6A7796312
U6A7796393

312 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Figure 1 unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Carrier Feedthrough	$V_C = 60\text{ mV (rms) sine wave}$		40		$\mu\text{V (rms)}$
	$f_C = 1.0\text{ kHz, offset adjusted}$				
	$V_C = 60\text{ mV (rms) sine wave}$		140		$\mu\text{V (rms)}$
	$f_C = 10\text{ MHz, offset adjusted}$				
	$V_C = 300\text{ mV}_{pp}\text{ square wave}$		0.04	0.2	mV (rms)
	$f_C = 1.0\text{ kHz, offset adjusted}$				
Carrier Suppression	$V_C = 300\text{ mV}_{pp}\text{ square wave}$		20	100	mV (rms)
	$f_C = 1.0\text{ kHz, offset not adjusted}$				
	$f_S = 10\text{ kHz, } 300\text{ mV (rms)}$	50	65		dB
	$f_C = 500\text{ kHz, } 60\text{ mV (rms) sine wave}$ offset adjusted				
Transadmittance Bandwidth	$f_S = 10\text{ kHz, } 300\text{ mV (rms)}$		50		dB
	$f_C = 10\text{ MHz, } 60\text{ mV (rms) sine wave}$ offset adjusted				
	$R_L = 50\Omega$		300		MHz
	Carrier Input Port, $V_C = 60\text{ mV (rms) sine wave}$ $f_S = 1.0\text{ kHz, } 300\text{ mV (rms) sine wave}$				
Voltage Gain, Signal Channel	Signal Input Port, $V_S = 300\text{ mV (rms) sine wave}$		80		MHz
	$V_7 - V_8 = 0.5\text{ V dc}$				
	$V_S = 100\text{ mV (rms), } f = 1.0\text{ kHz}$	2.5	3.5		V/V
Input Resistance, Signal Port	$V_7 - V_8 = 0.5\text{ V dc}$				
	$f = 5.0\text{ MHz}$		200		$\text{k}\Omega$
Input Capacitance, Signal Port	$V_7 - V_8 = 0.5\text{ V dc}$				
	$f = 5.0\text{ MHz}$		2.0		pF
Single Ended Output Resistance	$f = 10\text{ MHz}$		40		$\text{k}\Omega$
Single Ended Output Capacitance	$f = 10\text{ MHz}$		5.0		pF
Input Bias Current	$(I_1 + I_4)/2$		12	25	μA
Input Bias Current	$(I_7 + I_8)/2$		12	25	μA
Input Offset Current	$(I_1 - I_4)$		0.7	5.0	μA
Input Offset Current	$(I_7 - I_8)$		0.7	5.0	μA
Average Temperature Coefficient of Input Offset Current	$(-55^\circ\text{C} < T_A < +125^\circ\text{C})$		2.0		$\text{nA}/^\circ\text{C}$
Output Offset Current	$(I_6 - I_9)$		14	50	μA
Average Temperature Coefficient of Output Offset Current	$(-55^\circ\text{C} < T_A < +125^\circ\text{C})$		90		$\text{nA}/^\circ\text{C}$
Signal Port Common Mode Input Voltage Range	$f_S = 1.0\text{ kHz}$		5.0		V_{p-p}
Signal Port Common Mode Rejection Ratio	$V_7 - V_8 = 0.5\text{ V dc}$		-85		dB
Common Mode Quiescent Output Voltage			8.0		V_{dc}
Differential Output Swing Capability			8.0		V_{p-p}
Positive Supply Current	$(I_6 + I_9)$		2.0	3.0	mA
Negative Supply Current	(I_{10})		3.0	4.0	mA
Power Dissipation			33		mW

NOTES







- Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for Metal Can and $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP package.
- Voltage applied between pins 6-7, 8-1, 9-7, 9-8, 7-4, 7-1, 8-4, 6-8, 2-5, 3-5.
- Pin numbers are for TO-100 package in all specification tables. Parenthesis in Equivalent Circuit denotes DIP package.

393 GRADE

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, Figure 1 unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Carrier Feedthrough	$V_C = 60\text{ mV (rms) sine wave}$		40		$\mu\text{V (rms)}$
	$f_C = 1.0\text{ kHz, offset adjusted}$				
	$V_C = 60\text{ mV (rms) sine wave}$		140		$\mu\text{V (rms)}$
	$f_C = 10\text{ MHz, offset adjusted}$				
	$V_C = 300\text{ mV}_{pp}\text{ square wave}$		0.04	0.2	mV (rms)
	$f_C = 1.0\text{ kHz, offset adjusted}$				
Carrier Suppression	$V_C = 300\text{ mV}_{pp}\text{ square wave}$		20	150	mV (rms)
	$f_C = 1.0\text{ kHz, offset not adjusted}$				
	$f_S = 10\text{ kHz, } 300\text{ mV (rms)}$	50	65		dB
	$f_C = 500\text{ kHz, } 60\text{ mV (rms) sine wave}$				
	offset adjusted				
	$f_S = 10\text{ kHz, } 300\text{ mV (rms)}$		50		dB
Transadmittance Bandwidth	$f_C = 10\text{ MHz, } 60\text{ mV (rms) sine wave}$				
	offset adjusted				
	$R_L = 50\Omega$		300		MHz
	Carrier Input Port, $V_C = 60\text{ mV (rms) sine wave}$				
	$f_S = 1.0\text{ kHz, } 300\text{ mV (rms) sine wave}$				
	Signal Input Port, $V_S = 300\text{ mV (rms) sine wave}$		80		MHz
Voltage Gain, Signal Channel	$V_7 - V_8 = 0.5\text{ V dc}$				
	$V_S = 100\text{ mV (rms), } f = 1.0\text{ kHz}$	2.5	3.5		V/V
Input Resistance, Signal Port	$V_7 - V_8 = 0.5\text{ V dc}$				
	$f = 5.0\text{ MHz}$		200		$\text{k}\Omega$
Input Capacitance, Signal Port	$V_7 - V_8 = 0.5\text{ V dc}$				
	$f = 5.0\text{ MHz}$		2.0		pF
Single Ended Output Resistance	$V_7 - V_8 = 0.5\text{ V dc}$		40		$\text{k}\Omega$
Single Ended Output Capacitance	$f = 10\text{ MHz}$		5.0		pF
Input Bias Current	$f = 10\text{ MHz}$		12	30	μA
Input Bias Current	$(I_1 + I_4)/2$		12	30	μA
Input Offset Current	$(I_7 + I_8)/2$		0.7	5.0	μA
Input Offset Current	$(I_1 - I_4)$		0.7	5.0	μA
Average Temperature Coefficient of Input Offset Current	$(I_7 - I_8)$		2.0		$\text{nA}/^\circ\text{C}$
Output Offset Current	$0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$		14	60	μA
Average Temperature Coefficient of Output Offset Current	$(I_6 - I_9)$		90		$\text{nA}/^\circ\text{C}$
Signal Port Common Mode Input Voltage Range	$0^\circ\text{C} < T_A < +70^\circ\text{C}$		5.0		V_{p-p}
Signal Port Common Mode Rejection Ratio	$f_S = 1.0\text{ kHz}$		-85		dB
Common Mode Quiescent Output Voltage	$V_7 - V_8 = 0.5\text{ V dc}$		8.0		Vdc
Differential Output Swing Capability			8.0		V_{p-p}
Positive Supply Current			2.0	3.0	mA
Negative Supply Current	$(I_6 + I_9)$		3.0	4.0	mA
Power Dissipation	(I_{10})		33		mW

TYPICAL PERFORMANCE CURVES

CARRIER SUPPRESSION
VERSUS CARRIER
INPUT LEVELCARRIER SUPPRESSION
VERSUS FREQUENCYCARRIER FEEDTHROUGH
VERSUS FREQUENCYSIGNAL-PORT FREQUENCY
RESPONSESIDE BAND OUTPUT
VERSUS CARRIER LEVELSSIDE BAND AND SIGNAL
PORT TRANSMITTANCES
VERSUS FREQUENCY

TYPICAL APPLICATIONS


TYPICAL MODULATOR CIRCUIT



Note: S_1 is closed for "adjusted" measurements.

Fig. 1


PRODUCT DETECTOR



This figure shows the $\mu A796$ used as a single sideband (SSB) suppressed carrier demodulator (product detector). The carrier signal is applied to the carrier input port with sufficient amplitude for switching operation. A carrier input level of 300 mV(rms) is optimum. The composite SSB signal is applied to the signal input port with an amplitude of 5.0 to 500 mV(rms). All output signal components except the desired demodulated audio are filtered out, so that an offset adjustment is not required. This circuit may also be used as an AM detector by applying composite and carrier signals in the same manner as described for product detector operation.

Fig. 2

FREQUENCY DOUBLER



The frequency doubler circuit shown will double low-level signals with low distortion. The value of C should be chosen for low reactance at the operating frequency.

Signal level at the carrier input must be less than 25 mV peak to maintain operation in the linear region of the switching differential amplifier. Levels to 50 mV peak may be used with some distortion of the output waveform. If a larger input signal is available a resistive divider may be used at the carrier input, with full signal applied to the signal input.

Fig. 3

μA7800 SERIES

THREE - TERMINAL POSITIVE VOLTAGE REGULATORS

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The μA7800 series of Three-Terminal Positive Voltage Regulators are constructed using the Fairchild Planar* epitaxial process. These regulators employ internal current limiting, thermal shutdown and safe-area compensation making them essentially blow-out proof. If adequate heat sinking is provided, they can deliver over 1A output current. They are intended as fixed-voltage regulators in a wide range of applications including local, on-card regulation for elimination of noise and distribution problems associated with single point regulation. In addition to use as fixed voltage regulators, these devices can be used with external components to obtain adjustable output voltages and currents and as the power pass element in precision regulators.

- OUTPUT CURRENT IN EXCESS OF 1 AMP
- NO EXTERNAL COMPONENTS
- INTERNAL THERMAL OVERLOAD PROTECTION
- INTERNAL SHORT CIRCUIT CURRENT LIMITING
- OUTPUT TRANSISTOR SAFE-AREA COMPENSATION
- AVAILABLE IN THE PLASTIC TO-220 AND THE METAL TO-3 PACKAGE

ABSOLUTE MAXIMUM RATINGS

Input Voltage (5 V through 18 V)	35 V
(24 V)	40 V
Internal Power Dissipation (Note 1)	Internally Limited
Storage Temperature Range	-65°C to +150°C
Operating Junction Temperature Range	0°C to +125°C
Lead Temperature (Soldering, 60 second time limit) TO-3 Package	300°C
(Soldering, 10 second time limit) TO-220 Package	230°C

EQUIVALENT CIRCUIT




Note on following page.

VOLTAGE RANGE


μA7805	5 V
μA7806	6 V
μA7808	8 V
μA7812	12 V
μA7815	15 V
μA7818	18 V
μA7824	24 V

CONNECTION DIAGRAMS TO-220 PLASTIC POWER PACKAGE (TOP VIEW)



ORDER PART NOS: UGH7805393
UGH7806393
UGH7808393
UGH7812393
UGH7815393
UGH7818393
UGH7824393

TO-3 PACKAGE (TOP VIEW)



ORDER PART NOS: UGJ7805393
UGJ7806393
UGJ7808393
UGJ7812393
UGJ7815393
UGJ7818393
UGJ7824393

*Planar is a patented Fairchild process.

μ A7805**ELECTRICAL CHARACTERISTICS** ($V_{IN} = 10\text{ V}$, $I_{OUT} = 500\text{ mA}$, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	4.8	5.0	5.2	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100\text{ mA}$				
	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$		7.0	50	mV
	$8\text{ V} \leq V_{IN} \leq 12\text{ V}$		2.0	25	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500\text{ mA}$				
Load Regulation	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$		35	100	mV
	$8\text{ V} \leq V_{IN} \leq 12\text{ V}$		8.0	50	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		11	100	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		4.0	50	mV
Output Voltage	$7\text{ V} \leq V_{IN} \leq 20\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$	4.75		5.25	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.3	8.0	mA
Quiescent Current Change	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$			1.3	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		40		μV
Long Term Stability				20	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		70		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance			30		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		750		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		-1.3		$\text{mV}/^\circ\text{C}$

 μ A7806**ELECTRICAL CHARACTERISTICS** ($V_{IN} = 11\text{ V}$, $I_{OUT} = 500\text{ mA}$, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	5.75	6.0	6.25	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100\text{ mA}$				
	$8\text{ V} \leq V_{IN} \leq 25\text{ V}$		9.0	60	mV
	$9\text{ V} \leq V_{IN} \leq 13\text{ V}$		3.0	30	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500\text{ mA}$				
Load Regulation	$8\text{ V} \leq V_{IN} \leq 25\text{ V}$		43	120	mV
	$9\text{ V} \leq V_{IN} \leq 13\text{ V}$		10	60	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		13	120	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		5.0	60	mV
Output Voltage	$8\text{ V} \leq V_{IN} \leq 21\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$	5.7		6.3	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.3	8.0	mA
Quiescent Current Change	$8\text{ V} \leq V_{IN} \leq 25\text{ V}$			1.3	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		45		μV
Long Term Stability				24	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		65		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500\text{ mA}$		35		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		550		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		-1.0		$\text{mV}/^\circ\text{C}$

NOTE 1. Thermal resistance without a heat sink for junction to case temperature is $4.0^\circ\text{C}/\text{W}$ for TO-3 package, $2.0^\circ\text{C}/\text{W}$ for TO-220 package; ambient to case temperature is $35^\circ\text{C}/\text{W}$ for TO-3 package and $50^\circ\text{C}/\text{W}$ for TO-220 package.

μ A7808**ELECTRICAL CHARACTERISTICS** ($V_{IN} = 14$ V, $I_{OUT} = 500$ mA, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	7.7	8.0	8.3	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100$ mA				
	$10.5\text{ V} \leq V_{IN} \leq 25\text{ V}$		12	80	mV
	$11\text{ V} \leq V_{IN} \leq 17\text{ V}$		5.0	40	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500$ mA				
Load Regulation	$10.5\text{ V} \leq V_{IN} \leq 25\text{ V}$		50	160	mV
	$11\text{ V} \leq V_{IN} \leq 17\text{ V}$		22	80	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		26	160	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		9.0	80	mV
Output Voltage	$10.5\text{ V} \leq V_{IN} \leq 23\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$, $p \leq 15\text{ W}$	7.6		8.4	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.3	8.0	mA
Quiescent Current Change	$10.5\text{ V} \leq V_{IN} \leq 25\text{ V}$			1.0	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		52		μV
Long Term Stability				32	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		62		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500\text{ mA}$		40		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		450		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$	-1.0			$\text{mV}/^\circ\text{C}$

 μ A7812**ELECTRICAL CHARACTERISTICS** ($V_{IN} = 19$ V, $I_{OUT} = 500$ mA, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	11.5	12.0	12.5	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100$ mA				
	$14.5\text{ V} \leq V_{IN} \leq 30\text{ V}$		13	120	mV
	$16\text{ V} \leq V_{IN} \leq 22\text{ V}$		6.0	60	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500$ mA				
Load Regulation	$14.5\text{ V} \leq V_{IN} \leq 30\text{ V}$		55	240	mV
	$16\text{ V} \leq V_{IN} \leq 22\text{ V}$		24	120	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		46	240	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		17	120	mV
Output Voltage	$14.5\text{ V} \leq V_{IN} \leq 27\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$, $p \leq 15\text{ W}$			12.6	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.4	8.0	mA
Quiescent Current Change	$14.5\text{ V} \leq V_{IN} \leq 30\text{ V}$			1.0	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		75		μV
Long Term Stability				48	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		61		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500\text{ mA}$		75		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		350		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$	-2.0			$\text{mV}/^\circ\text{C}$

μ A7815ELECTRICAL CHARACTERISTICS ($V_{IN} = 23$ V, $I_{OUT} = 500$ mA, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	14.4	15.0	15.6	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100$ mA				
	$17.5\text{ V} \leq V_{IN} \leq 30\text{ V}$		14	150	mV
	$20\text{ V} \leq V_{IN} \leq 26\text{ V}$		6.0	75	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500$ mA				
Load Regulation	$17.5\text{ V} \leq V_{IN} \leq 30\text{ V}$		57	300	mV
	$20\text{ V} \leq V_{IN} \leq 26\text{ V}$		27	150	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		68	300	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		25	150	mV
Output Voltage	$17.5\text{ V} \leq V_{IN} \leq 30\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$, $p \leq 15\text{ W}$	14.25		15.75	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.4	8.0	mA
Quiescent Current Change	$17.5\text{ V} \leq V_{IN} \leq 30\text{ V}$			1.0	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		90		μV
Long Term Stability				60	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		60		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500\text{ mA}$		95		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		230		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		-2.0		$\text{mV}/^\circ\text{C}$

 μ A7818ELECTRICAL CHARACTERISTICS ($V_{IN} = 27$ V, $I_{OUT} = 500$ mA, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	17.3	18.0	18.7	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100$ mA				
	$21\text{ V} \leq V_{IN} \leq 33\text{ V}$		25	180	mV
	$24\text{ V} \leq V_{IN} \leq 30\text{ V}$		10	90	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500$ mA				
Load Regulation	$21\text{ V} \leq V_{IN} \leq 33\text{ V}$		90	360	mV
	$24\text{ V} \leq V_{IN} \leq 30\text{ V}$		50	180	mV
	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$		110	360	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		55	180	mV
Output Voltage	$21\text{ V} \leq V_{IN} \leq 33\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$, $p \leq 15\text{ W}$	17.1		18.9	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.5	8.0	mA
Quiescent Current Change	$21\text{ V} \leq V_{IN} \leq 33\text{ V}$			1.0	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.0\text{ A}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		110		μV
Long Term Stability				72	mV
Ripple Rejection	$I_{OUT} = 20\text{ mA}$, $f = 120\text{ Hz}$		59		dB
Dropout Voltage	$I_{OUT} = 1\text{ A}$, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500\text{ mA}$		110		$\text{m}\Omega$
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		200		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5\text{ mA}$, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		-1.0		$\text{mV}/^\circ\text{C}$

μ A7824ELECTRICAL CHARACTERISTICS ($V_{IN} = 33$ V, $I_{OUT} = 500$ mA, $0^\circ\text{C} < T_J < 125^\circ\text{C}$, unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_J = 25^\circ\text{C}$	23.0	24.0	35.0	V
Line Regulation	$T_J = 25^\circ\text{C}$, $I_{OUT} = 100$ mA				
	$27\text{ V} \leq V_{IN} \leq 38\text{ V}$		31	240	mV
	$30\text{ V} \leq V_{IN} \leq 36\text{ V}$		14	120	mV
	$T_J = 25^\circ\text{C}$, $I_{OUT} = 500$ mA				
	$27\text{ V} \leq V_{IN} \leq 38\text{ V}$		118	480	mV
	$30\text{ V} \leq V_{IN} \leq 36\text{ V}$		70	240	mV
Load Regulation	$T_J = 25^\circ\text{C}$, $5\text{ mA} \leq I_{OUT} \leq 1.0$ A		150	480	mV
	$250\text{ mA} \leq I_{OUT} \leq 750\text{ mA}$		85	240	mV
Output Voltage	$27\text{ V} \leq V_{IN} \leq 38\text{ V}$, $5\text{ mA} \leq I_{OUT} \leq 1.0$ A $p \leq 15$ W	22.8		25.2	V
Quiescent Current	$T_J = 25^\circ\text{C}$		4.6	8.0	mA
Quiescent Current Change	$27\text{ V} \leq V_{IN} \leq 38\text{ V}$			1.0	mA
	$5\text{ mA} \leq I_{OUT} \leq 1.0$ A			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$		170		μV
Long Term Stability				96	mV
Ripple Rejection	$I_{OUT} = 20$ mA, $f = 120$ Hz		56		dB
Dropout Voltage	$I_{OUT} = 1$ A, $T_J = 25^\circ\text{C}$		2.0		V
Output Resistance	$I_{OUT} = 500$ mA		150		m Ω
Short Circuit Current Limit	$T_J = 25^\circ\text{C}$		150		mA
Average Temperature Coefficient of Output Voltage	$I_{OUT} = 5$ mA, $0^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$	-1.0			mV/ $^\circ\text{C}$

TYPICAL PERFORMANCE CURVES


MAXIMUM AVERAGE POWER DISSIPATION AS A FUNCTION OF AMBIENT TEMPERATURE (TO-3 PACKAGE)




MAXIMUM AVERAGE POWER DISSIPATION AS A FUNCTION OF AMBIENT TEMPERATURE (TO-220 PACKAGE)




DROPOUT VOLTAGE AS A FUNCTION OF JUNCTION TEMPERATURE




PEAK OUTPUT CURRENT AS A FUNCTION OF INPUT-OUTPUT DIFFERENTIAL VOLTAGE



RIPPLE REJECTION AS A FUNCTION OF FREQUENCY




RIPPLE REJECTION AS A FUNCTION OF OUTPUT VOLTAGES




TYPICAL PERFORMANCE CURVES (cont'd)


OUTPUT VOLTAGE
AS A FUNCTION OF JUNCTION TEMPERATURE




QUIESCENT CURRENT
AS A FUNCTION OF TEMPERATURE




OUTPUT IMPEDANCE
AS A FUNCTION OF FREQUENCY



OUTPUT IMPEDANCE
AS A FUNCTION OF OUTPUT VOLTAGE




APPLICATIONS



NOTES:


- *To specify an output voltage, substitute voltage value for "XX".
- + Although no output capacitor is needed for stability, it does improve transient response.
- ++ Required if regulator is located an appreciable distance from power supply filter.

FIXED OUTPUT REGULATOR



 V_{OUT} , 7 V to 20 V

 $V_{IN} - V_{OUT} \geq 2$ V

ADJUSTABLE OUTPUT REGULATOR – HIGH LINE REGULATION


 R_1 determines output current.

CURRENT REGULATOR



HIGH CURRENT VOLTAGE REGULATOR

μA9614

DUAL DIFFERENTIAL LINE DRIVER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μA9614 is a TTL compatible Dual Differential Line Driver. It is designed to drive transmission lines either differentially or single-ended, back-matched or terminated. The outputs are similar to TTL, with the active pull-up and the pull-down split and brought out to adjacent pins. This allows multiplex operation (Wired-OR) at the driving site in either the single-ended mode via the uncommitted collector, or in the differential mode by use of the active pull-ups on one side and the uncommitted collectors on the other (See Fig. 5). The active pull-up is short circuit protected and offers a low output impedance to allow back-matching. The two pairs of outputs are complementary providing "NAND" and "AND" functions of the inputs, adding greater flexibility. The input and output levels are TTL compatible with clamp diodes provided at both, input and output, to handle line transients.

- SINGLE 5 VOLT SUPPLY
- TTL COMPATIBLE INPUTS
- OUTPUT SHORT CIRCUIT PROTECTION
- INPUT CLAMP DIODES
- OUTPUT CLAMP DIODES FOR TERMINATION OF LINE TRANSIENTS
- COMPLIMENTARY OUTPUTS FOR 'NAND', 'AND' OPERATION
- UNCOMMITTED COLLECTOR OUTPUTS FOR WIRED-OR APPLICATION
- MILITARY TEMPERATURE RANGE

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)


Storage Temperature	−65°C to +150°C
Temperature (Ambient) Under Bias	−55°C to +125°C
V _{CC} Pin Potential to Ground Pin	−0.7 V to +7.0 V
Input Voltage	−0.5 V to +5.5 V
Voltage Supplied to Outputs (Open Collector)	−0.5 V to +12 V
Lead Temperature (Soldering, 60 seconds)	300°C
Internal Power Dissipation (Note 1)	
Ceramic DIP	730 mW
Flatpak	570 mW

NOTE

- Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP and 7.1 mW/°C for the Flatpak Package.

ORDER INFORMATION — Specify U7B9614XXX for 16-pin Dual In-Line Package or U4L9614XXX for the 16-pin Flatpak where XXX is 51X for the −55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.

LOGIC DIAGRAM




V_{CC} = Pin 16
Gnd = Pin 8

Fig. 3

PHYSICAL DIMENSIONS

16 Lead Dual In-Line




NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers
They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for a conventional .020 inch diameter Lead
Leads are tin-plated kovar
Package weight is 2.2 grams
*The .037 dimension does not apply to the corner leads

Fig. 1

FLAT PACKAGE

16 Lead BeO Cerpak



NOTES:

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.4 gram

Fig. 2

ELECTRICAL CHARACTERISTICS

MILITARY TEMPERATURE RANGE (-55°C to $+125^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$) (U7B/4L961451X)

SYMBOL	CHARACTERISTIC	LIMITS							UNITS	CONDITIONS & COMMENTS	
		−55°C		+25°C			+125°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.			
V _{OL}	Output Low Voltage		400		200	400		400	mV	I _{OL} = 40 mA	V _{CC} = 4.5 V
V _{OH}	Output High Voltage	2.4		2.4	3.2		2.4		V	I _{OH} = −10 mA	V _{CC} = 4.5 V
I _{SC}	Output “Short Circuit” Current			−40	−90	−120			mA	V _{OUT} = 0.0 V	V _{CC} = 5.5 V
I _{CEX}	Output Leakage Current				10	100		200	μA	V _{CEX} = 12.0 V	V _{CC} = 5.5 V
I _F	Input Forward Current		−1.60		−1.10	−1.60		−1.60	mA	V _F = 0.4 V	V _{CC} = 5.5 V
I _R	Input Reverse Current				35	60		100	μA	V _R = 4.5 V	V _{CC} = 5.5 V
V _{IL}	Guaranteed Input Low Voltage		0.8		1.3	0.9		0.8	V	V _{CC} = 5.5 V	
V _{IH}	Guaranteed Input High Voltage	2.0		1.7	1.5		1.4		V	V _{CC} = 4.5 V	
V _{OLC}	Clamped Output Low Voltage				−0.8	−1.5			V	I _{OLC} = −40 mA	V _{CC} = 5.5 V
I _{CC}	Supply Current				34	48.7			mA	Inputs = 0 V	V _{CC} = 5.5 V
I _{max}	Supply Current				46	65.7			mA	Inputs = 0 V	V _{MAX} = 7.0 V
t _{PLH}	Turn-Off Time				14	20			ns	C _L = 30 pF	V _{CC} = 5.0 V
t _{PHL}	Turn-On Time				18	20			ns	See Fig. 4	V _M = 1.5 V
V _{IC}	Input Clamp Voltage				−1.0	−1.5			V	V _{CC} = 4.5 V	I _{IC} = −12 mA

ELECTRICAL CHARACTERISTICS

INDUSTRIAL TEMPERATURE RANGE (0°C to $+75^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 5\%$) (U7B/4L961459X)

SYMBOL	CHARACTERISTIC	LIMITS							UNITS	CONDITIONS & COMMENTS	
		0°C		+25°C			+75°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.			
V _{OL}	Output Low Voltage		450		200	450		450	mV	I _{OL} = 40 mA	V _{CC} = 4.75 V
V _{OH}	Output High Voltage	2.4		2.4	3.2		2.4		V	I _{OH} = −10 mA	V _{CC} = 4.75 V
I _{SC}	Output “Short Circuit” Current			−40	−90	−120			mA	V _{OUT} = 0.0 V	V _{CC} = 5.25 V
I _{CEX}	Output Leakage Current				10	100		200	μA	V _{CEX} = 5.25 V	V _{CC} = 5.25 V
I _F	Input Forward Current		−1.60		−1.10	−1.60		−1.60	mA	V _F = 0.45 V	V _{CC} = 5.25 V
I _R	Input Reverse Current				35	60		100	μA	V _R = 4.5 V	V _{CC} = 5.25 V
V _{IL}	Guaranteed Input Low Voltage		0.85		1.3	0.85		0.85	V	V _{CC} = 5.25 V	
V _{IH}	Guaranteed Input High Voltage	1.9		1.8	1.5		1.6		V	V _{CC} = 4.75 V	
V _{OLC}	Clamped Output Low Voltage				−0.8	−1.5			V	I _{OLC} = −40 mA	V _{CC} = 5.25 V
I _{CC}	Supply Current				33	48.7			mA	Inputs = 0 V	V _{CC} = 5.25 V
I _{max}	Supply Current				46	70			mA	Inputs = 0 V	V _{MAX} = 7.0 V
t _{PLH}	Turn-Off Time				14	30			ns	C _L = 30 pF	V _{CC} = 5.0 V
t _{PHL}	Turn-On Time				18	30			ns	See Fig. 4	V _M = 1.5 V
V _{IC}	Input Clamp Voltage				−1.0	−1.5			V	V _{CC} = 4.75 V	I _{IC} = −12 mA

SWITCHING CIRCUIT AND WAVEFORMS





Fig. 4












INPUT PULSE

Frequency = 500 kHz

Amplitude = $3.0 \pm 0.1\text{ V}$ Pulse Width = $110 \pm 10\text{ ns}$ $t_r = t_f \leq 5.0\text{ ns}$

TYPICAL ELECTRICAL CHARACTERISTICS

OUTPUT LOW CURRENT
VERSUS
OUTPUT LOW VOLTAGEOUTPUT HIGH CURRENT
VERSUS
OUTPUT HIGH VOLTAGELOGIC LEVELS VERSUS
AMBIENT TEMPERATURESUPPLY CURRENT
VERSUS
SUPPLY VOLTAGESUPPLY CURRENT VERSUS
TEMPERATURESUPPLY CURRENT VERSUS
OPERATING FREQUENCYPROPAGATION DELAY TIME
VERSUS
TEMPERATURETRANSFER CHARACTERISTICS
VERSUS
TEMPERATURETRANSFER CHARACTERISTICS
VERSUS
SUPPLY VOLTAGE

APPLICATIONS

DIFFERENTIAL MODE EXPANSION




Fig. 5

TYPICAL REFLECTION DIAGRAM




Fig. 6

μA9615

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μ A9615 is a dual differential line receiver designed to receive differential digital data from transmission lines and operate over the military and industrial temperature ranges using a single 5 volt supply. It can receive ± 500 mV of differential data in the presence of high level (± 15 V) common mode voltages and deliver undisturbed TTL logic to the output.

The response time can be controlled by use of an external capacitor. A strobe is provided along with a $130\ \Omega$ terminating resistor (at the inputs). The output has an uncommitted collector with an active pull-up available on an adjacent pin.

- TTL COMPATIBLE OUTPUT
- HIGH COMMON MODE VOLTAGE RANGE
- CHOICE OF AN UNCOMMITTED COLLECTOR OR ACTIVE PULL-UP
- STROBE
- FULL MILITARY TEMPERATURE RANGE
- SINGLE 5 VOLT SUPPLY VOLTAGES
- FREQUENCY RESPONSE CONTROL
- 130 Ω TERMINATING RESISTOR

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)

Storage Temperature	−65° C to +150° C
Temperature (Ambient) Under Bias	−55° C to +125° C
V _{CC1} Pin Potential to Ground Pin	−0.5 V to +7.0 V
Input Voltage Referred to Ground (Attenuator Inputs)	±20 V
Voltage Applied to Outputs for High Output State without Active Pull-up	−0.5 V to +13.2 V
Voltage Applied to Strobe	−0.5 V to +5.5 V
Lead Temperature (Soldering, 60 seconds)	300° C
Internal Power Dissipation (Note 1)	
Ceramic DIP	730 mW
Flatpak	570 mW

NOTE

1. Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP and 7.1 mW/°C for the Flatpak Package.

ORDER INFORMATION – Specify U7B9615XXX for 16-pin Dual In-Line Package or U4L9615XXX for 16-pin Flatpak where XXX is 51X for the -55°C to $+125^{\circ}\text{C}$ temperature range, or 59X for the 0°C to $+75^{\circ}\text{C}$ temperature range.





Fig. 3

PHYSICAL DIMENSION

16 Lead Dual In-Line



NOTES:

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers.

They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead

Hermetically sealed alumina ceramic package
Leads are tin-plated kovar


Package weight is 2.2 grams

*The .027/.037 dimension does not apply to the corner leads

Fig. 1

FLATPAK

16 Lead BeO Cerpak



NOTES:

All dimensions in inches

Leads are gold-plated kovar

Package weight is 0.4 gram

Fig. 2

ELECTRICAL CHARACTERISTICS (Temperature Range -55°C to $+125^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$) (Part No. U7B/4L961551X)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS & COMMENTS	
		-55°C MIN. MAX.		+25°C MIN. TYP. MAX.			+125°C MIN. MAX.			
V _{OL}	Output Low Voltage	0.40		0.18 0.40			0.40		Volts	V _{CC} = 4.5 V, V _{OUT} = ** I _{OL} = 15.0 mA, *V _{DIFF} = 0.5 V
V _{OH}	Output High Voltage	2.2		2.4 3.2			2.4		Volts	V _{CC} = 4.5 V, V _{OUT} = ** I _{OH} = -5.0 mA, *V _{DIFF} = -0.5 V
I _{CEX}	Output Leakage Current			100			200		μA	V _{CEX} = 12 V, *V _{DIFF} = V _{CC} = 4.5 V
I _{SC}	Output Shorted Current			-15 -39 -80					mA	V _{CC} = 5.5 V, **V _{SC} = 0 V, *V _{DIFF} = -0.5 V
I _{IN}	Input Current	-0.9		-0.49 -0.7			-0.7		mA	V _{CC} = 5.5 V, V _{IN} = 0.4 V Other Input = 5.5 V
I _{IN(ST)}	Strobe Input Current			-1.15 -2.4					mA	V _{CC} = 5.5 V, V _{IN} = 0.4 V *V _{DIFF} = 0.5 V
I _{IN(R-C)}	Response Control Input Current			-1.2 -3.4					mA	V _{CC} = 5.5 V, *V _{DIFF} = 0.5 V
V _{CM}	Common Mode Voltage	-15	+15	-15	±17.5	+15	-15	+15	Volts	V _{CC} = 5.0 V, *V _{DIFF} = 2.0 V
I _{R(ST)}	Strobe Input Leakage Current			2.0			5.0		μA	V _{CC} = 4.5 V, *V _{DIFF} = -0.5 V V _R = 4.5 V
R _{IN}	Input Resistor			77	130	167			ohms	V _{CC} = 5.0 V, V _{IN(R)} = 1.0 V, +Input = Gnd.
V _{TH}	Differential Input Threshold Voltage	500		80 500			500		mV	V _{CC} = 5.0 V ±10%
I _{CC}	Power Supply Current			28.7 50					mA	V _{CC} = 5.5 V, -Inputs = 0 V, +Inputs = 0.5 V
t _{pd+}	Turn-off Time			30 50					ns	R _L = 3.9 kΩ, V _{CC} = 5.0 V, C _L = 30 pF, Fig. 4
t _{pd-}	Turn-on Time			30 50					ns	R _L = 390 Ω, V _{CC} = 5.0 V, C _L = 30 pF, Fig. 4

* V_{DIFF} is a differential input voltage referred from "+IN A" to "-IN A" and from "+IN B" to "-IN B".

** Connect Output "A" to Active Pull-up "A" and Output "B" to Active Pull-up "B".


ELECTRICAL CHARACTERISTICS (Temperature Range 0°C to $+75^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 5\%$) (Part No. U7B/4L961559X)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS & COMMENTS
		0°C MIN. MAX.		+25°C MIN. TYP. MAX.		+75°C MIN. MAX.			
V _{OL}	Output Low Voltage	0.45		0.25 0.45		0.45		Volts	V _{CC} = 4.75 V, V _{OUT} = ** I _{OL} = 15.0 mA, *V _{DIFF} = 0.5 V
V _{OH}	Output High Voltage	2.4		2.4 3.3		2.4		Volts	V _{CC} = 4.75 V, V _{OUT} = ** I _{OH} = -5.0 mA, *V _{DIFF} = -0.5 V
I _{CEX}	Output Leakage Current			100		200		μA	V _{CEX} = 5.25 V, *V _{DIFF} = V _{CC} = 4.75 V
I _{SC}	Output Shorted Current			-14 -100				mA	V _{CC} = 5.25 V, **V _{SC} = 0 V, *V _{DIFF} = -0.5 V
I _{IN}	Input Current	-0.9		-0.49 -0.7		-0.7		mA	V _{CC} = 5.25 V, V _{IN} = 0.45 V Other Input = 5.25 V
I _{IN(ST)}	Strobe Input Current			-1.15 -2.4				mA	V _{CC} = 5.25 V, V _{IN} = 0.45 V *V _{DIFF} = 0.5 V
I _{IN(R-C)}	Response Control Input Current			-1.2 -3.4				mA	V _{CC} = 5.25 V, *V _{DIFF} = 0.5 V
V _{CM}	Common Mode Voltage	-15 +15	-15 ±17.5 +15			-15 +15	Volts	V _{CC} = 5.0 V, *V _{DIFF} = 2.0 V	
I _{R(ST)}	Strobe Input Leakage Current			5.0		10		μA	V _{CC} = 4.75 V, *V _{DIFF} = -0.5 V V _R = 4.5 V
R _{IN}	Input Resistor			74 130 179			ohms	V _{CC} = 5.0 V, V _{IN(R)} = 1.0 V, +Input = Gnd.	
V _{TH}	Differential Input Threshold Voltage	500		80 500	500		mV	V _{CC} = 5.0 V ±5%	
I _{CC}	Power Supply Current			28.7 50			mA	V _{CC} = 5.25 V, +Inputs = 0.5 V, -Inputs = 0 V	
t _{pd+}	Turn-off Time			30 75			ns	R _L = 3.9 kΩ, V _{CC} = 5.0 V, C _L = 30 pF, Fig. 4	
t _{pd-}	Turn-on Time			30 75			ns	R _L = 390 Ω, V _{CC} = 5.0 V, C _L = 30 pF, Fig. 4	

* V_{DIFF} is a differential input voltage referred from "+IN A" to "-IN A" and from "+IN B" to "-IN B".

** Connect Output "A" to Active Pull-up "A" and Output "B" to Active Pull-up "B".

SWITCHING TIME TEST CIRCUIT



WAVEFORMS






Fig. 4

Photograph of a 9615 switching differential data in the presence of high common mode noise.



VERTICAL=2.0V/DIV. HORIZONTAL=50ns/DIV.

Fig. 5

STANDARD USAGE





Fig. 6

FREQUENCY RESPONSE CONTROL



FREQUENCY RESPONSE VERSUS CAPACITANCE
















Fig. 7

TYPICAL ELECTRICAL CHARACTERISTICS

OUTPUT LOW VOLTAGE
VERSUS
OUTPUT LOW CURRENTOUTPUT HIGH VOLTAGE
VERSUS
OUTPUT HIGH CURRENTOUTPUT VOLTAGE VERSUS
AMBIENT TEMPERATUREINPUT-OUTPUT TRANSFER
CHARACTERISTIC
VERSUS V_{CC} INPUT-OUTPUT TRANSFER
CHARACTERISTIC
VERSUS TEMPERATURESTROBE INPUT-OUTPUT
TRANSFER CHARACTERISTIC
VERSUS V_{CC} STROBE INPUT-OUTPUT
TRANSFER CHARACTERISTIC
VERSUS AMBIENT TEMPERATUREOUTPUT VOLTAGE VERSUS
COMMON MODE VOLTAGEINPUT CURRENT VERSUS
INPUT VOLTAGEPOWER SUPPLY CURRENT
VERSUS
POWER SUPPLY VOLTAGEPOWER SUPPLY CURRENT
VERSUS
AMBIENT TEMPERATURESWITCHING TIME
VERSUS
AMBIENT TEMPERATURE

μA9620

DUAL DIFFERENTIAL LINE RECEIVER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μA9620 is a dual differential line receiver designed to receive differential digital data from transmission lines and operate over the military and industrial temperature ranges. It can receive ± 500 mV of differential data in the presence of high level (± 15 V) common mode voltages and deliver undisturbed TTL logic to the output. In addition to line reception the μA9620 can perform many functions, a few of which are presented in the applications section. It can interface with nearly all input logic levels including CML, CTL, HLLDTL, RTL and TTL. HLLDTL logic can be provided by tying the output to V_{CC2} (+12 V) through a resistor. The outputs can also be wire OR'ed. The μA9620 offers the advantages of logic compatible voltages (+5 V, +12 V), TTL output characteristics, and a flexible input array with a high common mode range. The direct inputs are provided in addition to the attenuated inputs (normally used) to allow the input attenuation and response time to be changed by use of external components.

- **TTL COMPATIBLE OUTPUT**
- **HIGH COMMON MODE VOLTAGE RANGE**
- **WIRED-OR CAPABILITY**
- **DIRECT INPUTS (A_D , B_D)**
- **FULL MILITARY TEMPERATURE RANGE**
- **LOGIC COMPATIBLE SUPPLY VOLTAGES**

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)


Storage Temperature	-65°C to +150°C
Temperature (Ambient) Under Bias	-55°C to +125°C
V_{CC1} Pin Potential to Ground Pin	-0.5 V to +7.0 V
Input Voltage Referred to Ground (Attenuator Inputs)	± 20 V
Voltage Applied to Outputs for High Output State	-0.5 V to +13.2 V
V_{CC2} Pin Potential to Ground Pin	V_{CC1} to +15 V
Lead Temperature (Soldering, 60 seconds)	300°C
Internal Power Dissipation (Note 1)	
Ceramic DIP	670 mW
Flatpak	570 mW

NOTE

- Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP and 7.1 mW/°C for the Flatpak Package.


ORDER INFORMATION — Specify U6A9620XXX for 14-pin Dual In-Line Package or U3I9620XXX for 14-pin Flatpak where XXX is 51X for the -55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.

LOGIC DIAGRAM



PHYSICAL DIMENSIONS

in accordance with JEDEC (TO-116) outline
14 Lead Dual-In-line




NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers.
- They are purposely shipped with "positive" misalignment to facilitate insertion.
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams

FLAT PACKAGE

14 Lead BeO Cerpak



NOTES:

- All dimensions in inches
- Leads are gold-plated kovar
- Package weight is 0.26 gram


ELECTRICAL CHARACTERISTICS (Temperature Range -55°C to $+125^{\circ}\text{C}$, $V_{CC1} = 5.0\text{ V} \pm 10\%$, $V_{CC2} = 12.0\text{ V} \pm 10\%$)

SYMBOL	CHARACTERISTIC	LIMITS						UNITS	CONDITIONS & COMMENTS	
		−55°C		+25°C		+125°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.		
V _{OL}	Output Low Voltage		0.40		0.21	0.40		0.45	Volts	V _{CC1} = 4.5 V I _{OL} = 15.0 mA V _{CC2} = 10.8 V *V _{DIFF} = 0.5 V
V _{OH}	Output High Voltage	2.8		3.0	3.7		2.9		Volts	V _{CC1} = 4.5 V I _{OH} = −0.2 mA V _{CC2} = 10.8 V *V _{DIFF} = −0.5 V
I _{CEX}	Output Leakage Current		50			100		200	μA	V _{CEX} = 13.2 V
I _{SC}	Output Shorted Current			−1.4	−2.15	−3.1			mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
I _F	Input Forward Current		−3.1		−2.1	−3.0		−3.0	mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V V _{Input} = 0 V ⁺
†V _{TH}	Differential Input Threshold Voltage		500		120	500		500	mV	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
†V _{CM}	Common Mode Voltage	−15	15	−15	±17.5	15	−15	15	Volts	V _{CC1} = 5.0 V *V _{DIFF} = 2.0 V V _{CC2} = 12.0 V
I _{VCC1}	5 V Supply Current		13		8.2	13		13	mA	V _{CC1} = 5.5 V V _{CC2} = 13.2 V +Input = 5.5 V −Input = 0 V
I _{VCC2}	12 V Supply Current		8.0		5.6	8.0		8.0	mA	V _{CC1} = 5.5 V V _{CC2} = 13.2 V +Input = 5.5 V −Input = 0 V
t _{pd+}	Turn-off Time				35	50			ns	R _L = 3.9 kΩ C _L = 30 pF
t _{pd−}	Turn-on Time				20	50			ns	R _L = 390 Ω C _L = 30 pF


$\dagger$ All input voltages are referred to the attenuated inputs (A^+ , A^- , B^+ , B^-)

$*V_{DIFF}$ is a differential input voltage referred from A^+ to A^- and from B^+ to B^- .

Fig. 1 — SCHEMATIC DIAGRAM



STANDARD USAGE



ELECTRICAL CHARACTERISTICS (Temperature Range 0°C to $+75^{\circ}\text{C}$, $V_{CC1} = 5.0\text{ V} \pm 5\%$, $V_{CC2} = 12.0\text{ V} \pm 5\%$)


SYMBOL	CHARACTERISTIC	LIMITS								UNITS	CONDITIONS & COMMENTS	
		0°C		+25°C			+75°C					
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.				
V _{OL}	Output Low Voltage		0.45		0.25	0.45		0.50	Volts	V _{CC1} = 4.75 V I _{OL} = 15.0 mA	V _{CC2} = 11.4 V *V _{DIFF} = 0.5 V	
V _{OH}	Output High Voltage	2.8		3.0	3.3		2.9		Volts	V _{CC1} = 4.75 V I _{OH} = −0.2 mA	V _{CC2} = 12.6 V *V _{DIFF} = −0.5 V	
I _{CEX}	Output Leakage Current		50			100		200	μA	V _{CEX} = 5.25 V		
I _{SC}	Output Shorted Current			−1.4	−2.15	−3.1			mA	V _{CC1} = 5.0 V	V _{CC2} = 12.0 V	
I _F	Input Forward Current		−3.1		−2.1	−3.0		−3.0	mA	V _{CC1} = 5.0 V	V _{CC2} = 12.0 V V _{Input} = 0 V +	
†V _{TH}	Differential Input Threshold Voltage		500		120	500		500	mV	V _{CC1} = 4.75 V	V _{CC2} = 12.6 V	
†V _{CM}	Common Mode Voltage	−12	12	−12	±17.5	12	−12	12	Volts	V _{CC1} = 5.0 V *V _{DIFF} = 2.0 V	V _{CC2} = 12.0 V	
I _{VCC1}	5 V Supply Current		13.5		8.2	13.5		13.5	mA	V _{CC1} = 5.25 V V _{CC2} = 12.6 V	+Input = 5.25 V −Input = 0 V	
I _{VCC2}	12 V Supply Current		8.5		5.6	8.5		8.5	mA	V _{CC1} = 5.25 V V _{CC2} = 12.6 V	+Input = 5.25 V −Input = 0 V	
t _{pd+}	Turn-off Time				35	75			ns	R _L = 3.9 kΩ	C _L = 30 pF	
t _{pd−}	Turn-on Time				20	75			ns	R _L = 390 Ω	C _L = 30 pF	

$\dagger$ All input voltages are referred to the attenuated inputs (A^+ , A^- , B^+ , B^-)


$*V_{DIFF}$ is a differential input voltage referred from A^+ to A^- and from B^+ to B^- .

Fig. 2 — SWITCHING TIME TEST CIRCUIT



$V_{CC1} = 5.0\text{ V}$
 $V_{CC2} = 12\text{ V}$



WAVEFORMS













Photograph of a 9620 switching differential data in the presence of high common mode noise.




VERT = 2.0 V/div. HORIZ = 50 ns/div.

TYPICAL ELECTRICAL CHARACTERISTICS


TYPICAL OUTPUT LOW VOLTAGE
VERSUS
OUTPUT LOW CURRENTTYPICAL OUTPUT HIGH VOLTAGE
VERSUS
OUTPUT HIGH CURRENTLOGIC LEVELS VERSUS
AMBIENT TEMPERATURETYPICAL V_{out} VERSUS V_{DIFF}
TRANSFER CHARACTERISTICTYPICAL V_{out} VERSUS V_{DIFF}
TRANSFER CHARACTERISTICTYPICAL V_{out} VERSUS V_{DIFF}
TRANSFER CHARACTERISTICTYPICAL V_{out} VERSUS V_{CM}
CHARACTERISTICSINPUT VOLTAGE VERSUS
INPUT CURRENTSWITCHING TIME VERSUS
AMBIENT TEMPERATUREPOWER DISSIPATION VERSUS
AMBIENT TEMPERATURE

APPLICATIONS


DIGITAL COMPARATOR WITH DIODE REFERENCE AND HIGH LEVEL LOGIC OUT



DIGITAL DIFFERENTIAL LINE RECEIVER WITH INPUTS ROLLED OFF




EXPANDED INTERFACE




V_{ref} = Resistor, Diodes, or Supply


DIGITAL DIFFERENTIAL AMPLIFIER (Line Receiver)




DIGITAL COMPARATOR



INTERFACING METHODS




DIGITAL COMPARATOR WITH RESISTIVE DIVIDER AS REFERENCE




APPLICATIONS

MULTIVIBRATOR




TYPICALLY
 $R_1 = 1.6 \text{ k}\Omega$, $R_2 = 2.7 \text{ k}\Omega$, $T = 1.3 R_3 C$

A.C. COUPLED DIGITAL AMPLIFIER WITH HYSTERESIS




TYPICALLY
 $R_1 = 1.6 \text{ k}\Omega$, $R_2 = 2.7 \text{ k}\Omega$

MONOSTABLE MULTIVIBRATOR NEGATIVE EDGE TRIGGERING




TYPICALLY
 $C_1 = 0.1 \text{ }\mu\text{F}$, $R_1 = 1.2 \text{ k}\Omega$, $R_2 = 1.0 \text{ k}\Omega$
 Pulse Width = $50 \text{ ns} + 3.15 \times 10^3 C_2$

DOUBLE-ENDED COMPARATOR




$V_{OH} = V_{ref1} < V_{IN} < V_{ref2}$

CRYSTAL CONTROLLED MULTIVIBRATOR



TYPICALLY
 $R_1 = 1.6 \text{ k}\Omega$, $R_2 = 2.7 \text{ k}\Omega$, $C = \frac{R_2}{1000}$

HIGH INPUT IMPEDANCE LINE RECEIVER (Positive Signals Only)



μA9621

DUAL-LINE DRIVER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA9621 was designed to drive transmission lines in either a differential or a single-ended mode. Output clamp diodes and back-matching resistors for 130 Ω twisted pair are provided. The output has the capability of driving high capacitance loads. It can typically switch >200 mA during transients.

- TTL COMPATIBILITY
- TRANSMISSION LINE BACK-MATCHING
- OUTPUT CLAMP DIODES
- HIGH CAPACITANCE DRIVE
- HIGH OUTPUT VOLTAGE
- MILITARY TEMPERATURE RANGE

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)


Storage Temperature	-65°C to +150°C
Temperature (Ambient) Under Bias	-55°C to +125°C
V _{CC1} Pin Potential to Ground Pin	+3.8 V to +8 V
Input Voltage	-0.5 V to +15 V
Voltage Applied to Outputs	-2 V to +V _{CC1} +1 V
V _{CC2} Pin Potential to Ground Pin	V _{CC1} to +15 V
Lead Temperature (Soldering, 60 seconds)	300°C
Internal Power Dissipation (Note)	
Ceramic DIP	670 mW
Flatpak	570 mW

NOTE

Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP and 7.1 mW/°C for the Flatpak Package.


ORDER INFORMATION — Specify U6A9621XXX for 14-pin Dual In-Line Package or U3I9621XXX for 14-pin Flatpak where XXX is 51X for the -55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.

SCHEMATIC DIAGRAM
(ONE SIDE ONLY)



PHYSICAL DIMENSIONS

Similar* to JEDEC (TO-116) outline
14 Lead Dual-In-Line




NOTES

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers
They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020 inch diameter lead
Leads are tin-plated kovar
Package weight is 2.0 grams

FLAT PACKAGE


16 Lead BeO Cerpak



NOTES:

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.26 gram

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

MILITARY TEMPERATURE RANGE -55°C to $+125^{\circ}\text{C}$ (UXX962151X)

SYMBOL	NOTES	CHARACTERISTICS	LIMITS							UNITS	CONDITIONS & COMMENTS	
			-55°C		+25°C			+125°C				
			MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.			
V _{OL}		Output Low Voltage		350		200	350		400	mV	I _{OL} = 20 mA	V _{CC1} = 4.5 V V _{CC2} = 10.8 V
V _{OH}		Output High Voltage	4.0		4.0	4.3		4.0		V	I _{OH} = -20 mA	V _{CC1} = 4.5 V V _{CC2} = 10.8 V
I _{SC}	1	Output "Short Circuit" Current			-180	-420				mA	V _{OUT} = 0 V	V _{CC1} = 4.5 V V _{CC2} = 10.8 V
I _{OL}	1	Output Low Current			150	200				mA	V _{OUT} = 5.0 V	V _{CC1} = 4.5 V V _{CC2} = 10.8 V
I _F		Input Forward Current		-1.8		-1.15	-1.8		-1.8	mA	V _F = 0 V	V _{CC1} = 5.5 V V _{CC2} = 13.2 V
I _R		Input Reverse Current		2.0		<1.0	2.0		5.0	μA	V _R = 5.5 V	V _{CC1} = 5.5 V V _{CC2} = 13.2 V
V _{OLR}	2	Resistive Output Low Voltage				380	500			V	I _{OL} = 2.8 mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OHR}	2	Resistive Output High Voltage			4.0	4.2				V	I _{OH} = -2.3 mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OLC}	3	Clamped Output Low Voltage				-1.0	-2.0			V	I _{OL} = -20 mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OHC}	3	Clamped Output High Voltage				6.0	7.0			V	I _{OH} = 20 mA	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
I _{CC1}		+5 V Supply Current		7.0		4.7	7.0		7.3	mA	Inputs Open	V _{CC1} = 5.5 V V _{CC2} = 13.2 V
I _{CC2}		+12 V Supply Current		9.8		6.5	9.8		9.8	mA		
t _{pd+}	4	Turn-Off Time				30	150			ns	C _L = 5000 pF	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
t _{pd-}	4	Turn-On Time				80	150			ns		
t _{pd+}		Turn-Off Time				13	25			ns	C _L = 30 pF	V _{CC1} = 5.0 V V _{CC2} = 12.0 V
t _{pd-}		Turn-On Time				9	25			ns		
V _{IL}		Input Low Voltage		1.3		1.5	1.0		0.7	V	V _{CC1} = 5.5 V V _{CC2} = 10.8 V	
V _{IH}		Input High Voltage	2.2		2.0	1.7		1.8		V	V _{CC1} = 4.5 V V _{CC2} = 13.2 V	

NOTES:

- (1) Pulse tests to insure transient current handling (test time = 3 seconds maximum — one side only).
- (2) Test output resistance including 105Ω output resistor.
- (3) Tests output clamp diodes.
- (4) With both sides loaded at $T_A = +125^{\circ}\text{C}$, maximum frequency = 500 kHz for Dual In-Line package ($\theta_{JA} = 95^{\circ}\text{C/W}$) or 300 kHz for Ceramic Flat Pak ($\theta_{JA} = 165^{\circ}\text{C/W}$).

ELECTRICAL CHARACTERISTICS

INDUSTRIAL TEMPERATURE RANGE 0°C to +75°C (UXX962159X)


SYMBOL	NOTES	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS & COMMENTS	
			0°C		+25°C			+75°C			
			MIN.	MAX.	MIN.	TYP.	MAX.	MIN.			MAX.
V _{OL}		Output Low Voltage		400		200	400		450	mV	I _{OL} = 20 mA V _{CC1} = 4.75 V V _{CC2} = 11.4 V
V _{OH}		Output High Voltage	4.2		4.2	4.4		4.2		V	I _{OH} = −20 mA V _{CC1} = 4.75 V V _{CC2} = 11.4 V
I _{SC}	1	Output “Short Circuit” Current			−100	−420				mA	V _{OUT} = 0 V V _{CC1} = 4.75 V V _{CC2} = 11.4 V
I _{OL}	1	Output Low Current			75	200				mA	V _{OUT} = 5.0 V V _{CC1} = 4.75 V V _{CC2} = 11.4 V
I _F		Input Forward Current		1.8		1.15	1.8		1.8	mA	V _F = 0 V V _{CC1} = 5.25 V V _{CC2} = 12.6 V
I _R		Input Reverse Current		5.0		<1.0	5.0		10.0	μA	V _R = 5.5 V V _{CC1} = 5.25 V V _{CC2} = 12.6 V
V _{OLR}	2	Resistive Output Low Voltage				380	500			V	I _{OL} = 2.8 mA V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OHR}	2	Resistive Output High Voltage			4.0	4.2				V	I _{OH} = −2.3 mA V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OLC}	3	Clamped Output Low Voltage				−1.0	−2.0			V	I _{OL} = −20 mA V _{CC1} = 5.0 V V _{CC2} = 12.0 V
V _{OHC}	3	Clamped Output High Voltage				6.0	7.0			V	I _{OH} = 20 mA V _{CC1} = 5.0 V V _{CC2} = 12.0 V
I _{CC1}		+5 V Supply Current		7.0		4.7	7.0		7.3	mA	Inputs Open V _{CC1} = 5.25 V V _{CC2} = 12.6 V
I _{CC2}		+12 V Supply Current		9.8		6.5	9.8		9.8	mA	
t _{pd+}	4	Turn-Off Time				30	200			ns	C _L = 5000 pF V _{CC1} = 5.0 V V _{CC2} = 12.0 V
t _{pd−}	4	Turn-On Time				80	200			ns	
t _{pd+}		Turn-Off Time				13	40			ns	C _L = 30 pF V _{CC1} = 5.0 V V _{CC2} = 12.0 V
t _{pd−}		Turn-On Time				9	40			ns	
V _{IL}		Input Low Voltage		1.3		1.5	1.0		0.7	V	V _{CC1} = 5.25 V V _{CC2} = 12.6 V
V _{IH}		Input High Voltage	2.2		2.0	1.7		1.8		V	V _{CC1} = 4.75 V V _{CC2} = 11.4 V

NOTES:


- (1) Pulse tests to insure transient current handling (test time = 3 seconds maximum — one side only).
- (2) Test output resistance including 105 Ω output resistor.
- (3) Tests output clamp diodes.
- (4) Maximum frequency = 500 kHz with both sides loaded at $T_A = +75^\circ\text{C}$ for both Dual In-Line package and Ceramic Flat Pak.

TYPICAL ELECTRICAL CHARACTERISTICS


OUTPUT LOW
CURRENT VERSUS
OUTPUT LOW VOLTAGE




OUTPUT HIGH
CURRENT VERSUS
OUTPUT HIGH VOLTAGE




LOGIC LEVELS VERSUS
AMBIENT TEMPERATURE




SUPPLY CURRENT VERSUS
SUPPLY VOLTAGE
INPUTS GROUNDED




SUPPLY CURRENT VERSUS
SUPPLY VOLTAGE
INPUTS OPEN




SUPPLY CURRENT VERSUS
SUPPLY VOLTAGE




TYPICAL OUTPUT IMPEDANCE
WITH BACK MATCHING
RESISTORS




SWITCHING TIME VERSUS
TEMPERATURE




SWITCHING TIME VERSUS
TEMPERATURE




SUPPLY CURRENT
VERSUS FREQUENCY



SWITCHING TIME TEST CIRCUIT



WAVEFORMS



DESCRIPTION OF REFLECTION DIAGRAM USAGE

The reflections on any line may be found by using the following procedure:

1. Draw the driver output characteristics for both the "high state" and the "low state" on an I - V graph in the same manner as the reflection diagram.
2. Draw the receiver input characteristic on the same graph. The two points of intersection of the receiver and driver characteristics are the two DC operating points.
3. Choose to analyze either the reflections for the output going low or high. In the example chosen the negative transition is analyzed.
4. Draw a line with a slope equal to the impedance of the line to be used, ($Z_0 = 100\Omega$ in the example), from the "high state" operating point (labeled A on our graph) to the "low state" output device characteristic (B_1). B_1 equals the conditions at the driver output immediately after turn-on.
5. Reverse the slope of Z_0 and sketch it from B_1 to the receiver input characteristic (C_1). C_1 equals the conditions at the receiver when the wavefront B_1 first reaches it.
6. By continuing this procedure of reversing the slope of Z_0 at each node all the reflections ($B_1, C_1, B_2, C_2, B_3, C_3 \dots B_N, C_N$), where B_x is the voltage at the driver and C_x is the voltage at the receiver, can be found.

The same procedure is used to check the reflections when switching the output high.


BACK-MATCHING, also referred to as reverse termination, offers several advantages to the user. It reduces the system power by not requiring the high current for resistive termination and it reduces the DC line losses because IR drops in the line become minimum.

To back-match any line (output switching low):

1. Measure the output resistance, R_{out} , from the "low state" operating point to B_1 .
2. Subtract R_{out} from Z . ($R_{out} + R_M = Z_0$). This value R_M , is the required back-matching resistance.
3. Place R_M in series with the output of driver.
4. The reflections that occur on the line with R_M inserted can be treated in the same manner as the general case. The results are B_1' and C_1' and the receiver will not see any reflections.

When switching the line differentially $R_M + R_{out} = Z_0/2$. The matched output characteristics of the 9621 make it possible to back-match effectively and require analysis of switching only one state.


TYPICAL REFLECTION DIAGRAM*



* GRAPHICAL ANALYSIS

First Presented by John B. James of I.C.T. (Eng.) LTD.





REFLECTION TEST CIRCUIT



The reflections are two delay's of the line wide. R_{term} is the total impedance seen at the receiving end.

BACK MATCHING TABLE

Z_0	R_M when used single ended	R_M when used differentially
50 Ω	32 Ω	16 Ω
75 Ω	62 Ω	30 Ω
92 Ω	82 Ω	41 Ω
100 Ω	90 Ω	45 Ω
130 Ω	120 Ω	60 Ω
300 Ω	290 Ω	145 Ω
600 Ω	590 Ω	295 Ω



μA9622

DUAL LINE RECEIVER

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The μA9622 is a dual line receiver designed to discriminate a worst case logic swing of 2 volts from a ±10 volt common mode noise signal or ground shift. A 1.5 volt threshold is built into the differential amplifier to offer a TTL compatible threshold voltage and maximum noise immunity. The offset is obtained by use of current sources and matched resistors and varies only ±5% (75 mV) over the military and industrial temperature ranges.

The μA9622 allows the choice of output states with the inputs open without affecting circuit performance by use of S3. A 130 Ω terminating resistor is provided at the input of each line receiver. An enable is also provided for each line receiver. The output is TTL compatible. The output high level can be increased to +12 V by tying it to a positive supply through a resistor. The outputs can be wire-OR'ed.

- TTL COMPATIBLE THRESHOLD VOLTAGE
- INPUT TERMINATING RESISTORS
- CHOICE OF OUTPUT STATE WITH INPUTS OPEN
- TTL COMPATIBLE OUTPUT
- HIGH COMMON MODE
- WIRE-OR CAPABILITY
- ENABLE INPUTS
- FULL MILITARY TEMPERATURE RANGE
- LOGIC COMPATIBLE SUPPLY VOLTAGES

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)


Storage Temperature	−65°C to +150°C
Temperature (Ambient) Under Bias	−55°C to +125°C
Internal Power Dissipation (Note 1)	
Ceramic DIP	670 mW
Flatpak	570 mW
V _{CC} Pin Potential to Ground Pin	−0.5 V to +7 V
Input Voltage	±15 V
Voltage Applied to Outputs for High Output State	−0.5 V to +13.2 V
V _{EE} Pin Potential to Ground Pin	−0.5 V to −12 V
Enable Pin Potential to Ground Pin	−0.5 V to +15 V
Lead Temperature (Soldering, 60 seconds)	300°C

NOTE

- Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP and 7.1 mW/°C for the Flatpak Package.


ORDER INFORMATION — Specify U6A9622XXX for 14-pin Dual In-Line Package, U3I9622XXX for 14-pin Flatpak where XXX is 51X for the −55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.

LOGIC DIAGRAM



TYPICAL DUAL IN-LINE PACKAGE


In Accordance With
JEDEC (TO-116) Outline



NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers.
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for a conventional .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams

**FLAT PACKAGE
TOP VIEW**




NOTES:

- All dimensions in inches
- Leads are gold-plated kovar
- Package weight is 0.26 gram

ELECTRICAL CHARACTERISTICS (Temperature Range -55°C to $+125^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS & COMMENTS	
		-55°C		+25°C		+125°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.		
V _{OL}	Output Low Voltage		0.40		0.17	0.40		0.40	V	V _{CC} = 4.5 V *V _{DIFF} = 2.0 V V _{EE} = -11 V I _{OL} = 12.4 mA
V _{OH}	Output High Voltage	2.8		3.0	3.3		2.9		V	V _{CC} = 4.5 V *V _{DIFF} = 1.0 V V _{EE} = -9.0 V I _{OH} = -0.2 mA
I _{CEX}	Output Leakage Current		50			100		200	μA	V _{CC} = 4.5 V *V _{DIFF} = 1.0 V V _{EE} = -11 V V _{CEX} = 12 V
I _{SC}	Output Shorted Current	-1.3	-3.1	-1.4	-2.15	-3.1	-1.3	-3.1	mA	V _{CC} = 5.0 V *V _{DIFF} = 1.0 V V _{EE} = -10 V V _{SC} = 0 V
I _{R(ENABLE)}	Enable Input Leakage Current					2.0		5.0	μA	V _{CC} = 4.5 V S ₃ = 4.5 V V _{EE} = -11 V V _R = 4.0 V
I _{F(ENABLE)}	Enable Input Forward Current		-1.5		-0.96	-1.5		-1.5	mA	V _{CC} = 5.5 V S ₃ = 0 V V _{EE} = -9.0 V V _F = 0 V
I _{F(+Input)}	+ Input Forward Current		-2.3		-1.67	-2.1		-2.0	mA	V _{CC} = 5.0 V - Input = Gnd V _{EE} = -10 V V _F = 0 V
I _{F(-Input)}	- Input Forward Current		-2.6		-1.87	-2.4		-2.3	mA	V _{CC} , S ₃ = 5.0 V + Input = Gnd V _{EE} = -10 V V _F = 0 V
V _{IL(ENABLE)}	Input Low Voltage		1.3		1.4	1.0		0.7	V	V _{CC} = 5.0 V ±10% V _{EE} = -10 V ±10%
V _{th}	Differential Input Threshold Voltage	1.0	2.0	1.0	1.5	2.0	1.0	2.0	V	V _{CC} = 5.0 V ±10% V _{EE} = -10 V ±10%
V _{CM}	Common Mode Voltage			-10	±12	+10			V	V _{CC} = 5.0 V *V _{DIFF} = 1.0 V or 2.0 V V _{EE} = -10 V
R _{130Ω}	Terminating Resistance			100	130	175			Ω	
I _{CC}	5 V Supply Current				13.7	22.9			mA	V _{CC} = 5.5 V S ₃ , + Inputs = 5.5 V, - Inputs = 0 V V _{EE} = -11 V
I _{EE}	-10 V Supply Current				-6.5	-11.1			mA	V _{CC} = 5.5 V S ₃ , + Inputs = 5.5 V, - Inputs = 0 V V _{EE} = -11 V
t _{pd+}	Turn-off Time				38	50			ns	V _{CC} = 5.0 V V _{IN} 0→3 V, R _L = 3.9 kΩ, C _L = 30 pF V _{EE} = -10 V
t _{pd-}	Turn-on Time				35	50			ns	V _{CC} = 5.0 V V _{IN} 0→3.0 V, R _L = 0.39 kΩ, C _L = 30 pF V _{EE} = -10 V

$*V_{DIFF}$ is a differential input voltage referred from A+ to A- and from B+ to B-.


SCHEMATIC DIAGRAM

ELECTRICAL CHARACTERISTICS (Temperature Range 0°C to $+75^{\circ}\text{C}$, $V_{CC} = 5.0\text{ V} \pm 5\%$)


SYMBOL	CHARACTERISTICS	LIMITS							UNITS	CONDITIONS & COMMENTS	
		0°C		+25°C			+75°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.			
V _{OL}	Output Low Voltage		0.45		0.17	0.45		0.45	V	V _{CC} = 4.75 V *V _{DIFF} = 2.0 V	V _{EE} = -10.5 V I _{OL} = 14.1 mA
V _{OH}	Output High Voltage	2.9		3.0	3.3		2.9		V	V _{CC} = 4.75 V *V _{DIFF} = 1.0 V	V _{EE} = -9.5 V I _{OH} = -0.2 mA
I _{CEX}	Output Leakage Current		80			100		200	μA	V _{CC} = 4.75 V *V _{DIFF} = 1.0 V	V _{EE} = -10.5 V V _{CEX} = 5.25 V
I _{SC}	Output Shorted Current	-1.3	-3.1	-1.4	-2.15	-3.2	-1.3	-3.1	mA	V _{CC} = 5.0 V *V _{DIFF} = 1.0 V	V _{EE} = -10 V V _{SC} = 0 V
I _{R(ENABLE)}	Enable Input Leakage Current					5		10	μA	V _{CC} = 4.75 V S ₃ = 4.75 V	V _{EE} = -10.5 V V _R = 4.0 V
I _{F(ENABLE)}	Enable Input Forward Current		-1.5		-0.96	-1.5		-1.5	mA	V _{CC} = 5.25 V S ₃ = 0 V	V _{EE} = -9.5 V V _F = 0 V
I _{F(+Input)}	+ Input Forward Current		-2.6		-1.67	-2.4		-2.3	mA	V _{CC} = 5.0 V - Input = Gnd	V _{EE} = -10 V V _F = 0 V
I _{F(-Input)}	- Input Forward Current		-2.9		-1.87	-2.7		-2.6	mA	V _{CC} , S ₃ = 5.0 V + Input = Gnd	V _{EE} = -10 V V _F = 0 V
V _{IL(ENABLE)}	Input Low Voltage		1.2		1.4	1.0		0.85	V	V _{CC} = 5.0 V ±5% V _{EE} = -10 V ±5%	
V _{th}	Differential Input Threshold Voltage	1.0	2.0	1.0	1.5	2.0	1.0	2.0	V	V _{CC} = 5.0 V ±5% V _{EE} = -10 V ±5%	
V _{CM}	Common Mode Voltage			-7.5	±12	+7.5			V	V _{CC} = 5.0 V *V _{DIFF} = 1.0 V or 2.0 V	V _{EE} = -10 V
R _{I30Ω}	Terminating Resistance			91	130	185			Ω		
I _{CC}	5 V Supply Current				13.7	22.9			mA	V _{CC} = 5.25 V S ₃ , +Inputs = 5.25 V, -Inputs = 0 V	V _{EE} = -10.5 V
I _{EE}	-10 V Supply Current				-6.5	-11.1			mA	V _{CC} = 5.25 V S ₃ , +Inputs = 5.25 V, -Inputs = 0 V	V _{EE} = -10.5 V
t _{pd+}	Turn-off Time				38	100			ns	V _{CC} = 5.0 V V _{IN} 0→3.0 V, R _L = 3.9 kΩ, C _L = 30 pF	V _{EE} = -10 V
t _{pd-}	Turn-on Time				35	100			ns	V _{CC} = 5.0 V V _{IN} 0→3.0 V, R _L = 0.39 kΩ, C _L = 30 pF	V _{EE} = -10 V

* V_{DIFF} is a differential input voltage referred from A+ to A- and from B+ to B-.


SWITCHING TIME TEST CIRCUIT












WAVEFORMS



STANDARD USAGE



TYPICAL ELECTRICAL CHARACTERISTICS

OUTPUT LOW VOLTAGE
VERSUS
OUTPUT LOW CURRENTOUTPUT HIGH VOLTAGE
VERSUS
OUTPUT HIGH CURRENTLOGIC LEVELS VERSUS
AMBIENT TEMPERATURE $V_{OUT} - V_{DIFF}$ TRANSFER
CHARACTERISTICSOUTPUT VOLTAGE
VERSUS
COMMON MODE VOLTAGEINPUT CURRENT VERSUS
INPUT VOLTAGETURN ON TIME VERSUS
AMBIENT TEMPERATURETURN OFF TIME VERSUS
AMBIENT TEMPERATUREPOWER DISSIPATION VERSUS
AMBIENT TEMPERATURE

μA9624 • μA9625

DUAL TTL, MOS INTERFACE ELEMENTS

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA9624 is a dual two-input TTL compatible interface gate specifically designed to drive MOS. The output swing is adjustable and will allow it to be used as a data driver, clock driver or discrete MOS driver. It has an active output for driving medium capacitive loads.

The μA9625 is a dual MOS to TTL level converter. It is designed to convert standard negative MOS logic levels to TTL levels. The μA9625 features a high input impedance which allows preservation of the driving MOS logic level.

Both the μA9624 and μA9625 are available in the 14-pin Ceramic Dual In-Line Package and the 1/4 x 1/4 Flatpak.



NOTE: The TTL and MOS devices manufactured by Fairchild Semiconductor are considered as positive TRUE logic (the more positive voltage level is assigned the binary state of "1" or TRUE). Following MIL-STD-806B logic symbol specifications, the μA9624 is represented as a NAND gate and the μA9625 as a non-inverting buffer. This convention (of assuming MOS as a positive TRUE logic) has not been uniformly accepted by the industry; therefore, it is necessary to note that with negative TRUE MOS logic (the more negative voltage level is assigned the binary state "1" or TRUE), the μA9624 acts as an AND gate and the μA9625 as an inverter.

- **TTL COMPATIBLE INPUTS/OUTPUT**
- **MOS COMPATIBLE OUTPUT/INPUTS**
- **LOW POWER**

ABSOLUTE MAXIMUM RATINGS (above which the useful life may be impaired)

Storage Temperature	−65°C to +150°C
Temperature (Ambient) Under Bias	−55°C to +125°C
V _{CC} Pin Potential to Ground Pin	V _{DD} to +10 V
Voltage Applied to Outputs for High Output State (μA9624)	V _{DD} to +V _{CC} value
Voltage Applied to Outputs for High Output State (μA9625)	−0.5 V to V _{CC} value
Input Voltage (D.C.) (μA9624)	−0.5 V to +5.5 V
Input Voltage (D.C.) (μA9625)	V _{CC} to V _{DD}
V _{DD} Pin Potential to Ground Pin	−30 V to +0.5 V
V _{DD} Pin Potential to Tap Pin (μA9624)	−30 V to +0.5 V
V _{TAP}	V _{CC} +0.5 V
Internal Power Dissipation (Note 3)	
Ceramic DIP	670 mW
Flatpak	570 mW
Lead Temperature (Soldering, 60 seconds)	300°C


ORDER INFORMATION — Specify U6A9624XXX and U6A9625XXX for 14-pin TO-116 Dual In-Line Package or U3I9624XXX and U3I9625XXX for 14-pin Flatpak where XXX is 51X for the −55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.



Notes on following page.

TYPICAL DUAL IN-LINE PACKAGE

In Accordance With
JEDEC (TO-116) Outline




NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers.
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for a conventional .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams

FLATPAK

in accordance with JEDEC (TO-86) outline
14 Lead CERPAK



NOTES:

- All dimensions in inches
- Leads are gold-plated kovar
- Package weight is 0.26 gram

TABLE I—

ELECTRICAL CHARACTERISTICS ($T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS	
		−55°C		+25°C		+125°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.			MAX.
V _{OH1}	Output High Voltage	−1.0		−1.0	−0.5		−1.0		Volts	V _{CC} = 4.5 V, V _{DD} = −28 V, V _{TAP} = 0 V I _{OH} = −10 μA
V _{OH2}	Output High Voltage	+3.5		+3.5	+4.0		+3.5			V _{CC} = 5.5 V, V _{DD} = −20 V, V _{TAP} = 5.5 V Inputs at threshold voltages (V _{IL}) I _{OH} = −10 μA
V _{OL}	Output Low Voltage			See Note 1					Volts	V _{CC} = 4.5 V, I _{OL} = 10 mA, V _{DD} = −15 to −28 V @ V _{IH} , 0 ≤ V _{TAP} ≤ V _{CC} (Note 2)
V _{IH}	Input High Voltage	2.1		1.9			1.7		Volts	Guaranteed input high threshold for all inputs
V _{IL}	Input Low Voltage		1.4			1.1		0.8	Volts	Guaranteed input low threshold for all inputs
I _F	Input Load Current		−1.40			−1.25		−1.13	mA	V _{CC} = 5.5 V, V _F = 0.4 V V _{DD} = −11 to −28 V
I _R	Input Leakage Current		2.0			2.0		5.0	μA	V _{CC} = 5.5 V, V _R = 4.0 V V _{DD} = −11 to −28 V
I _{CEX}	Output Leakage Current					50			μA	V _{CC} = 5.5 V, V _{TAP} = 0 V V _{DD} = −28 V, V _{OUT} = 0 V
I _{SC}	Output Short Circuit Current	−12	−31	−14		−32	−11	−28	mA	V _{CC} = 4.5 V, V _{TAP} = 0 V, V _{IN} = 0 V V _{DD} = −11 V, V _{OUT} = −11 V
I _{VCC}	V _{CC} Supply Current					6.1			mA	V _{CC} = 5.5V, V _{DD} = −15 V, V _{TAP} = 0 V Inputs Open
I _{MAX}	Max. Current					10			mA	V _{CC} = 10 V, V _{DD} = −30 V, Inputs Open V _{TAP} = 0 V
t _{pd+}	Switching Speed				190	250			ns	V _{CC} = 5.0 V, See Figure 2
t _{pd−}	Switching Speed				50	100			ns	V _{DD} = −13 V, V _{TAP} = 0 V

NOTES

1. $\text{Max} = V_{DD} + 1.0\text{ V}$ over Temperature Range. $\text{Typ} = V_{DD} + 0.2\text{ V}$ over Temperature Range.
2. At no time shall the voltage from V_{DD} to V_{TAP} exceed 30 volts. See Absolute Maximum Ratings on Page 1.
3. Rating applies to ambient temperatures up to 70°C . Above 70°C derate linearly at $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak package.


 μ A9624 SCHEMATIC DIAGRAM

Fig. 1


TABLE II —

 ELECTRICAL CHARACTERISTICS ($T_A = 0^\circ\text{C}$ to $+75^\circ\text{C}$, $V_{CC} = 5.0\text{ V} \pm 5\%$)


SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS
		0°C		+25°C		+75°C			
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.		
V _{OH1}	Output High Voltage	-1.0		-1.0 -0.5		-1.0		Volts	V _{CC} = 4.75 V, V _{DD} = -28 V, V _{TAP} = 0 V I _{OH} = -10 μA
V _{OH2}	Output High Voltage	+3.25		+3.25 +3.75		+3.25		Volts	V _{CC} = 5.25 V, V _{DD} = -20 V, V _{TAP} = 5.25 V I _{OH} = -10 μA Inputs at threshold voltages (V _{IL} or V _{IH})
V _{OL}	Output Low Voltage			See Note 1				Volts	V _{CC} = 4.5 V, I _{OL} = 10 mA, V _{DD} = -11 to -28 V @ 0 ≤ V _{TAP} ≤ V _{CC} (Note 2)
V _{IH}	Input High Voltage	2.0		1.9		1.8		Volts	Guaranteed input high threshold for all inputs
V _{IL}	Input Low Voltage	1.2		1.1		0.95		Volts	Guaranteed input low threshold for all inputs
I _F	Input Load Current	-1.32		-1.25		-1.20		mA	V _{CC} = 5.25 V, V _F = 0.45 V
I _R	Input Leakage Current	5.0		5.0		10		μA	V _{CC} = 5.25 V, V _R = 4.5 V
I _{CEX}	Output Leakage Current			100				μA	V _{CC} = 5.25 V, V _{TAP} = 0 V V _{DD} = -28 V, V _{OUT} = 0 V
I _{SC}	Output Short Circuit Current	-12	-31	-14		-32	-12 -31	mA	V _{CC} = 4.75 V, V _{TAP} = 0 V, V _{IN} = 0 V V _{DD} = -11 V, V _{OUT} = -11 V
I _{VCC}	V _{CC} Supply Current			6.1				mA	V _{CC} = 5.25 V, V _{DD} = -15 V, V _{TAP} = 0 V Input Open
I _{MAX}	Max. Current			10				mA	V _{CC} = 10 V, V _{DD} = -30 V, V _{TAP} = 0 V Input Open
t _{pd+}	Switching Speed			190 250				ns	V _{CC} = 5.0 V, See Figure 2
t _{pd-}	Switching Speed			50 100				ns	V _{DD} = -13 V, V _{TAP} = 0 V

 TYPICAL ELECTRICAL CHARACTERISTICS • $\mu A9624$


THRESHOLD VOLTAGE VERSUS AMBIENT TEMPERATURE




OUTPUT CURRENT VERSUS OUTPUT VOLTAGE (LOW STATE)




OUTPUT CURRENT VERSUS OUTPUT VOLTAGE (HIGH STATE)




POWER DISSIPATION VERSUS AMBIENT TEMPERATURE



SWITCHING TIME VERSUS LOAD CAPACITANCE



SWITCHING TIME VERSUS AMBIENT TEMPERATURE



SWITCHING TIME TEST CIRCUIT AND WAVEFORMS μ A9624





Fig. 2


LOADING RULES:




*The extender pin allows the number of inputs to be extended by adding diodes or the DT μ L 933 extender.

**Fan out into MOS is limited only by MOS leakage currents.

APPLICATION:



CLOCK DRIVING (using a high capacitance drive scheme)



TYPICAL SWITCHING TIMES VERSUS LOAD CAPACITANCE




TABLE III —

 ELECTRICAL CHARACTERISTICS ($T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS
		−55°C		+25°C		+125°C			
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.		
V _{OH}	Output High Voltage	2.5		2.6		2.5		Volts	V _{CC} = 4.5 V, I _{OH} = −60 μA V _{DD} = −11 V Inputs at threshold voltages (V _{IH})
V _{OL}	Output Low Voltage	0.5		0.5		0.5		Volts	V _{CC} = 5.5 V, I _{OL} = 1.5 mA V _{CC} = 4.5 V, I _{OL} = 1.2 mA V _{DD} = −11 V Inputs at threshold voltages (V _{IL})
V _{IH}	Input High Voltage	−3.0		−3.0		−3.0		Volts	Guaranteed input high threshold for all inputs
V _{IL}	Input Low Voltage	−9.0		−9.0		−9.0		Volts	Guaranteed input low threshold for all inputs
I _F	Input Load Current	210		210		210		μA	V _{CC} = 5.0 V, V _F = −3.0 V, V _{DD} = −13 V
I _{CEX}	Output Leakage Current			50				μA	V _{CC} = V _{CEX} = 4.5 V, V _{DD} = −13 V
I _{VCCL}	Supply Current			4.8				mA	V _{CC} = 5.5 V, V _{DD} = −15 V, V _{IN} = −10 V
I _{VCCH}	Supply Current			2.1					V _{CC} = 5.5 V, V _{DD} = −15 V, V _{IN} = 0 V
I _{VDD}	V _{DD} Supply Current			−9.0				mA	V _{CC} = 5.5 V, V _{DD} = −15 V Input open or gnd
I _{MAX}	Max. V _{DD} Supply Current			−25				mA	V _{CC} = 8.0 V, V _{DD} = −20 V, V _{IN} = 0 V
t _{pd+}	Switching Speed			55 100				ns	V _{CC} = 5.0 V, V _{DD} = −13 V
t _{pd−}	Switching Speed			90 150				ns	See Figure 4





 μ A9625 SCHEMATIC DIAGRAM


Fig. 3


TABLE IV —

ELECTRICAL CHARACTERISTICS ($T_A = 0^\circ\text{C}$ to $+75^\circ\text{C}$, $V_{CC} = 5.0\text{ V} \pm 5\%$)

SYMBOL	CHARACTERISTICS	LIMITS						UNITS	CONDITIONS
		0°C		+25°C		+75°C			
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.		
V _{OH}	Output High Voltage	2.5		2.6		2.5		Volts	V _{CC} = 4.75 V, I _{OH} = −60 μA V _{DD} = −11 V Inputs at threshold voltages (V _{IH})
V _{OL}	Output Low Voltage	0.5		0.5		0.5		Volts	V _{CC} = 5.25 V, I _{OL} = 1.52 mA V _{CC} = 4.75 V, I _{OL} = 1.33 mA Inputs at threshold voltages (V _{IL})
V _{IH}	Input High Voltage	−3.0		−3.0		−3.0		Volts	Guaranteed input high threshold for all inputs
V _{IL}	Input Low Voltage	−9.0		−9.0		−9.0		Volts	Guaranteed input low threshold for all inputs
I _F	Input Load Current	210		210		210		μA	V _{CC} = 5.0 V, V _F = −3.0 V, V _{DD} = −13 V
I _{CEX}	Output Leakage Current			100				μA	V _{CC} = V _{CEX} = 4.75 V, V _{DD} = −13 V
I _{VCCL}	Supply Current			4.8				mA	V _{CC} = 5.25 V, V _{DD} = −15 V, V _{IN} = −10 V
I _{VCCH}	Supply Current			2.1				mA	V _{CC} = 5.25 V, V _{DD} = −15 V, V _{IN} = 0 V
I _{VDD}	V _{DD} Supply Current			−9.0				mA	V _{CC} = 5.5 V, V _{DD} = −15 V Input open or gnd
I _{MAX}	Max. V _{DD} Supply Current			−25				mA	V _{CC} = 8.0 V, V _{DD} = −20 V, V _{IN} = 0 V
t _{pd+}	Switching Speed			55 100				ns	V _{CC} = 5.0 V, V _{DD} = −13 V
t _{pd−}	Switching Speed			90 150				ns	See Figure 4

TYPICAL ELECTRICAL CHARACTERISTICS • μA9625 

SWITCHING TIME TEST CIRCUIT AND WAVEFORMS



TESTS	CONDITIONS			
t_{pd+} , t_{pd-}	T_A ($^\circ\text{C}$)	V_{CC} (Volts)	V_{DD} (Volts)	R ($\text{k}\Omega$)
	25	5.0	-13	3.75

Fig. 4

μA9644

DUAL HIGH-VOLTAGE, HIGH CURRENT DRIVER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The μA9644 is a Dual 4-Input NAND Gate whose output can sink 500 mA in the low state, and maintain 30 volts in the high state. The outputs are uncommitted collectors in a Darlington configuration which have typical saturation voltages of 0.8 volts at low currents and 1.2 volts at 500 mA. The inputs are TTL Compatible and feature input clamp diodes. The input fan-in requirement is typically 1/2 a normal DTL Unit Load. An input strobe common to both gates is provided, and an expander input node on each gate is available for input diode expansion. Separate ground pins are provided for each gate to minimize ground pin offset voltages at high current levels.

- 500 mA CURRENT SINKING CAPABILITY
- OUTPUT VOLTAGES UP TO 30 VOLTS
- LOW AVERAGE POWER, TYPICALLY 30 mW PER GATE
- HIGH SPEED, TYPICALLY 50 ns DELAY TIMES
- TTL COMPATIBLE INPUTS
- INPUT CLAMP DIODES
- LOW FAN-IN LOADING REQUIREMENTS
- COMMON STROBE INPUT
- EXPANDER NODE FOR INPUT DIODE EXPANSION

ABSOLUTE MAXIMUM RATING

Storage Temperature	-65°C to +175°C
Temperature (Ambient) Under Bias	-55°C to +125°C
V _{CC} Pin Potential to Ground Pin	-0.5 V to +8.0 V
Input Voltages (D.C.)	-0.5 V to +5.5 V
Voltage Applied to Outputs (Output High)	-0.5 V to +30 V
Output Current (D.C.) (Output Low)	640 mA
Internal Power Dissipation (Note)	730 mW
Lead Temperature (Soldering, 60 seconds)	300°C

See Safe Area

NOTE

Rating applies to ambient temperatures up to 70°C. Above 70°C derate linearly at 8.3 mW/°C for the Ceramic DIP

ORDER INFORMATION — Specify U7B9644XXX for 16-pin Dual In-Line Package where XXX is 51X for the -55°C to +125°C temperature range, or 59X for the 0°C to +75°C temperature range.

LOGIC DIAGRAM





Fig. 1

PHYSICAL DIMENSIONS

16 Lead MSI Dual In-Line



NOTES:

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for a conventional .020 inch diameter lead
- Leads are tin plated kovar
- Package weight is 2.2 grams
- *The .037 dimension does not apply to the corner leads

Fig. 2

CONNECTION DIAGRAM




Fig. 3


ELECTRICAL CHARACTERISTICS ($T_A = -55^\circ\text{C}$ to $+125^\circ\text{C}$, $V_{CC} = 5.0\text{ V} \pm 10\%$)

SYMBOL	CHARACTERISTIC	LIMITS						UNITS	CONDITIONS	
		−55°C		+25°C		+125°C				
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.		
V _{OL}	Output Low Voltage	1.7		1.25	1.5		1.5		Volts	V _{CC} = 4.5 V, I _{OL} = 500 mA, Inputs = V _{IH}
				0.8	1.0				Volts	V _{CC} = 5.0 V, I _{OL} = 100 mA, Inputs = V _{IH}
I _{CEX}	Output Leakage Current			<1.0	200		500		μA	V _{CC} = 5.5 V, V _{CEX} = 30 V, V _{IN} = V _{IL}
I _R	Input Reverse Current			<1.0	2.0		5.0		μA	V _{CC} = 5.5 V, V _{IN} = 4.5 V, Other Inputs = Gnd
I _F	Input Forward Current	−0.75		−0.18	−0.75		−0.75		mA	V _{CC} = 5.5 V, V _{IN} = 0.4 V
I _{RS}	Strobe Reverse Current			<1.0	4.0		10		μA	V _{CC} = 5.5 V, V _{IN} = 4.5 V, Other Inputs = Gnd
I _{FS}	Strobe Forward Current	−1.5		−0.36	−1.5		−1.5		mA	V _{CC} = 5.5 V, V _{IN} = 0.4 V
I _{FX}	Expander Node Forward Current			−2.68	−3.9				mA	V _{CC} = 5.5 V, V _{IN} = 0.4 V
I _{CC}	V _{CC} Current (Gate On)			20.4	30				mA	V _{CC} = 5.5 V, Inputs = Open
I _{MAX}	Max. V _{CC} Rating			7.0	12				mA	V _{CC} = 8.0 V, Inputs = Gnd
V _{F3}	Input Clamp Diode Voltage			−0.8	−1.5				Volts	V _{CC} = 4.5 V, I _{IN} = −10 mA, Other Inputs = Open
V _{IL}	Input Low Voltage	1.3		1.1	1.0		0.7		Volts	Guaranteed Input Low Threshold
V _{IH}	Input High Voltage	2.3		2.1	1.7		1.9		Volts	Guaranteed Input High Threshold
t _{pd+}	Propagation Delay			50	100				ns	V _{CC} = 5.0 V, C _L = 40 pF,
t _{pd−}	Propagation Delay			50	100				ns	R _L = 75 Ω to +30 V (See Fig. 3)

ELECTRICAL CHARACTERISTICS ($T_A = 0^\circ\text{C}$ to $+75^\circ\text{C}$, $V_{CC} = 5.0 \pm 5\%$)

SYMBOL	CHARACTERISTIC	LIMITS						UNITS	CONDITIONS
		0°C		+25°C		+75°C			
		MIN.	MAX.	MIN.	TYP.	MAX.	MIN.	MAX.	
V _{OL}	Output Low Voltage	1.6		1.25	1.5	1.5		Volts	V _{CC} = 4.75 V, I _{OL} = 500 mA, Inputs = V _{IH}
				0.8	1.0			Volts	V _{CC} = 5.0 V, I _{OL} = 100 mA, Inputs = V _{IH}
I _{CEX}	Output Leakage Current			<1.0	250	500		μA	V _{CC} = 5.25 V, V _{CEX} = 30 V, V _{IN} = V _{IL}
I _R	Input Reverse Current			<1.0	5.0	10		μA	V _{CC} = 5.25 V, V _{IN} = 4.5 V, Other Inputs = Gnd
I _F	Input Forward Current	−0.75		−0.18	−0.75	−0.75		mA	V _{CC} = 5.25 V, V _{IN} = 0.45 V
I _{RS}	Strobe Reverse Current			<1.0	10	20		μA	V _{CC} = 5.25 V, V _{IN} = 4.5 V, Other Inputs = Gnd
I _{FS}	Strobe Forward Current	−1.5		−0.36	−1.5	−1.5		mA	V _{CC} = 5.25 V, V _{IN} = 0.45 V
I _{FX}	Expander Node Forward Current			−2.68	−3.9			mA	V _{CC} = 5.25 V, V _{IN} = 0.45 V
I _{CC}	V _{CC} Current (Gate On)			20.4	30			mA	V _{CC} = 5.25 V, Inputs = Open
I _{MAX}	Max. V _{CC} Rating			7.0	12.8			mA	V _{CC} = 8.0 V, Inputs = Gnd
V _{F3}	Input Clamp Diode Voltage			−0.8	−1.5			Volts	V _{CC} = 4.75 V, I _{IN} = −10 mA, Other Inputs = Open
V _{IL}	Input Low Voltage	0.85		1.1	0.85	0.75		Volts	Guaranteed Input Low Threshold
V _{IH}	Input High Voltage	2.2		2.1	1.7	2.1		Volts	Guaranteed Input High Threshold
t _{pd+}	Propagation Delay			50	200			ns	V _{CC} = 5.0 V, C _L = 40 pF,
t _{pd−}	Propagation Delay			50	200			ns	R _L = 75 Ω to +30 V (See Fig. 3)

TYPICAL ELECTRICAL CHARACTERISTICS

OUTPUT LOW VOLTAGE VERSUS
INPUT LOW CURRENT

SAFE AREA CURVE













OUTPUT LOW VOLTAGE VERSUS
AMBIENT TEMPERATUREOUTPUT VOLTAGE VERSUS
INPUT VOLTAGE AND
SUPPLY VOLTAGEOUTPUT VOLTAGE VERSUS
INPUT VOLTAGE
AND TEMPERATURECOLLECTOR CUTOFF CURRENT
VERSUS INPUT VOLTAGESUPPLY CURRENT VERSUS
SUPPLY VOLTAGESUPPLY CURRENT VERSUS
AMBIENT TEMPERATUREINPUT CURRENT VERSUS
INPUT VOLTAGEPROPAGATION DELAY VERSUS
AMBIENT TEMPERATURECURRENT SINKING DERATING
CURVE

Fig. 3 — SWITCHING CIRCUIT AND WAVEFORMS




Input Requirements:


Frequency ≈ 100 kHz
 Amplitude 3 ± 0.1 V
 Pulse Width ≈ 500 ns
 Rise Time ≤ 10 ns
 Fall Time ≤ 10 ns

$R_L = 75 \Omega$
 $C_L = 40$ pF

APPLICATIONS



MULTIPLE LAMP DRIVING




The clamp diode must be capable of keeping the $\mu A9644$ within its SAFE AREA. The clamp diode must handle all the coil current.

RELAY DRIVING

+V	$R_{COIL} \text{ (min)}$	I_{max}
28 V	280 Ω	100 mA
24 V	160 Ω	150 mA
18 V	57 Ω	300 mA
15 V	35 Ω	400 mA
12 V	22 Ω	500 mA
6 V	10 Ω	500 mA
5 V	8 Ω	500 mA

FAIRCHILD LINEAR INTEGRATED CIRCUITS

- PRECISION MONOLITHIC MATCHING
- DESIGN FLEXIBILITY
- CUSTOM APPLICATIONS

[illegible]

237

- MATCHED MONOLITHIC GENERAL PURPOSE TRANSISTORS
- h_{FE} MATCHED $\pm 10\%$
- V_{BE} MATCHED ± 2 mV CA3018A (± 5 mV CA3018)
- OPERATION FROM DC TO 120 MHz

- WIDE OPERATING CURRENT RANGE
- CA3018A PERFORMANCE CHARACTERISTICS CONTROLLED FROM $10 \mu A$ TO 10 mA
- LOW NOISE FIGURE — 3.2 dB TYPICAL AT 1 kHz
- FULL MILITARY TEMPERATURE RANGE CAPABILITY (-55 TO $+125^\circ C$)

APPLICATIONS

- General Use in Signal Processing Systems in DC Through VHF Range
- Custom Designed Differential Amplifiers
- Temperature Compensated Amplifiers

ABSOLUTE MAXIMUM RATINGS

Power Dissipation (Note 1)

Any One Transistor

Total Package

Temperature Range

Operating Temperature

Storage Temperature

The following ratings apply for each transistor in the device:

Collector-to-Emitter Voltage, V_{CEO} Collector-to-Base Voltage, V_{CBO} Collector-to-Substrate Voltage, V_{CISO} (Note 2)Emitter-to-Base Voltage, V_{EBO} Collector Current, I_C **CA3018**

300 mW

450 mW

 $-55^\circ C$ to $+125^\circ C$ $-65^\circ C$ to $+200^\circ C$

15 V

20 V

20 V

5 V

50 mA

CA3018A

300 mW

450 mW

 $-55^\circ C$ to $+125^\circ C$ $-65^\circ C$ to $+200^\circ C$


15 V

30 V

40 V

5 V

50 mA

EQUIVALENT CIRCUIT**ELECTRICAL CHARACTERISTICS** ($T_A = 25^\circ C$ unless otherwise specified)

PARAMETER	UNIT	CONDITIONS	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	UNITS
CA3018									
Collector-Cutoff Current	I_{CBO}	$V_{CB} = 10$ V, $I_E = 0$		0.002	100		0.002	40	nA
Collector-Cutoff Current	I_{CEO}	$V_{CE} = 10$ V, $I_B = 0$		See Curve	5		See Curve	0.5	μA
Collector-Cutoff Current Darlington Pair	I_{CEOD}	$V_{CE} = 10$ V, $I_B = 0$						5	μA
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1$ mA, $I_B = 0$	15	24		15	24		V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10 \mu A$, $I_E = 0$	20	60		30	60		V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10 \mu A$, $I_C = 0$	5	7		5	7		V
Collector-to-Substrate Breakdown Voltage	$V_{(BR)CIO}$	$I_C = 10 \mu A$, $I_{CI} = 0$	20	60		40	60		V
Collector-to-Emitter Saturation Voltage	V_{CES}	$I_B = 1$ mA, $I_C = 10$ mA		0.23			0.23	0.5	V
Static Forward Current Transfer Ratio	h_{FE}	$V_{CE} = 3$ V, $\begin{cases} I_C = 10 \text{ mA} \\ I_C = 1 \text{ mA} \\ I_C = 10 \mu A \end{cases}$	30	100	54	50	100	60	
Magnitude of Static-Beta Ratio (Isolated Transistors Q_1 and Q_2)		$V_{CE} = 3$ V, $I_{C1} = I_{C2} = 1$ mA	0.9	0.97		0.9	0.97		
Static Forward Current Transfer Ratio Darlington Pair (Q_3 & Q_4)	h_{FED}	$V_{CE} = 3$ V, $\begin{cases} I_C = 1 \text{ mA} \\ I_C = 100 \mu A \end{cases}$	1500	5400		2000	5400	1000	
Base-to-Emitter Voltage	V_{BE}	$V_{CE} = 3$ V, $\begin{cases} I_E = 1 \text{ mA} \\ I_E = 10 \text{ mA} \end{cases}$		0.715	0.800	0.600	0.715	0.800	V
Input Offset Voltage	$\begin{vmatrix} V_{BE1} \\ V_{BE2} \end{vmatrix}$	$V_{CE} = 3$ V, $I_E = 1$ mA		0.48	5		0.48	2	mV
Temperature Coefficient: Base-to-Emitter Voltage Q_1, Q_2	$\frac{\Delta V_{BE}}{\Delta T}$	$V_{CE} = 3$ V, $I_E = 1$ mA		-1.9			-1.9		mV/ $^\circ C$
Base (Q_3)-to-Emitter (Q_4) Voltage-Darlington Pair	V_{BED} (V_{9-1})	$V_{CE} = 3$ V, $\begin{cases} I_E = 10 \text{ mA} \\ I_E = 1 \text{ mA} \end{cases}$		1.46	1.32	1.10	1.46	1.60	V
Temperature Coefficient: Base-to-Emitter Voltage Darlington Pair- Q_3, Q_4	$\frac{\Delta V_{BED}}{\Delta T}$	$V_{CE} = 3$ V, $I_E = 1$ mA		4.4			4.4		mV/ $^\circ C$
Temperature Coefficient of Input-Offset Voltage	$\frac{V_{BE1} - V_{BE2}}{\Delta T}$	$V_{CC} = +6$ V, $V_{EE} = -6$ V,		10			10		$\mu V/^\circ C$

NOTES1. Derate at $5 \text{ mW}/^\circ C$ for $T_A > 85^\circ C$.


2. Substrate must be connected to the most negative voltage to maintain normal operation.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
Low Frequency Noise Figure	NF	$f = 1\text{ kHz}, V_{CE} = 3\text{ V}, I_C = 100\text{ }\mu\text{A}$ Source resistance = $1\text{ k}\Omega$		3.25		dB
Low-Frequency, Small-Signal Equivalent Circuit Characteristics:						
Forward Current-Transfer Ratio	h_{fe}			110		
Short-Circuit Input Impedance	h_{ie}	$f = 1\text{ kHz}, V_{CE} = 3\text{ V}, I_C = 1\text{ mA}$		3.5		$\text{k}\Omega$
Open-Circuit Output Impedance	h_{oe}			15.6		μmho
Open-Circuit Reverse Voltage-Transfer Ratio	h_{re}			1.8×10^{-4}		
Admittance Characteristics:						
Forward Transfer Admittance	Y_{fe}			$31 - j1.5$		mmho
Input Admittance	Y_{ie}	$f = 1\text{ MHz}, V_{CE} = 3\text{ V}, I_C = 1\text{ mA}$		$0.3 + j0.04$		mmho
Output Admittance	Y_{oe}			$0.001 + j0.03$		mmho
Reverse Transfer Admittance	Y_{re}			See Curve		mmho
Gain-Bandwidth Product	f_T	$V_{CE} = 3\text{ V}, I_C = 3\text{ mA}$	300	500		MHz
Emitter-to-Base Capacitance	C_{eb}	$V_{EB} = 3\text{ V}, I_E = 0$		0.6		pF
Collector-to-Base Capacitance	C_{Cl}	$V_{CB} = 3\text{ V}, I_C = 0$		0.58		pF
Collector-to-Substrate Capacitance	C_{Cl}	$V_{Cl} = 3\text{ V}, I_C = 0$		2.8		pF

TYPICAL PERFORMANCE CURVES


COLLECTOR-TO-BASE CUTOFF CURRENT VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR




COLLECTOR-TO-EMITTER CUTOFF CURRENT VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR




STATIC FORWARD CURRENT-TRANSFER AND BETA RATIO FOR TRANSISTORS Q1, Q2 VERSUS EMITTER CURRENT




STATIC FORWARD CURRENT-TRANSFER RATIO FOR DARLINGTON CONNECTED TRANSISTORS Q3, Q4 VERSUS EMITTER CURRENT



STATIC BASE-TO-EMITTER VOLTAGE AND INPUT OFFSET VOLTAGE FOR Q1, Q2 VERSUS EMITTER CURRENT




STATIC INPUT VOLTAGE FOR DARLINGTON PAIR Q3, Q4 VERSUS EMITTER CURRENT




TYPICAL PERFORMANCE CURVES


OFFSET VOLTAGE CHARACTERISTIC VERSUS AMBIENT TEMPERATURE












BASE-TO-EMITTER VOLTAGE CHARACTERISTIC FOR EACH TRANSISTOR VERSUS AMBIENT TEMPERATURE



STATIC INPUT VOLTAGE FOR DARLINGTON PAIR (Q3, Q4) VERSUS AMBIENT TEMPERATURE




TYPICAL DYNAMIC CHARACTERISTICS FOR EACH TRANSISTOR

GAIN-BANDWIDTH PRODUCT (f_T) VERSUS COLLECTOR CURRENTNORMALIZED h PARAMETERS VERSUS COLLECTOR CURRENTFORWARD TRANSFER ADMITTANCE (Y_{fe}) VERSUS FREQUENCYINPUT ADMITTANCE (Y_{ie}) VERSUS FREQUENCYOUTPUT ADMITTANCE (Y_{oe}) VERSUS FREQUENCYREVERSE TRANSFER ADMITTANCE (Y_{re}) VERSUS FREQUENCYNOISE FIGURE VERSUS COLLECTOR CURRENT, $R_S = 500 \Omega$ NOISE FIGURE VERSUS COLLECTOR CURRENT, $R_S = 1 k\Omega$ NOISE FIGURE VERSUS COLLECTOR CURRENT, $R_S = 10 k\Omega$ 

- EXCELLENT DIODE MATCHING – 1 mV TYP.
- LOW REVERSE LEAKAGE CURRENT – 5 mA TYP.

EQUIVALENT CIRCUIT



APPLICATIONS

- Modulator
- Mixer
- Balanced Modulator
- Analog Switch
- Diode Gate for Chopper-Modulator Applications

ABSOLUTE MAXIMUM RATINGS

Power Dissipation		
For each Diode		20 mW
Total For Device		120 mW
Temperature Range		
Storage Temperature		-65°C to +200°C
Operating Temperature		-55°C to +125°C
Voltage (Note 1)		18 V







ELECTRICAL CHARACTERISTICS (For each diode, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
DC Forward Voltage Drop	V_F	DC Forward Current, $I_F = 1\text{ mA}$		0.73	0.78	V
DC Reverse Breakdown Voltage	$V_{(BR)R}$	DC Reverse Current, $I_R = -10\text{ }\mu\text{A}$	4.0	6.0		V
DC Reverse Breakdown Voltage Between any Diode Unit and Substrate	$V_{(BR)R}$	DC Reverse Current, $I_R = -10\text{ }\mu\text{A}$	25	80		V
DC Reverse (Leakage) Current	I_R	DC Reverse Voltage, $V_R = -4\text{ V}$		0.0055	10	μA
DC Reverse (Leakage) Current Between any Diode Unit and Substrate	I_R	DC Reverse Voltage, $V_R = -4\text{ V}$		0.010	10	μA
Magnitude of Diode Offset Voltage (Difference in DC Forward Voltage Drops of any Two Diode Units)	$ V_{F1} - V_{F2} $	DC Forward Current, $I_F = 1\text{ mA}$		1.0	5.0	mV
Single Diode Capacitance	C_D	Frequency, $f = 1\text{ MHz}$ DC Reverse Voltage, $V_R = -2\text{ V}$		1.8		pF
Diode Quad-to-Substrate Capacitance	C_{DQ-1}	Frequency, $f = 1\text{ MHz}$ DC Reverse Voltage, V_R between Pins 2,5,6, or 8 of Diode Quad and Pin 7 (Substrate) = -2 V				
		Pin 2 or 6 to Pin 7		4.4		pF
		Pin 5 or 8 to Pin 7		2.7		pF
Series Gate Switching Pedestal Voltage	V_S			10		mV

NOTE

1. Substrate (Pin 7) must be connected to the most negative potential.


TYPICAL PERFORMANCE CURVES

DC FORWARD VOLTAGE DROP
(EACH DIODE) VERSUS
TEMPERATUREREVERSE (LEAKAGE) CURRENT
(EACH DIODE) VERSUS
TEMPERATUREDIODE CAPACITANCE
(EACH DIODE) VERSUS
REVERSE VOLTAGEDIODE QUAD-TO-SUBSTRATE
CAPACITANCE VERSUS
REVERSE VOLTAGEDIODE QUAD-TO-SUBSTRATE
CAPACITANCE VERSUS
REVERSE VOLTAGESERIES GATE SWITCHING
TEST SETUP

- LOW INPUT OFFSET VOLTAGE — ± 5 mV
- WIDEBAND OPERATION
- INDEPENDENTLY ACCESSIBLE INPUTS AND OUTPUTS
- TWO MATCHED DIFFERENTIAL AMPLIFIERS

APPLICATIONS

- Dual Sense Amplifiers
- Dual Schmitt Triggers
- Multifunction Combinations — RF/Mixer/Oscillator; Converter/IF
- IF Amplifiers (Differential and/or Cascode)
- Product Detectors
- Doubly Balanced Modulators and Demodulators

EQUIVALENT CIRCUIT

- Balanced Quadrature Detectors
- Cascade Limiters
- Synchronous Detectors
- Pairs of Balanced Mixers
- Synthesizer Mixers
- Balanced (Push-Pull) Cascode Amplifiers

ABSOLUTE MAXIMUM RATINGS (For Each Transistor)

Power Dissipation (Note 1)

Any One Transistor

Total Package

Temperature Range

Operating Temperature

Storage Temperature

CA3026

300 mW

600 mW

-55°C to +125°C

-65°C to +200°C

CA3054

300 mW

750 mW

0°C to +85°C

-25°C to +85°C

The following ratings apply for each transistor in the device

Collector-to-Emitter Voltage, V_{CEO} Collector-to-Base Voltage, V_{CBO} Collector-to-Substrate Voltage, V_{CIO} (Note 2)Emitter-to-Base Voltage, V_{EBO} Collector Current, I_C

15 V

20 V

20 V

5 V

50 mA

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified) CA3026 and CA3054







PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
For Each Differential Amplifier						
Input Offset Voltage	V_{IO}			0.45	5	mV
Input Offset Current	I_{IO}	$V_{CB} = 3$ V		0.3	2	μA
Input Bias Current	I_I			10	24	μA
Quiescent Operating Current Ratio	$I_{C(Q1)} \text{ or } I_{C(Q5)}$ $I_{C(Q2)} \text{ or } I_{C(Q6)}$	$I_{E(Q3)} = I_{E(Q4)} = 2$ mA		0.98 to 1.02		
Temperature Coefficient Magnitude of Input-Offset Voltage	$\Delta V_{IO} $ ΔT			1.1		$\mu\text{V}/^\circ\text{C}$
For Each Transistor						
DC Forward Base-to-Emitter Voltage	V_{BE}	$V_{CB} = 3$ V $I_C = 50$ μA 1 mA 3 mA 10 mA		0.630 0.715 0.750 0.800	0.700 0.800 0.850 0.900	V
Temperature Coefficient of Base-to-Emitter Voltage	ΔV_{BE} ΔT	$V_{CB} = 3$ V, $I_C = 1$ mA		-1.9		mV/ $^\circ\text{C}$
Collector-Cutoff Current	I_{CBO}	$V_{CB} = 10$ V, $I_E = 0$		0.002	100	nA
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1$ mA, $I_B = 0$	15	24		V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10$ μA , $I_E = 0$	20	60		V
Collector-to-Substrate Breakdown Voltage	$V_{(BR)CIO}$	$I_C = 10$ μA , $I_{CI} = 0$	20	60		V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10$ μA , $I_C = 0$	5	7		V

NOTES1. For $T_A > 55^\circ\text{C}$; CA3026 derates at 5 mW/ $^\circ\text{C}$ and CA3054 at 6.67 mW/ $^\circ\text{C}$

2. The collector of each transistor of the CA3026 and CA3054 is isolated from the substrate by an integral diode. Substrate must be connected to the most negative voltage to maintain normal operation.


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified) CA3026 and CA3054 (Continued)

PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
Common-Mode Rejection Ratio for Each Amplifier	CMR	$V_{CC} = 12\text{ V}$		100		dB
AGC Range, One Stage	AGC	$V_{EE} = -6\text{ V}$		75		dB
Voltage Gain, Single Stage Double-Ended Output	A	$V_X = -3.3\text{ V}$		32		dB
AGC Range, Two Stage	AGC	$f = 1\text{ kHz}$		105		dB
Voltage Gain, Two Stage Double-Ended Output	A			60		dB
Low-Frequency, Small-Signal Equivalent-Circuit Characteristics:						
(for Single Transistor)						
Forward Current-Transfer Ratio	h_{fe}			110		
Short-Circuit Input Impedance	h_{ie}	$f = 1\text{ kHz}, V_{CE} = 3\text{ V},$		3.5		$k\Omega$
Open-Circuit Output Impedance	h_{oe}	$I_C = 1\text{ mA}$		15.6		μmho
Open-Circuit Reverse Voltage-Transfer Ratio	h_{re}			1.8×10^{-4}		
1/f Noise Figure (for Single Transistor)	NF	$f = 1\text{ kHz}, V_{CE} = 3\text{ V}$		3.25		dB
Gain-Bandwidth Product (for Single Transistor)	f_T	$V_{CE} = 3\text{ V}, I_C = 3\text{ mA}$		550		MHz
Admittance Characteristics; Differential Circuit Configuration:						
(for Each Amplifier)						
Forward Transfer Admittance	Y_{21}	$V_{CB} = 3\text{ V}$		$-20 + j 0$		mmho
Input Admittance	Y_{11}	Each Collector		$0.22 + j 0.1$		mmho
Output Admittance	Y_{22}	$I_C \approx 1.25\text{ mA}$		$0.01 + j 0$		mmho
Reverse Transfer Admittance	Y_{12}	$f = 1\text{ MHz}$		$-0.003 + j 0$		mmho
Admittance Characteristics; Cascode Circuit Configuration:						
(for Each Amplifier)						
Forward Transfer Admittance	Y_{21}	$V_{CB} = 3\text{ V}$		$68 - j 0$		mmho
Input Admittance	Y_{11}	Total Stage		$0.55 + j 0$		mmho
Output Admittance	Y_{22}	$I_C \approx 2.5\text{ mA}$		$0 + j 0.02$		mmho
Reverse Transfer Admittance	Y_{12}	$f = 1\text{ MHz}$		$0.004 - j 0.005$		μmho
Noise Figure	NF	$f = 100\text{ MHz}$		8		dB


TYPICAL PERFORMANCE CURVES**COLLECTOR-TO-BASE CUTOFF CURRENT VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR****INPUT BIAS CURRENT CHARACTERISTIC VERSUS COLLECTOR CURRENT FOR EACH TRANSISTOR****BASE-TO-EMITTER VOLTAGE CHARACTERISTIC FOR EACH TRANSISTOR VERSUS AMBIENT TEMPERATURE****OFFSET VOLTAGE CHARACTERISTIC VERSUS AMBIENT TEMPERATURE FOR DIFFERENTIAL PAIRS****STATIC BASE-TO-EMITTER VOLTAGE CHARACTERISTIC AND INPUT OFFSET VOLTAGE FOR DIFFERENTIAL PAIRS VS EMITTER CURRENT****INPUT OFFSET CURRENT FOR MATCHED DIFFERENTIAL PAIRS VERSUS COLLECTOR CURRENT**

TYPICAL PERFORMANCE CURVES





COMMON MODE REJECTION RATIO



SINGLE STAGE VOLTAGE GAIN



TWO-STAGE VOLTAGE GAIN





Pin numbers are shown for CA3054 (DIP) only.


TYPICAL DYNAMIC CHARACTERISTICS FOR EACH TRANSISTOR

NORMALIZED h PARAMETER
VERSUS COLLECTOR
CURRENT FOR
EACH TRANSISTOR


GAIN BANDWIDTH PRODUCT (f_T)
VERSUS COLLECTOR CURRENT




FORWARD TRANSFER
ADMITTANCE (Y_{21})
VERSUS FREQUENCY




INPUT ADMITTANCE (Y_{11})
VERSUS FREQUENCY







OUTPUT ADMITTANCE (Y_{22})
VERSUS FREQUENCY



REVERSE TRANSFER
ADMITTANCE (Y_{12})
VERSUS FREQUENCY



TYPICAL DYNAMIC CHARACTERISTICS FOR EACH CASCODE AMPLIFIER

FORWARD TRANSFER
ADMITTANCE (Y_{21})
VERSUS FREQUENCYINPUT ADMITTANCE (Y_{11})
VERSUS
FREQUENCYOUTPUT ADMITTANCE (Y_{22})
VERSUS
FREQUENCYREVERSE TRANSFER
ADMITTANCE (Y_{12})
VERSUS
FREQUENCY

- MATCHED TRANSISTOR PERFORMANCE
- LOW NOISE PERFORMANCE
- 200 MHz GAIN BANDWIDTH PRODUCT

APPLICATIONS


- Stereo Phonograph Preamplifiers
- Low-level Stereo and Single Channel Amplifier Stages
- Low-noise, Emitter-follower Differential Amplifiers
- Operational Amplifier Drivers

ABSOLUTE MAXIMUM RATINGS (For Each Transistor)

Power Dissipation		
Any One Transistor		300 mW
Total For Array		300 mW
Temperature Range		
Operating Temperature		-55°C to +125°C
Storage Temperature		-65°C to +200°C
The following ratings apply for each transistor in the array		
Collector-to-Emitter Voltage, V_{CEO}		15 V
Collector-to-Base Voltage, V_{CBO}		30 V
Emitter-to-Base Voltage, V_{EBO}		5 V
Collector Current, I_C		50 mA

EQUIVALENT CIRCUIT

CASE




ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
For Each Transistor (Q ₁ , Q ₂ , Q ₃ , Q ₄)						
Collector-Cutoff Current	I _{CBO}	V _{CB} = 5 V, I _E = 0			0.5	μA
Collector-Cutoff Current	I _{CEO}	V _{CE} = 15 V, I _B = 0			5.0	μA
Collector-to-Emitter Breakdown Voltage	V _{(BR)CEO}	I _C = 1 mA, I _B = 0	15	20		V
Collector-to-Base Breakdown Voltage	V _{(BR)CBO}	I _C = 10 μA, I _E = 0	30	44		V
Emitter-to-Base Breakdown Voltage	V _{(BR)EBO}	I _E = 10 μA, I _C = 0	5.0	6.0		V
For Either Input Transistor (Q ₁ or Q ₃)						
Static Forward Current-Transfer Ratio	h _{FE}	I _{C1} or I _{C3} = 1 mA	30	82		
For Either Darlington Pair (Q ₁ , Q ₂ or Q ₃ , Q ₄)						
Emitter-to-Base Breakdown Voltage	V _{(BR)EBO(D)}	I _{E2} or I _{E4} = 10 μA	10	12.6		V
Static Forward Current-Transfer Ratio	h _{FE(D)}	$\left. \begin{array}{l} I_{C1} + I_{C2} \\ \text{or} \\ I_{C3} + I_{C4} \end{array} \right\} = 1 \text{ mA}$	1000	4540		
For Each Input Transistor (Q ₁ or Q ₃)						
Short-Circuit Forward Current-Transfer Ratio	h _{fe}			82		
Short-Circuit Input Impedance	h _{ie}	f = 1 kHz		2.6		kΩ
Open-Circuit Output Admittance	h _{oe}	I _{C1} or I _{C3} = 1 mA		7.0		μmho
Open-Circuit Reverse Voltage-Transfer Ratio	h _{re}			9.8 × 10 ⁻⁵		
For Either Darlington Pair (Q ₁ , Q ₂ or Q ₃ , Q ₄)						
Short-Circuit Forward Current-Transfer Ratio	h _{fe(D)}	f = 1 kHz		1300		
Short-Circuit Input Impedance	h _{ie(D)}	$\left. \begin{array}{l} I_{C1} + I_{C2} \\ \text{or} \\ I_{C3} + I_{C4} \end{array} \right\} = 1 \text{ mA}$		82		kΩ
Open-Circuit Output Admittance	h _{oe(D)}			108		μmho
Open-Circuit Reverse Voltage-Transfer Ratio	h _{re(D)}			2.7 × 10 ⁻³		
Noise Voltage	E _N	$\left. \begin{array}{l} f = 100 \text{ Hz} \\ f = 1 \text{ kHz} \\ f = 10 \text{ kHz} \end{array} \right\}$		$\left. \begin{array}{l} 0.2 \\ 0.05 \\ 0.012 \end{array} \right\}$	$\left. \begin{array}{l} 3.0 \\ 0.3 \\ 0.1 \end{array} \right\}$	$\frac{\mu\text{V (rms)}}{\sqrt{f(\text{Hz})}}$
For Either Input Transistor (Q ₁ or Q ₃)						
Forward Transfer Admittance	Y _{fe}			0.68 + j 7.9		mmho
Input Admittance (Output Short-Circuited)	Y _{ie}	f = 50 MHz		4.4 + j 5.95		mmho
Output Admittance (Input Short-Circuited)	Y _{oe}	I _{C1} or I _{C3} = 2 mA		1.94 + j 2.64		mmho
Reverse Transfer Admittance (Input Short-Circuited)	Y _{re}			Negligible		mmho
For Either Darlington Pair (Q ₁ , Q ₂ , or Q ₃ , Q ₄)						
Input Admittance (Output Short-Circuited)	Y _{ie(D)}	f = 50 MHz		1.71 + j 2.8		mmho
Output Admittance (Input Short-Circuited)	Y _{oe(D)}	$\left. \begin{array}{l} I_{C1} + I_{C2} \\ \text{or} \\ I_{C3} + I_{C4} \end{array} \right\} = 2 \text{ mA}$		3.96 + j 2.6		mmho
Gain-Bandwidth Product	f _{T(D)}		150	200		MHz

- EXCELLENT DIODE MATCHING – 1 mV TYP.
- REVERSE RECOVERY TIME – 1 ns TYP.
- LOW DIODE CAPACITANCE – 0.65 pF @ $V_R = -2$ V

APPLICATIONS

- Balanced Modulators or Demodulators
- Ring Modulators
- High Speed Diode Gates
- Analog Switches

EQUIVALENT CIRCUIT**ABSOLUTE MAXIMUM RATINGS**

Power Dissipation (See note)	
Any One Diode Unit	100 mW
Total for Device	600 mW
Temperature Range	
Operating Temperature	-55°C to +125°C
Storage Temperature	-65°C to +200°C
Voltages and Currents	
Peak Inverse Voltage, PIV for: D ₁ - D ₅	5 V
D ₆	0.5 V
Peak Diode-to-Substrate Voltage, V_{DI} for D ₁ - D ₅ (term. 1,4,5,8 or 12 to term. 10)	+20, -1 V
DC Forward Current, I_F	25 mA
Peak Recurrent Forward Current, I_F	100 mA
Peak Forward Surge Current, I_F (surge)	100 mA


ELECTRICAL CHARACTERISTICS (For each diode unit, $T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
DC Forward Voltage Drop	V_F	$I_F = 50 \mu\text{A}$		0.65	0.69	V
		1 mA		0.73	0.78	V
		3 mA		0.76	0.80	V
		10 mA		0.81	0.90	V
DC Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = -10 \mu\text{A}$	5.0	7.0		V
DC Reverse Breakdown Voltage Between any Diode Unit and Substrate	$V_{(BR)R}$	$I_R = -10 \mu\text{A}$	20			V
DC Reverse (Leakage) Current	I_R	$V_R = -4$ V		0.016	100	nA
DC Reverse (Leakage) Current Between any Diode Unit and Substrate	I_R	$V_R = -10$ V		0.022	100	nA
Magnitude of Diode Offset Voltage (Difference in DC Forward Voltage Drops of any Two Diode Units)	$ V_{F1} - V_{F2} $	$I_F = 1$ mA		0.5	5.0	mV
Temperature Coefficient of $ V_{F1} - V_{F2} $	$\frac{\Delta V_{F1} - V_{F2} }{\Delta T}$	$I_F = 1$ mA		1.0		$\mu\text{V}/^\circ\text{C}$
Temperature Coefficient of Forward Drop	$\frac{\Delta V_F}{\Delta T}$	$I_F = 1$ mA		-1.9		$\text{mV}/^\circ\text{C}$
DC Forward Voltage Drop for Anode-to-Substrate Diode (D ₆)	V_F	$I_F = 1$ mA		0.65		V
Reverse Recovery Time	t_{rr}	$I_F = 10$ mA, $I_R = 10$ mA		1.0		ns
Diode Resistnace	R_D	$f = 1$ kHz, $I_F = 1$ mA	25	30	45	Ω
Diode Capacitance	C_D	$V_R = -2$ V, $I_F = 0$		0.65		pF
Diode-to-Substrate Capacitance	C_{DI}	$V_{DI} = +4$ V, $I_F = 0$		3.2		pF


NOTE: Derate at 5.7 mW/ $^\circ\text{C}$ for $T_A > 55^\circ\text{C}$.

TYPICAL PERFORMANCE CURVES


DC FORWARD VOLTAGE DROP
(ANY DIODE) AND DIODE
OFFSET VOLTAGE VERSUS
DC FORWARD CURRENT




DIODE OFFSET VOLTAGE
(ANY DIODE) VERSUS
TEMPERATURE




DC REVERSE (LEAKAGE) CURRENT
(DIODES 1, 2, 3, 4, 5) VERSUS
TEMPERATURE




DC FORWARD VOLTAGE DROP
(ANY DIODE) VERSUS
TEMPERATURE




DC REVERSE (LEAKAGE)
CURRENT BETWEEN DIODES
(1, 2, 3, 4, 5) AND SUBSTRATE
VERSUS TEMPERATURE




DIODE RESISTANCE
(ANY DIODE) VERSUS
DC FORWARD CURRENT



DIODE CAPACITANCE
(DIODES 1, 2, 3, 4, 5) VERSUS
REVERSE VOLTAGE




DIODE-TO-SUBSTRATE
CAPACITANCE VERSUS
REVERSE VOLTAGE



- LOW INPUT OFFSET VOLTAGE
- WIDEBAND OPERATION
- LOW NOISE

APPLICATIONS

- General Use in all Types of Signal Processing Systems Operating Anywhere in the Frequency Range From DC to VHF
- Custom Designed Differential Amplifiers
- Temperature Compensated Amplifiers

EQUIVALENT CIRCUIT**ABSOLUTE MAXIMUM RATINGS (For Each Transistor)**

Power Dissipation (Note 1)

At $T_A = 25^\circ\text{C}$ At $T_A = 25^\circ\text{C}$ to 55°C At $T_A = 25^\circ\text{C}$ to 75°C

Voltages and Currents

Collector-to-Emitter Voltage, V_{CEO} Collector-to-Base Voltage, V_{CBO} Collector-to-Substrate Voltage, V_{CISO} (Note 2)Emitter-to-Base Voltage, V_{EBO} Collector Current, I_C

Temperature Range

Operating Temperature

Storage Temperature

CA3045

Each Transistor

300 mW

300 mW

15 V

20 V

20 V

5 V

50 mA

 -55°C to $+125^\circ\text{C}$ -65°C to $+200^\circ\text{C}$

Total Package

750 mW

750 mW

CA3046/3086

Each Transistor

300 mW

300 mW

15 V

20 V

20 V

5 V

50 mA

(CA3046) 0°C to $+85^\circ\text{C}$ (CA3086) -40°C to $+85^\circ\text{C}$ -55°C to $+125^\circ\text{C}$ **ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)**







PARAMETER		CONDITIONS	CA3045, CA3046			CA3086			UNITS
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10 \mu\text{A}, I_E = 0$	20	60		20	60		V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1 \text{ mA}, I_B = 0$	15	24		15	24		V
Collector-to-Substrate Breakdown Voltage	$V_{(BR)CISO}$	$I_C = 10 \mu\text{A}, I_C = 0$	20	60		20	60		V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10 \mu\text{A}, I_C = 0$	5.0	7.0		5.0	7.0		V
Collector-Cutoff Current	I_{CBO}	$V_{CB} = 10 \text{ V}, I_E = 0$		0.002	40		0.002	100	nA
Collector-Cutoff Current	I_{CEO}	$V_{CE} = 10 \text{ V}, I_B = 0$		See curve	0.5		See curve	5.0	μA
Static Forward Current-Transfer Ratio (Static Beta)	h_{FE}	$I_C = 10 \text{ mA}$	40	100		40	100		
		$I_C = 1 \text{ mA}$		100			100		
		$I_C = 10 \mu\text{A}$		54			54		
Input Offset Current for Matched Pair Q_1 and Q_2 $ I_{IO1} - I_{IO2} $		$V_{CE} = 3 \text{ V}, I_C = 1 \text{ mA}$		0.3	2.0				μA
Base-to-Emitter Voltage	V_{BE}	$V_{CE} = 3 \text{ V}, I_E = 1 \text{ mA}$		0.715			0.715		V
		$I_E = 10 \text{ mA}$		0.800			0.800		
Magnitude of Input Offset Voltage for Differential Pair $ V_{BE1} - V_{BE2} $		$V_{CE} = 3 \text{ V}, I_C = 1 \text{ mA}$		0.45	5.0				mV
Magnitude of Input Offset Voltage for Isolated Transistors $ V_{BE3} - V_{BE4} $, $ V_{BE4} - V_{BE5} $, $ V_{BE5} - V_{BE3} $		$V_{CE} = 3 \text{ V}, I_C = 1 \text{ mA}$		0.45	5.0				mV
Temperature Coefficient of Base-to-Emitter Voltage	$\frac{\Delta V_{BE}}{\Delta T}$	$V_{CE} = 3 \text{ V}, I_C = 1 \text{ mA}$		-1.9			-1.9		$\text{mV}/^\circ\text{C}$
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_B = 1 \text{ mA}, I_C = 10 \text{ mA}$		0.23			0.23		V
Temperature Coefficient of Input-Offset Voltage	$\frac{ \Delta V_{IO} }{\Delta T}$	$V_{CE} = 3 \text{ V}, I_C = 1 \text{ mA}$		1.1					$\mu\text{V}/^\circ\text{C}$

NOTES











- CA3046 and CA3086 derate at $6.67 \text{ mW}/^\circ\text{C}$ for $T_A > 55^\circ\text{C}$, CA3045 at $8 \text{ mW}/^\circ\text{C}$ for $T_A > 75^\circ\text{C}$.
- Substrate (Pin 10) must be connected to the most negative voltage to maintain normal operation.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified) (Continued)

PARAMETER		CONDITIONS	MIN.	TYP.	MAX.	UNITS
Low-Frequency Noise Figure	NF	$f = 1\text{ kHz}, V_{CE} = 3\text{ V}, I_C = 100\text{ }\mu\text{A}$ $R_S = 1\text{ k}\Omega$		3.25		dB
Low-Frequency, Small-Signal Equivalent-Circuit Characteristics:						
Forward Current-Transfer Ratio	h_{fe}			110 (CA3045, CA3046)		
Forward Current-Transfer Ratio	h_{fe}			110 (CA3086)		
Short-Circuit Input Impedance	h_{ie}	$f = 1\text{ kHz}, V_{CE} = 3\text{ V}, I_C = 1\text{ mA}$		3.5		$\text{k}\Omega$
Open-Circuit Output Impedance	h_{oe}			15.6		μmho
Open-Circuit Reverse Voltage-Transfer Ratio	h_{re}			1.8×10^{-4}		
Admittance Characteristics:						
Forward Transfer Admittance	Y_{fe}			$31 - j 1.5$		
Input Admittance	Y_{ie}	$f = 1\text{ MHz}, V_{CE} = 3\text{ V}, I_C = 1\text{ mA}$		$0.3 + j 0.04$		
Output Admittance	Y_{oe}			$0.001 + j 0.03$		
Reverse Transfer Admittance	Y_{re}			See curve		
Gain-Bandwidth Product	f_T	$V_{CE} = 3\text{ V}, I_C = 3\text{ mA}$	300	550		
Emitter-to-Base Capacitance	C_{EB}	$V_{EB} = 3\text{ V}, I_E = 0$		0.6		pF
Collector-to-Base Capacitance	C_{CB}	$V_{CB} = 3\text{ V}, I_C = 0$		0.58		pF
Collector-to-Substrate Capacitance	C_{CI}	$V_{CS} = 3\text{ V}, I_C = 0$		2.8		pF

TYPICAL PERFORMANCE CURVES**COLLECTOR-TO-BASE CUTOFF CURRENT VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR****COLLECTOR-TO-EMITTER CUTOFF CURRENT VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR****STATIC FORWARD CURRENT-TRANSFER AND BETA RATIO FOR TRANSISTORS Q1, Q2 VERSUS EMITTER CURRENT****INPUT OFFSET CURRENT FOR MATCHED TRANSISTOR PAIR Q1, Q2 VERSUS COLLECTOR CURRENT****STATIC BASE-TO-EMITTER VOLTAGE AND INPUT OFFSET VOLTAGE VERSUS EMITTER CURRENT****BASE-TO-EMITTER VOLTAGE CHARACTERISTIC VERSUS AMBIENT TEMPERATURE FOR EACH TRANSISTOR**

TYPICAL PERFORMANCE CURVES

INPUT OFFSET VOLTAGE
FOR DIFFERENTIAL PAIR AND
PAIRED ISOLATED TRANSISTORS
VERSUS AMBIENT TEMPERATURENORMALIZED h PARAMETERS
VERSUS COLLECTOR CURRENTGAIN-BANDWIDTH PRODUCT
VERSUS
COLLECTOR CURRENTNOISE FIGURE
VERSUS
COLLECTOR CURRENTNOISE FIGURE
VERSUS
COLLECTOR CURRENTNOISE FIGURE
VERSUS
COLLECTOR CURRENTFORWARD TRANSFER ADMITTANCE
VERSUS
FREQUENCYINPUT ADMITTANCE
VERSUS
FREQUENCYOUTPUT ADMITTANCE
VERSUS
FREQUENCYREVERSE TRANSFER ADMITTANCE
VERSUS
FREQUENCY

CA3064

TV AUTOMATIC FINE-TUNING CIRCUIT

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The CA3064 is a TV automatic fine-tuning linear integrated circuit constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The CA3064 combines all of the automatic fine-tuning circuitry, except transformers, in one integrated circuit. Systems with low level I.F. amplifiers can now achieve tuning accuracies of ± 25 kHz due to the CA3064's high sensitivity. Internal voltage regulation improves overall performance and reduces system cost.

- **HIGH SENSITIVITY**
- **25 kHz MAX. FREQUENCY DEVIATION**
- **INTERNAL VOLTAGE REGULATOR**
- **INTERNAL AGC**

ABSOLUTE MAXIMUM RATINGS (Note 1)


Supply Voltage
Internal Power Dissipation (Note 3)
Detector Differential Voltage (V_{1-3})
Detector Input Voltage Range (V_1, V_3)
I.F. Amp Output (V_2)
Bias Voltage (V_6)
Storage Temperature Range
Operating Temperature range
Lead Temperature (soldering, 60 seconds)

Note 2
700 mW
 ± 10 V
+ 5 V, -6 V
+ 20 V, 0 V
+ 2 V, 0 V
-65°C to + 150°C
-40°C to + 85°C
300°C

NOTES:


- (1) All voltages referenced to V^- except as noted.
- (2) V^+ terminal may be connected to any positive voltage source through a suitable dropping resistor, provided the dissipation rating is not exceeded.
- (3) Derate linearly at 5.6 mW/°C for ambient temperatures above + 25°C.

CONNECTION DIAGRAM (TOP VIEW)



ORDER PART NO: CA3064

BLOCK DIAGRAM



*SEE FOLLOWING PAGES FOR COIL DATA.


*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS ($V_{CC} = +30\text{ V}$, $R_S = 1.5\text{ k}\Omega$, $T_A = 25^\circ\text{C}$ unless otherwise specified)


PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Power Consumption	$T_A = +25^\circ\text{C}$	130	140	150	mW
	$T_A = -25^\circ\text{C}$		135	150	mW
	$T_A = +85^\circ\text{C}$		145	150	mW
Supply Current — I^+	$V^+ = +10.5\text{ V}$	4.0	6.5	9.5	mA
Regulated Supply Voltage — V^+		10.9	11.8	12.8	V
Quiescent Operating Current — I_2		1.0	2.0	4.0	mA
Quiescent Operating Voltages — V_4, V_5		5.0	6.9	8.0	V
Output Offset Voltage — ($V_4 - V_5$)		-1.0	0	1.0	V
Input Admittance — Y_{11}	$f = 45.75\text{ MHz}$		$0.41 + j 1.0$		mmho
Reverse Transfer Admittance — Y_{12}	$f = 45.75\text{ MHz}$		$0 + j 3.4$		μmho
Forward Transfer Admittance — Y_{21}	$f = 45.75\text{ MHz}$		$24.5 - j 29$		mmho
Output Admittance — Y_{22}	$f = 45.75\text{ MHz}$		$0.04 + j 0.9$		mmho
Correction Control Voltage — V_4 (Test Circuit 1)	$V_{IN} = 18\text{ mV RMS}$				
	$f_o = 45.750\text{ MHz}$				
	Δf as listed (MHz)				
	-0.030	85			% V^+
	+ 0.030			25	% V^+
	-0.900	80			% V^+
	+ 0.900			35	% V^+
	-1.500			80	% V^+
Correction Control Voltage — V_5 (Test Circuit 1)	$V_{IN} = 18\text{ mV RMS}$				
	$f_o = 45.750\text{ MHz}$				
	Δf as listed (MHz)				
	-0.030			25	% V^+
	+ 0.030	85			% V^+
	-0.900			35	% V^+
	+ 0.900	80			% V^+
	-1.500	35			% V^+
	+ 1.500			80	% V^+

TYPICAL PERFORMANCE CURVES

**NARROW-BAND DYNAMIC
CONTROL
VOLTAGE CHARACTERISTICS**




**WIDE-BAND DYNAMIC
CONTROL
VOLTAGE CHARACTERISTICS**



SEE TEST CIRCUIT 1

TEST CIRCUIT 1 CORRECTION VOLTAGES



NOTE: Parts placement is critical. Use P.C. board layout on last page for best results.

L_1 is aligned for symmetrical bandwidth on either side of 45.750 MHz.

L_2 tertiary winding wound on L_1 coil form

L_3 is aligned for zero differential output between terminals 4 and 5 at $f_o = 45.750$ MHz

REFERENCE VOLTAGE PERCENTAGES

Ref. A	85% of V_{10}
Ref. B	25% of V_{10}
Ref. C	80% of V_{10}
Ref. D	35% of V_{10}

COIL DATA FOR DISCRIMINATOR WINDINGS

L_1 — Discriminator Primary: 3 1/6 turns; #20 Enamel-covered wire—close-wound, at bottom of coil form. Inductance of $L_1 = 0.165 \mu\text{H}$; $Q_o = 120$ at $f_o = 45.75$ MHz.

Start winding at Terminal #6; finish at Terminal #1. See Notes below.


L_2 — Tertiary Windings: 2 1/6 turns; #20 Enamel-covered wire—close wound over bottom end of L_1 . Start winding at Terminal #3; finish at Terminal #4. See Notes below.

L_3 — Discriminator Secondary: 3 1/2 turns; center-tapped, space wound at bottom of coil form. Inductance of $L_3 = 0.180 \mu\text{H}$; $Q_o = 150$ at $f_o = 45.75$ MHz.

Start winding at Terminal #2; finish at Terminal #5, connect center tap to Terminal #7. See Notes below.

- Notes:
1. Coil Forms; Cylindrical; 0.30" Dia. max.
 2. Tuning Core: 0.250" Dia. x 0.37" Length.
: Material: Carbinol J or equivalent.
 3. Coil Form Base: See drawing below.
 4. End of coil nearest terminal board to be designated the winding start end.


COIL FORM BASE TERMINAL DIAGRAM




Coil
(L_1 , L_2)
 L_3

RCA Distributor Part No.
122 213
122 203


CA3064 EQUIVALENT CIRCUIT



**PRINTED CIRCUIT BOARD FOR CORRECTION
VOLTAGE TEST CIRCUIT**
Full Size Bottom View



TEST CIRCUIT 2
Regulated Voltage, Total Supply Current and
Quiescent Current at Terminal 2



CA3065

TV/FM SOUND SYSTEM

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The CA3065 Monolithic TV/FM Sound System consists of a Multi-stage Limiting IF Amplifier, DC Gain (Volume) control, FM Detector, and an Audio Driver constructed on a single silicon chip using the Fairchild planar* epitaxial process. Excellent sensitivity, high AM rejection and an internally regulated power supply coupled with low external component requirement makes the CA3065 suitable for a wide variety of applications including TV Sound Channels, Line Operated and Automobile FM Radios and Mobile Communications Equipment.


- **DC VOLUME CONTROL ELIMINATES NEED FOR SHIELDED CABLES**
- **EXCELLENT AM REJECTION -50dB TYPICAL AT 4.5 MHz**
- **DIFFERENTIAL PEAK DETECTOR REQUIRES ONLY ONE SINGLE-TUNED COIL**
- **INTERNAL ZENER DIODE REGULATED SUPPLY**
- **LOW HARMONIC DISTORTION**

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	
Internal Power Dissipation (Note 2)	
Power Supply Current	
Operating Temperature Range	
Storage Temperature Range	
Lead Temperature Range (Soldering, 60 seconds)	

Note 1	
670 mW	
50 mA	
-40°C to +85°C	
-65°C to +150°C	
300°C	

CONNECTION DIAGRAM (TOP VIEW)




ORDER PART NO: CA3065

NOTES

1. V^+ terminal may be connected to any positive voltage through a suitable dropping resistor, provided the dissipation rating is not exceeded.
2. Rating applies to ambient temperature up to 70°C. Above 70°C ambient derate linearly 8.3 mW/°C for the Ceramic DIP.

BLOCK DIAGRAM



*Planar is a patented Fairchild process


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $I^+ = 30\text{ mA}$ unless otherwise specified)

PARAMETER	CONDITIONS	TEST CIRCUIT	MIN	TYP	MAX	UNITS
STATIC CHARACTERISTICS						
Zener Regulating Voltage (V_5)			10.3	11.2	12.2	Volts
Supply Current (I_5)	$V_{\text{Supply}} = 9.0\text{V}$		10	16	24	mA
Internal Power Dissipation	$I^+ = 33\text{mA}$		343	370	400	mW
Voltage at IF Input Bias (V_1)				2.0		Volts
Voltage at DC Volume Control (V_6)				4.8		Volts
Voltage at De Emphasis (V_7)				6.1		Volts
Voltage at Quad Detector (V_9)				3.7		Volts
Voltage at Audio Output (V_{12})			4.0	5.1	5.8	Volts
DYNAMIC CHARACTERISTICS						
IF AMPLIFIER	$(f_0 = 4.5\text{ MHz, FM} \pm 25\text{ kHz at } 400\text{ Hz, } V_{\text{IN}} = 100\mu\text{V})$	1				
Input Limiting Voltage at -3dB point				200	400	μV
AM Rejection	AM = 30% at 4.5 MHz	1	40	50		dB
IF Transconductance Magnitude	$f = 4.5\text{ MHz}$			500		mmho
Phase Angle				46		degrees
Feedback Capacitance	$f = 1.0\text{ MHz, Pin 2 to Pin 9}$			<0.02		pF
Input Impedance Components	$f = 4.5\text{ MHz, Pin 1 to Pin 2}$					
Parallel Input Resistance				17		k Ω
Parallel Input Capacitance				4.0		pF
Output Impedance Components	$f = 4.5\text{ MHz, Pin 9 to Ground}$					
Parallel Output Resistance				3.25		k Ω
Parallel Output Capacitance				75		pF
DETECTOR	$(f_0 = 4.5\text{ MHz, FM} = \pm 25\text{ kHz at } 400\text{ Hz, } V_{\text{IN}} = 100\text{ mV})$					
Recovered AF Voltage		1	0.5	0.75		Vrms
Total Harmonic Distortion		1		0.9	2.0	%
Output Resistance						
De emphasis Output				7.5		k Ω
Detector Output				300		Ω
ATTENUATOR						
Max. Attenuation	$R_x = \infty$	1	60	80		dB
Max. Play-through Voltage*	$R_x = \infty$	1		0.075	1.0	mV
AUDIO AMPLIFIER						
Voltage Gain	$V_1 = 0.1\text{ Vrms, } f = 400\text{ Hz}$	2	17.5	20		dB
Total Harmonic Distortion	$V_0 = 2\text{ Vrms, } f = 400\text{ Hz}$	2		1.5		%
Undistorted Output Voltage	THD = 5%, $f = 400\text{ Hz}$	2	2.0	2.5		Vrms
Input Resistance	$f = 400\text{ Hz}$			70		k Ω
Output Resistance	$f = 400\text{ Hz}$			270		Ω


*Play-through voltage is the unwanted signal, measured at the detector output, when the volume control is set for minimum output.

TYPICAL PERFORMANCE CURVES


FREQUENCY RESPONSE OF IF AMPLIFIER SECTION



FREQUENCY RESPONSE OF AUDIO AMPLIFIER SECTION




AUDIO GAIN REDUCTION VERSUS DC VOLUME CONTROL RESISTANCE



TEST CIRCUITS

TEST CIRCUIT 1

INPUT LIMITING VOLTAGE, AM REJECTION, RECOVERED AUDIO, TOTAL HARMONIC DISTORTION, MAXIMUM ATTENUATION, MAXIMUM "PLAY-THROUGH" TEST CIRCUIT.




PINS 11, 12, 13, 14 NO CONNECTION

* $L_1 = 16\mu\text{H}$ NOMINAL
 $Q(\text{UNLOADED}) = 50$

TEST CIRCUIT 2


AUDIO VOLTAGE GAIN
(UNDISTORTED OUTPUT)



PINS 7, 8, 11, 13 NO CONNECTION

TEST CIRCUIT 3


IF AMPLIFIER SECTION



$E_{IN} = 100\mu\text{Vrms}$

TEST CIRCUIT 4


AUDIO AMPLIFIER SECTION



$E_{IN} = 100\text{ mV}$


TYPICAL APPLICATION

TV SOUND SYSTEM



* $L_1 = 16\mu\text{H}$ NOMINAL , $Q(\text{UNLOADED}) = 50$

SUGGESTED CIRCUIT LAYOUT
COMPONENT SIDE



LM101A • LM201A • LM301A

GENERAL PURPOSE OPERATIONAL AMPLIFIERS

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The LM101A, LM201A and LM301A are general purpose monolithic operational amplifiers constructed on a single silicon chip, using the Fairchild Planar* epitaxial process. These integrated circuits are intended for applications requiring low input offset voltage or low input offset current. The accuracy of long interval integrators, timers and sample and hold circuits is improved due to the low drift and low bias currents of the LM101A, LM201A, or LM301A. Frequency response may be matched to the individual circuit need with one external capacitor. The absence of "Latch-Up" coupled with internal short circuit protection make the LM101A, LM201A and LM301A virtually foolproof. The LM101A, LM201A and LM301A are pin compatible with the popular μ A709, μ A741, μ A748 and μ A777.

- LOW OFFSET CURRENT AND VOLTAGE
- LOW OFFSET CURRENT DRIFT
- LOW BIAS CURRENT
- SHORT CIRCUIT PROTECTED
- LOW POWER CONSUMPTION

ABSOLUTE MAXIMUM RATINGS

Supply Voltage

Military and Instrument (LM101A and LM201A)
Commercial (LM301A)

± 22 V
 ± 18 V

Internal Power Dissipation (Note 1)

Metal Can

500 mW

Ceramic DIP

670 mW

Silicone DIP

340 mW

Flatpak

570 mW

Mini DIP

310 mW

Differential Input Voltage

± 30 V

Input Voltage (Note 2)

± 15 V

Storage Temperature Range

Metal Can, Ceramic DIP, and Flatpak

-65°C to $+150^{\circ}\text{C}$

Mini DIP and Silicone DIP

-55°C to $+125^{\circ}\text{C}$

Operating Temperature Range

Military (LM101A)

-55°C to $+125^{\circ}\text{C}$

Instrument (LM201A)

-25°C to $+85^{\circ}\text{C}$

Commercial (LM301A)

0°C to $+70^{\circ}\text{C}$

Lead Temperature (Soldering)

Metal Can, Ceramic DIP and Flatpak (60 seconds)


300°C

Mini DIP and Silicone DIP (10 seconds)

260°C

Output Short Circuit Duration (Note 3)


Indefinite



Notes on following pages.

CONNECTION DIAGRAMS (TOP VIEW)


8 LEAD METAL CAN



ORDER PART NOS.

LM101AH
LM201AH
LM301AH

14 LEAD DIP




FOR CERAMIC DIP ORDER PART NOS.

LM101AD
LM201AD
LM301AD

FOR SILICONE DIP ORDER PART NO.

LM301AP

FLATPACK




ORDER PART NOS.

LM101AF*
LM201AF*

* Available on special request

MINIDIP



ORDER PART NO.




LM301AN

*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS FOR LM101A and LM201A ($\pm 5.0V \leq V_s \leq \pm 20V$, $T_A = 25^\circ C$, $C_1 = 30 \text{ pF}$ unless otherwise specified)

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
Input Offset Voltage	$R_s \leq 50 \text{ k}\Omega$		0.7	2.0	mV
Input Offset Current			1.5	10	nA
Input Bias Current			30	75	nA
Input Resistance		1.5	4.0		$M\Omega$
Supply Current	$V_s = \pm 20V$		1.8	3.0	mA
Large Signal Voltage Gain	$V_s = \pm 15V$ $V_{OUT} = \pm 10V$, $R_L \geq 2 \text{ k}\Omega$	50	160		V/mV
The following specifications apply for $-55^\circ C \leq T_A \leq +125^\circ C$: (Note 4)					
Input Offset Voltage	$R_s \leq 50 \text{ k}\Omega$			3.0	mV
Average Temperature Coefficient of Input Offset Voltage			3.0	15	$\mu V/^\circ C$
Input Offset Current				20	nA
Average Temperature Coefficient of Input Offset Current	$+25^\circ C \leq T_A \leq +125^\circ C$ $-55^\circ C \leq T_A \leq +25^\circ C$		0.01 0.02	0.1 0.2	nA/ $^\circ C$ nA/ $^\circ C$
Input Bias Current				100	nA
Supply Current	$T_A = +125^\circ C$, $V_s = \pm 20V$		1.2	2.5	mA
Large Signal Voltage Gain	$V_s = \pm 15V$, $V_{OUT} = \pm 10V$ $R_L \geq 2 \text{ k}\Omega$	25			V/mV
Output Voltage Swing	$V_s = \pm 15V$, $R_L = 10 \text{ k}\Omega$ $R_L = 2 \text{ k}\Omega$	± 12 ± 10	± 14 ± 13		V V
Input Voltage Range	$V_s = \pm 20V$	± 15			V
Common Mode Rejection Ratio	$R_s \leq 50 \text{ k}\Omega$	80	96		dB
Supply Voltage Rejection Ratio	$R_s \leq 50 \text{ k}\Omega$	80	96		dB

GUARANTEED PERFORMANCE CURVES (LM101A AND LM201A)






ELECTRICAL CHARACTERISTICS FOR LM301A ($\pm 5.0\text{ V} \leq V_s \leq \pm 15\text{ V}$, $T_A = 25^\circ\text{C}$, $C_1 = 30\text{ pF}$ unless otherwise specified)












PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
Input Offset Voltage	$R_s \leq 50\text{ k}\Omega$		2.0	7.5	mV
Input Offset Current			3	50	nA
Input Bias Current			70	250	nA
Input Resistance		0.5	2		M Ω
Supply Current	$V_s = \pm 15\text{ V}$		1.8	3.0	mA
Large Signal Voltage Gain	$V_s = \pm 15\text{ V}$ $V_{OUT} = \pm 10\text{ V}$, $R_L \geq 2\text{ k}\Omega$	25	160		V/mV
The following specifications apply for $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$:					
Input Offset Voltage	$R_s \leq 50\text{ k}\Omega$			10	mV
Average Temperature Coefficient of Input Offset Voltage			6.0	30	$\mu\text{V}/^\circ\text{C}$
Input Offset Current				70	nA
Average Temperature Coefficient of Input	$25^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $0^\circ\text{C} \leq T_A \leq 25^\circ\text{C}$		0.01 0.02	0.3 0.6	nA/ $^\circ\text{C}$ nA/ $^\circ\text{C}$
Input Bias Current				300	nA
Large Signal Voltage Gain	$V_s = \pm 15\text{ V}$, $V_{OUT} = \pm 10\text{ V}$ $R_L \geq 2\text{ k}\Omega$	15			V/mV
Output Voltage Swing	$V_s = \pm 15\text{ V}$, $R_L = 10\text{ k}\Omega$ $R_L = 2\text{ k}\Omega$	± 12 ± 10	± 14 ± 13		V V
Input Voltage Range	$V_s = \pm 15\text{ V}$	± 12			V
Common Mode Rejection Ratio	$R_s \leq 50\text{ k}\Omega$	70	90		dB
Supply Voltage Rejection Ratio	$R_s \leq 50\text{ k}\Omega$	70	96		dB

NOTES:

- (1) Rating applies to ambient temperature up to 70°C . Above 70°C ambient derate linearly at $6.3\text{ mW}/^\circ\text{C}$ for the Metal Can, $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP, $6.3\text{ mW}/^\circ\text{C}$ for the Silicone DIP, $5.6\text{ mW}/^\circ\text{C}$ for the Mini DIP and $7.1\text{ mW}/^\circ\text{C}$ for the Flatpak.
- (2) For supply voltages less than $\pm 15\text{ V}$, the absolute maximum input voltage is equal to the supply voltage.
- (3) Short circuit may be to ground or either supply. LM 101A and LM201A ratings apply to $+125^\circ\text{C}$ case temperature or $+75^\circ\text{C}$ ambient temperature. LM301A ratings apply for case temperatures to 70°C .
- (4) All LM201A specifications apply for $-25^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$ unless otherwise specified.


GUARANTEED PERFORMANCE CURVES
(LM301A)

TYPICAL PERFORMANCE CURVES




COMPENSATION CIRCUITS


SINGLE POLE COMPENSATION



TWO POLE COMPENSATION




FEEDFORWARD COMPENSATION




TYPICAL PERFORMANCE CURVES


OPEN LOOP FREQUENCY RESPONSE




OPEN LOOP FREQUENCY RESPONSE




OPEN LOOP FREQUENCY RESPONSE




LARGE SIGNAL FREQUENCY RESPONSE




LARGE SIGNAL FREQUENCY RESPONSE




LARGE SIGNAL FREQUENCY RESPONSE




VOLTAGE FOLLOWER PULSE RESPONSE



VOLTAGE FOLLOWER PULSE RESPONSE




INVERTER PULSE RESPONSE




TYPICAL APPLICATIONS
(All pin numbers shown refer to 8 pin TO-5 package)

**INVERTING AMPLIFIER
—WITH BALANCING CIRCUIT**




[†] May be zero or equal to parallel combination of R1 and R2 for minimum offset.

FAST VOLTAGE FOLLOWER




Power Bandwidth: 15 kHz
Slew Rate: 1V/μs


BILATERAL CURRENT SOURCE




FAST SUMMING AMPLIFIER




**MULTIPLE APERTURE
WINDOW DISCRIMINATOR**



**VOLTAGE COMPARATOR FOR
DRIVING RTL LOGIC OR HIGH
CURRENT DRIVER**




**VOLTAGE COMPARATOR FOR
DRIVING DTL OR TTL
INTEGRATED CIRCUITS**




TYPICAL APPLICATIONS (CON'D)
(All pin numbers shown refer to 8 pin TO-5 package)


LOW FREQUENCY SQUARE WAVE GENERATOR




DOUBLE ENDED LIMIT DETECTOR




PRACTICAL DIFFERENTIATOR




CIRCUIT FOR OPERATING WITHOUT A NEGATIVE SUPPLY




FREE-RUNNING MULTIVIBRATOR



PULSE WIDTH MODULATOR



GAIN TEST CIRCUIT



LM109•LM209•LM309

5 VOLT REGULATOR

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The LM109, LM209 and LM309 are complete 5 volt regulators constructed on a single silicon chip using the Fairchild Planar* epitaxial process. These regulators employ internal current limiting, thermal shutdown and safe-area compensation making them essentially blow-out proof. They are intended for use as local regulators, eliminating noise and distribution problems associated with single point regulation. If adequate heat sinking is provided, they can provide over 1 A. The LM109, LM209 and LM309 are intended primarily for use with TTL and DTL logic and are completely specified under worst case conditions to match the power supply requirements of these logic families. In addition to use as a fixed 5 volt regulator, these devices can be used with external components to obtain adjustable output voltages and currents and as the power pass element in precision regulators.


- OUTPUT CURRENT IN EXCESS OF 1 AMP
- SPECIFIED TO MATCH WORST CASE TTL AND DTL REQUIREMENTS
- NO EXTERNAL COMPONENTS
- INTERNAL THERMAL OVERLOAD PROTECTION
- OUTPUT TRANSISTOR SAFE-AREA COMPENSATION

ABSOLUTE MAXIMUM RATINGS

Input Voltage	35 V
Internal Power Dissipation	Internally Limited
Storage Temperature Range	-65°C to +150°C
Operating Junction Temperature Range	
LM109	-55°C to +150°C
LM209	-25°C to +150°C
LM309	0°C to +125°C
Lead Temperature (Soldering, 60 second time limit)	300°C

CONNECTION DIAGRAM

TO-3 PACKAGE (TOP VIEW)




Case is connected to ground.


ORDER PART NO:

LM109K
LM209K
LM309K

EQUIVALENT CIRCUIT



PHYSICAL DIMENSIONS TO-3 PACKAGE



NOTES

All dimensions in inches
Leads 1 and 2 electrically isolated from case
Case is third electrical connection
Leads are gold-plated copper cored kovar
Package weight is 7.4 grams.

*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS FOR LM109 AND LM209 (Note 1)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_j = 25^\circ\text{C}$	4.7	5.05	5.3	V
Line Regulation	$T_j = 25^\circ\text{C}$ $7\text{ V} \leq V_{IN} \leq 25\text{ V}$		4.0	50	mV
Load Regulation	$T_j = 25^\circ\text{C}$ $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		50	100	mV
Output Voltage	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$ $5\text{ mA} \leq I_{OUT} \leq I_{MAX}$ $P \leq P_{MAX}$	4.6		5.4	V
Quiescent Current	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$		5.2	10	mA
Quiescent Current Change	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$ $5\text{ mA} \leq I_{OUT} \leq I_{MAX}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$ $10\text{ Hz} \leq f \leq 100\text{ kHz}$		40		μV
Long Term Stability				10	mV
Thermal Resistance Junction to Case (Note 2)			3.0		$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS FOR LM309 (Note 3)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage	$T_j = 25^\circ\text{C}$	4.8	5.05	5.2	V
Line Regulation	$T_j = 25^\circ\text{C}$ $7\text{ V} \leq V_{IN} \leq 25\text{ V}$		4.0	50	mV
Load Regulation	$T_j = 25^\circ\text{C}$ $5\text{ mA} \leq I_{OUT} \leq 1.5\text{ A}$		50	100	mV
Output Voltage	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$ $5\text{ mA} \leq I_{OUT} \leq I_{MAX}$ $P \leq P_{MAX}$	4.75		5.25	V
Quiescent Current	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$		5.2	10	mA
Quiescent Current Change	$7\text{ V} \leq V_{IN} \leq 25\text{ V}$ $5\text{ mA} \leq I_{OUT} \leq I_{MAX}$			0.5	mA
Output Noise Voltage	$T_A = 25^\circ\text{C}$ $10\text{ Hz} \leq f \leq 100\text{ kHz}$		40		μV
Long Term Stability				20	mV
Thermal Resistance Junction to Case (Note 2)			3.0		$^\circ\text{C/W}$


NOTES

1. Unless otherwise specified, these specifications apply for $-55^\circ\text{C} \leq T_j \leq 150^\circ\text{C}$ ($-25^\circ\text{C} \leq T_j \leq 150^\circ\text{C}$ for the LM209), $V_{IN} = 10\text{ V}$ and $I_{OUT} = 0.5\text{ A}$.
2. Without a heat sink, the thermal resistance is about 150°C/W . With a heat sink, the effective thermal resistance can only approach the values specified, depending on the efficiency of the sink.
3. Unless otherwise specified, these specifications apply for $0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$, $V_{IN} = 10\text{ V}$ and $I_{OUT} = 0.5\text{ A}$. $I_{MAX} = 1.0\text{ A}$ and $P_{MAX} = 20\text{ W}$.


TYPICAL PERFORMANCE CURVES

(For all grades unless otherwise specified)


TO-3 MAXIMUM AVERAGE POWER DISSIPATION (LM109 and LM209)




TO-3 MAXIMUM AVERAGE POWER DISSIPATION (LM309)




OUTPUT IMPEDANCE




TO-3 PEAK OUTPUT CURRENT




RIPPLE REJECTION




DROPOUT VOLTAGE (LM109 and LM209)




DROPOUT VOLTAGE (LM309)




DROPOUT CHARACTERISTIC




OUTPUT VOLTAGE (LM109 and LM209)




OUTPUT VOLTAGE (LM309)




OUTPUT NOISE VOLTAGE



QUIESCENT CURRENT




QUIESCENT CURRENT



APPLICATIONS

FIXED 5 V REGULATOR




NOTES:

* Required if regulator is located an appreciable distance from power supply filter.

† Although no output capacitor is needed for stability, it does improve transient response.

PRECISION VOLTAGE REGULATOR




NOTES:

* Regulation better than 0.01% load, line and temperature, can be obtained.


† Determines zener current. May be adjusted to minimize thermal drift.

‡ Solid tantalum.

ADJUSTABLE OUTPUT REGULATOR



CURRENT REGULATOR



NOTES:

* Determines output current.

SN7524 • SN7525

TWO CHANNEL CORE MEMORY SENSE AMPLIFIERS

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The SN7524 and SN7525 are two channel core memory sense amplifiers constructed on a silicon chip using the patented Fairchild Planar* epitaxial process. They can be used for small (1K to 8K words) memories as well as larger memory systems. The devices are suitable for small core sizes facilitating very fast memory cycle times. The SN7524 and SN7525 feature tight threshold accuracy, fast response time, and independent strobe selection. Unit to unit variations are minimized so that individual adjustments of the threshold and strobe timing are not necessary.


All logic inputs and outputs are fully TTL compatible. The SN7524 and SN7525 can be combined with the Fairchild MSI Quad Latch 9314 to provide complete memory data register capability.

- ± 2 mV THRESHOLD VARIATION
- 25 ns PROPAGATION DELAY
- DUAL INDEPENDENT STROBES
- TTL COMPATIBLE

ABSOLUTE MAXIMUM RATINGS


Differential Input Voltage	± 5.0 V
Supply Voltage	± 7.0 V
Logic Input Voltage	+5.5 V
Power Dissipation	730 mW
Storage Temperature	-65°C to $+150^{\circ}\text{C}$
Operating Temperature	0°C to $+70^{\circ}\text{C}$
Lead Temperature (Soldering 60 seconds)	$+300^{\circ}\text{C}$
Signal Input	± 3.0 V
Reference Input	± 3.0 V

BLOCK DIAGRAM



PHYSICAL DIMENSIONS

16 Lead Ceramic Dual In-Line




NOTES:

All dimensions in inches
Leads are intended for insertion in hole rows on .300" centers. They are purposely shipped with "positive" misalignment to facilitate insertion
Board-drilling dimensions should equal your practice for .020" diameter lead
Leads are tin-plated kovar
Package weight is 2.2 grams
The .037/.027 dimension does not apply to the corner leads

ORDER PART NOS.

SN7524J
SN7525J

CONNECTION DIAGRAM



*Planar is a patented Fairchild process.

ELECTRICAL CHARACTERISTICS ($V^+ = 5.0\text{ V}$, $V^- = -5.0\text{ V}$, 0°C to $+70^\circ\text{C}$ either Amplifier unless otherwise specified)

PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
SN7524					
Differential Input Threshold Voltage	$V_{\text{ref}} = 15\text{ mV}$	11		19	mV
	$V_{\text{ref}} = 40\text{ mV}$	36		44	mV
SN7525					
Differential Input Threshold Voltage	$V_{\text{ref}} = 15\text{ mV}$	8.0		22	mV
	$V_{\text{ref}} = 40\text{ mV}$	33		47	mV
The following specifications apply to either the SN7524 or the SN7525:					
Threshold Voltage Range					
Minimum			10		mV
Maximum			50		nV
Threshold Uncertainty			± 2.0		mV
Differential Input Bias Current	$V_{\text{IND}} = 0\text{ mV}$		15	75	μA
Differential Input Offset Current	$V_{\text{IND}} = 0\text{ mV}$		1.0		μA
Differential Input Impedance	$f = 1.0\text{ kHz}$		2.5		$\text{k}\Omega$
Positive Supply Current	$T_A = 25^\circ\text{C}$, $V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$		25	40	mA
Negative Supply Current	$T_A = 25^\circ\text{C}$, $V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$		10	20	mA
Output Short Circuit Current	$V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$	2.1		3.5	mA
LOGIC INPUT/OUTPUT CONDITIONS (See Fig. 2)					
Output Voltage Logical "1"	1 Load = $400\text{ }\mu\text{A}$	2.4	3.9		V
	$V_{\text{IN}(1)} \text{ Strobe} = 2.0\text{ V}$				
	$V_{\text{IN}(0)} \text{ Strobe} = 0.8\text{ V}$				
	$V^+ = 4.75\text{ V}$, $V^- = -4.75\text{ V}$				
Output Voltage Logical "0"	I Sink = 16 mA		0.25	0.4	V
	$V_{\text{IN}(0)} \text{ Strobe} = 0.8\text{ V}$				
	$V^+ = 4.75\text{ V}$, $V^- = -4.75\text{ V}$				
Logical "1" Input (Strobe Inputs)	$V_{\text{IN}(0)} \text{ Strobe} = 0.8\text{ V}$	2.0			V
	$V^+ = 4.75\text{ V}$, $V^- = -4.75\text{ V}$				
Logical "0" Input (Strobe Inputs)	$V_{\text{IN}(1)} \text{ Strobe} = 2.0\text{ V}$			0.8	V
	$V^+ = 4.75\text{ V}$, $V^- = -4.75\text{ V}$				
Logical "0" Input Current (Strobe Inputs)	$V_{\text{IN}(0)} \text{ Strobe} = 0.4\text{ V}$		-1.0	-1.6	mA
	$V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$				
Logical "1" Input Current (Strobe Inputs)	$V_{\text{IN}(1)} \text{ Strobe} = 2.4\text{ V}$			40	μA
	$V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$				
Logical "1" Input Current (Strobe Inputs)	$V_{\text{IN}(1)} \text{ Strobe} = V^+$			1.0	mA
	$V^+ = 5.25\text{ V}$, $V^- = -5.25\text{ V}$				
A.C. CHARACTERISTICS					
$T_A = 25^\circ\text{C}$					
Common Mode Input Firing Voltage	$t_r = t_f \leq 15\text{ ns}$		± 3.0		V
	$t_p = 50\text{ ns}$				
Differential Input Overload Recovery Time	$V_{\text{IN}} = 2.0\text{ V}$,		20		ns
	$t_r = t_f = 20\text{ ns}$				
Common Mode Input Overload Recovery Time	$V_{\text{IN CM}} = \pm 2.0\text{ V}$,		20		ns
	$t_r = t_f = 20\text{ ns}$				
Input to Output Delay (See Figure 1)	$t_{\text{pd}}(1)\text{ D}$		25	40	ns
	$t_{\text{pd}}(0)\text{ D}$		35		ns
Strobe to Output Delay (See Figure 1)	$t_{\text{pd}}(1)\text{ Strobe}$		15	30	ns
	$t_{\text{pd}}(0)\text{ Strobe}$		25		ns

TYPICAL PERFORMANCE CURVES













THRESHOLD VOLTAGE
VERSUS
REFERENCE VOLTAGETHRESHOLD VOLTAGE
VERSUS
SUPPLY VOLTAGEDIFFERENTIAL-INPUT
BIAS CURRENT VERSUS
AMBIENT TEMPERATUREDIFFERENTIAL-INPUT
OFFSET CURRENT VERSUS
AMBIENT TEMPERATURELOGICAL "1" LEVEL
INPUT CURRENT VERSUS
INPUT VOLTAGELOGICAL "0" LEVEL
INPUT CURRENT VERSUS
INPUT VOLTAGEOUTPUT VOLTAGE
VERSUS DIFFERENTIAL
INPUT VOLTAGELOGICAL "0" OUTPUT
VOLTAGE VERSUS
SINK CURRENTLOGICAL "1" OUTPUT
VOLTAGE VERSUS
LOAD CURRENTCOMMON-MODE FIRING
VOLTAGE VERSUS
AMBIENT TEMPERATURE

FIG. 1 PROPAGATION DELAY

TEST CIRCUITS




VOLTAGE WAVEFORMS



NOTES:

1. Pulse generators have the following characteristics:
 $Z_{OUT} = 50 \Omega$, $t_r = t_f = 15 (\pm 5) \text{ ns}$, $t_{p1} = 100 \text{ ns}$, $t_{p2} = 300 \text{ ns}$,
 $\text{PRR} = 1 \text{ MHz}$.
2. Strobe input pulse is applied to Strobe A when inputs $A_1 - A_2$ are being tested and to Strobe B when inputs $B_1 - B_2$ are being tested.
3. C_1 includes probe and jig capacitance.

FIG. 2 DC TEST



TEST TABLE

TYPE	INPUTS	V_{ref}	V_{inD}	OUTPUT		
				V_{out}	I_{sink}	I_{load}
SN7524	$A_1 - A_2$ or $B_1 - B_2$	15 mV	$< 11 \text{ mV}$	$\leq 0.4 \text{ V}$	16 mA	—
	$A_1 - A_2$ or $B_1 - B_2$	15 mV	$> 19 \text{ mV}$	$\geq 2.4 \text{ V}$	—	$-400 \mu\text{A}$
	$A_1 - A_2$ or $B_1 - B_2$	40 mV	$< 36 \text{ mV}$	$\leq 0.4 \text{ V}$	16 mA	—
	$A_1 - A_2$ or $B_1 - B_2$	40 mV	$> 44 \text{ mV}$	$\geq 2.4 \text{ V}$	—	$-400 \mu\text{A}$
SN7525	$A_1 - A_2$ or $B_1 - B_2$	15 mV	$< 8 \text{ mV}$	$\leq 0.4 \text{ V}$	16 mA	—
	$A_1 - A_2$ or $B_1 - B_2$	15 mV	$> 22 \text{ mV}$	$\geq 2.4 \text{ V}$	—	$-400 \mu\text{A}$
	$A_1 - A_2$ or $B_1 - B_2$	40 mV	$< 33 \text{ mV}$	$\leq 0.4 \text{ V}$	16 mA	—
	$A_1 - A_2$ or $B_1 - B_2$	40 mV	$> 47 \text{ mV}$	$\geq 2.4 \text{ V}$	—	$-400 \mu\text{A}$

SN75450

DUAL PERIPHERAL DRIVER

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The SN75450 is a versatile general purpose dual interface driver circuit that employs TTL or DTL logic. The SN75450 features two standard series 74 TTL gates and two uncommitted, high current, high voltage transistors offering the system designer the flexibility to tailor the circuit to his application. The SN75450 is useful in high speed logic buffers, power drivers, lamp drivers, relay drivers, line drivers, MOS drivers, clock drivers and memory drivers.


- **HIGH SPEED**
- **300 mA CURRENT CAPABILITY**
- **HIGH VOLTAGE CAPABILITY**
- **UNCOMMITTED OUTPUT DEVICES**
- **TTL OR DTL INPUT COMPATIBILITY**

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (Note 1)	+7 V
Internal Power Dissipation (Note 2)	800 mW
Input Voltage (Note 3)	5.5 V
V _{CC} to Substrate or Collector to Substrate Voltage	35 V
Collector to Base Voltage	35 V
Emitter To Base Voltage	5 V
Collector to Base Voltage (Note 4)	30 V
Continuous Collector Current	300 mA
Operating Temperature Range	0°C to + 70°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature Range (Soldering, 60 seconds)	300°C


CONNECTION DIAGRAMS (TOP VIEW)

14 LEAD DIP




ORDER PART NO.
SN75450J

EQUIVALENT CIRCUIT



BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS ($0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$, $T_A = 25^{\circ}\text{C}$ for typical values, unless otherwise specified.) (Note 5)

PARAMETER	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
TTL Gate					
Input HIGH Voltage	$V^+ = 4.75\text{ V}$	2.0			V
Input LOW Voltage	$V^+ = 4.75\text{ V}$			0.8	V
Output HIGH Voltage	$V^+ = 4.75\text{ V}$, $V_{IN} = 0.8\text{ V}$, $I_{OUT} = -400\text{ }\mu\text{A}$	2.4	3.3		V
Output LOW Voltage	$V^+ = 4.75\text{ V}$, $V_{IN} = 2\text{ V}$, $I_{SINK} = 16\text{ mA}$		0.22	0.40	V
Low Level Input Current	$V^+ = 5.25\text{ V}$, $V_{IN} = 0.4\text{ V}$				
Input A				-1.6	mA
Input B				-3.2	mA
High Level Input Current					
Input A	$V^+ = 5.25\text{ V}$, $V_{IN} = 2.4\text{ V}$			40	μA
Input B				80	μA
Input A	$V^+ = 5.25\text{ V}$, $V_{IN} = 5.5\text{ V}$			1.0	mA
Input B				2.0	mA
Short Circuit Output Current (Note 7)	$V^+ = 5.25\text{ V}$	-18		-55	mA
Output LOW Supply Current	$V^+ = 5\text{ V}$, All Inputs HIGH		6.0	11	mA
Output HIGH Supply Current	$V^+ = 5\text{ V}$, All Inputs LOW		2.0	4.0	mA
Output Transistor					
Collector to Base Breakdown Voltage	$I_C = 100\text{ }\mu\text{A}$, $I_E = 0$	35	48		V
Emitter to Base Breakdown Voltage	$I_E = 100\text{ }\mu\text{A}$, $I_C = 0$	5.0	6.0		V
Collector to Emitter Breakdown Voltage	$I_C = 100\text{ }\mu\text{A}$, $R_{BE} = 500\text{ }\Omega$	30			V
*Collector Substrate Breakdown Voltage	$I_{CS} = 100\text{ }\mu\text{A}$	35	50		V
Static Forward Current Transfer Ratio	$V_{CE} = 2\text{ V}$, $I_C = 100\text{ mA}$, $T_A = 25^{\circ}\text{C}$	25			
(Note 6)	$V_{CE} = 2\text{ V}$, $I_C = 300\text{ mA}$, $T_A = 25^{\circ}\text{C}$	30			
	$V_{CE} = 2\text{ V}$, $I_C = 100\text{ mA}$, $T_A = 0^{\circ}\text{C}$	20			
	$V_{CE} = 2\text{ V}$, $I_C = 300\text{ mA}$, $T_A = 0^{\circ}\text{C}$	25			
Saturated Base to Emitter Forward Voltage	$I_C = 100\text{ mA}$, $I_B = 10\text{ mA}$		0.85	1.00	V
(Note 6)	$I_C = 300\text{ mA}$, $I_B = 30\text{ mA}$		1.05	1.2	V
Collector to Emitter Saturated Voltage	$I_C = 100\text{ mA}$, $I_B = 10\text{ mA}$		0.25	0.40	V
(Note 6)	$I_C = 300\text{ mA}$, $I_B = 30\text{ mA}$		0.50	0.70	V

AC CHARACTERISTICS — $V^+ = +5\text{ V}$, $T_A = 25^{\circ}\text{C}$, $C_L = 15\text{ pF}$, $R_L = 400\text{ }\Omega$


TTL Gate					
Turn Off Delay Input to Output, t_{PLH}	Figure 1		12	22	ns
Turn On Delay Input to Output, t_{PHL}			8.0	15	ns
Output Transistor					
	$I_C = 200\text{ mA}$, $I_B^+ = 20\text{ mA}$, $I_B^- = 40\text{ mA}$				
Delay Time, t_d			8.0	15	ns
Rise Time, t_r	Figure 2		12	20	ns
Storage Time, t_s			7.0	15	ns
Fall Time, t_f			6.0	15	ns
Combined Gate and Transistor					
	$I_C = 200\text{ mA}$, $I_B = I_{OS}$, $C_L = 15\text{ pF}$				
Turn Off Delay Time, t_{PLH}			17		ns
Turn On Delay Time, t_{PHL}	Figure 3		16		ns
Turn Off Transistion Time, t_{TLH}			7.0		ns
Turn On Transistion Time, t_{THL}			9.0		ns

NOTES:


1. All voltage values are with respect to device ground terminal.
2. Rating applies for ambient temperatures to 70°C .
3. Input voltage should be zero or positive with respect to device ground terminal.
4. Applies for $R_{BE} < 500\text{ }\Omega$
5. The substrate pin must always be tied to the most negative voltage for proper operation.
6. These parameters must be measured using pulse techniques. $t_w = 300\text{ }\mu\text{s}$, duty cycle = 2%.
7. Not more than one output should be shorted at a time.

TYPICAL CHARACTERISTICS


TTL GATE
HIGH-LEVEL OUTPUT VOLTAGE
VERSUS
HIGH-LEVEL OUTPUT CURRENT




TRANSISTOR
STATIC FORWARD CURRENT
TRANSFER RATIO VERSUS
COLLECTOR CURRENT



TRANSISTOR
BASE TO EMITTER VOLTAGE
VERSUS
COLLECTOR CURRENT




TRANSISTOR
COLLECTOR TO EMITTER
SATURATION VOLTAGE VERSUS
COLLECTOR CURRENT




SWITCHING CHARACTERISTICS

PROPAGATION DELAY TIMES, EACH GATE



TEST CIRCUIT




VOLTAGE WAVEFORMS


NOTES:

- The pulse generator has the following characteristics:
 $t_w = 0.5 \mu s$, $PRR = 1 \text{ MHz}$, $Z_{out} \approx 50 \Omega$.
- C_L include probe and jig capacitance.
- All diodes are 1N3064.

SWITCHING TIMES, EACH TRANSISTOR



TEST CIRCUIT




VOLTAGE WAVEFORMS


NOTES:

- The pulse generator has the following characteristics:
 $t_w = 0.3 \mu s$, duty cycle $\leq 1\%$, $Z_{out} \approx 50 \Omega$.
- C_L includes probe and jig capacitance.

SWITCHING TIMES, GATE AND TRANSISTOR



TEST CIRCUIT



VOLTAGE WAVEFORMS


NOTES:

- The pulse generator has the following characteristics:
 $t_w = 0.5 \mu s$, $PRR = 1 \text{ MHz}$, $Z_{out} \approx 50 \Omega$.
- C_L includes probe and jig capacitance.

$$Y = \overline{G} + 1A \cdot 2A + 1\overline{A} \cdot 2\overline{A}$$

The diagram illustrates a 1T1R memory array driver circuit. It consists of a PNP transistor (SN75450) and an NPN transistor. The PNP transistor's emitter is connected to +V1, and its base is connected to a network of resistors (R1, R2, R3) and a diode. The collector of the PNP transistor is connected to the base of the NPN transistor. The NPN transistor's emitter is connected to -V2, and its collector is connected to a network of resistors (R4, R5, R6) and a diode. The circuit is controlled by three inputs: SOURCE, STROBE, and SINK. The SOURCE and STROBE inputs are connected to the bases of the PNP and NPN transistors, respectively. The SINK input is connected to the collector of the NPN transistor. The circuit is connected to a selection diode array, which is connected to memory drive lines. The diagram is labeled 'SUBSTRATE Note 5'.

APPLICATIONS (cont'd)



WORD LINE MEMORY DRIVER USING SN75450

SN75450 CIRCUIT APPLICATIONS

- Dual Lamp Driver
- Dual Relay Driver
- Gated Comparator
- Floating Switch
- Dual MOS-to-TTL Driver
- Dual TTL-to-MOS Driver
- 500 mA Sink Driver
- Dual Linear Amplifier
- Dual Photo Switch (TTL Compatible Output)
- NAND Gate Schmitt (Timed Relay or Lamp Control)
- High Input Impedance Low Speed Schmitt with TTL Output
- Dual High-Speed Gate
- Square Wave Generator
- SCR Gate Driver
- Super TTL Gate with 250 mA Sinking Ability
- Dual-Channel Single-Ended Line Driver
- Memory System Current Sink
- Memory System Current Source
- Film Memory Digit Driver
- Core Memory Driver
- Phase Detector
- DC to AC Converter
- Dwell Meter Driver
- Tachometer
- MOS Memory Write Driver

TAA630 †

PAL TV CHROMA DEMODULATOR

FAIRCHILD LINEAR INTEGRATED CIRCUIT

GENERAL DESCRIPTION — The TAA630 is a synchronous demodulator for direct drive of color video output stages constructed on a single silicon chip using the Fairchild Planar* epitaxial process. It is designed for use in color television receivers operating on the Phase Alternate Line (PAL) system. The circuit consists of two synchronous demodulators, a decoding matrix, a PAL switch with internal multivibrator, and a color killer switch.


- **DOUBLE-BALANCED SYNCHRONOUS DEMODULATOR**
- **INTERNAL DECODING MATRIX**
- **EMITTER FOLLOWER OUTPUTS**
- **INTERNAL PAL SWITCH**
- **INTERNAL COLOR KILLER**
- **PROVISION FOR OUTPUT DC LEVEL MATCHING**

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (Note 1)
 Internal Power Dissipation (Note 2)
 Color Difference Output Currents
 Operating Temperature Range
 Storage Temperature Range
 Lead Temperature (Soldering, 60 seconds)

13.2 V
 730 mW
 5 mA
 -40°C to +85°C
 -65°C to +150°C
 300°C

CONNECTION DIAGRAM (TOP VIEW)




ORDERING INFORMATION

Ceramic Dual In-Line TAA630/6B
 Ceramic Quad In-Line TAA630/7H**


**Available from factory on special request.

† Formerly referred to as the μ A786

BLOCK DIAGRAM




TEST CIRCUIT 1




1. 16 volts is permissible during warmup.
2. Rating applies for ambient temperatures to 70°C. Derate linearly at 9.1 mW/°C above 70°C.
3. Killer Voltage, $V_{10} = 0.9$ V; Reference Voltages V_2 and $V_8 = 1$ Vp-p @ 4.4 MHz, V_2 leads by 90°; Line Input Pulses, V_{14} and $V_{15} = -2.5$ V peak; Chroma Input voltages V_9 and $V_{13} = 50$ mVp-p; Identification Input Voltage, $V_1 = 4$ Vp-p.
4. DC Output Levels at R-Y and G-Y outputs are adjustable to B-Y level with a variable voltage ($V \leq 1.2$ V) or with variable resistors connected between pins 11 and 12 to ground. See typical application.
5. G-Y Output is typically equal to 0.51 (R-Y) - 0.19 (B-Y).
6. Gain Linearity is greater than 0.7.

EQUIVALENT CIRCUIT



TYPICAL APPLICATION – PAL COLOR TV SYSTEM



TAA640[†]

TV/FM SOUND SYSTEM

FAIRCHILD LINEAR INTEGRATED CIRCUITS


GENERAL DESCRIPTION — The TAA640 is a monolithic TV/FM sound system constructed on a single silicon chip using the Fairchild Planar* epitaxial process. The device consists of a four stage limiting IF amplifier, modified FM slope detector, and an audio preamplifier. The circuit incorporates a dc volume control and may be remotely controlled over a 60 dB range. Excellent sensitivity, high AM rejection, an internally regulated power supply, coupled with low external component count, make the TAA640 an ideal choice for TV sound channels and line operated or automobile FM radios.

- 100 μ V SENSITIVITY
- 44 dB AM REJECTION
- DC VOLUME CONTROL
- INTERNALLY REGULATED SUPPLY
- SINGLE COIL SLOPE DETECTOR
- LOW EXTERNAL COMPONENT COUNT

ABSOLUTE MAXIMUM RATINGS

Supply Voltages (Note 1) V_7	32 V
V_8	9 V
Supply Currents (Note 1) $I_1+I_7+I_8$	40 mA
I_1	28 mA
Internal Power Dissipation (Note 2) Ceramic DIP	670 mW
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 60 seconds)	300°C

CONNECTION DIAGRAM (TOP VIEW)




ORDERING INFORMATION

Ceramic Dual In-Line TAA640/6A
Ceramic Quad In-Line TAA640/7F**

**Available from factory on special request.

[†] Formerly referred to as μ A784

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$. See note 3.


Parameter	Condition	MIN	TYP	MAX	UNITS
Zener Voltage, V_1			7.4	8.5	V
Voltage at Pin 7			22		V
Current at Pin 7			0.7		mA
IF Input Voltage for 3 dB Limiting			100		μV
IF Amplifier Voltage Gain		70	76		dB
IF Output Voltage			1.7		V _{p-p}
AM Rejection	30% AM		44		dB
Audio Output Voltage	$\Delta f = \pm 50\text{ kHz}$		1.6		V _{rms}
Total Distortion	$\Delta f = \pm 15\text{ kHz}$		1.6		%
	$\Delta f = \pm 50\text{ kHz}$			5.0	%
Remote Volume Control Range		60			dB

NOTES


1. Rating permissible during warmup.
2. Rating applies to ambient temperatures up to 70°C . Above 70°C ambient derate linearly at $8.3\text{ mW}/^\circ\text{C}$ for the Ceramic DIP package.
3. Test Circuit 1 applicable. Adjust $I_1 + I_7 + I_8$ to equal $= 26.7\text{ mA}$. IF input = 5.5 MHz ; modulation = $\pm 15\text{ kHz}$ unless otherwise specified.

TEST CIRCUIT AND TYPICAL APPLICATION

TV SOUND SYSTEM



- Notes:
1. Adjust V_S and R_S so that $I_S = 26.7\text{ mA}$.
 2. Detector coil for 5.5 MHz operation: 6.5 turns 0.5 mm wire; Coil Former: Ferroxcube AP 3016/02 less frame; Can: AP 3015/02; Core: 3122 104 93040.

EQUIVALENT CIRCUIT

TBA550 †

TV SIGNAL PROCESSING CIRCUIT

FAIRCHILD LINEAR INTEGRATED CIRCUITS

GENERAL DESCRIPTION — The TBA550 is a TV signal Processing Circuit constructed on a single silicon chip using the Fairchild Planar* Epitaxial process. This device serves as a central processing and distribution circuit for the video, AGC, noise, and synchronization signals for both monochrome and color TV systems including receivers, monitors and cameras. Other applications are in raster-scan alpha-numeric displays, video tape recorders and studio and broadcast equipment.

- VIDEO PREAMPLIFIER WITH EMITTER FOLLOWER OUTPUT
- GATED AGC DETECTOR SUPPLYING CONTROL VOLTAGES FOR VIDEO I.F. AGC AND TUNER DELAYED AGC
- AUTOMATIC FREQUENCY CONTROL VOLTAGE FOR HORIZONTAL OSCILLATOR
- VERTICAL SYNC PULSE SEPARATOR
- VIDEO BLANKING FACILITY
- NOISE CANCELLATION IN AGC AND SYNC CIRCUITS


ABSOLUTE MAXIMUM RATINGS

Supply Voltage (Note 1)	16 V
Power Dissipation (Note 2)	730 mW
Operating Temperature Range	-25°C to +125°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering)	300°C

Ceramic DIP
Ceramic DIP, 60 Seconds

CONNECTION DIAGRAM

(TOP VIEW)




ORDERING INFORMATION

Ceramic Dual-in-line **TBA550/6B**
Ceramic Quad-in-line **TBA550/7H***

* Available on special request.

† Formerly referred to as μ A785/TAA700

BLOCK DIAGRAM




ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, $V_S = +12\text{ V}$, Test Circuit 1, unless otherwise specified)

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current, I_S	$R_L = \infty$, $V_{10} = 0$		19	25	mA
	$R_L = 1\text{ k}\Omega$, $V_{10} = 0$		30		mA
VIDEO PREAMPLIFIER					
Voltage Gain			3.0		V/V
Input Resistance, R_{10}			2.7		k Ω
Input Capacitance, C_{10}				1.0	pF
Bandwidth	-3dB	5.0	14		MHz
Black Level at Video Output	$V_{10} = 2V_{P-P}$, Direct Coupled		5.0		V
Video DC Output Voltage, V_{12}	$V_{10} = 0$	8.5	9.8	10.6	V
Tracking of Video Output Voltage with Supply Variation, $\frac{\Delta V_{12}}{\Delta V_5}$	$V_{10} = 0$		0.7		V/V
Peak Video Output Current	(Note 3)		14		mA
Required Video Blanking Input Voltage Pulse, V_{11}	(Note 4)	1.0			V
Required Video Blanking Input Current Pulse, I_{11}	(Note 4)	1.0			mA
Required Flyback Gating Voltage Pulse, V_3	(Note 4)	1.0			V
Required Flyback Gating Current Pulse, I_3	(Note 4)	1.0			mA
AGC CIRCUIT					
Control Voltage at IF AGC Terminal, V_4	$V_{10} = 0\text{V}$		0		V
	$V_{10} = -2.5V_{DC}$		8.0		V
Control Voltage at Tuner AGC Terminal, V_6	$V_{10} = 0\text{V}$		0		V
	$V_{10} = -2.5V_{DC}$		7.0		V
SYNCHRONIZATION CIRCUIT					
AFC Operating Reference Voltage, V_2	$V_1 = 3V_{DC}$, $V_2 = 7V_{P-P}$, (Note 5)		7.0		V_{DC}
Vertical Sync Pulse Output, V_{15}		10	11.5		V_{P-P}
Vertical Sync Output Resistance			2.0		k Ω
Slicing Level (Percentage Below Top of Sync Pulse)	(Note 6)		30		%
NOISE GATE					
Amplitude of Noise Pulses Above Sync Tips to Activate Noise Gate	(Note 7)		0.9		V
Minimum Frequency of Noise Pulses to Activate Noise Gate	(Note 7)		3.5		MHz
Video Input Level to reduce V_8 to 10 V			3.3		V_{PEAK}

NOTES

- Rating permissible during warm-up; however, continuous maximum supply voltage is 14 volts.
- Derate linearly at $9.1\text{ mW}/^\circ\text{C}$ for ambient temperatures above 70°C .
- Operation with R_L less than 430Ω is not recommended.
- The TBA550 may be operated ungated if pin 3 is connected to the positive supply line via a resistor of a suitable value (e.g. $10\text{ k}\Omega$). However, the following precaution should be taken: The decoupling capacitors at the i.f. and tuner control points must be larger to prevent ripple voltages due to the vertical sync pulses. As a consequence the AGC will not follow fast input signal fluctuations (airplane flutter). Since the horizontal phase detector is designed to be gated, ungated operation will result in the phase detector not operating as a frequency detector when the horizontal oscillator is out of sync. This considerably decreases the pull-in range.
- These values apply for an oscillator-reactance stage having a control sensitivity of 400 Hz/V . This yields a hold-in range of about $\pm 1000\text{ Hz}$. If the phase detector is gated a pull-in range of about $\pm 700\text{ Hz}$ is obtained without affecting the noise immunity.
- The slicing level is independent of the video input level.
- The noise detector of the TBA550 is frequency and amplitude selective, i.e., frequencies and noise levels above the values given will turn off the sync and AGC detectors.

TYPICAL TV RECEIVER APPLICATION



For Complete Ordering Information See Page 304

Planned New Products

Consumer Products
Interface Elements
Voltage Comparators
Operational Amplifiers

LINEAR
LINEAR
LINEAR
LINEAR

μA791 HIGH POWER OPERATIONAL AMPLIFIER

DESCRIPTION — The μA791 is a high performance monolithic operational amplifier intended for use in a wide variety of applications including audio amplifiers, servo amplifiers, and power supplies. The high gain and high output power capability provide superior performance wherever an operational amplifier/power booster combination is required.

- CURRENT OUTPUT TO 1 AMP
- SHORT CIRCUIT PROTECTION
- OFFSET VOLTAGE NULL CAPABILITY
- NO LATCH-UP
- LARGE COMMON-MODE AND DIFFERENTIAL MODE RANGES

TBA 641B AUDIO AMPLIFIER


DESCRIPTION — The TBA 641B is a monolithic integrated circuit particularly designed for use as audio power amplifier in car radio and television receivers and in industrial applications which require high output power, low distortion and high reliability performance.

Special features of the circuit include a low quiescent current, self centering bias for operation at supply voltage ranging from 6 V to 16 V, direct coupling of the input.


The circuit requires a minimum number of external components.

- OUTPUT POWER 4.5 W (14 V — 4 Ω)
- LOW DISTORTION
- LOW QUIESCENT CURRENT
- SELF CENTERING BIAS
- HIGH INPUT IMPEDANCE
- LOW SUPPLY VOLTAGE RANGE EXCELLENT FOR CAR RADIO APPLICATION

BLOCK DIAGRAM



BLOCK DIAGRAM



CA3075

FM IF AMPLIFIER-LIMITER, DETECTOR, AND AUDIO PREAMPLIFIER

DESCRIPTION — The CA3075 is an integrated circuit which provides, in a single monolithic chip, an FM IF subsystem for Communications and High-Fidelity Receivers. This device, consists of a multistage IF amplifier-limiter section with a Zener regulated power supply, an FM detector stage, and an AF preamplifier section.

The three-stage, emitter-follower-coupled IF amplifier section provides a 60 dB typical voltage gain at an operating frequency of 10.7 MHz and features, because of its transistor constant-current sink, an output stage with exceptionally good limiting characteristics.


The FM detector section, which utilizes a differential-peak-detection circuit, requires only a single coil in the associated outboard detector circuit; hence, tuning the detector circuit is a simple procedure.

The audio preamplifier circuit provides a 21 dB voltage gain with low output impedance for driving subsequent audio amplifier stages.

The CA3075 utilizes a 14-lead dual in-line package.

- **GOOD SENSITIVITY: INPUT LIMITING VOLTAGE (KNEE) = 250 μ V TYPICAL AT 10.7 MHz**
- **EXCELLENT AM REJECTION: 55 dB TYPICAL AT 10.7 MHz**
- **INTERNAL ZENER DIODE REGULATION FOR THE IF AMPLIFIER SECTION**
- **LOW HARMONIC DISTORTION**
- **DIFFERENTIAL PEAK DETECTION: PERMITS SIMPLIFIED SINGLE-COIL TUNING**
- **AUDIO PREAMPLIFIER VOLTAGE GAIN: 21 dB TYPICAL**
- **MINIMUM NUMBER OF EXTERNAL PARTS REQUIRED**
- **FM IF AMPLIFIER APPLICATIONS UP TO 20 MHz**

BLOCK DIAGRAM



CA3076

HIGH-GAIN WIDE-BAND IF AMPLIFIER-LIMITER


DESCRIPTION — The CA3076 monolithic integrated circuit is a high-gain wide-band amplifier-limiter for use in the IF sections of Communications and High-Fidelity FM Receivers. The CA3076 consists of a four stage IF amplifier-limiter section with a voltage regulator section.

The four-stage emitter-follower-coupled IF amplifier section provides an 80 dB voltage gain with a 2 k Ω load at a frequency of 10.7 MHz. The output stage has exceptionally good limiting characteristics because of its transistor constant-current sink. The voltage regulator section provides zener-regulated, decoupled voltages for the IF amplifier.

The CA3076 utilizes an hermetically-sealed 8-lead TO-5 type package.

- **EXCEPTIONALLY GOOD SENSITIVITY: INPUT LIMITING VOLTAGE (KNEE) = 50 μ V TYPICAL AT 10.7 MHz**
- **HIGH GAIN: 80 dB WITH 2 k Ω LOAD**
- **INTERNAL VOLTAGE SUPPLY REGULATOR**
- **WIDE FREQUENCY CAPABILITY: >20 MHz**

BLOCK DIAGRAM



* R₁, R₂ selected for proper filter matching.


ULN2131

FM IF AMPLIFIER

DESCRIPTION — The type ULN-2131 FM Gain Block linear monolithic integrated circuit is designed for use in communications and high fidelity FM receivers. This device consists of a three-stage limiting amplifier section, a regulated power supply, an AM detector and 330 Ω input and output terminations with 7 pF shunting capacitance required for 10.7 MHz ceramic filters. Gain can be adjusted without effect on input and output conditions by addition of a fixed resistor between pins 5 and 12. The device is housed in an eight pin Mini DIP, ideally suited for saving space in the receiver.

- THREE-STAGE LIMITING AMPLIFIER
- HIGH VOLTAGE GAIN
- REGULATED POWER SUPPLY
- AM DETECTOR

BLOCK DIAGRAM




μ A782

COLOR TV CHROMA PROCESSOR

DESCRIPTION — The μ A782 monolithic integrated circuit performs the entire chroma processing function in a color TV receiver and provides four (4) demodulated chroma outputs. With a resistor matrix added externally to the outputs to obtain the R-Y, B-Y and G-Y signals the outputs may be used to drive direct coupled a color difference output amplifier or an RGB type output amplifier.

- CHROMA DEMODULATION
- COLOR KILLING
- GAIN CONTROLLED CHROMA IF AMPLIFICATION
- SYNCHRONOUS ACC DETECTION
- PHASE LOCKED 3.58 MHz OSCILLATOR
- SYNCHRONOUS APC DETECTION
- BURST GATING PLUS OSCILLATOR OUTPUT BLANKING
- INTERNAL BIASING
- EXTERNAL COMPONENT COUNT GREATLY REDUCED

BLOCK DIAGRAM



CA3066/CA3067

TELEVISION CHROMA SYSTEM

DESCRIPTION — The CA3066 and CA3067 are monolithic silicon integrated circuits that constitute a complete chroma system for color television receivers. The CA3066 provides subcarrier regeneration and total chroma signal processing prior to demodulation; the CA3067 performs the demodulation and tint control functions. Each device utilizes a 16-lead quad-in-line plastic package.


CA3066

- COMPLETE COLOR SYNC CIRCUIT
- BLANKED CHROMA AMPLIFIER
- CHROMA BAND-PASS AMPLIFIER
- LOW OUTPUT IMPEDANCE CHROMA DRIVER
- ACC DETECTOR-AMPLIFIER
- KILLER DETECTOR-AMPLIFIER
- DC CHROMA GAIN CONTROL
- ZENER DIODE FOR REGULATED VOLTAGE REFERENCE
- SHORT-CIRCUIT PROTECTION ON ALL TERMINALS

CA3067

- BALANCED CHROMA DEMODULATORS
- COLOR DIFFERENCE MATRIX
- DC TINT CONTROL
- THREE LOW OUTPUT IMPEDANCE DRIVERS FOR DIRECT COUPLING
- REFERENCE SUBCARRIER LIMITER
- ZENER DIODE FOR REGULATED VOLTAGE REFERENCE
- INTERNAL RF FILTERING

BLOCK DIAGRAM



CA3068


DESCRIPTION — The CA3068 is a monolithic integrated circuit that incorporates an entire video TV-IF subsystem on a single chip. Circuit innovations make it ideally suited for use in color and black-and-white TV receivers.

The primary functions performed by the IF subsystem are video IF amplification, linear detection, video output amplification, AGC from a keyed supply, AGC delay for tuner, sound carrier detection, sound carrier amplification, and a buffered AFT output. The advanced circuit design of the CA3068 also includes secondary functions for improved noise immunity and minimal airplane flutter. An isolated zener reference diode, incorporated in the IC, provides a convenient and economical means for controlling the regulated voltage supply. The inherent wide bandwidth capability (10-70 MHz) and high overall gain (87 dB) make the CA3068 suitable for other AM IF applications whose frequencies range within this bandwidth.

The CA3068 utilizes a unique 20-lead quad in-line plastic package. This package also includes a wrap-around shield that serves to minimize interlead capacitances.

- HIGH-GAIN WIDE-BAND IF AMPLIFIER:
75 dB TYPICAL AT 45 MHz
- GAIN REDUCTION WITH EXCELLENT STABILITY:
50 dB TYPICAL AT 45 MHz
- VIDEO DETECTOR WITH LINEAR CHARACTERISTICS
- VIDEO AMPLIFIER; 12 dB GAIN
- IMPULSE NOISE LIMITER
- KEYED AGC WITH NOISE IMMUNITY CIRCUITS
- DELAYED AGC FOR TUNER
- BUFFERED AFT OUTPUT
- SEPARATE SOUND IF INTERCARRIER AMPLIFICATION
- SOUND CARRIER DETECTOR
- 4.5 MHz SOUND CARRIER AMPLIFIER
- ISOLATED ZENER REFERENCE DIODE FOR
REGULATED VOLTAGE SUPPLY

BLOCK DIAGRAM




μA9616 TRIPLE EIA RS-232-C LINE DRIVER

DESCRIPTION — The μA9616 is a Triple EIA RS-232-C Line Driver which meets the specifications of EIA RS-232-C and CCITT V.24. External capacitors have been eliminated by internal slew rate limiting. All outputs are protected against RS-232-C fault conditions. A true inhibit function as required by the user has been provided. All inputs including the inhibit function are TTL compatible.

- THREE CHANNELS PER PACKAGE
- NO EXTERNAL CAPACITORS REQUIRED FOR SLEW RATE LIMITING
- MEETS ALL RS-232-C SPECIFICATIONS
- TRUE INHIBIT FUNCTION
- MULTIPLE INPUTS
- MEETS CCITT V-24 SPECIFICATIONS

BLOCK DIAGRAM




μA9617 TRIPLE EIA RS-232-C LINE RECEIVER

DESCRIPTION — The μA9617 is a triple line receiver designed to meet the terminator electrical requirements of EIA RS-232-C and CCITT V.24. It receives line signals produced by the μA9616, an EIA/CCITT driver, and converts them to TTL compatible logic levels. The inputs have a resistance between 3 kΩ and 7 kΩ and can withstand ±25 V. Each receiver can operate in either hysteresis or non-hysteresis (slicing) modes, and each receiver provides fail-safe operation as defined by Section 2.5 of RS-232-C. Noise immunity may be increased by connecting a capacitor between the response control pin and ground.

- MEETS ALL EIA RS-232-C AND CCITT V.24 SPECIFICATIONS
- FAIL-SAFE OPERATION
- HYSTERESIS OR NON-HYSTERESIS MODE
- INDIVIDUAL RESPONSE CONTROLS
- TTL COMPATIBLE OUTPUT
- SINGLE +5 V SUPPLY

BLOCK DIAGRAM




SN55/75107 SN55/75108 DUAL LINE RECEIVERS

DESCRIPTION — The SN55/75107 and SN55/75108 are high-speed, two channel line receivers with common voltage supply and ground terminals. They are designed to detect input signals of 25 mV (or greater) amplitude and convert the polarity of the signal into appropriate TTL-compatible output logic levels. They feature high input impedance and low input currents which induce very little loading on the transmission line making these devices ideal for use in party line systems. The receiver input common mode voltage range is ± 3 V but can be increased to ± 15 V by the use of input attenuators. Separate or common strobes are available. The SN55/75107 circuit features an active pull-up (totem pole output). The SN55/75108 circuit features an open collector output configuration that permits wired-OR connections. The receivers are designed to be used with the SN55/75109 and SN55/75110 line drivers. The SN55/75107 and SN55/75108 line receivers are useful in high-speed balanced, unbalanced and party line transmission systems and as data comparators.

- HIGH SPEED
- STANDARD SUPPLY VOLTAGES
- DUAL CHANNELS
- HIGH COMMON-MODE REJECTION RATIO
- HIGH INPUT IMPEDANCE
- HIGH INPUT SENSITIVITY
- INPUT COMMON-MODE VOLTAGE RANGE OF ± 3 V
- SEPARATE OR COMMON STROBES
- TTL OR DTL DRIVE CAPABILITY
- WIRED-OR OUTPUT CAPABILITY
- HIGH D-C NOISE MARGINS

BLOCK DIAGRAM



SN55/75109 SN55/75110 DUAL LINE DRIVERS


DESCRIPTION — The SN55/75109 and SN55/75110 are dual line drivers featuring independent channels with common voltage supply and ground terminals. The significant difference between the two drivers is in the output-current specification. The driver circuits feature a constant output current that is switched to either of two output terminals by the appropriate logic levels at the input terminals. The output current can be switched off (inhibited) by appropriate logic levels on the inhibit inputs. The output current is nominally 6 mA for the SN55/75109 and 12 mA for the SN55/75110. System design determines which driver is best suited to a particular application.

The inhibit feature is provided so the circuits can be used in party-line or data-bus applications. A strobe or inhibitor, common to both drivers, is included for increased driver-logic versatility. The output current in the inhibited mode, $I_{O(off)}$, is specified so that minimum line loading is induced when the driver is used in a party-line system with other drivers. The output impedance of the driver in the inhibited mode is very high—the output impedance of a transistor biased to cutoff.

The driver outputs have a common-mode voltage range of -3 volts to $+10$ volts, allowing common-mode voltage on the line without affecting driver performance.

- HIGH SPEED
- STANDARD SUPPLY VOLTAGES
- DUAL CHANNELS
- TTL INPUT COMPATIBILITY
- CURRENT-MODE OUTPUT
(6 mA or 12 mA TYPICAL)
- HIGH OUTPUT IMPEDANCE
- HIGH COMMON-MODE OUTPUT VOLTAGE RANGE
(-3 V TO 10 V)
- INHIBITOR AVAILABLE FOR DRIVER SELECTION

BLOCK DIAGRAM



SN75325

MEMORY DRIVER

DESCRIPTION - The SN75325 is a monolithic integrated circuit memory driver with logic inputs and is designed for use with magnetic memories.

The devices contain two 600 mA source-switch pairs and two 600 mA sink-switch pairs. Source selection is determined by one of two logic inputs, and source turn-on is determined by the source strobe. Likewise, sink selection is determined by one of two logic inputs, and sink turn-on is determined by the sink strobe. This arrangement allows selection of one of the four switches and its subsequent turn-on with minimum time skew of the output current rise.

- 600 mA OUTPUT CAPABILITY
- FAST SWITCHING TIMES
- OUTPUT SHORT-CIRCUIT PROTECTION
- DUAL SINK AND DUAL SOURCE OUTPUTS
- MINIMUM TIME SKEW BETWEEN ADDRESS AND OUTPUT CURRENT RISE
- 24 VOLT OUTPUT CAPABILITY
- SOURCE BASE DRIVE EXTERNALLY ADJUSTABLE
- TTL OR DTL COMPATIBILITY
- INPUT CLAMPING DIODES
- TRANSFORMER COUPLING ELIMINATED
- RELIABILITY INCREASED
- DRIVE-LINE LENGTHS REDUCED
- USE OF EXTERNAL COMPONENTS MINIMIZED

SN75451

DUAL PERIPHERAL DRIVERS

DESCRIPTION - The SN75451 is a versatile general purpose dual interface driver circuit that employs TTL or DTL logic. The SN75451 features two standard series 74 TTL gates and two high current, high voltage transistors which offer the system designer the flexibility to tailor the circuit to his application. The power output transistor is internally connected to the TTL gate but the collector remains uncommitted for high voltage applications. The SN75451 is useful in high speed logic buffers, power drivers, lamp drivers, relay drivers, line drivers, MOS drivers, clock drivers and memory drivers. The SN75451 is offered in a low cost mini-DIP package.


- HIGH SPEED
- 300 mA CURRENT CAPABILITY
- HIGH VOLTAGE CAPABILITY
- TTL OR DTL INPUT COMPATIBILITY

TRUTH TABLE


A	B	Y
L	L	L (on state)
L	H	L (on state)
H	L	L (on state)
H	H	H (off state)

H = High Level, L = Low Level

LOGIC DIAGRAM



LOGIC DIAGRAM




μ A9650

4-BIT D/A AND A/D CURRENT SOURCE

DESCRIPTION – The μ A9650 is a high speed, 4-bit precision current source, intended for use in D/A and A/D converters with up to 12-bit accuracy. It consists of a reference transistor and 4 logic operated precision current sources connected to a single output summing line. Logic inputs are fully TTL compatible.

- 200 ns SETTLING TIME ($12 \pm 1/2$ LSB)
- STANDARD SUPPLY LEVELS
- VARIABLE BIT CURRENTS
- REFERENCE COMPENSATION
- TTL COMPATIBLE

TYPICAL 12 - BIT DIGITAL-TO-ANALOG CONVERTER



μA750 DUAL HIGH CURRENT COMPARATOR

DESCRIPTION — The μA750 is a dual high current comparator. The two comparators function completely independent; each has strobing capability, built-in hysteresis for positive switching, output current sinking capability and a high current source. The dual comparator operates over a wide supply range, has a separate reference voltage available for external circuitry bias and has adjustable excess current and chip temperature protection.

The device is designed for systems requiring dual comparator functions such as air conditioners, two-direction position controls and window detectors. Although primarily intended for systems with high load currents, the device will reduce package count in all systems using more than one comparator. Both comparator and strobe inputs are TTL compatible.


- HIGH OUTPUT SOURCING CURRENT CAPABILITY
- POSITIVE SWITCHING BY MEANS OF BUILT-IN HYSTERESIS
- OUTPUT CURRENT SINKING CAPABILITY
- THERMAL AND EXCESS-CURRENT PROTECTIVE SHUT-DOWN, RESETTABLE BY INTERRUPTING SUPPLY CURRENT
- WIDE SUPPLY VOLTAGE RANGE
- REFERENCE VOLTAGE OUTPUT FOR ADDED CONVENIENCE
- OPERATES FROM SINGLE SUPPLY

LM108/108A SERIES HIGH PRECISION OPERATIONAL AMPLIFIER


DESCRIPTION — The LM108 series are high-precision operational amplifiers. Extremely high input impedance coupled with low noise input offsets and temperature drift are made possible through use of high-beta processing, making the device suitable for applications requiring high accuracy and low drift performance. The LM108A series is specially selected for extremely low offset voltage and drift, and high common mode rejection, making possible superior performance in applications where offset nulling is undesirable. Increased slew rate without performance compromise is available through use of feedforward compensation techniques, maximizing performance in high speed sample-and-hold circuits and precision high speed summing amplifiers, while the wide supply range and excellent supply voltage rejection assure maximum flexibility in voltage follower, summing, and general feedback applications.

- GUARANTEED LOW INPUT CHARACTERISTICS
- HIGH INPUT IMPEDANCE
- LOW OFFSET CURRENT — 400 pA MAXIMUM
- LOW BIAS CURRENTS — 3.0 nA MAXIMUM
- OPERATION OVER WIDE SUPPLY RANGE

BLOCK DIAGRAM



EQUIVALENT CIRCUIT



LINEAR INTEGRATED CIRCUIT DICE POLICY

General Information

Fairchild Linear Integrated Circuits is proud to offer the most complete line of circuits in dice form in the industry. All are constructed using the Fairchild Planar* Epitaxial process. The chips are identical to those used in standard Fairchild assembled products.

These linear dice can be conveniently used in hybrid or module designs where size and cost savings are required.

Electrical Characteristics

Each chip is electrically tested at 25°C to DC parameters as evidenced by the probe marks on the bonding pads.

Quality Assurance

All Fairchild linear dice are visually inspected and conform to MIL-STD-883 Method 2010.1 Condition B as a minimum to a quality control level of 1-1/2% AQL.

As an aid to die attach, each die is gold backed. For protection in handling and assembly, each die has a glassivated coating over the metalization. Only the bonding pads are exposed.

Chip geometries and manufacturing processes may be improved periodically. However, such changes will not affect the electrical characteristics of the circuits.

Shipping Packages

Linear dice are packaged in containers with an anti-static sheet inserted between the lid and the dice. This anti-static sheet guards against electrostatic damage during shipment and storage.

The clear plastic carrier allows visual inspection of all the packaged dice. Each carrier is heat sealed within a transparent bag. A small piece of dehydrator paper with humidity indicating color is inserted in each bag prior to sealing.

Ordering Information

Minimum order quantity is 100 chips. All orders above 100 peices must be in 100 piece multiples.

Each Linear Integrated Circuit chip has its own 10 digit product code which completely describes the family, device type, and device number. The meaning of the digits and their position are as follows:

1. Generic Device Type — UXX7741XXD — Microcircuit
2. Microcircuit Family — UXX7741XXD — Linear Device
3. Device Number — UXX7741XXD — Device Type
4. Dice Indicator — UXX7741XXD — Dice

Note: The XX designation replaces the package type and temperature range.


*Planar is a patented Fairchild process.

PRODUCT AVAILABLE IN DICE FORM

μA702	μA715	μA725	μA732	μA746	μA757	μA796	μA9622	CA3018	CA3045
μA703	μA716	μA726	μA733	μA747	μA777	μA9614	μA9624	CA3019	CA3054
μA709	μA719	μA727	μA734	μA748	μA780	μA9615	μA9625	CA3026	LM101A
μA710	μA722	μA729	μA739	μA749	μA781	μA9620	μA9626	CA3036	SN7525
μA711	μA723	μA730	μA741	μA754	μA792	μA9621	μA9627	CA3039	

Hi-Rel Unique 38510

PROCESS SUMMARY



* Group "B" is performed by generic type every 6 weeks.

Group "C" is performed by generic type every 12 weeks.

** "QP" devices are essentially Fairchild Standard product with 168 hr burn-in.

Fine leak is performed to an LTPD of "10" and gross leak is performed to an LTPD of "3". Flatpak have the following additional processing: Bake 883/1008/C 24 hrs and Centrifuge 883/2001/E.

The UNIQUE 38510 Program is written in accordance with MIL-M-38510 and MIL-STD-883. The Program establishes quality and reliability screening requirements to match the particular screening level required by the application.

The UNIQUE 38510 General Specification establishes the controls and reliability assurance levels for product screening. Five levels — QA, QB, QC, QD, and QP — of product screening are available.

Detailed electrical and specific device characteristics are specified for each family of devices in the Detail Specification.

FAMILY

Operational Amplifier
Comparators
Voltage Regulators
Interface Circuits

DETAIL SPECIFICATION

UNIQUE 38510/A1
UNIQUE 38510/A2
UNIQUE 38510/A3
UNIQUE 38510/12

The UNIQUE 38510 General Specification and Detail Specification are available upon request.

Devices available on the Program and marking are detailed on Page 302. For other LIC products that can be processed per the UNIQUE 38510 Program, check with your local Fairchild Sales Office.

QB and QP processed product is stocked for immediate delivery. Check with your local Fairchild Distributor or Fairchild Sales Office for delivery.

Qualified Products Code:

1st Digit	Q	Indicates Qualified Line
2nd Digit	A	Indicates Class A part
	B	Indicates Class B part
	C	Indicates Class C part
	D	Indicates Class D part (see para. 6.5)
	P	Indicates Class D Part (see para 6.5.1)
3rd Digit	X	Part of four-digit code indicating die type
4th Digit	X	
5th Digit	X	
6th Digit	X	

Number Options: These options apply to operations performed on each unit delivered:

OPTION 1	Lead form to dimensions in detail specification, followed by hermetic seal tests.
OPTION 2	Hot solder dip finish
OPTION 3	Read and record critical parameters before and after burn-in.
OPTION 4	Initial qualification, Group B&C quality conformance not required.
OPTION 5	Radiographic inspection shall be performed on all devices.
OPTION 6	Special marking required.
OPTION 7	Non-conforming variation—refer to procurement documents for details (must be negotiated with factory).

Letter Options: These options apply once per Purchase Order or line item and are considered Test Charges:

OPTION A	Group B testing shall be performed on customer's parts.
OPTION B	Group C testing shall be performed on customer's parts.
OPTION C	Generic data to be supplied from the latest completed lot.
OPTION D	UNIQUE 38510 program plan, pertinent to the device family being purchased, shall be supplied.

UNIQUE PROGRAM DEVICE PART NUMBER—MARKING CROSS REFERENCE

Product Code	Part Number & Marking	Product Code	Part Number & Marking
U5B7101311	Q/A17101BC	U6A7733312	Q/A17733BA
U6A7101311	Q/A17101BA	U3F7741312	Q/A17741BF
U3F7702312	Q/A17702BF	U5B7741312	Q/A17741BC
U5B7702312	Q/A17702BC	U6A7741312	Q/A17741BA
U3F7709312	Q/A17709BF	U5F7747312	Q/A17747BA
U5B7709312	Q/A17709BC	U7A7747312	Q/A17747BA
U6A7709312	Q/A16609BA	U6A7749312	Q/A17749BA
U3F7710312	Q/A27710BF	U4L961451X	Q/I29614BL
U5B7710312	Q/A27710BC	U7B961451X	Q/I29614BB
U6A7710312	Q/A27710BA	U4L961551X	Q/I29615BL
U3F7711312	Q/A27711BF	U7B961551X	Q/I29615BB
U5F7711312	Q/A27711BG	U3I962051X	Q/I29620BI
U5F7715312	Q/A17715BG	U6A962051X	Q/I29620BA
U6A7715312	Q/A17715BA	U3I962151X	Q/I29621BI
U5R7723312	Q/A37723BR	U6A962151X	Q/I29621BA
U6A7723312	Q/A37723BA	U3I962251X	Q/I29622BI
U5T7725312	Q/A17725BT	U6A962251X	Q/I29622BA
U3F7733312	Q/A17733BF	U3I962451X	Q/I29624BI
U5F7733312	Q/A17733BG	U6A962451X	Q/I29624BA

Application Information

The following is a list of selected linear integrated circuit application notes. For your convenience, they are organized by application note number and product type. The latest, complete Fairchild Semiconductor Application Literature Index is available from:

Fairchild Semiconductor

Technical Information Center

P.O. Box 880A

Mountain View, California 94040

SELECTED LIC APPLICATION NOTE INDEX BY NUMBER

116	The Operation and Use of a Fast Integrated Circuit Comparator	225	Gated Pulse Rate Function Multiplier
123	Core Memory Sense Amplifier Designs Using an Integrated Circuit	229	Analog-to-Pulse Width Converter
124	Designing with Off-the-shelf Linear Microcircuits	231	Variable Area, Four-Quadrant Analog Multiplier
125	A Versatile Tester for Linear Integrated Circuits	243	Some Useful Signal-Processing Circuits Using FET's and Operational Amplifiers
171	Applications of the μ A739 and μ A749 Dual Preamplifier Integrated Circuits in Home Entertainment Equipment	244	Some Characteristics of Junction FET's in the Linear Region
175	The μ A739, A Low-Noise Dual Operational Amplifier	246	An Economical D/A or Staircase Generator Using the μ A739
186	Marker Beacon Receiver and Display	276	More Voltage Regulator Applications Using the μ A723
192	A Unique Circuit Design for a High Performance Operational Especially Suited to Monolithic Construction	283	Even More Voltage Regulator Applications Using the μ A723
195	Radiation Testing of Linear Microcircuits	289	Applications of the μ A741 Operational Amplifier
210	Integrated TV Chroma Processing System	311	μ A760, A High Speed Monolithic Comparator
218	The μ A776, An Operational Amplifier with Programmable Gain, Bandwidth, Slew-Rate and Power Dissipation	312	μ A7800 Series Three Terminal Positive Voltage Regulator

SELECTED LIC APPLICATION NOTE INDEX BY PRODUCT

μ A709	124, 125, 192, 195, 229, 244	μ A746	210
μ A710	116, 124, 125, 195, 225	μ A760	311
μ A711	116, 123, 124, 125	μ A776	218
μ A723	276, 283	μ A780	210
μ A739	171, 175, 186, 246	μ A781	210
μ A741	186, 231, 243, 289	μ A7800	312
μ A742	Trigac Brochure		

Ordering Information

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +85°C	-20°C to +85°C	DICE (+25°C)
μ A702	3F		U3F7702312		
	5B	U5B7702393	U5B7702312		
	6A	U6A7702393	U6A7702312		
	DICE				UXX7703XXD
μ A703	5Z	U5Z7703394			
	DICE				UXX7703XXD
μ A709	3F		U3F7709311		
			U3F7709312		
	5B	U5B7709393	U5B7709311		
			U5B7709312		
	6A	U6A7709393	U6A7709311		
	DICE		U6A7709312		UXX7709XXD
μ A710	3F		U3F7710312		
	5B	U5B7710393	U5B7710312		
	6A	U6A7710393	U6A7710312		
	DICE				UXX7710XXD
μ A711	3F		U3F7711312		
	5F	U5F7711393	U5F7711312		
	6A	U6A7711393	U6A7711312		
	DICE				UXX7711XXD
μ A715	5F	U5F7715393	U5F7715312		
	6A	U6A7715393	U6A7715312		
	DICE				UXX7715XXD
μ A716	5B	U5B7716393			
	DICE				UXX7716XXD
μ A722	3M			U3M7722333	
	DICE			U3M7722334	UXX7722XXD
μ A723	5R	U5R7723393	U5R7723312		
	6A	U6A7723393	U6A7723312		
	9A	U9A7723393			
	DICE				UXX7723XXD

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +125°C	-20°C to +85°C	DICE (+25°C)
μA725	5T	U5T7725393	U5T7725312	U5T7725333	
	6A DICE	U6A7725393	U6A7725312	U6A7725333	UXX7725XXD
μA726	5U DICE	(0° TO +85°C) U5U7726323	U5U7726312		UXX7726XXD
μA727	5U DICE		U5U7727312	U5U7727333	UXX7727XXD
μA729	6A DICE	U6A7729394			UXX7729XXD
μA730	5B DICE	U5B7730393	U5B7730312		UXX7730XXD
μA732	6A DICE	U6A7732394			UXX7732XXD
μA733	3F 5F 6A DICE	U5F7733393 U6A7733393	U3F7733312 U5F7733312 U6A7733312		UXX7733XXD
μA734	5F 6A 9A 9T DICE	U5F7734393 U6A7734393 U9A7734393 U9T7734393	U5F7734312 U6A7734312		UXX7734XXD
μA739	6A DICE	U6A7739393			UXX7739XXD
μA740	5B	U5B7740393	U5B7740312		
μA741	3F 5B 6A 9A 9T DICE	U5B7741393 U6A7741393 U9A7741393 U9T7741391	U3F7741312 U5B7741312 U6A7741312		UXX7741XXD
μA742	6A	U6A7742393			
μA746	5E 6A DICE	U5E7746394 U6A7746394			UXX7746XXD
μA747	5F 7A DICE	U5F7747393 U7A7747393	U5F7747312 U7A7747312		UXX7747XXD
μA748	3F 5B 6A 9T DICE	U5B7748393 U6A7748393 U9T7748393	U3F7748312 U5B7748312 U6A7748312		UXX7748XXD

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +125°C	-20°C to +85°C	DICE (+25°C)
μA749	5B 6A DICE	U5B7749394 U6A7749393	U6A7749312		UXX7749XXD
μA754	5E 6A DICE	U5E7754394 U6A7754394			UXX7754XXD
μA757	6A DICE	U6A7757393	U6A7757312		UXX7757XXD
μA760	5B 6A 9T DICE	U5B7760393 U6A7760393 U9T7760393	U5B7760312 U6A7760312		UXX77603XXD
μA767	6A	U6A7767394			
μA776	5B 6A	U5B7776393 U6A7776393	U5B7776312 U6A7776312		
μA777	5B 6A 9T DICE	U5B7777393 U6A7777393 U9T7777393	U5B7777312 U6A7777312		UXX7777XXD
μA780	6B DICE	U6B7780394			UXX7780XXD
μA781	6A DICE	U6A7781394			UXX7781XXD
μA795	6A	U6A7795393			
μA796	5E 6A DICE	U5E7796393 U6A7796393	U5E7796312 U6A7796312		UXX7796XXD
μA7805	GH GJ	UGH7805393 UGJ7805393			
μA7806	GH GJ	UGH7806393 UGJ7806393			
μA7808	GH GJ	UGH7808393 UGJ7808393			
μA7812	GH GJ	UGH7812393 UGJ7812393			
μA7815	GH GJ	UGH7815393 UGJ7815393			
μA7818	GH GJ	UGH7818393 UGJ7818393			
μA7824	GH GJ	UGH7824393 UGJ7824393			

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +75°C	-55°C to +125°C	-40°C to +85°C	DICE (+25°C)
μA9614	4L 7B DICE	U4L961459X U7B961459X	U4L961451X U7B961451X		UXX9614XXD
μA9615	4L 7B DICE	U4L961559X U7B961559X	U4L961551X U7B961551X		UXX9615XXD
μA9620	3I 6A DICE	U3I962059X U6A962059X	U3I962051X U6A962051X		UXX9620XXD
μA9621	3I 6A DICE	U3I962159X U6A962159X	U3I962151X U6A962151X		UXX9621XXD
μA9622	3I 6A DICE	U3I962259X U6A962259X	U3I962251X U6A962251X		UXX9622XXD
μA9624	3I 6A DICE	U3I962459X U6A962459X	U3I962451X U6A962451X		UXX9624XXD
μA9625	3I 6A DICE	U3I962559X U6A962559X	U3I962551X U6A962551X		UXX9625XXD
μA9644	7B	U7B964459X	U7B964451X		

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +125°C	-40°C to +85°C	DICE (+25°C)
CA3018	5G DICE		CA3018		UXX7018XXD
CA3018A	5G		CA3018A		
CA3019	5E DICE		CA3019		UXX7019XXD
CA3026	5G DICE		CA3026		UXX7026XXD
CA3036	5E DICE		CA3036		UXX7036XXD
CA3039	5G DICE		CA3039		UXX7039XXD
CA3045	6A DICE		CA3045		UXX7045XXD


DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +125°C	-40°C to +85°C	DICE (+25°C)
CA3046	6A	CA3046			
CA3054	6A DICE	CA3054			UXX7054XXD
CA3064	5A			CA3064/5A	
CA3065	7F			CA3065/7F	
LM101D	6A		LM101D		
LM101H	5B		LM101H		
LM101AD	6A		LM101AD		
LM101AF	3F		LM101AF		
LM101AH	5B		LM101AH		
LM201D	6A	LM201D			
LM201H	5B	LM201H			

DEVICE	PACKAGE See outline drawing section, page 309 ff.	ORDER NUMBER			
		0°C to +70°C	-55°C to +125°C	-20°C to +85°C	DICE (+25°C)
LM201AD	6A			LM201AD	
LM201AF	3F			LM201AF	
LM201AH	5B			LM201AH	
LM301A	DICE				UXX7101XXD
LM301AD	6A	LM301AD			
LM301AH	5B	LM301AH			
LM301AN	9T	LM301AN			
LM109K	GJ		LM109K		
LM209K	GJ			LM209K	
LM309K	GJ	LM309K			
SN7524J	7B	SN7524J			
SN7525	DICE				UXX7525XXD
SN7525J	7B	SN7525J			
SN75450J	6A	SN75450J			
TAA630 (Formerly μ A786)	6A 7F	TAA630/6A TAA630/7F			
TAA640 (Formerly μ A784)	6A 7F	TAA640/6A TAA640/7F			
TBA550 (Formerly μ A785/TAA700)	6B 7H	TBA550/6B TBA550/7H			

LINEAR
LINEAR
LINEAR
LINEAR

in accordance with
JEDEC (TO-91) outline
10 Lead Cerpak

3F




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.26 gram

in accordance with
JEDEC (TO-86) outline
14 Lead Cerpak

3I




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.26 gram
Lead 1 orientation may be either tab or dot

24 Lead Flat Pak

3M




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.8 gram

16 Lead BeO Cerpak


4L



NOTES


All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.4 gram

5B



Seven leads through, lead No. 4 connected to case


5E



All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 gram
Ten leads through

in accordance with
JEDEC (TO-100) outline
(15 mil kovar header)

5F




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 gram
Nine leads through, lead No. 5 is connected
to case

Similar* to
JEDEC (TO-101) outline
(15 mil kovar header)

5G




NOTES

All dimensions in inches
Leads are gold-plated kovar
Similar to JEDEC 10-T01 except for no
standoff
Package weight is 1.03 gram

Similar* to
JEDEC (TO-3) outline

5H




NOTES

All dimensions in inches
Similar to JEDEC TO-3 except for 10 pins
on 11 pin circle

Similar* to
JEDEC (TO-96) outline
(15 mil kovar header)

5R




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 gram
Nine leads through, lead No. 5 is connected
to case
*Dimensions similar to JEDEC TO-96 except
for standoff

Similar* to
JEDEC (TO-100) outline
(15 mil kovar header)

5T




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.22 gram
*Dimensions similar to JEDEC TO-100
except for 8 leads spaced 45° apart
Eight leads through

in accordance with
JEDEC (TO-100) outline
(15 mil kovar header)

5U




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 1.32 gram
High RTH package
Ten leads through

in accordance with
JEDEC (TO-78) outline
(50 mil kovar header)

5Z




NOTES

All dimensions in inches
Leads are gold-plated kovar
Package weight is 0.95 gram

in accordance with
JEDEC (TO-116) outline
14 Lead SSI Dual In-line

6A
DG




NOTES

All dimensions in inches
Leads are intended for insertion in hole
rows on .300" centers
They are purposely shipped with "positive"
misalignment to facilitate insertion
Board-drilling dimensions should equal your
practice for .020 inch diameter lead
Leads are tin-plated kovar
Package weight is 2.0 grams

16 Lead SSI Dual In-line

6B




NOTES

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams
- *The .027/.037 dimension does not apply to the corner leads

Similar* to JEDEC (TO-116) outline 14 Lead MSI Dual In-line

7A




NOTES

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for a conventional .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.2 grams
- *Similar to JEDEC TO-116 except for package width

16 Lead MSI Dual In-line

7B




NOTES

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.2 grams
- The .037/.027 dimension does not apply to the corner leads

Similar * to JEDEC (TO-116) outline 14 Lead SSI Quad In-Line

7F




NOTES

- All dimensions in inches
- Leads are intended for insertion in hole rows on .300" centers
- They are purposely shipped with "positive" misalignment to facilitate insertion
- Board-drilling dimensions should equal your practice for .020 inch diameter lead
- Leads are tin-plated kovar
- Package weight is 2.0 grams
- *This is a 6A package with the leads formed in assembly

16 Lead SSI Quad** In-Line

7H



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers

They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead

Leads are tin-plated kovar


Package weight is 2.0 grams

*The .037/.027 dimension does not apply to the corner leads

**This is a 6B package with the leads formed in assembly

in accordance with JEDEC (TO-116) outline 14 Lead Silicone Dual In-line

9A



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers

They are purposely shipped with "positive" misalignment to facilitate insertion


Board-drilling dimensions should equal your practice for .020 inch diameter lead

Leads are tin-plated kovar

Package weight is 0.9 gram

16 Lead Silicone Dual In-line

9B



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers

They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead


Leads are tin-plated kovar

Package weight is 0.9 gram

*The .037/.025 dimension does not apply to the corner leads

Similar* to JEDEC (TO-116) Outline 14 Lead Silicone Quad In-line

9C



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers

They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead


Leads are tin-plated kovar

Package weight is 0.9 gram

*This is a 9A package with the leads formed in assembly

16 Lead Silicone Quad** In-line

9D



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers.

They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 inch diameter lead

Leads are tin-plated kovar


Package weight is 0.9 gram

*The .037/.027 dimension does not apply to the corner leads

**This is a 9B package with the leads formed in assembly

8 Lead Plastic Dual In-line

9T



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .300" centers

They are purposely shipped with "positive" misalignment to facilitate insertion


Board-drilling dimensions should equal your practice for .020 inch diameter lead

Package weight is 0.6 gram

Leads are tin or gold-plate kovar

20 Lead Plastic Quad In-line with RF Shield

9Y



NOTES

All dimensions in inches

This is a 9B package with an extended lead frame, leads formed in assembly, and a wrap around RF shield

Leads 11 and 20 are omitted

Board-drilling dimensions should equal your practice for a .020 diameter lead


Leads are tin-plated kovar

Package weight is 1.5 grams

*The .037/.027 dimension does not apply to leads 1,2,9,10,12 and 19

20 Lead Plastic Dip

9Z



NOTES

All dimensions in inches

Leads are intended for insertion in hole rows on .400" centers.


They are purposely shipped with "positive" misalignment to facilitate insertion

Board-drilling dimensions should equal your practice for .020 diameter lead

Leads are tin-plated kovar

in accordance with
JEDEC (TO-220) outline
Plastic Power Package

GH




NOTES

All dimensions in inches
Mounting tab is electrically connected to
COMMON
Package is plastic with nickel-plated copper
tab and leads
Package weight is 2.1 grams

in accordance with
JEDEC (TO-3) outline

GJ




NOTES

All dimensions in inches
Leads 1 and 2 electrically isolated from case
Case is third electrical connection
(COMMON)
Leads are gold-plated copper cored kovar
Package weight is 7.4 grams

in accordance with
JEDEC (TO-220) outline
Plastic Power Package

GM



NOTES

All dimensions in inches
Center lead is in electrical contact with the
mounting tab
Package is silicon plastic with nickel-plated
copper tab and leads
Mechanically interchangeable with TO-66
Package weight is 2.1 grams

Glossary

FAIRCHILD LINEAR INTEGRATED CIRCUIT GLOSSARY

ABSOLUTE ERROR — The worst-case deviation from a straight line drawn through zero and the 25°C value of the full-scale output current.

ACC DETECTOR SENSITIVITY — The ratio of the incremental differential DC voltage change at the ACC Detector Output Terminals to the incremental change in peak-to-peak voltage at the ACC Detector Input Terminal for a specified burst input level, with the local oscillator locked.

ACQUISTION TIME — The time from change of input until last time output exceeds specified percent of final value.

APC DETECTOR SENSITIVITY — The ratio of the incremental differential DC voltage change at the APC Detector Output Terminals to the incremental change in relative phase at the APC Detector Input Terminal for a specified burst input level.

AVERAGE INPUT OFFSET CURRENT DRIFT — The change in input offset current divided by the change in ambient temperature producing it.

AVERAGE INPUT OFFSET VOLTAGE DRIFT — The change in input offset voltage divided by the change in ambient temperature producing it.

AVERAGE TEMPERATURE COEFFICIENT OF INPUT OFFSET CURRENT — The ratio of the change in Input Offset Current over the operating temperature range to the temperature range.

AVERAGE TEMPERATURE COEFFICIENT OF INPUT OFFSET VOLTAGE — The ratio of the change in Input Offset Voltage over the operating temperature range to the temperature range.

AVERAGE TEMPERATURE COEFFICIENT OF OUTPUT VOLTAGE — The percentage change in output voltage for a specified change in ambient temperature.

BANDWIDTH — The frequency at which the differential gain is 3 dB below its low frequency value.

CLOSED LOOP VOLTAGE GAIN ERROR — Deviation from the theoretical closed loop voltage gain due to finite open loop voltage gain and input resistance, and non-zero output resistance.

COLOR-DIFFERENCE DEMODULATION ANGLE — A color-difference demodulation angle is defined as the instantaneous phase of the (+) Chroma input signal which produces the most positive voltage at the respective color-difference output with the phase of Reference "A" taken at 3 degrees and the phase of Reference "B" taken at 106 degrees.

(+) CHROMA INPUT — A composite chroma signal containing the burst at a phase of 180 degrees is demodulated to produce specified color-difference demodulation angles when applied to the (+) Chroma input.

(-) CHROMA INPUT — A composite chroma signal containing the burst at a phase of 0 degrees is demodulated to produce specified color-difference demodulation angles when applied to the (-) Chroma input.

COMMON MODE FIRING VOLTAGE — The CM input voltage that exceeds the dynamic range of the inputs with strobe enabled resulting in the output switching states.

COMMON MODE GAIN — A ratio of the differential output voltage to the change in applied input common mode voltage.

COMMON MODE INPUT RESISTANCE — The resistance looking into both inputs tied together.

COMMON MODE RECOVERY TIME — The time from the turn off of the CM signal to the analog input threshold of the earliest sense line pulse signal that can be processed normally. Processed normally refers to bi-polar signals greater than or less than the input threshold with a corresponding proper output.

DIFFERENTIAL INPUT VOLTAGE RANGE — The range of voltage between the input terminals for which operation within specifications is assured.

DIFFERENTIAL LOAD REJECTION — The ratio of the change in input offset voltage to the change in differential load current producing it.

DIFFERENTIAL INPUT RESISTANCE — The resistance looking into either input terminal with the other grounded.

DIFFERENTIAL OUTPUT VOLTAGE SWING — The peak differential output swing that can be obtained without clipping.

DIFFERENTIAL VOLTAGE GAIN — The ratio of the change in differential output voltage to the change in differential input voltage producing it.

DROPOUT VOLTAGE — The input-output voltage differential at which the circuit ceases to regulate against further reductions in input voltage.

EQUIVALENT INPUT COMMON MODE NOISE VOLTAGE — The change in input offset voltage due to common mode input noise.

EQUIVALENT INPUT RIPPLE VOLTAGE — The change in input offset voltage due to ripple on the applied supply voltage.

FULL SCALE OUTPUT CURRENT — The output current for all bits turned on.

GAIN MAXIMUM AVAILABLE (GMA) — This gain figure is the theoretical maximum power gain of an amplifier with conjugate matching at both the input and the output terminals and assumes no reverse transadmittance (feedback component) in the amplifier.

GAIN MAXIMUM STABLE (GMS) — This gain figure gives the maximum possible gain based on stability criteria only. This gain figure does not necessarily represent the realizable power gain of an amplifier. For unneutralized amplifiers, the maximum power gain realizable based on normal circuit tolerance is either (GMS - 6.0 dB) or GMA, whichever is smaller.

INPUT BIAS CURRENT — The average of the two input currents.

INPUT CAPACITANCE — The capacitance looking into either input terminal with the other grounded.

INPUT COMMON MODE REJECTION RATIO — The ratio of the input voltage range to the maximum change in input offset voltage over this range.

INPUT NOISE VOLTAGE — The square root of the mean square narrow-band noise voltage at the output divided by the measurement system gain with low source resistance.

INPUT OFFSET CURRENT — The difference in the currents into the two input terminals with the output at zero volts.

INPUT OFFSET VOLTAGE — That voltage which must be applied between the input terminals to obtain zero output voltage. The input offset voltage may also be defined for the case where two equal resistances are inserted in series with the input leads.

INPUT-OUTPUT VOLTAGE DIFFERENTIAL — The range of voltage difference between the supply voltage and the regulated output voltage over which the regulator will operate.

INPUT RESISTANCE — The resistance looking into either input terminal with the other grounded.

INPUT VOLTAGE RANGE — The range of voltage which, if exceeded on either input terminal, could cause the amplifier to cease functioning properly.

LARGE-SIGNAL VOLTAGE GAIN — The ratio of the maximum output voltage swing with load to the change in input voltage required to drive the output from zero to this voltage.

LINEARITY ERROR — The deviation from the theoretical response.

LINE REGULATION — The percentage change in output voltage for a specified change in input voltage.

LOAD REGULATION — The percentage change in output voltage for a specified change in load current.

LOGIC INPUT HIGH VOLTAGE — The minimum voltage allowed at a bit control gate to hold the bit off.

LOGIC INPUT LOW VOLTAGE — The maximum voltage allowed at a bit control gate to hold the bit on.

LONG TERM STABILITY — Output voltage stability under accelerated life-test conditions after 1000 hours with maximum rated voltage and power dissipation.

MAXIMUM POWER DISSIPATION — The maximum total device dissipation for which the regulator will operate within specifications.

NEGATIVE OUTPUT LEVEL — The DC output voltage in the negative direction with the input voltage equal to or greater than a minimum specified amount.

NEGATIVE SUPPLY CURRENT — The current required from the negative power supply to operate the device with no load.

OSCILLATOR CONTROL SENSITIVITY — The ratio of the incremental change in oscillator free running frequency to the incremental change in the differential DC voltage at the APC Detector Output Terminals.

OUTPUT COMMON MODE VOLTAGE — The average of the voltages at the two output terminals.

OUTPUT OFFSET VOLTAGE — The difference between the voltages at the two output terminals with the inputs grounded.

OUTPUT NOISE VOLTAGE — The rms output noise voltage with constant load and no input ripple.

OUTPUT RESISTANCE — The resistance seen looking into the output terminal with the output at null. This parameter is defined only under small signal conditions at frequencies above a few hundred cycles to eliminate the influence of drift and thermal feedback.

OUTPUT SHORT-CIRCUIT CURRENT — The maximum output current available from the amplifier with the output shorted to ground or to either supply.

OUTPUT SINK CURRENT — The maximum negative current that can be delivered by the comparator.

OUTPUT VOLTAGE RANGE — The range of output voltage over which the regulator will operate.

OUTPUT VOLTAGE SWING — The peak output swing, referred to zero, that can be obtained without clipping.

PEAK OUTPUT CURRENT — The maximum current that may flow into the output load without causing damage to the comparator.

POSITIVE OUTPUT LEVEL — The DC output voltage in the positive direction with the input voltage equal to or greater than a minimum specified amount.

POSITIVE SUPPLY CURRENT — The current required from the positive power supply to operate the device with no load.

POWER CONSUMPTION — The DC power required to operate the amplifier with the output at zero and with no load current.

PROPAGATION DELAY — The interval between the application of an input voltage step and its arrival at either output, measured at 50% of the final value.

QUIESCENT CURRENT — That part of input current to the regulator that is not delivered to the load.

REFERENCE VOLTAGE — The output of the reference amplifier measured with respect to the negative supply.

RESPONSE TIME — The interval between the application of an input step function and the time when the output crosses the logic threshold voltage. The input step drives the comparator from some initial, saturated input voltage to an input level just barely in excess of that required to bring the output from saturation to the logic threshold voltage overdrive.

RIPPLE REJECTION — The ratio of the peak-to-peak input ripple voltage to the peak-to-peak output ripple voltage.

RISE TIME — The time required for an output voltage step to change from 10% to 90% of its final value.

SENSE VOLTAGE — The voltage between current sense and current limit terminals necessary to cause current limiting.

SETTING TIME — The time from output first reaching final value until last time output exceeds specified percent of final value.

SHORT CIRCUIT CURRENT LIMIT — The output current of the regulator with the output shorted to the negative supply.

SLEW RATE — The maximum rate of change of output under large signal condition.

STANDBY CURRENT DRAIN — The supply current drawn by the regulator with no output load and no reference voltage load.

STROBE CURRENT — The maximum current drawn by the strobe terminals when it is at the zero logic level.

STROBE DELAY — The time delay measured from strobe to output threshold with a signal present exceeding the input threshold.

STROBE RELEASE TIME — The time required for the output to rise to the logic threshold voltage after the strobe terminal has been driven from the zero to the one logic level. Appropriate input conditions are assumed.

STROBED OUTPUT LEVEL — The DC output voltage, independent of input voltage, with the voltage on the strobe terminal equal to or less than a minimum specified amount.

SUPPLY CURRENT — The current required from the power supply to operate the amplifier with no load and the output at zero.

SUPPLY REGULATION — The change in voltage at the Supply Terminal for a specified change in the V^+ voltage.

SUPPLY VOLTAGE REJECTION RATIO — The ratio of the change in input offset voltage to the change in supply voltage producing it.

SWITCHING SPEED — The time required to turn on the least significant bit.

TEMPERATURE STABILITY OF VOLTAGE GAIN — The maximum variation of the voltage gain over the specified temperature range.

THRESHOLD UNCERTAINTY — With all sense amps sharing the same input threshold less the uncertainty as a "0". This includes unit to unit, power supply and temperature variations.

THRESHOLD VOLTAGE — The typical referred to input voltage which determines whether an input is a "1" or a "0". A signal whose magnitude is greater than the threshold level is sensed as a logic "1" and a signal whose magnitude is less as a "0".

TOTAL HARMONIC DISTORTION — The ratio of the sum of the amplitudes of all signals harmonically related to the fundamental, and the amplitude of the fundamental signal.

ZERO SCALE OUTPUT CURRENT — The output current for all bits turned off.

